

mkkin -
Routines for fitting kinetic models with one or more
state variables to chemical degradation data

Johannes Ranke
Product Safety
Harlan Laboratories Ltd.
Zelgliweg 1, CH-4452 Itingen, Switzerland

May 19, 2010

Abstract

In the regulatory evaluation of chemical substances like plant protection products (pesticides), biocides and other chemicals, degradation data play an important role. For the evaluation of pesticide degradation experiments, detailed guidance has been developed, based on nonlinear optimisation. The R add-on package **mkkin** implements fitting some of the models recommended in this guidance from within R and calculates some statistical measures for data series within one or more compartments, for parent and metabolites.

Contents

| | | |
|----------|-----------------------------|----------|
| 1 | Introduction | 1 |
| 2 | Example | 1 |
| 2.1 | Data format | 1 |
| 2.2 | Model definition | 2 |
| 2.3 | Fitting the model | 3 |

Key words: Kinetics, FOCUS, nonlinear optimisation

1 Introduction

Many approaches are possible regarding the evaluation of chemical degradation data. The **kinfit** package ([Ranke, 2010a](#)) in R ([R Development Core Team, 2010](#)) implements the approach recommended in the kinetics report provided by the FORum for Co-ordination of pesticide fate models and their USe ([FOCUS Work Group on Degradation Kinetics, 2006](#)) for simple data series for one parent compound in one compartment.

The **mkim** package ([Ranke, 2010b](#)) extends this approach to data series with metabolites and more than one compartment and includes the possibility for back reactions.

2 Example

In the following, requirements for data formatting are explained. Then the procedure for fitting the four kinetic models recommended by the FOCUS group to an example dataset for parent only given in the FOCUS kinetics report is illustrated. The explanations are kept rather verbose in order to lower the barrier for R newcomers.

2.1 Data format

The following listing shows example dataset C from the FOCUS kinetics report as distributed with the **kinfit** package

```
R> library("mkim")
```

This product includes software developed by the University of Chicago, as Operator of Argonne National Laboratory.

See the LICENSE file distributed with the minpack.lm source code or <http://www.netlib.org/minpack/disclaimer> for the full license.

```
R> FOCUS_2006_C
```

| | <i>name</i> | <i>time</i> | <i>value</i> |
|---|---------------|-------------|--------------|
| 1 | <i>parent</i> | 0 | 85.1 |
| 2 | <i>parent</i> | 1 | 57.9 |
| 3 | <i>parent</i> | 3 | 29.9 |
| 4 | <i>parent</i> | 7 | 14.6 |
| 5 | <i>parent</i> | 14 | 9.7 |
| 6 | <i>parent</i> | 28 | 6.6 |
| 7 | <i>parent</i> | 63 | 4.0 |
| 8 | <i>parent</i> | 91 | 3.9 |
| 9 | <i>parent</i> | 119 | 0.6 |

Note that the data needs to be in the format of a data frame containing a variable **name** specifying the observed variable, indicating the compound name and, if applicable, the compartment, a variable **time** containing sampling times, and a numeric variable **value** specifying the observed value of the variable. If a further variable **error** is present, this will be used to give different weights to the data points (the higher the error, the lower the weight, see the help page of the **modCost** function of the **FME** package ([Soetaert and Petzoldt, 2010](#))). Replicate measurements are not recorded in extra columns but simply appended, leading to multiple occurrences of the sampling times **time**.

Small to medium size dataset can be conveniently entered directly as R code as shown in the following listing

```
R> example_data <- data.frame(  
+   time = c(0, 1, 3, 7, 14, 28, 63, 91, 119),  
+   parent = c(85.1, 57.9, 29.9, 14.6, 9.7, 6.6, 4, 3.9, 0.6)  
+ )
```

2.2 Model definition

The next task is to define the model to be fitted to the data. In order to facilitate this task, a convenience function **mkmod** is available.

```
R> SF0 <- mkmod(parent = list(type = "SF0"))  
R> SFORB <- mkmod(parent = list(type = "SFORB"))  
R> SF0_SF0 <- mkmod(  
+   parent = list(type = "SF0", to = "m1", sink = TRUE),  
+   m1 = list(type = "SF0"))  
R> SFORB_SF0 <- mkmod(  
+   parent = list(type = "SFORB", to = "m1", sink = TRUE),  
+   m1 = list(type = "SF0"))
```

2.3 Fitting the model

Then the model parameters should be fitted to the data. The function `mkinfitt` internally creates a cost function using `modCost` from the **FME** package and the produces a fit using `modFit` from the same package.

```
R> # Do not show significance stars as they interfere with vignette generation
R> options(show.signif.stars = FALSE)
R> SFO.fit <- mkinfit(SFO, FOCUS_2006_C)
```

```
Model cost at call 1 : 4718.97
Model cost at call 4 : 4718.97
Model cost at call 5 : 572.411
Model cost at call 7 : 572.4109
Model cost at call 8 : 236.2073
Model cost at call 9 : 236.2073
Model cost at call 11 : 198.9360
Model cost at call 12 : 198.9360
Model cost at call 14 : 196.6777
Model cost at call 15 : 196.6777
Model cost at call 16 : 196.6777
Model cost at call 17 : 196.5422
Model cost at call 18 : 196.5422
Model cost at call 19 : 196.5422
Model cost at call 20 : 196.5341
Model cost at call 21 : 196.5341
Model cost at call 22 : 196.5341
Model cost at call 23 : 196.5336
Model cost at call 25 : 196.5336
Model cost at call 26 : 196.5336
Model cost at call 28 : 196.5336
Model cost at call 29 : 196.5336
Model cost at call 33 : 196.5336
```

```
R> summary(SFO.fit)
```

Equations:

```
[1] d_parent = - k_parent_sink * parent
```

Starting values for optimised parameters:

| | initial | type | lower | upper |
|---------------|---------|--------|-------|-------|
| parent_0 | 100.0 | state | 0 | Inf |
| k_parent_sink | 0.1 | deparm | 0 | Inf |

Fixed parameter values:

None

Optimised parameters:

```
Estimate Std. Error t value Pr(>|t|)
```

| | | | | |
|---------------|---------|--------|--------|----------|
| parent_0 | 82.4919 | 4.7402 | 17.402 | 5.09e-07 |
| k_parent_sink | 0.3061 | 0.0459 | 6.668 | 0.000286 |

Residual standard error: 5.299 on 7 degrees of freedom

Chi2 error levels in percent:

| | | | |
|----------|---------|---------|----|
| | err.min | n.optim | df |
| All data | 15.84 | 2 | 7 |
| parent | 15.84 | 2 | 7 |

Estimated disappearance times

| | | |
|--------|-------|-------|
| | DT50 | DT90 |
| parent | 2.265 | 7.523 |

Data:

| time | variable | observed | predicted | residual |
|------|----------|----------|-----------------|----------|
| 0 | parent | 85.1 | 82.491918964177 | 2.608 |
| 1 | parent | 57.9 | 60.742411633568 | -2.842 |
| 3 | parent | 29.9 | 32.934530029534 | -3.035 |
| 7 | parent | 14.6 | 9.682173180746 | 4.918 |
| 14 | parent | 9.7 | 1.136403227206 | 8.564 |
| 28 | parent | 6.6 | 0.015654900288 | 6.584 |
| 63 | parent | 4.0 | 0.000000361297 | 4.000 |
| 91 | parent | 3.9 | -0.000000014466 | 3.900 |
| 119 | parent | 0.6 | -0.000000001821 | 0.600 |

R> SFORB.fit <- mkinfit(SFORB, FOCUS_2006_C)

Model cost at call 1 : 7044.136
 Model cost at call 4 : 7044.136
 Model cost at call 7 : 3460.066
 Model cost at call 9 : 3460.066
 Model cost at call 11 : 3460.066
 Model cost at call 13 : 309.8375
 Model cost at call 15 : 309.8375
 Model cost at call 17 : 309.8375
 Model cost at call 18 : 27.19125
 Model cost at call 20 : 27.19124
 Model cost at call 23 : 4.43924
 Model cost at call 25 : 4.43924
 Model cost at call 28 : 4.362922
 Model cost at call 31 : 4.362922
 Model cost at call 33 : 4.362712
 Model cost at call 38 : 4.36271
 Model cost at call 43 : 4.36271
 Model cost at call 47 : 4.36271
 Model cost at call 49 : 4.36271

R> summary(SFORB.fit)

Equations:

```
[1] d_parent_free = - k_parent_free_sink * parent_free - k_parent_free_bound * parent_free
[2] d_parent_bound = + k_parent_free_bound * parent_free - k_parent_bound_free * parent_free
```

Starting values for optimised parameters:

| | initial | type | lower | upper |
|---------------------|---------|--------|-------|-------|
| parent_free_0 | 100.0 | state | 0 | Inf |
| k_parent_free_sink | 0.1 | deparm | 0 | Inf |
| k_parent_free_bound | 0.1 | deparm | 0 | Inf |
| k_parent_bound_free | 0.1 | deparm | 0 | Inf |

Fixed parameter values:

| | value | type |
|--------------|-------|-------|
| parent_bound | 0 | state |

Optimised parameters:

| | Estimate | Std. Error | t value | Pr(> t) |
|---------------------|-----------|------------|---------|----------|
| parent_free_0 | 85.002720 | 0.890669 | 95.437 | 2.39e-09 |
| k_parent_free_sink | 0.395043 | 0.014308 | 27.610 | 1.17e-06 |
| k_parent_free_bound | 0.061599 | 0.007289 | 8.451 | 0.000381 |
| k_parent_bound_free | 0.020764 | 0.003752 | 5.533 | 0.002644 |

Residual standard error: 0.9341 on 5 degrees of freedom

Chi2 error levels in percent:

| | err.min | n.optim | df |
|----------|---------|---------|----|
| All data | 2.662 | 4 | 5 |
| parent | 2.662 | 4 | 5 |

Estimated disappearance times

| | DT50 | DT90 |
|--------|-------|-------|
| parent | 1.887 | 21.25 |

Data:

| time | variable | observed | predicted | residual |
|------|----------|----------|-----------|----------|
| 0 | parent | 85.1 | 85.003 | 0.09728 |
| 1 | parent | 57.9 | 58.039 | -0.13912 |
| 3 | parent | 29.9 | 30.054 | -0.15358 |
| 7 | parent | 14.6 | 13.866 | 0.73388 |
| 14 | parent | 9.7 | 9.787 | -0.08655 |
| 28 | parent | 6.6 | 7.532 | -0.93201 |
| 63 | parent | 4.0 | 4.033 | -0.03265 |
| 91 | parent | 3.9 | 2.446 | 1.45351 |
| 119 | parent | 0.6 | 1.484 | -0.88421 |

```
R> SFO_SFO.fit <- mkinfit(SFO_SFO, FOCUS_2006_D)
```

Model cost at call 1 : 18994.29

Model cost at call 3 : 18994.29

```

Model cost at call 7 : 10641.39
Model cost at call 8 : 10641.39
Model cost at call 12 : 7145.459
Model cost at call 14 : 7145.458
Model cost at call 17 : 411.9739
Model cost at call 18 : 411.9738
Model cost at call 22 : 371.2194
Model cost at call 23 : 371.2194
Model cost at call 27 : 371.2127
Model cost at call 28 : 371.2127
Model cost at call 29 : 371.2127
Model cost at call 31 : 371.2127
Model cost at call 32 : 371.2127
Model cost at call 34 : 371.2127
Model cost at call 37 : 371.2127
Model cost at call 39 : 371.2127

```

```
R> summary(SFO_SFO.fit)
```

Equations:

```

[1] d_parent = - k_parent_sink * parent - k_parent_m1 * parent
[2] d_m1 = - k_m1_sink * m1 + k_parent_m1 * parent

```

Starting values for optimised parameters:

| | initial | type | lower | upper |
|---------------|---------|--------|-------|-------|
| parent_0 | 100.0 | state | 0 | Inf |
| k_parent_sink | 0.1 | deparm | 0 | Inf |
| k_m1_sink | 0.1 | deparm | 0 | Inf |
| k_parent_m1 | 0.1 | deparm | 0 | Inf |

Fixed parameter values:

| | value | type |
|----|-------|-------|
| m1 | 0 | state |

Optimised parameters:

| | Estimate | Std. Error | t value | Pr(> t) |
|---------------|-----------|------------|---------|----------|
| parent_0 | 9.960e+01 | 1.614e+00 | 61.720 | < 2e-16 |
| k_parent_sink | 4.792e-02 | 3.750e-03 | 12.778 | 6.10e-15 |
| k_m1_sink | 5.261e-03 | 7.159e-04 | 7.349 | 1.15e-08 |
| k_parent_m1 | 5.078e-02 | 2.094e-03 | 24.248 | < 2e-16 |

Residual standard error: 3.211 on 36 degrees of freedom

Chi2 error levels in percent:

| | err.min | n.optim | df |
|----------|---------|---------|----|
| All data | 6.565 | 4 | 16 |
| parent | 6.827 | 3 | 6 |
| m1 | 4.748 | 1 | 10 |

Estimated disappearance times

| | DT50 | DT90 |
|--------|---------|--------|
| parent | 7.023 | 23.33 |
| m1 | 131.760 | 437.70 |

Data:

| time | variable | observed | predicted | residual |
|------|----------|----------|------------|-------------|
| 0 | parent | 99.46 | 99.5984955 | -0.1384955 |
| 0 | parent | 102.04 | 99.5984955 | 2.4415045 |
| 1 | parent | 93.50 | 90.2378767 | 3.2621233 |
| 1 | parent | 92.50 | 90.2378767 | 2.2621233 |
| 3 | parent | 63.23 | 74.0731772 | -10.8431772 |
| 3 | parent | 68.99 | 74.0731772 | -5.0831772 |
| 7 | parent | 52.32 | 49.9120561 | 2.4079439 |
| 7 | parent | 55.13 | 49.9120561 | 5.2179439 |
| 14 | parent | 27.27 | 25.0125879 | 2.2574121 |
| 14 | parent | 26.64 | 25.0125879 | 1.6274121 |
| 21 | parent | 11.50 | 12.5346040 | -1.0346040 |
| 21 | parent | 11.64 | 12.5346040 | -0.8946040 |
| 35 | parent | 2.85 | 3.1478595 | -0.2978595 |
| 35 | parent | 2.91 | 3.1478595 | -0.2378595 |
| 50 | parent | 0.69 | 0.7162355 | -0.0262355 |
| 50 | parent | 0.63 | 0.7162355 | -0.0862355 |
| 75 | parent | 0.05 | 0.0607374 | -0.0107374 |
| 75 | parent | 0.06 | 0.0607374 | -0.0007374 |
| 100 | parent | NA | 0.0051506 | NA |
| 100 | parent | NA | 0.0051506 | NA |
| 120 | parent | NA | 0.0007155 | NA |
| 120 | parent | NA | 0.0007155 | NA |
| 0 | m1 | 0.00 | 0.0000000 | 0.0000000 |
| 0 | m1 | 0.00 | 0.0000000 | 0.0000000 |
| 1 | m1 | 4.84 | 4.8029613 | 0.0370387 |
| 1 | m1 | 5.64 | 4.8029613 | 0.8370387 |
| 3 | m1 | 12.91 | 13.0240164 | -0.1140164 |
| 3 | m1 | 12.96 | 13.0240164 | -0.0640164 |
| 7 | m1 | 22.97 | 25.0447743 | -2.0747743 |
| 7 | m1 | 24.47 | 25.0447743 | -0.5747743 |
| 14 | m1 | 41.69 | 36.6900224 | 4.9999776 |
| 14 | m1 | 33.21 | 36.6900224 | -3.4800224 |
| 21 | m1 | 44.37 | 41.6531097 | 2.7168903 |
| 21 | m1 | 46.44 | 41.6531097 | 4.7868903 |
| 35 | m1 | 41.22 | 43.3131256 | -2.0931256 |
| 35 | m1 | 37.95 | 43.3131256 | -5.3631256 |
| 50 | m1 | 41.19 | 41.2183070 | -0.0283070 |
| 50 | m1 | 40.01 | 41.2183070 | -1.2083070 |
| 75 | m1 | 40.09 | 36.4470161 | 3.6429839 |
| 75 | m1 | 33.85 | 36.4470161 | -2.5970161 |
| 100 | m1 | 31.04 | 31.9815991 | -0.9415991 |
| 100 | m1 | 33.13 | 31.9815991 | 1.1484009 |

| | | | | |
|-----|----|-------|------------|------------|
| 120 | m1 | 25.15 | 28.7898086 | -3.6398086 |
| 120 | m1 | 33.31 | 28.7898086 | 4.5201914 |

References

- FOCUS Work Group on Degradation Kinetics. *Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration. Report of the FOCUS Work Group on Degradation Kinetics*, 2006. URL <http://focus.jrc.ec.europa.eu/dk>. EC Document Reference Sanco/10058/2005 version 2.0.
- R Development Core Team. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria, 2010. URL <http://www.R-project.org>. ISBN 3-900051-07-0.
- Johannes Ranke. *kinfit: Routines for fitting simple kinetic models to chemical degradation data*, 2010a. URL <http://CRAN.R-project.org>.
- Johannes Ranke. *mkln: Routines for fitting kinetic models with one or more state variables to chemical degradation data*, 2010b. URL <http://CRAN.R-project.org>.
- Karline Soetaert and Thomas Petzoldt. Inverse modelling, sensitivity and monte carlo analysis in R using package FME. *Journal of Statistical Software*, 33(3):1–28, 2010. URL <http://www.jstatsoft.org/v33/i03/>.