

Package ‘sasLM’

April 13, 2020

Version 0.1.2

Title 'SAS' Linear Model

Description This is a core implementation of 'SAS' procedures for linear models - GLM, REG, and ANOVA. Well-known `\{ \}`package{car} provides type II and type III SS. However, the results for nested and complex designs often different from those of 'SAS.' Different results does not necessarily mean incorrectness. However, many wants the same results to SAS. This package aims to achieve that. Reference: Littell RC, Stroup WW, Freund RJ (2002, ISBN:0-471-22174-0).

Depends R (\geq 3.0.0)

Author Kyun-Seop Bae [aut]

Maintainer Kyun-Seop Bae <k@acr.kr>

Copyright 2020, Kyun-Seop Bae

License GPL-3

Repository CRAN

URL <https://cran.r-project.org/package=sasLM>

R topics documented:

sasLM-package	2
af	2
ANOVA	3
aov1	3
aov2	4
aov3	5
cSS	6
e1	7
e2	7
e3	8
est	9
GLM	10
lfit	11
ModelMatrix	11
REG	12
SS	13
Index	14

sasLM-package

'SAS' Linear Model

Description

This is a core implementation of 'SAS' procedures for linear models - GLM, REG, and ANOVA. Well-known 'car' package provides type II and type III SS. However, the results for nested and complex designs often different from those of 'SAS.' Different results does not necessarily mean incorrectness. However, many wants the same results to SAS. This package aims to achieve that. Reference: Littell RC, Stroup WW, Freund RJ (2002, ISBN:0-471-22174-0).

Details

This will serve those who want SAS PROC GLM, REG, and ANOVA in R.

Author(s)

Kyun-Seop Bae k@acr.kr

af

Convert some columns of a data.frame to factors

Description

Conveniently convert some columns of data.frame into factors.

Usage

```
af(DataFrame, Cols)
```

Arguments

DataFrame	a data.frame
Cols	column names or indices to be converted

Details

It performs conversion of some columns in a `data.frame` into factors conveniently.

Value

Returns a `data.frame` with converted columns.

Author(s)

Kyun-Seop Bae k@acr.kr

ANOVA

*Analysis of Variance similar to SAS PROC ANOVA***Description**

Analysis of variance with type I, II, and III sum of squares.

Usage

```
ANOVA(Formula, Data)
```

Arguments

Formula	a conventional formula for a linear model.
Data	a <code>data.frame</code> to be analyzed

Details

It performs the core function of SAS PROC ANOVA.

Value

The result is comparable to that of SAS PROC ANOVA.

ANOVA	ANOVA table for the model
Type I	Type I sum of square table
Type II	Type II sum of square table
Type III	Type III sum of square table

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
ANOVA(uptake ~ Plant + Type + Treatment + conc, C02)
```

aov1

*ANOVA with Type I SS***Description**

ANOVA with Type I SS.

Usage

```
aov1(Formula, Data)
```

Arguments

Formula	a conventional formula for a linear model.
Data	a <code>data.frame</code> to be analyzed

Details

It performs the core function of SAS PROC ANOVA.

Value

The result table is comparable to that of SAS PROC ANOVA.

Df	degree of freedom
Sum Sq	sum of square for the set of contrasts
Mean Sq	mean square
F value	F value for the F distribution
Pr(>F)	proability of larger than F value

Author(s)

Kyun-Seop Bae `k@acr.kr`

Examples

```
aov1(uptake ~ Plant + Type + Treatment + conc, C02)
```

aov2	<i>ANOVA with Type II SS</i>
------	------------------------------

Description

ANOVA with Type II SS.

Usage

```
aov2(Formula, Data)
```

Arguments

Formula	a conventional formula for a linear model.
Data	a <code>data.frame</code> to be analyzed

Details

It performs the core function of SAS PROC ANOVA.

Value

The result table is comparable to that of SAS PROC ANOVA.

Df	degree of freedom
Sum Sq	sum of square for the set of contrasts
Mean Sq	mean square
F value	F value for the F distribution
Pr(>F)	probability of larger than F value

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
aov2(uptake ~ Plant + Type + Treatment + conc, C02)
```

aov3	<i>ANOVA with Type III SS</i>
------	-------------------------------

Description

ANOVA with Type III SS.

Usage

```
aov3(Formula, Data)
```

Arguments

Formula	a conventional formula for a linear model.
Data	a <code>data.frame</code> to be analyzed

Details

It performs the core function of SAS PROC ANOVA.

Value

The result table is comparable to that of SAS PROC ANOVA.

Df	degree of freedom
Sum Sq	sum of square for the set of contrasts
Mean Sq	mean square
F value	F value for the F distribution
Pr(>F)	probability of larger than F value

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
aov3(uptake ~ Plant + Type + Treatment + conc, C02)
```

cSS	<i>Sum of Square with a Given Contrast Set</i>
-----	--

Description

Calculates sum of squares of a contrast from a `lfit` result.

Usage

```
cSS(K, rx)
```

Arguments

K	contrast matrix. Each column is a contrast.
rx	a result of <code>lfit</code> function

Details

It calculates sum of squares with given a contrast matrix and a `lfit` result. It corresponds to SAS PROC GLM CONTRAST.

Value

Returns sum of square and its F value and p-value.

Df	degree of freedom
Sum Sq	sum of square for the set of contrasts
Mean Sq	mean square
F value	F value for the F distribution
Pr(>F)	probability of larger than F value

Author(s)

Kyun-Seop Bae `k@acr.kr`

Examples

```
x = ModelMatrix(uptake ~ Type, C02)
y = model.frame(uptake ~ Type, C02)[,1]
rx = lfit(x, y)
cSS(c(0, -1, 1), rx) # sum of square
ANOVA(uptake ~ Type, C02) # compare with the above
```

e1	<i>Get a Contrast Matrix for Type I SS</i>
----	--

Description

Makes a contrast matrix for type I SS using forward Doolittle method.

Usage

```
e1(Formula, Data, eps=1e-8)
```

Arguments

Formula	a conventional formula for a linear model
Data	a <code>data.frame</code> to be analyzed
eps	Less than this value is considered as zero.

Details

It makes a contrast matrix for type I SS.

Value

A contrast matrix for type I SS.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
round(e1(uptake ~ Plant + Type + Treatment + conc, C02), 12)
```

e2	<i>Get a Contrast Matrix for Type II SS</i>
----	---

Description

Makes a contrast matrix for type II SS.

Usage

```
e2(Formula, Data)
```

Arguments

Formula	a conventional formula for a linear model
Data	a <code>data.frame</code> to be analyzed

Details

It makes a contrast matrix for type II SS.

Value

Returns a contrast matrix for type II SS.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
round(e2(uptake ~ Plant + Type + Treatment + conc, C02), 12)
```

e3

Get a Contrast Matrix for Type III SS

Description

Makes a contrast matrix for type III SS.

Usage

```
e3(Formula, Data, eps=1e-8)
```

Arguments

Formula	a conventional formula for a linear model
Data	a <code>data.frame</code> to be analyzed
eps	Less than this value is considered as zero.

Details

It makes a contrast matrix for type III SS.

Value

Returns a contrast matrix for type III SS.

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
round(e3(uptake ~ Plant + Type + Treatment + conc, C02), 12)
```

est	<i>Estimate Linear Contrast</i>
-----	---------------------------------

Description

Estimates Linear Contrast(s) with a given GLM result.

Usage

```
est(L, rx)
```

Arguments

L	a matrix of linear contrast rows to be tested
rx	a result of <code>lfit</code> function

Details

It tests rows of linear contrast. It corresponds to SAS PROC GLM ESTIMATE.

Value

Returns a table of expectations, t values and p-values.

Estimate	point estimate of the input linear constrast
Std. Error	standard error of the point estimate
t value	value for t distribution
Pr(> t	probability of larger than absolute t value from t distribution with residual's degree of freedom

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
x = ModelMatrix(uptake ~ Type, C02)
y = model.frame(uptake ~ Type, C02)[,1]
rx = lfit(x, y)
est(t(c(0, -1, 1)), rx) # Quevec - Mississippi
t.test(uptake ~ Type, C02) # compare with the above
```

GLM*General Linear Model similar to SAS PROC GLM*

Description

GLM is the main function of this package.

Usage

```
GLM(Formula, Data)
```

Arguments

Formula	a conventional formula for a linear model.
Data	a <code>data.frame</code> to be analyzed

Details

It performs the core function of SAS PROC GLM.

Value

The result is comparable to that of SAS PROC GLM.

ANOVA	ANOVA table for the model
Type I	Type I sum of square table
Type II	Type II sum of square table
Type III	Type III sum of square table
Parameter	Parameter table with standard error, t value, p value

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
GLM(uptake ~ Plant + Type + Treatment + conc, C02)
```

lfit	<i>Linear Fit</i>
------	-------------------

Description

Fits a least square linear model.

Usage

```
lfit(x, y, eps=1e-8)
```

Arguments

x	a result of ModelMatrix
y	a column vector of response, dependent variable
eps	Less than this value is considered as zero.

Details

Minimum version of least square fit of a linear model

Value

coefficients	beta coefficients
g2	g2 inverse
rank	rank of the model matrix
DFr	degree of freedom for the residual
SSE	sum of square error

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[ModelMatrix](#)

ModelMatrix	<i>Model Matrix</i>
-------------	---------------------

Description

This model matrix is similar to `model.matrix`. But it does not omit unnecessary columns.

Usage

```
ModelMatrix(Formula, Data, NOINT=FALSE, KeepOrder=FALSE)
```

Arguments

Formula	a conventional formula for a linear model
Data	a <code>data.frame</code> to be analyzed
NOINT	If NOINT is TRUE, no intercept model will be used. Always -1 or +0 will be ignored in the formula.
KeepOrder	If KeepOrder is TRUE, terms in Formula will be kept. This is for Type I SS.

Details

It makes the `model(design)` matrix for GLM.

Value

Model matrix and attributes similar to the output of `model.matrix`.

X	design matrix, i.e. model matrix
terms	detailed information about terms such as formula and labels
termsIndices	term indices
assign	assignment of columns for each terms in order, different way of expressing term indices

Author(s)

Kyun-Seop Bae `k@acr.kr`

 REG

Regression of Linear Least square

Description

REG is similar to SAS PROC REG.

Usage

```
REG(Formula, Data, NOINT=FALSE)
```

Arguments

Formula	a conventional formula for a linear model.
Data	a <code>data.frame</code> to be analyzed
NOINT	If NOINT is TRUE, no intercept model will be used. Always -1 or +0 will be ignored in the formula.

Details

It performs the core function of SAS PROC REG.

Value

The result is comparable to that of SAS PROC REG.

Estimate	point estimate of parameters, coefficients
Std. Error	standard error of the point estimate
t value	value for t distribution
Pr(> t	probability of larger than absolute t value from t distribution with residual's degree of freedom

Author(s)

Kyun-Seop Bae k@acr.kr

Examples

```
REG(uptake ~ Plant + Type + Treatment + conc, C02)
```

SS	<i>Sum of Square</i>
----	----------------------

Description

Sum of squares with ANOVA.

Usage

```
SS(x, rx, L, eps=1e-8)
```

Arguments

x	a result of <code>ModelMatrix</code> containing design information
rx	a result of <code>lfit</code>
L	linear hypothesis, a full matrix matching the information in x
eps	Less than this value is considered as zero.

Details

It calculates sum of squares and completes the ANOVA table.

Value

ANOVA table a classical ANOVA table without the residual(Error) part.

Author(s)

Kyun-Seop Bae k@acr.kr

See Also

[ModelMatrix](#), [lfit](#),

Index

af, [2](#)
ANOVA, [3](#)
aov1, [3](#)
aov2, [4](#)
aov3, [5](#)

cSS, [6](#)

e1, [7](#)
e2, [7](#)
e3, [8](#)
est, [9](#)

GLM, [10](#)

lfit, [11](#), [13](#)

ModelMatrix, [11](#), [11](#), [13](#)

REG, [12](#)

sasLM-package, [2](#)
SS, [13](#)