

Package ‘ChileDataAPI’

July 17, 2025

Type Package

Title Access Chilean Data via APIs and Curated Datasets

Version 0.1.0

Maintainer Renzo Caceres Rossi <arenzocaceresrossi@gmail.com>

Description Provides functions to access data from the 'FINDIC API' and the 'REST Countries API', related to Chile's financial indicators, international country information, and more.

Additionally, the package includes curated datasets related to Chile, covering topics such as human rights violations during the Pinochet regime, electoral data, census samples, health surveys, seismic events, territorial codes, and environmental measurements.

The package supports research and analysis focused on Chile by integrating open APIs with high-quality datasets from multiple domains. For more details on 'FINDIC', see <<https://findic.cl/>>,

and for 'REST Countries', see <<https://restcountries.com/>>.

License GPL-3

URL <https://github.com/lightbluetitan/chiledataapi>,
<https://lightbluetitan.github.io/chiledataapi/>

BugReports <https://github.com/lightbluetitan/chiledataapi/issues>

Encoding UTF-8

LazyData true

Depends R (>= 4.1.0)

Imports utils, httr, jsonlite, dplyr

Suggests ggplot2, testthat (>= 3.0.0), knitr, rmarkdown

RoxygenNote 7.3.2

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author Renzo Caceres Rossi [aut, cre] (ORCID:
<<https://orcid.org/0009-0005-0744-854X>>)

Repository CRAN

Date/Publication 2025-07-16 15:20:13 UTC

Contents

census_chile_2017_df	2
ChileDataAPI	4
chile_earthquakes_tbl_df	5
chile_election_2021_df	6
chile_health_survey_df	7
chile_plebiscite_df	8
get_chile_bitcoin	9
get_chile_copper_pound	10
get_chile_dollar	11
get_chile_euro	12
get_chile_ipsa	13
get_chile_uf	14
get_chile_utm	15
get_chile_yen	16
get_country_info	17
malleco_tree_rings_ts	18
pinochet_regime_df	19
territorial_codes_tbl_df	21
view_datasets_ChileDataAPI	22

Index	23
--------------	-----------

census_chile_2017_df	<i>Chilean Census Example Data (San Pablo Commune, 2017)</i>
----------------------	--

Description

This dataset, `census_chile_2017_df`, is a data frame containing microdata from the 2017 Chilean census, specifically from the commune of San Pablo. It was selected due to its relatively small size, making it suitable for inclusion in CRAN and GitHub repositories. The dataset includes 7,512 observations and 60 variables related to housing, households, individuals, migration, education, and geographic information. All variable names and data values are in Spanish, as retrieved from the original source.

Usage

```
data(census_chile_2017_df)
```

Format

A data frame with 7,512 observations and 60 variables:

region Administrative region code

provincia Province code

comuna Commune code

dc Census district code

area Urban/rural area indicator
zc_loc Census location zone
id_zona_loc Location zone ID
nviv Number of dwellings
nhogar Number of households
personan Person number
p07 Sex
p08 Relationship to head of household
p09 Age
p10 Place of birth (Chile or abroad)
p10comuna Commune of birth
p10pais Country of birth
p11 Last place of residence
p11comuna Commune of last residence
p11pais Country of last residence
p12 Place of residence in 2012
p12comuna Commune of residence in 2012
p12pais Country of residence in 2012
p12a_llegada Year of arrival
p12a_tramo Time range of arrival
p13 Health insurance
p14 Marital status
p15 Educational level
p15a Currently attending school
p16 Employment status
p16a Occupation type
p16a_otro Other occupation (free text)
p17 Disability indicator
p18 Ethnic group
p19 Language spoken
p20 Language understood
p21m Month of migration
p21a Year of migration
p10pais_grupo Grouped birth country
p11pais_grupo Grouped last residence country
p12pais_grupo Grouped 2012 residence country
escolaridad Years of schooling

p16a_grupo Grouped occupation
region_15r Region code (15-region system)
provincia_15r Province code (15-region system)
comuna_15r Commune code (15-region system)
p10comuna_15r Commune of birth (15-region system)
p11comuna_15r Commune of last residence (15-region system)
p12comuna_15r Commune of residence in 2012 (15-region system)
geocode Geographical identifier
p01 Type of dwelling
p02 Dwelling condition
p03a Material of exterior walls
p03b Material of floor
p03c Material of roof
p04 Number of rooms
p05 Number of bedrooms
cant_hog Number of households in the dwelling
cant_per Number of persons in the dwelling
tipo_hogar Type of household
tipo_operativo Census operation type

Details

The dataset name has been kept as `census_chile_2017_df` to avoid confusion with other datasets in the R ecosystem. This naming convention helps distinguish this dataset as part of the ChileDataAPI package and assists users in identifying its specific characteristics. The suffix `df` indicates that the dataset is a data frame. The original content has not been modified.

Source

Data taken from the `ismtchile` package version 2.1.5.

ChileDataAPI

ChileDataAPI: Access Chilean Data via APIs and Curated Datasets

Description

This package provides functions to access data from the 'FINDIC API' and the 'REST Countries API', related to Chile's financial indicators, international country information, additionally, the package includes curated datasets related to Chile.

Details

ChileDataAPI: Access Chilean Data via APIs and Curated Datasets
Access Chilean Data via APIs and Curated Datasets.

Author(s)

Maintainer: Renzo Caceres Rossi <arenzocaceresrossi@gmail.com>

See Also

Useful links:

- <https://github.com/lightbluetitan/chiledataapi>

chile_earthquakes_tbl_df

Chilean Earthquakes Data

Description

This dataset, `chile_earthquakes_tbl_df`, is a tibble containing information about significant (perceptible) earthquakes that occurred in Chile from January 1st, 2012 to the present. The data was originally compiled by the Centro Sismológico Nacional (Chile) and was published on Kaggle by Nicolás González Muñoz. The dataset includes 4,018 observations and 5 variables, capturing relevant geophysical characteristics such as the date and time of occurrence, geographic coordinates, depth, and magnitude of each seismic event.

Usage

```
data(chile_earthquakes_tbl_df)
```

Format

A tibble with 4,018 observations and 5 variables:

Date(UTC) Timestamp of the earthquake in UTC (POSIXct)

Latitude Latitude coordinate of the event (numeric)

Longitude Longitude coordinate of the event (numeric)

Depth Depth in kilometers (numeric)

Magnitude Richter magnitude of the earthquake (numeric)

Details

The dataset name has been kept as `'chile_earthquakes_tbl_df'` to avoid confusion with other datasets in the R ecosystem. This naming convention helps distinguish this dataset as part of the ChileDataAPI package and assists users in identifying its specific characteristics. The suffix `'tbl_df'` indicates that the dataset is a tibble (a modern data frame). The original content has not been modified in any way. Variable names and values are in English, as originally provided by the source.

Source

Data taken from Kaggle: <https://www.kaggle.com/datasets/nicolasgonzalezmunoz/earthquakes-on-chile>

chile_election_2021_df

Chilean 2021 First Round Presidential Election

Description

This dataset, `chile_election_2021_df`, is a data frame containing the results of the first round of the 2021 Chilean presidential elections. It includes vote counts for seven presidential candidates, as well as counts for blank and null votes. Each observation corresponds to an individual ballot box, identified by its unique ID and associated electoral district. Additionally, the dataset includes demographic information on the age distribution of voters for each ballot box, and a logical indicator for mismatches or inconsistencies in the vote counts.

Usage

```
data(chile_election_2021_df)
```

Format

A data frame with 46,606 observations and 21 variables:

REGION Administrative region (character)

ELECTORAL.DISTRICT Electoral district (character)

BALLOT.BOX Unique identifier for the ballot box (character)

C1 Votes for Candidate 1 (integer)

C2 Votes for Candidate 2 (integer)

C3 Votes for Candidate 3 (integer)

C4 Votes for Candidate 4 (integer)

C5 Votes for Candidate 5 (integer)

C6 Votes for Candidate 6 (integer)

C7 Votes for Candidate 7 (integer)

BLANK.VOTES Count of blank votes (integer)

NULL.VOTES Count of null votes (integer)

X18.19 Voters aged 18–19 (integer)

X20.29 Voters aged 20–29 (integer)

X30.39 Voters aged 30–39 (integer)

X40.49 Voters aged 40–49 (integer)

X50.59 Voters aged 50–59 (integer)

X60.69 Voters aged 60–69 (integer)

X70.79 Voters aged 70–79 (integer)

X80. Voters aged 80 and older (integer)

MISMATCH Logical indicator of inconsistency in vote reporting (logical)

Details

The dataset name has been kept as `chile_election_2021_df` to avoid confusion with other datasets in the R ecosystem. This naming convention helps distinguish this dataset as part of the `ChileDataAPI` package and assists users in identifying its specific characteristics. The suffix `df` indicates that the dataset is a data frame. The original content has not been modified.

Source

Data taken from the `fastei` package version 0.0.0.7.

`chile_health_survey_df`

Chilean National Health Survey (2016–2017)

Description

This dataset, `chile_health_survey_df`, is a data frame containing information collected by the Chilean National Health Survey conducted between 2016 and 2017. The objective of the survey was to study the health status of the Chilean population and support health-related public policy design. The dataset includes biometric, behavioral, demographic, and educational variables from 3,211 individuals.

Usage

```
data(chile_health_survey_df)
```

Format

A data frame with 3,211 observations and 12 variables:

pas, pad Systolic and diastolic blood pressure (numeric)

age Age of the respondent (integer)

waist, bmi Waist circumference and body mass index (numeric)

sedentary, smoker, diabetes, depression Health behavior and condition indicators (integer)

male Sex of the respondent (1 = male, 0 = female) (integer)

scholar2, scholar3 Education level indicators (integer)

Details

The dataset name has been kept as '`chile_health_survey_df`' to avoid confusion with other datasets in the R ecosystem. This naming convention helps distinguish this dataset as part of the `ChileDataAPI` package and assists users in identifying its specific characteristics. The suffix '`df`' indicates that the dataset is a data frame. The original content has not been modified in any way.

Source

Data taken from the `abms` package version 0.2

chile_plebiscite_df	<i>Voting Intentions in the 1988 Chilean Plebiscite</i>
---------------------	---

Description

This dataset, `chile_plebiscite_df`, is a data frame containing information on voting intentions in the 1988 Chilean plebiscite. The data were collected from a national survey conducted by FLACSO/Chile during April and May of 1988. The dataset consists of 2,700 observations and 8 variables, including demographic details such as region, sex, age, education, and income, as well as voting preferences and support for the status quo. Some observations contain missing values.

Usage

```
data(chile_plebiscite_df)
```

Format

A data frame with 2,700 observations and 8 variables:

region Region of the respondent (factor with 5 levels: "C", "M", "N", "S", ...)

population Population size of the respondent's area (integer)

sex Sex of the respondent (factor: "F", "M")

age Age in years (integer)

education Education level (factor with 3 levels: "P", "PS", "S")

income Income of the respondent (integer)

statusquo Support for the status quo (numeric scale)

vote Intended vote (factor with 4 levels)

Details

The dataset name has been kept as 'chile_plebiscite_df' to avoid confusion with other datasets in the R ecosystem. This naming convention helps distinguish this dataset as part of the ChileDataAPI package and assists users in identifying its specific characteristics. The suffix 'df' indicates that the dataset is a data frame. The original content has not been modified in any way.

Source

Data taken from the carData package version 3.0-5

get_chile_bitcoin*Get Observed Bitcoin Value from the findic.cl API*

Description

This function retrieves the observed value of Bitcoin in US Dollars from the API endpoint: <https://findic.cl/api/bitcoin>. The data is provided by the Chilean website findic.cl.

Usage

```
get_chile_bitcoin()
```

Details

The values returned by the API include metadata and a time series of daily values. The names of the variables and the values are in Spanish, exactly as provided by the API. For example, the result includes columns named *fecha* (date) and *valor* (value).

The function sends a GET request to the `/api/bitcoin` endpoint. If the request is successful (HTTP 200), it parses the JSON response and extracts the time series data under the key `serie`.

All names and values are kept in Spanish as provided by the API and no translation or modification is applied.

Value

A tibble (data frame) with the following columns:

- *fecha*: Fecha del valor observado (en formato "YYYY-MM-DD").
- *valor*: Valor del bitcoin en dólares estadounidenses (numérico).

Note

Requires internet connection. The function returns the values exactly as provided in Spanish.

See Also

[GET, fromJSON, as_tibble](#)

Examples

```
## Not run:  
bitcoin_data <- get_chile_bitcoin()  
head(bitcoin_data)  
  
## End(Not run)
```

`get_chile_copper_pound`*Get Observed Copper Price per Pound from the findic.cl API*

Description

This function retrieves the observed daily value of the copper price per pound ("Libra de Cobre") in U.S. Dollars from the API endpoint: https://findic.cl/api/libra_cobre. The data is provided by the Chilean website findic.cl.

Usage

```
get_chile_copper_pound()
```

Details

The values returned by the API include metadata and a time series of daily prices. The names of the variables and the values are in Spanish, exactly as provided by the API. For example, the result includes columns named *fecha* (date) and *valor* (value).

The function sends a GET request to the `/api/libra_cobre` endpoint. If the request is successful (HTTP 200), it parses the JSON response and extracts the time series data under the key `serie`.

All names and values are kept in Spanish as provided by the API and no translation or modification is applied.

Value

A tibble (data frame) with the following columns:

- *fecha*: Fecha del valor observado (in format "YYYY-MM-DD").
- *valor*: Valor de la libra de cobre en dólares estadounidenses (numeric).

Note

Requires internet connection. The function returns the values exactly as provided in Spanish.

See Also

[GET](#), [fromJSON](#), [as_tibble](#)

Examples

```
## Not run:  
copper_data <- get_chile_copper_pound()  
head(copper_data)  
  
## End(Not run)
```

get_chile_dollar*Get Observed Dollar Exchange Rate from the findic.cl API*

Description

This function retrieves the observed exchange rate ("Dólar observado") in Chilean Pesos from the API endpoint: <https://findic.cl/api/dolar>. The data is provided by the Chilean website findic.cl.

Usage

```
get_chile_dollar()
```

Details

The values returned by the API include metadata and a time series of daily exchange rates. The names of the variables and the values are in Spanish, exactly as provided by the API. For example, the result includes columns named *fecha* (date) and *valor* (value).

The function sends a GET request to the `/api/dolar` endpoint. If the request is successful (HTTP 200), it parses the JSON response and extracts the time series data under the key `serie`.

All names and values are kept in Spanish as provided by the API and no translation or modification is applied.

Value

A tibble (data frame) with the following columns:

- *fecha*: Fecha del valor observado (en formato "YYYY-MM-DD").
- *valor*: Valor del dólar observado en pesos chilenos (numérico).

Note

Requires internet connection. The function returns the values exactly as provided in Spanish.

See Also

[GET, fromJSON, as_tibble](#)

Examples

```
## Not run:  
dolar_data <- get_chile_dollar()  
head(dolar_data)  
  
## End(Not run)
```

`get_chile_euro`*Get Observed Euro Exchange Rate from the findic.cl API*

Description

This function retrieves the observed exchange rate ("Euro (pesos por euro)") in Chilean Pesos from the API endpoint: <https://findic.cl/api/euro>. The data is provided by the Chilean website findic.cl.

Usage

```
get_chile_euro()
```

Details

The values returned by the API include metadata and a time series of daily exchange rates. The names of the variables and the values are in Spanish, exactly as provided by the API. For example, the result includes columns named *fecha* (date) and *valor* (value).

The function sends a GET request to the `/api/euro` endpoint. If the request is successful (HTTP 200), it parses the JSON response and extracts the time series data under the key `serie`.

All names and values are kept in Spanish as provided by the API and no translation or modification is applied.

Value

A tibble (data frame) with the following columns:

- `fecha`: Fecha del valor observado (en formato "YYYY-MM-DD").
- `valor`: Valor del euro observado en pesos chilenos (numérico).

Note

Requires internet connection. The function returns the values exactly as provided in Spanish.

See Also

[GET, fromJSON, as_tibble](#)

Examples

```
## Not run:  
euro_data <- get_chile_euro()  
head(euro_data)  
  
## End(Not run)
```

get_chile_ipsa	<i>Get IPSA (Índice de Precios Selectivo de Acciones) from the findic.cl API</i>
----------------	--

Description

This function retrieves the historical values of the IPSA index ("Índice de Precios Selectivo de Acciones") from the API endpoint: <https://findic.cl/api/ipsa>. The data is provided by the Chilean website findic.cl.

Usage

```
get_chile_ipsa()
```

Details

The values returned by the API include metadata and a time series of daily IPSA index values. The names of the variables and the values are in Spanish, exactly as provided by the API. For example, the result includes columns named *fecha* (date) and *valor* (value).

The function sends a GET request to the `/api/ipsa` endpoint. If the request is successful (HTTP 200), it parses the JSON response and extracts the time series data under the key `serie`.

All names and values are kept in Spanish as provided by the API and no translation or modification is applied.

Value

A tibble (data frame) with the following columns:

- *fecha*: Fecha de la observación (in "YYYY-MM-DD" format).
- *valor*: Valor del índice IPSA en puntos (numeric).

Note

Requires internet connection. The function returns the values exactly as provided in Spanish.

See Also

[GET, fromJSON, as_tibble](#)

Examples

```
## Not run:  
ipsa_data <- get_chile_ipsa()  
head(ipsa_data)  
  
## End(Not run)
```

`get_chile_uf`*Get Unidad de Fomento (UF) from the findic.cl API*

Description

This function retrieves the Unidad de Fomento (UF) daily values in Chilean Pesos from the API endpoint: <https://findic.cl/api/uf>. The data is provided by the Chilean website findic.cl.

Usage

```
get_chile_uf()
```

Details

The values returned by the API include metadata and a time series of daily UF values. The names of the variables and the values are in Spanish, exactly as provided by the API. For example, the result includes columns named *fecha* (date) and *valor* (value).

The function sends a GET request to the `/api/uf` endpoint. If the request is successful (HTTP 200), it parses the JSON response and extracts the time series data under the key `serie`.

All names and values are kept in Spanish as provided by the API and no translation or modification is applied.

Value

A tibble (data frame) with the following columns:

- *fecha*: Fecha del valor observado (in "YYYY-MM-DD" format).
- *valor*: Valor diario de la UF en pesos chilenos (numeric).

Note

Requires internet connection. The function returns the values exactly as provided in Spanish.

See Also

[GET, fromJSON, as_tibble](#)

Examples

```
## Not run:  
uf_data <- get_chile_uf()  
head(uf_data)  
  
## End(Not run)
```

get_chile_utm*Get Monthly Tax Unit (UTM) from the findic.cl API*

Description

This function retrieves the historical values of the Unidad Tributaria Mensual (UTM) in Chilean Pesos from the API endpoint: <https://findic.cl/api/utm>. The data is provided by the Chilean website findic.cl.

Usage

```
get_chile_utm()
```

Details

The values returned by the API include metadata and a time series of monthly values. The names of the variables and the values are in Spanish, exactly as provided by the API. For example, the result includes columns named *fecha* (date) and *valor* (value).

The function sends a GET request to the `/api/utm` endpoint. If the request is successful (HTTP 200), it parses the JSON response and extracts the time series data under the key `serie`.

All names and values are kept in Spanish as provided by the API and no translation or modification is applied.

Value

A tibble (data frame) with the following columns:

- `fecha`: Fecha de referencia del valor mensual (in format "YYYY-MM-DD").
- `valor`: Valor mensual de la Unidad Tributaria Mensual (UTM) en pesos chilenos (numeric).

Note

Requires internet connection. The function returns the values exactly as provided in Spanish.

See Also

[GET, fromJSON, as_tibble](#)

Examples

```
## Not run:  
utm_data <- get_chile_utm()  
head(utm_data)  
  
## End(Not run)
```

`get_chile_yen`*Get Observed Yen Exchange Rate from the findic.cl API*

Description

This function retrieves the observed exchange rate ("Yen (pesos por yen)") in Chilean Pesos from the API endpoint: <https://findic.cl/api/yen>. The data is provided by the Chilean website findic.cl.

Usage

```
get_chile_yen()
```

Details

The values returned by the API include metadata and a time series of daily exchange rates. The names of the variables and the values are in Spanish, exactly as provided by the API. For example, the result includes columns named *fecha* (date) and *valor* (value).

The function sends a GET request to the `/api/yen` endpoint. If the request is successful (HTTP 200), it parses the JSON response and extracts the time series data under the key `serie`.

All names and values are kept in Spanish as provided by the API and no translation or modification is applied.

Value

A tibble (data frame) with the following columns:

- *fecha*: Fecha del valor observado (en formato "YYYY-MM-DD").
- *valor*: Valor del yen observado en pesos chilenos (numérico).

Note

Requires internet connection. The function returns the values exactly as provided in Spanish.

See Also

[GET](#), [fromJSON](#), [as_tibble](#)

Examples

```
## Not run:  
yen_data <- get_chile_yen()  
head(yen_data)  
  
## End(Not run)
```

`get_country_info`*Get Key Country Information from the REST Countries API*

Description

Retrieves selected, essential information about Chile or any other country by its full name. The data is retrieved from the REST Countries API. See the API documentation at <https://restcountries.com/>. Example API usage: <https://restcountries.com/v3.1/name/chile?fullText=true>.

Usage

```
get_country_info(name)
```

Arguments

`name` Full country name (common or official). For example: "Chile", "Peru", "France".

Details

This function returns readable details such as the country's common and official name, capital, region, subregion, population, area, and official languages.

The function sends a GET request to the REST Countries API. If the request is successful (HTTP 200), it parses the JSON and extracts the key fields. If the country is not found or there's an error, the function returns NULL with a user-friendly message.

Value

A data frame with 8 columns:

- `name_common`: Common name of the country.
- `name_official`: Official name of the country.
- `capital`: Capital city.
- `region`: Geographic region.
- `subregion`: Subregion.
- `population`: Total population.
- `area`: Total area in square kilometers.
- `languages`: Official languages, separated by commas.

See Also

[GET](#), [fromJSON](#), [tibble](#)

Examples

```
## Not run:  
get_country_info("Chile")  
get_country_info("Japan")  
get_country_info("France")  
  
## End(Not run)
```

malleco_tree_rings_ts *Average Araucaria Araucana Tree Ring Width*

Description

This dataset, malleco_tree_rings_ts, is a time series object ('ts') containing the average annual tree ring width, measured in millimeters, for Araucaria Araucana trees located in the Malleco region of Chile. The data spans 734 years, from 1242 to 1975, and was originally collected for use in climate and environmental reconstructions. The frequency of the series is annual (one observation per year). The series shows interannual variability in growth and is suitable for time series analysis and dendrochronological studies.

Usage

```
data(malleco_tree_rings_ts)
```

Format

A time series object with 734 annual observations:

Start year 1242

End year 1975

Frequency Annual (1)

Values Average annual ring width in millimeters (numeric)

Details

The dataset name has been kept as 'malleco_tree_rings_ts' to avoid confusion with other datasets in the R ecosystem. This naming convention helps distinguish this dataset as part of the ChileDataAPI package and assists users in identifying its specific characteristics. The suffix 'ts' indicates that the dataset is a time series object. The original content has not been modified in any way.

Source

Data taken from the LSTS package version 2.1

pinochet_regime_df *Human Rights Abuses in the Pinochet Regime (1973–1990)*

Description

This dataset, `pinochet_regime_df`, is a data frame containing detailed information about human rights violations that occurred in Chile during the military dictatorship of Augusto Pinochet, spanning from 1973 to 1990. The data includes victim-level records such as names, age, gender, affiliation, nature of the violence, methods used, and geographic information when available. It is based on the National Truth and Reconciliation Commission Report (1991, ISBN:9780268016463). The dataset also includes georeferenced locations across multiple levels for incidents where such data could be retrieved.

Usage

```
data(pinochet_regime_df)
```

Format

A data frame with 2,398 observations and 59 variables:

individual_id Victim ID
group_id Group ID for collective incidents
start_date_daily Start date (day precision)
end_date_daily End date (day precision)
start_date_monthly Start date (month precision)
end_date_monthly End date (month precision)
last_name Victim's last name
first_name Victim's first name
minor Indicator if victim was a minor
age Age of the victim
male Indicator if victim was male
occupation Victim's occupation
occupation_detail Detailed occupation description
victim_affiliation Affiliation of the victim
victim_affiliation_detail Detailed affiliation
violence Type of violence experienced
method Method of violence
interrogation Interrogation indicator
torture Torture indicator
mistreatment Mistreatment indicator

targeted Targeting category
press Indicator for press involvement
war_tribunal War tribunal indicator
number_previous_arrests Number of previous arrests
perpetrator_affiliation Affiliation of perpetrator
perpetrator_affiliation_detail Detailed affiliation of perpetrator
nationality Victim's nationality
place_1 First incident location
location_1 First location detail
latitude_1 Latitude of first location
longitude_1 Longitude of first location
exact_coordinates_1 Indicator of coordinate precision (1 = exact)
place_2 Second incident location
location_2 Second location detail
latitude_2 Latitude of second location
longitude_2 Longitude of second location
exact_coordinates_2 Indicator of coordinate precision (2nd)
place_3 Third incident location
location_3 Third location detail
latitude_3 Latitude of third location
longitude_3 Longitude of third location
exact_coordinates_3 Indicator of coordinate precision (3rd)
place_4 Fourth incident location
location_4 Fourth location detail
latitude_4 Latitude of fourth location
longitude_4 Longitude of fourth location
exact_coordinates_4 Indicator of coordinate precision (4th)
place_5 Fifth incident location
location_5 Fifth location detail
latitude_5 Latitude of fifth location
longitude_5 Longitude of fifth location
exact_coordinates_5 Indicator of coordinate precision (5th)
place_6 Sixth incident location
location_6 Sixth location detail
latitude_6 Latitude of sixth location
longitude_6 Longitude of sixth location
exact_coordinates_6 Indicator of coordinate precision (6th)
page Source page in the original report
additional_comments Additional remarks or context

Details

The dataset name has been kept as `pinochet_regime_df` to avoid confusion with other datasets in the R ecosystem. This naming convention helps distinguish this dataset as part of the `ChileDataAPI` package and assists users in identifying its specific characteristics. The suffix `df` indicates that the dataset is a data frame. The original content has not been modified.

Source

Data taken from the `pinochet` package version 0.1.0.

`territorial_codes_tbl_df`

Official Codes for Chilean Communes, Provinces, and Regions

Description

This dataset, `territorial_codes_tbl_df`, is a tibble containing official codes for communes, provinces, and regions in Chile. The codes were provided by the Chilean government agency SUBDERE. The names of the administrative divisions were converted to ASCII characters to avoid encoding issues. All variable names and data values are in Spanish, as retrieved from the original source.

Usage

```
data(territorial_codes_tbl_df)
```

Format

A tibble with 346 observations and 6 variables:

codigo_comuna, nombre_comuna Official commune code and commune name (character, in Spanish)

codigo_provincia, nombre_provincia Official province code and province name (character, in Spanish)

codigo_region, nombre_region Official region code and region name (character, in Spanish)

Details

The dataset name has been kept as `'territorial_codes_tbl_df'` to avoid confusion with other datasets in the R ecosystem. This naming convention helps distinguish this dataset as part of the `ChileDataAPI` package and assists users in identifying its specific characteristics. The suffix `'df'` indicates that the dataset is a data frame. The original content has not been modified in any way.

Source

Data taken from the `chilemapas` package version 0.3.0

`view_datasets_ChileDataAPI`*View Available Datasets in ChileDataAPI*

Description

This function lists all datasets available in the 'ChileDataAPI' package. If the 'ChileDataAPI' package is not loaded, it stops and shows an error message. If no datasets are available, it returns a message and an empty vector.

Usage

```
view_datasets_ChileDataAPI()
```

Value

A character vector with the names of the available datasets. If no datasets are found, it returns an empty character vector.

Examples

```
if (requireNamespace("ChileDataAPI", quietly = TRUE)) {  
  library(ChileDataAPI)  
  view_datasets_ChileDataAPI()  
}
```

Index

`as_tibble`, [9–16](#)

`census_chile_2017_df`, [2](#)

`chile_earthquakes_tbl_df`, [5](#)

`chile_election_2021_df`, [6](#)

`chile_health_survey_df`, [7](#)

`chile_plebiscite_df`, [8](#)

`ChileDataAPI`, [4](#)

`ChileDataAPI`-package (`ChileDataAPI`), [4](#)

`fromJSON`, [9–17](#)

`GET`, [9–17](#)

`get_chile_bitcoin`, [9](#)

`get_chile_copper_pound`, [10](#)

`get_chile_dollar`, [11](#)

`get_chile_euro`, [12](#)

`get_chile_ipsa`, [13](#)

`get_chile_uf`, [14](#)

`get_chile_utm`, [15](#)

`get_chile_yen`, [16](#)

`get_country_info`, [17](#)

`malleco_tree_rings_ts`, [18](#)

`pinochet_regime_df`, [19](#)

`territorial_codes_tbl_df`, [21](#)

`tibble`, [17](#)

`view_datasets_ChileDataAPI`, [22](#)