

Package ‘LifeHist’

January 20, 2025

Type Package

Title Life History Models of Individuals

LazyLoad yes

LazyData yes

Version 1.0-1

Date 2015-08-31

Author Ruben H. Roa-Ureta

Maintainer Ruben H. Roa-Ureta <ruben.roa.ureta@mail.com>

Depends R (>= 3.0.0), Hmisc

Imports optimx (>= 2013.8.6), BB

Description Likelihood-based estimation of individual growth and sexual maturity models for organisms, usually fish and invertebrates. It includes methods for data organization, plotting standard exploratory and analytical plots, predictions.

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2015-09-03 12:20:03

Contents

LifeHist-package	2
as.GroAgeData	4
BlackAngler.agematdat	6
BlackAngler.lenmatdat	7
BlackAngler.wgtmatdat	7
deltamethod	8
GroAgeData	9
GroAgeExp	10
groageexp	10
GroAgeFit	12
GroAgeMod	15

groagemod	16
ksbream	17
MatCount	18
MatData	19
MatFit	20
plot.GroAgeData	22
plot.GroAgeExp	22
plot.GroAgeMod	23
plot.MatData	24

Index	25
--------------	-----------

LifeHist-package *Life History Models of Individuals*

Description

Likelihood-based estimation of individual growth and sexual maturity models for organisms, usually fish and invertebrates. It includes methods for data organization, plotting standard exploratory and analytical plots, predictions.

Details

The DESCRIPTION file:

Package:	LifeHist
Type:	Package
Title:	Life History Models of Individuals
LazyLoad:	yes
LazyData:	yes
Version:	1.0-1
Date:	2015-08-31
Author:	Ruben H. Roa-Ureta
Maintainer:	Ruben H. Roa-Ureta < ruben.roa.ureta@mail.com >
Depends:	R (>= 3.0.0), Hmisc
Imports:	optimx (>= 2013.8.6), BB
Description:	Likelihood-based estimation of individual growth and sexual maturity models for organisms, usually fish and invertebrates
License:	GPL (>= 2)

Index of help topics:

BlackAngler.agematdat	Black Anglerfish Age, Sex, Month, Maturity Stage Data
BlackAngler.lenmatdat	Black Anglerfish Length, Sex, Month, Maturity Stage Data
BlackAngler.wgtmatdat	Black Anglerfish Body Weight, Sex, Month, Maturity Stage Data

GroAgeData	Class Attribute of LifeHist Data Object
GroAgeExp	Class Attribute of LifeHist Exploratory Model Object
GroAgeFit	Fit Growth Model with Age and Length Data by Maximum Likelihood
GroAgeMod	Class Attribute of LifeHist Fitted Model Object
LifeHist-package	Life History Models of Individuals
MatCount	Build Databases for Sexual Maturity Modeling by Logistic Regression
MatData	Class Attribute of LifeHist Data Object
MatFit	Wrapper Function to Estimate a 2- or 3-Parameters Logistic Regression of Sexual Maturity
as.GroAgeData	Create a Data Object to Fit Individual Growth Models with Age-Length Observations
deltamethod	First-order Taylor Series Expansion of Functions of Random Variables
groageexp	Exploratory Growth Modeling with Age and Length Data
groagemod	Predictions from an Object of Class GroAgeMod
ksbream	King Soldier Bream Individual Biological Data
plot.GroAgeData	Exploratory Analysis of Agen and Length Individual Data
plot.GroAgeExp	Exploratory Modeling of Individual Growth with Age and Length Data
plot.GroAgeMod	Examination of Results from Fitting Growth Models
plot.MatData	Exploratory Analisys of a Logistic Model on a Graphical Display

Create data objects for maturity and growth modeling with MatCount() and as.GroAgeData(), respectively. Fit sexual maturity models with MatFit() for two types of models and any numerical method accepted by optimx() from package optimx. Explore raw growth data with generic function plot() applied on an object of class 'GroAgeData' created by as.GroAgeData(). Create predictions with initial parameter values for growth models using groageexp() and examine how good these initial values are with generic function plot() applied on an object of class 'GroAgeExp' created by groageexp(). Fit any of four type of models with any of five likelihood models and any numerical method acpted by optimx() from package optimx, using GroAgeFit(). Graphically examines results with generic function plot() applied on an object of class 'GroAgeMod' created by GroAgeFit().

Author(s)

Ruben H. Roa-Ureta

Maintainer: Ruben H. Roa-Ureta <ruben.roa.ureta@mail.com>

References

- R. Roa, B. Ernst, F. Tapia. 1999. Estimation of size at sexual maturity: evaluation of analytical and resampling procedures. *Fishery Bulletin (US)* 97:570-580.
- Arkhipkin, A., Roa-Ureta, R. 2005. Identification of growth models for squids. *Marine and Freshwater Research* 56:371-386.
- Roa-Ureta, R. 2010. A Likelihood-based Model of Fish Growth with Multiple Length Frequency Data. *Journal of Agricultural, Biological and Environmental Statistics* 15:416-429.

Examples

```
#See examples for functions MatFit() and GroAgeFit()
```

`as.GroAgeData`

Create a Data Object to Fit Individual Growth Models with Age-Length Observations

Description

From a data.frame identify columns with data on length and age from a single sex category, two sexes, or two sexes plus unsexed individuals, and optionally include date, body weight, liver weight, and gonad weight, to create a data object with a class attribute.

Usage

```
as.GroAgeData(x, sex, maleskey = NULL, femaleskey = NULL, colsex = NULL,
               colage, collen, colbw = NULL, colliver = NULL, colgonad = NULL,
               coldate = NULL, lentype, unitsage, unitslen, unitsbw = NULL,
               unitsliver = NULL, unitsgonad = NULL, spec)
```

Arguments

<code>x</code>	Data.frame containing the data, where each line is an individual.
<code>sex</code>	Character, either "Females", "Males", "Pooled", "Both", or "Total".
<code>maleskey</code>	Usually a numeric key indicating whether the individual is male.
<code>femaleskey</code>	Usually a numeric key indicating whether the individual is female.
<code>colsex</code>	Integer. The column in 'x' with the sex key.
<code>colage</code>	Integer. The column in 'x' with the age data.
<code>collen</code>	Integer. The column in 'x' with the length data.
<code>colbw</code>	Integer. Optionally, the column in 'x' with the body weight data.
<code>colliver</code>	Integer. Optionally, the column in 'x' with the liver weight data.
<code>colgonad</code>	Integer. Optionally, the column in 'x' with the gonad weight data.
<code>coldate</code>	Integer. Optionally, the column in 'x' with the collection date data.

lentype	Character. In the case of fish, this indicates whether the length is total, fork, or standard.
unitsage	Character. The units of age.
unitslen	Character. The units of length.
unitsbw	Character. Optionally, the units of body weight.
unitsliver	Character. Optionally, the units of liver weight.
unitsgonad	Character. Optionally, the units of gonad weight.
spec	Character. A species identification key.

Details

When 'sex' is "Females" or "Males", the data.frame 'x' contains data for a single sex. When 'sex' is "Pooled" the sex has not been determined and both sexes might be mixed. When 'sex' is "Both" all individuals have been sexed. Finally, when 'sex' is 'Total' some individuals have been sexed but some have been not so there is a third sex category which implicitly corresponds to unsexed individuals. For instance this could happen with very young individuals for which their sex could not be determined.

Value

A list with class attribute 'GroAgeData' with the following components:

Properties	A data.frame with properties of the data, such as the species key, the type of sex, units of age, units of length, and the other optional properties
Sex 1	A data.frame with an individual key, the age, the length, and optionally other individual data
Sex 2	Optionally, the same as the previous component but for the other sex
Sex 3	Optionally, the same as the previous components but for the unsexed individuals

Note

NAs are allowed in all data column and later ignored in the modeling functions.

Author(s)

Ruben H. Roa-Ureta

Examples

```
data(ksbream)
KSream.AgeLen <- as.GroAgeData(x=ksbream,
                                    sex="Total",
                                    maleskey=1,
                                    femaleskey=2,
                                    coldate=1,
                                    colsex=9,
                                    colage=11,
                                    collen=2,
```

```

colbw=5,
colliver=7,
colgonad=8,
lentype="Total",
unitsage="Years",
unitslen="mm",
unitsbw="g",
unitsliver="g",
unitsgonad="g",
spec="KSbream")
plot(KSbream.AgeLen)

```

BlackAngler.agematdat *Black Anglerfish Age, Sex, Month, Maturity Stage Data*

Description

Black anglerfish individual-based data from the Bay of Biscay sampled from the catch of an industrial fishing fleet.

Usage

```
data("BlackAngler.agematdat")
```

Format

A data frame with 711 observations on the following 4 variables.

<code>pred</code>	Integer, age in years
<code>sex</code>	Integer, 1 for males and 2 for females
<code>month</code>	Integer, the month of capture
<code>stages</code>	Integer, stages of maturity encompassing a gradual advance from juvenile to sexually mature individual

Details

Age has been fixed by biologists examining rings in otoliths. Maturity stages have been fixed by biologists using macroscopic aspect of the fish gonads.

Source

<http://www.azti.es>

Examples

```
data(BlackAngler.agematdat)
```

BlackAngler.lenmatdat *Black Anglerfish Length, Sex, Month, Maturity Stage Data*

Description

Black anglerfish individual-based data from the Bay of Biscay sampled from the catch of an industrial fishing fleet.

Usage

```
data("BlackAngler.lenmatdat")
```

Format

A data frame with 1367 observations on the following 4 variables.

pred Numeric, total fish length in cm
sex Integer, 1 for males and 2 for females
month Integer, the month of capture
stages Integer, stages of maturity encompassing a gradual advance from juvenile to sexually mature individual

Details

Maturity stages have been fixed by biologists using macroscopic aspect of the fish gonads.

Source

<http://www.azti.es>

Examples

```
data(BlackAngler.lenmatdat)
```

BlackAngler.wgtmatdat *Black Anglerfish Body Weight, Sex, Month, Maturity Stage Data*

Description

Black anglerfish individual-based data from the Bay of Biscay sampled from the catch of an industrial fishing fleet.

Usage

```
data("BlackAngler.wgtmatdat")
```

Format

A data frame with 479 observations on the following 4 variables.

pred Numeric, fish body weight length in g
sex Integer, 1 for males and 2 for females
month Integer, the month of capture
stages Integer, stages of maturity encompassing a gradual advance from juvenile to sexually mature individual

Details

Maturity stages have been fixed by biologists using macroscopic aspect of the fish gonads.

Source

<http://www.azti.es>

Examples

```
data(BlackAngler.wgtmatdat)
```

deltamethod

First-order Taylor Series Expansion of Functions of Random Variables

Description

The delta method for approximating the standard error of a transformation $g(X)$ of a random variable $X = (x_1, x_2, \dots)$, given estimates of the mean and covariance matrix of X .

Usage

```
deltamethod(g, mean, cov, ses = TRUE)
```

Arguments

- | | |
|-------------|--|
| g | A formula representing the transformation. The variables must be labelled x_1, x_2, \dots . For example, $\sim 1 / (x_1 + x_2)$. If the transformation returns a vector, then a list of formulae representing (g_1, g_2, \dots) can be provided, for example <code>list(~ x1 + x2, ~ x1 / (x1 + x2))</code> . |
| mean | The estimated mean of X . |
| cov | The estimated covariance matrix of X . |
| ses | If TRUE, then the standard errors of $g_1(X), g_2(X), \dots$ are returned. Otherwise the covariance matrix of $g(X)$ is returned. |

Details

This function was copied from package msm. It is used in CatDyn to backtransform from the logarithm because CatDyn parameters are all estimated in the log scale to improve numerical performance. For more details see the help pages for function `deltamethod` of package `msm`.

Value

A vector containing the standard errors of $g_1(X)$, $g_2(X)$, ... or a matrix containing the covariance of $g(X)$.

Author(s)

C. H. Jackson <chris.jackson@mrc-bsu.cam.ac.uk>

Examples

#See the examples in package `msm`.

GroAgeData

Class Attribute of LifeHist Data Object

Description

To be used by `plot.GroAgeData()` to examine raw length, age data before modeling.

Usage

`GroAgeData(x, ...)`

Arguments

- | | |
|-----|--|
| x | A list object coming from <code>as.GroAgeData()</code> . |
| ... | Not used. |

Value

A class attribute

Author(s)

Ruben H. Roa-Ureta

Examples

#See example for `as.GroAgeData()`.

GroAgeExp

*Class Attribute of LifeHist Exploratory Model Object***Description**

To be used by plot.GroAgeExp() to examine the quality of initial parameter values before fitting a growth model.

Usage

```
GroAgeExp(x, ...)
```

Arguments

- x A list object coming from groageexp().
- ... Not used.

Value

A class attribute

Author(s)

Ruben H. Roa-Ureta

Examples

```
#See examples for plot.AgeGroExp()
```

groageexp

*Exploratory Growth Modeling with Age and Length Data***Description**

For a data object of class 'GroAgeData' examine the goodness of initial guessed values of model parameters by making predictions and calculating residuals.

Usage

```
groageexp(x, m, unsex.action = NULL, par, distr)
```

Arguments

x	An object of class 'GroAgeData'.
m	Character, the specific growth model to be examined, either 'vonBer' (von Bertalanffy), 'schnute1', 'schnute2', or 'schnute3'
unsex.action	Character, optionally, when there are unsexed individual, what to do with these, either 'split' (random assignment of half to males and half to females), 'males' (complete assignment to males), 'females' (complete assignment to females), or 'ignore'.
par	Numeric, the logarithm of the vector of initial parameter values.
distr	Character, the distribution of the data, either 'apnormal' (adjusted profile approximation to the normal likelihood), 'aplnormal' adjusted profile approximation to the lognormal likelihood), 'normal', 'lognormal', or 'gamma'.

Details

When the distribution of the data is 'normal', 'lognormal', or 'gamma', an additional dispersion parameter has to be provided along with the growth model parameters, and placed at the end of the parameter vector.

Value

A list with class attribute 'GroAgeExp' with the following components:

Properties	Properties of the data, passed from 'x'
Data	A data.frame with age, observed length, predicted length, and 'deviance' residuals
Data	Optionally, the same as previous component but for the other sex

Note

Model types 'schnute1', 'schnute2', 'schnute3' have 5, 3, and 2 parameters respectively. 'schnute1' is described in Arkhipkin and Roa-Ureta (2005) whereas 'schnute2' and 'schnute3' are described in Roa-Ureta (2010).

Author(s)

Ruben H. Roa-Ureta

References

- Arkhipkin, A., Roa-Ureta, R. 2005. Identification of growth models for squids. Marine and Freshwater Research 56:371-386.
- Roa-Ureta, R. 2010. A likelihood-based model of fish growth with multiple length frequency data. Journal of Agricultural, Biological and Environmental Statistics 15:416-429

Examples

```
#Schnute - Normal
data(ksbream)
KSbream.AgeLen <- as.GroAgeData(x=ksbream,
                                    sex="Total",
                                    maleskey=1,
                                    femaleskey=2,
                                    coldate=1,
                                    colsex=9,
                                    collage=11,
                                    collen=2,
                                    colbw=5,
                                    colliver=7,
                                    colgonad=8,
                                    lentype="Total",
                                    unitsage="Years",
                                    unitslen="mm",
                                    unitsbw="g",
                                    unitsliver="g",
                                    unitsgonad="g",
                                    spec="KSbream")

#par ini
l1.f <- 175
a1.f <- 1
mu.f <- 250
g1.f <- 0.15
g2.f <- 0.1
l1.m <- 175
a1.m <- 1
mu.m <- 210
g1.m <- 0.25
g2.m <- 0.1
psi.f <- 0.5
psi.m <- 0.45
par.ini <- log(c(l1.f,a1.f,mu.f,g1.f,g2.f,l1.m,a1.m,mu.m,g1.m,g2.m,psi.f,psi.m))
KSbream.AgeLen.exp <- groageexp(x=KSbream.AgeLen,
                                   unsex.action="split",
                                   m="schnute1",
                                   par=par.ini,
                                   distr="normal")
plot(KSbream.AgeLen.exp)
```

Description

A wrapper and post-processing tool that calls optimx() (from package optimx) with any of four possible versions of the growth models and any of 5 possible versions of likelihood models (as internal functions), in addition to possible multiple numerical methods for optimization and then it post-processes optimx() results and join all results in a list of lists.

Usage

```
GroAgeFit(x, m, unsex.action = NULL, par, distr, method, control = list(),
           hessian = TRUE, itnmax)
```

Arguments

x	An object of class GroAgeData. See as.GroAgeData.
m	Character, the specific growth model to be examined, either 'vonBer' (von Bertalanffy), 'schnute1', 'schnute2', or 'schnute3'
unsex.action	Character, optionally, when there are unsexed individual, what to do with these, either 'split' (random assignment of half to males and half to females), 'males' (complete assignment to males), 'females' (complete assignment to females), or 'ignore'.
par	Numeric, the logarithm of the vector of initial parameter values.
distr	Character, the distribution of the data, either 'apnormal' (adjusted profile approximation to the normal likelihood), 'aplnormal' adjusted profile approximation to the lognormal likelihood), 'normal', 'lognormal', or 'gamma'.
method	Character. Any method accepted by optimx() can be used, but some may return warnings or errors.
control	A list of control arguments to be passed to optimx().
hessian	Logical. Defaults to TRUE. If set to FALSE all numerical methods tried will fail.
itnmax	Numeric. Maximum number of iterations, to pass to optimx().

Details

When 'x' has been set with 'sex' equal to "Both" or "Total" then GroAgeFit will automatically fit separate models for females, males, and for both sexes pooled.

Care should be taken in selecting good initial values to pass in the par argument. To accomplish this LifeHist includes the GroAgeExp class, and the groageexp() and the plot.GroAgeExp() functions to graphically fine tune the initial values for model parameters.

Initial parameter values must be passed log-transformed by the user. GroAgeFit() will backtransform the maximum likelihood estimates and its numerical Hessian matrix without user intervention using the delta method.

The difference between "normal" and "apnormal", "lognormal" and "aplnormal" is that in the former the dispersion parameters is included in the likelihood function and it is a free parameter to be estimated along with the parameters of the generalized depletion model (and therefore an initial value for the dispersion has to be provided) whereas in the latter the dispersion is eliminated by using the adjusted profile likelihood approximation.

Value

A list of length four with a class attribute 'groage'.

Data	The original data and its properties
------	--------------------------------------

Initial	Initial parameter values in their original scale
Methods	The numerical methods passed to optimx()
Model	A list of length equal to one when 'sex' is 'Females', 'Males', or 'Pooled' or of length equal to three when 'sex' is 'Both' or 'Total'. Each component is a list of length equal to the number of numerical methods. The list for each numerical method is in turn a list with the type of growth model, the chosen distribution for the data, the integer code describing the success or not of convergence returned by the method, the Karush Kuhn Tucker conditions, hopefully TRUE and TRUE, the value of the Akaike Information Criterion, not comparable between different distributions, the back-transformed (from log) maximum likelihood estimates, the numerical gradients at each maximum likelihood estimate, the standard errors of backtransformed (from log) maximum likelihood estimates, and the correlation matrix of the back-transformed (from log) maximum likelihood estimates.

Note

Some effort has been made to avoid being kicked out of numerical optimization by just one numerical method that fails, so that optimization continues with other methods, but there may remain some cases when the whole optimization process is aborted by failure in just one method. Try taking out some suspicious methods and optimize again.

Author(s)

Ruben H. Roa-Ureta

Examples

```

data(ksbream)
KSream.AgeLen <- as.GroAgeData(x=ksbream,
                                    sex="Total",
                                    maleskey=1,
                                    femaleskey=2,
                                    coldate=1,
                                    colsex=9,
                                    colage=11,
                                    collen=2,
                                    colbw=5,
                                    colliver=7,
                                    colgonad=8,
                                    lentype="Total",
                                    unitsage="Years",
                                    unitslen="mm",
                                    unitsbw="g",
                                    unitsliver="g",
                                    unitsgonad="g",
                                    spec="KSream")

11.f <- 175
a1.f <- 1
mu.f <- 250

```

```

g1.f <- 0.15
g2.f <- 0.1
l1.m <- 175
a1.m <- 1
mu.m <- 210
g1.m <- 0.25
g2.m <- 0.1
psi.f <- 0.5
psi.m <- 0.45
par.ini <- log(c(l1.f,a1.f,mu.f,g1.f,g2.f,l1.m,a1.m,mu.m,g1.m,g2.m,psi.f,psi.m))
KSream.AgeLen.fit.n <- GroAgeFit(x=KSream.AgeLen,
                                    m="schnute1",
                                    unsex.action="split",
                                    par=par.ini,
                                    distr="normal",
                                    method=c("CG","spg", "Nelder-Mead"),
                                    itnmax=100)
KSream.AgeLen.pred.n.spg <- groagmod(x=KSream.AgeLen.fit.n,method="spg")
plot(KSream.AgeLen.pred.n.spg)

```

GroAgeMod*Class Attribute of LifeHist Fitted Model Object***Description**

To be used by plot.GroAgeMod() to examine results of fitting a growth model.

Usage

```
GroAgeMod(x, ...)
```

Arguments

- | | |
|-----|--|
| x | A list object coming from GroAgeFit(). |
| ... | Not used. |

Value

A class attribute

Author(s)

Ruben H. Roa-Ureta

Examples

```
#See examples for plot.AgeGroMod()
```

groagemod*Predictions from an Object of Class GroAgeMod***Description**

For a data object of class 'GroAgeMod' examine the results of model fit by making predictions and calculating residuals.

Usage

```
groagemod(x, method)
```

Arguments

- | | |
|--------|---|
| x | An object of class 'GroAgeMod'. |
| method | Character, one of the numerical methods used to fit the model with GroAgeFit. |

Details

If the sex is 'Both' or 'Total' predictions will be calculated for females, males and both sexes pooled, and if the numerical has failed to fit any of these three arrangements of the data then predictions will be calculated only for the successful fits.

Value

A list of length 3.

- | | |
|-------------|---|
| Properties | The properties of the data, information carried over from the creation of the data object with <code>as.GroAgeData</code> . |
| Model | The type of growth model, the distribution for the data, and the numerical method. |
| Predictions | A list of length one, two or three, with each component a data.frame with the age and length data, predicted length by the model, and the 'deviance' residuals. |

Author(s)

Ruben H. Roa-Ureta

Examples

```
#See examples in help pages of function GroAgeFit()
```

ksbream*King Soldier Bream Individual Biological Data*

Description

King soldier bream individual-based data from the Arabian Gulf sampled from the catch of two artisanal fishing fleets.

Usage

```
data("ksbream")
```

Format

A data frame with 797 observations on the following 14 variables.

CollectionDate Date of capture
TL.mm Total length in mm
FL.mm Fork length in mm
SL.mm Standard length in mm
TW.g Body weight in g
Ewt.g Eviscerated body weight in g
Liver.Wt.g Liver weight in g
GW.g Gonad weight in g
Sex 1 for males, 2 for females
Mature 1 for mature, 0 for juvenile
Age.yr Age in years
MaturityStage Macroscopic maturity stages

Examples

```
data(ksbream)
```

Description

From a data.frame of one continuous predictor (length, age, etc), and keys for ordinal predictor sex, month, and maturity stage, this function will build a list of variables ready to be used in a 2- or 3-parameter logistic model

Usage

```
MatCount(matdat, fem.key, mal.key, stage.key, season.key)
```

Arguments

<code>matdat</code>	A data.frame where each row is an individual fish, and the columns are a continuous predictor, and ordinal keys for sex, month, and maturity stage
<code>fem.key</code>	Integer, the ordinal key identifying females
<code>mal.key</code>	Integer, the ordinal key identifying males
<code>stage.key</code>	Integer, the ordinal key identifying the last maturity stage of juveniles. This key will split the individual into immature (all having stage <= stage.key) and mature.
<code>season.key</code>	Integer vector with two components, the first and last month of the reproductive season

Details

The year is divided into two seasons, the reproductive season and the non-reproductive season

Value

<code>mal.nrep</code>	A data.frame with the continuous predictor duplicated and sorted, a binary for mature individuals, a binary for juveniles, and the count of males in the non reproductive season
<code>mal.rep</code>	A data.frame with the continuous predictor duplicated and sorted, a binary for mature individuals, a binary for juveniles, and the count of males in the reproductive season
<code>fem.nrep</code>	A data.frame with the continuous predictor duplicated and sorted, a binary for mature individuals, a binary for juveniles, and the count of females in the non reproductive season
<code>fem.rep</code>	A data.frame with the continuous predictor duplicated and sorted, a binary for mature individuals, a binary for juveniles, and the count of females in the reproductive season

Author(s)

Ruben H. Roa-Ureta

References

R. Roa, B. Ernst, F. Tapia. 1999. Estimation of size at sexual maturity: evaluation of analytical and resampling procedures. Fishery Bulletin (US) 97:570-580.

Examples

```
data(BlackAngler.lenmatdat)
MatCount(matdat=BlackAngler.lenmatdat, fem.key=2, mal.key=1, stage.key=2,
         season.key=c(5,7))
```

MatData

Class Attribute of LifeHist Data Object

Description

To be used by plot.MatData() to examine data versus model predictions.

Usage

```
MatData(x)
```

Arguments

x An object of class MatData, generated by function MatCount().

Details

This generic function will be used to give a class to the four components of the list output by function MatCount().

Value

A class attribute.

Note

Objects of class MatData are plotted for exploration of parameter values (initial or maximum likelihood) in 2- or 3-parameter logistic regression

Author(s)

Ruben H. Roa-Ureta

Examples

```
#See example in man pages for plot.MatData().
```

MatFit	<i>Wrapper Function to Estimate a 2- or 3-Parameters Logistic Regression of Sexual Maturity</i>
--------	---

Description

Define the logistic model, pass the initial parameter values, the data, and the numerical optimization method(s) to estimate the model and to organize results in a list.

Usage

```
MatFit(p, par, matdat, method, control = ls(), itnmax)
```

Arguments

p	Integer, either 2 or 3, determining if the asymptotic proportion is assumed known at 1 or estimated.
par	Numeric vector of 2 or 3 components with initial parameter values.
matdat	A data.frame where each row is an individual fish, and the columns are a continuous predictor, and ordinal keys for sex, month, and maturity stage.
method	Character or character vector, defining the list of numerical methods to use. See help pages for function optimx().
control	List, optimization control parameters to be passed to optimx. See help for function optimx().
itnmax	Integer, maximum number of iterations, to be passed to optimx().

Details

The function controls the estimation process. From a valid value of p, it will define the proper process model, either 2-parameters or 3-parameters logistic regression. The 3-parameter model might be useful outside the reproductive season when not all adult individuals are ready to reproduce, whereas the 2-parameter model assumes that above certain value of the continuous predictor all individuals are reproducing.

The function will re-organize optimx()'s output by adding some items (AIC, standard errors, correlation matrix) and ignoring other items. The output is a list of results in a list of optimization methods.

Value

model	Type of model, matlik.2p or matlik.3p
method	Name of numerical optimization method
converg	Convergence message
kkt	The Karush-Kuhn-Tucker optimality conditions
AIC	The Akaike Information Criterion

<code>pars</code>	Maximum likelihood estimates of model parameters
<code>num.grads</code>	Numerical gradients at the maximum likelihood estimates
<code>stdev</code>	Estimated standard deviations of maximum likelihood estimates of model parameters
<code>Cor</code>	The estimated correlation matrix of maximum likelihood estimates of model parameters

Author(s)

Ruben H. Roa-Ureta

Examples

```

data(BlackAngler.lenmatdat)
BA.matlen      <- MatCount(matdat=BlackAngler.lenmatdat,
                           fem.key=2,
                           mal.key=1,
                           stage.key=2,
                           season.key=c(5,7))
plot(BA.matlen[[2]],
     pred.50=35,
     pred.95=55,
     pred.unit="Length (cm)",
     top.text="Males Rep Season",
     lwd=2, xlab="", ylab="")
par(mfrow=c(2,2), mar=c(4,4,1,1), oma=c(4,4,1,1))
plot(BA.matlen[[1]],pred.50=35,pred.95=55,pred.unit="Length (cm)",
     top.text="Males NoRep Season", lwd=2, xlab="", ylab="")
plot(BA.matlen[[2]],pred.50=35,pred.95=55,pred.unit="Length (cm)",
     top.text="Males Rep Season", lwd=2, xlab="", ylab="")
plot(BA.matlen[[3]],pred.50=85,pred.95=110,pred.unit="Length (cm)",
     top.text="Females NoRep Season", lwd=2, xlab="", ylab="")
plot(BA.matlen[[4]],pred.50=55,pred.95=75,pred.unit="Length (cm)",
     top.text="Females Rep Season", lwd=2, xlab="", ylab="")
require(optimx)
BA.matlen.mal <- MatFit(p=2,
                           par=c(35,55),
                           matdat=BA.matlen[[2]],
                           method=c("spg", "CG", "Nelder-Mead"),
                           itnmax=100)
#
plot(BA.matlen[[2]],
     pred.50=BA.matlen.mal[[1]]$par.mle[1],
     pred.95=BA.matlen.mal[[1]]$par.mle[2],
     pred.unit="Length (cm)",
     top.text="Males Reproductive Season",
     lwd=2,
     xlab="Length (cm)",
     ylab="Proportion Mature")

```

plot.GroAgeData

*Exploratory Analysis of Agen and Length Individual Data***Description**

Allows examining the relation between age and length in order to estimate individual growth models, and optionally other individual processes such as the relation between length and body weight and the timing of organ growth along the annual season.

Usage

```
## S3 method for class 'GroAgeData'
plot(x, ...)
```

Arguments

- | | |
|-----|---|
| x | An object of class 'GroAgeData' produced by function as.GroAgeData(). |
| ... | Not used. |

Value

A multipanel plot.

Author(s)

Ruben H. Roa-Ureta

Examples

```
#See examples in help pages for function as.GroAgeData()
```

plot.GroAgeExp

*Exploratory Modeling of Individual Growth with Age and Length Data***Description**

Evaluate and refine the goodness of initial parameter values before fitting growth models to data.

Usage

```
## S3 method for class 'GroAgeExp'
plot(x, ...)
```

Arguments

- | | |
|-----|---|
| x | An object of class 'GroAgeExp' created by function groageexp(). |
| ... | Not used. |

Value

A multipanel plot.

Author(s)

Ruben H. Roa-Ureta

Examples

```
#See examples for function groageexp()
```

plot.GroAgeMod

Examination of Results from Fitting Growth Models

Description

After model fit and prediction, examine model results on a graphical display.

Usage

```
## S3 method for class 'GroAgeMod'  
plot(x, ...)
```

Arguments

x	An object of class 'GroAgeMod' created by function GroAgeFit().
...	Not used.

Value

A multipanel plot.

Author(s)

Ruben H. Roa-Ureta

Examples

```
#See examples in help pages of function AgeGroFit()
```

Description

A one panel plot with data on proportion of sexual maturity and a line built with initial parameter values or with maximum likelihood estimates

Usage

```
## S3 method for class 'MatData'
plot(x, pred.50, pred.95, top.text, ...)
```

Arguments

x	An object of class MatData.
pred.50	Numeric, the predictor value at 0.5 proportion mature.
pred.95	Numeric, the predictor value at 0.95 proportion mature.
top.text	Character, to be used as main for plot.
...	Pass additional parameters to plot().

Value

A plot of data and model

Author(s)

Ruben H. Roa-Ureta

Examples

```
data(BlackAngler.lenmatdat)
BA.matlen <- MatCount(matdat=BlackAngler.lenmatdat,
                      fem.key=2,
                      mal.key=1,
                      stage.key=2,
                      season.key=c(5,7))
plot(BA.matlen[[2]],pred.50=35,pred.95=55,top.text="Males Rep Season")
```

Index

- * **& &nonlinear**
 - plot.MatData, 24
- * **~classes**
 - GroAgeData, 9
 - GroAgeExp, 10
 - GroAgeMod, 15
- * **~datasets**
 - GroAgeFit, 12
- * **~distribution**
 - GroAgeFit, 12
- * **~iplot**
 - GroAgeFit, 12
 - plot.GroAgeData, 22
 - plot.GroAgeExp, 22
 - plot.GroAgeMod, 23
- * **~manip**
 - as.GroAgeData, 4
 - GroAgeFit, 12
- * **~models**
 - groageexp, 10
 - GroAgeFit, 12
 - groagemod, 16
- * **~optimize**
 - GroAgeFit, 12
- * **datasets**
 - BlackAngler.agematdat, 6
 - BlackAngler.lenmatdat, 7
 - BlackAngler.wgtmatdat, 7
 - ksbream, 17
- * **manip**
 - MatCount, 18
- * **models**
 - MatFit, 20
 - plot.MatData, 24
- * **optimize**
 - MatFit, 20
 - plot.MatData, 24
- * **package**
 - LifeHist-package, 2
- as.GroAgeData, 4
- BlackAngler.agematdat, 6
- BlackAngler.lenmatdat, 7
- BlackAngler.wgtmatdat, 7
- deltamethod, 8
- GroAgeData, 9
- GroAgeExp, 10
- groageexp, 10
- GroAgeFit, 12
- GroAgeMod, 15
- groagemod, 16
- ksbream, 17
- LifeHist (LifeHist-package), 2
- LifeHist-package, 2
- MatCount, 18
- MatData, 19
- MatFit, 20
- plot.GroAgeData, 22
- plot.GroAgeExp, 22
- plot.GroAgeMod, 23
- plot.MatData, 24