

Package ‘RPESE’

January 20, 2025

Type Package

Title Estimates of Standard Errors for Risk and Performance Measures

Version 1.2.5

Date 2022-09-07

Author Anthony Christidis <anthony.christidis@stat.ubc.ca>,
Xin Chen <chenx26@uw.edu>

Maintainer Anthony Christidis <anthony.christidis@stat.ubc.ca>

Description Estimates of standard errors of popular risk and performance measures for asset or portfolio returns using methods as described in Chen and Martin (2021) <[doi:10.21314/JOR.2020.446](https://doi.org/10.21314/JOR.2020.446)>.

Biarch true

License GPL (>= 2)

Imports xts, zoo, boot, RPEIF, RPEGLMEN, RobStatTM

Suggests testthat, R.rsp, PerformanceAnalytics

RoxigenNote 7.2.1

VignetteBuilder R.rsp

NeedsCompilation no

Repository CRAN

Date/Publication 2022-09-08 07:22:55 UTC

Contents

DSR.SE	2
ES.SE	3
ESratio.SE	5
EstimatorSE	6
LPM.SE	8
Mean.SE	10
OmegaRatio.SE	11
printSE	13
RachevRatio.SE	14

robMean.SE	15
SD.SE	17
SemiSD.SE	18
SoR.SE	20
SR.SE	21
VaR.SE	23
VaRratio.SE	24

Index	26
--------------	-----------

DSR.SE	<i>Standard Error Estimate for Downside Sharpe Ratio (DSR) of Returns</i>
--------	---

Description

DSR.SE computes the standard error of the downside Sharpe ratio of the returns.

Usage

```
DSR.SE(
  data,
  rf = 0,
  se.method = c("IFIid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[c(1, 4)],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  corOut = c("none", "retCor", "retIFCor", "retIFCorPW")[1],
  return.coef = FALSE,
  ...
)
```

Arguments

<code>data</code>	Data of returns for one or multiple assets or portfolios.
<code>rf</code>	Risk free rate.
<code>se.method</code>	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: "IFIid" (default), "IFcor" (default), "IFcorPW", "IFcorAdapt", "BOOTiid" or "BOOTcor".
<code>cleanOutliers</code>	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if FALSE.
<code>fitting.method</code>	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
<code>d.GLM.EN</code>	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.

<code>freq.include</code>	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate."
<code>freq.par</code>	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.
<code>corOut</code>	Return correlation of the returns or the influence function transformed returns. Must be one of "retCor", "retIFCor" or "none" (default).
<code>return.coef</code>	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if FALSE.
<code>...</code>	Additional parameters.

Value

A vector or a list depending on `se.method`.

Author(s)

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
DSR.SE(edhec, se.method = c("IFIid", "IFcor"),
        cleanOutliers = FALSE,
        fitting.method = c("Exponential", "Gamma")[1])
```

Description

`ES.SE` computes the standard error of the expected shortfall of the returns.

Usage

```
ES.SE(
  data,
  p = 0.95,
  se.method = c("IFIid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[1:2],
  cleanOutliers = FALSE,
```

```

fitting.method = c("Exponential", "Gamma")[1],
d.GLM.EN = 5,
freq.include = c("All", "Decimate", "Truncate")[1],
freq.par = 0.5,
corOut = c("none", "retCor", "retIFCor", "retIFCorPW")[1],
return.coef = FALSE,
...
)

```

Arguments

<code>data</code>	Data of returns for one or multiple assets or portfolios.
<code>p</code>	Confidence level for calculation. Default value is <code>p = 0.95</code> .
<code>se.method</code>	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: " <code>IFiid</code> " (default), " <code>IFcor</code> " (default), " <code>IFcorPW</code> ", " <code>IFcorAdapt</code> ", " <code>BOOTiid</code> " or " <code>BOOTcor</code> ".
<code>cleanOutliers</code>	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if <code>FALSE</code> .
<code>fitting.method</code>	Distribution used in the standard errors computation. Should be one of " <code>Exponential</code> " (default) or " <code>Gamma</code> ".
<code>d.GLM.EN</code>	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
<code>freq.include</code>	Frequency domain inclusion criteria. Must be one of " <code>All</code> " (default), " <code>Decimate</code> " or " <code>Truncate</code> ".
<code>freq.par</code>	Percentage of the frequency used if " <code>freq.include</code> " is " <code>Decimate</code> " or " <code>Truncate</code> ". Default is 0.5.
<code>corOut</code>	Return correlation of the returns or the influence function transformed returns. Must be one of " <code>retCor</code> ", " <code>retIFCor</code> " or " <code>none</code> " (default).
<code>return.coef</code>	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if <code>FALSE</code> .
<code>...</code>	Additional parameters.

Value

A vector or a list depending on `se.method`.

Author(s)

Xin Chen, <chenx26@uw.edu>

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
ES.SE(edhec, se.method = c("IFIid", "IFcor"),
       cleanOutliers = FALSE,
       fitting.method = c("Exponential", "Gamma")[1])
```

ESratio.SE

Standard Error Estimate for Expected Shortfall Ratio (ESratio) of Returns

Description

ESratio.SE computes the standard error of the expected shortfall ratio of the returns.

Usage

```
ESratio.SE(
  data,
  alpha = 0.1,
  rf = 0,
  se.method = c("IFIid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[c(1, 4)],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  corOut = c("none", "retCor", "retIFCor", "retIFCorPW")[1],
  return.coef = FALSE,
  ...
)
```

Arguments

data	Data of returns for one or multiple assets or portfolios.
alpha	Lower tail probability.
rf	Risk-free interest rate.
se.method	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: "IFIid" (default), "IFcor", "IFcorPW", "IFcorAdapt" (default), "BOOTiid" or "BOOTcor".

<code>cleanOutliers</code>	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if FALSE.
<code>fitting.method</code>	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
<code>d.GLM.EN</code>	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
<code>freq.include</code>	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate."
<code>freq.par</code>	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.
<code>corOut</code>	Return correlation of the returns or the influence function transformed returns. Must be one of "retCor", "retIFCor" or "none" (default).
<code>return.coef</code>	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if FALSE.
<code>...</code>	Additional parameters.

Value

A vector or a list depending on `se.method`.

Author(s)

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
ESratio.SE(edhec, se.method=c("IFIid","IFcorAdapt"),
            cleanOutliers=FALSE,
            fitting.method=c("Exponential", "Gamma")[1])
```

Description

`EstimatorSE` computes the standard error for specified risk and performance measures.

Usage

```
EstimatorSE(
  data,
  estimator.fun = c("DSR", "ES", "ESratio", "LPM", "Mean", "OmegaRatio", "RachevRatio",
    "robMean", "SD", "SemiSD", "SR", "SoR", "VaR", "VaRratio")[1],
  se.method = c("IFIid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[1],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  a = 0.3,
  b = 0.7,
  return.coef = FALSE,
  ...
)
```

Arguments

<code>data</code>	Data of returns for one or multiple assets or portfolios.
<code>estimator.fun</code>	Risk or performance measure to compute estimates of standard errors.
<code>se.method</code>	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One of: "IFIid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor", or "none".
<code>cleanOutliers</code>	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default is FALSE.
<code>fitting.method</code>	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
<code>d.GLM.EN</code>	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
<code>freq.include</code>	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate."
<code>freq.par</code>	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.
<code>a</code>	First adaptive method parameter.
<code>b</code>	Second adaptive method parameter.
<code>return.coef</code>	Boolean variable to indicate whether the coefficients of the Exponential or Gamma fit are returned. Default is FALSE.
<code>...</code>	Additional parameters.

Value

A vector standard error estimates.

Author(s)

Xin Chen, <chenx26@uw.edu>
 Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the three influence functions based approaches
EstimatorSE(edhec[, "CA"], se.method = c("IFcor"),
            cleanOutliers = FALSE,
            fitting.method = c("Exponential", "Gamma")[1])
```

LPM.SE

Standard Error Estimate for Lower Partial Moment (LPM) of Returns

Description

LPM.SE computes the standard error of the LPM of the returns.

Usage

```
LPM.SE(
  data,
  const = 0,
  order = 1,
  se.method = c("IFiid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[1:2],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  corOut = c("none", "retCor", "retIFCor", "retIFCorPW")[1],
  return.coef = FALSE,
  ...
)
```

Arguments

data	Data of returns for one or multiple assets or portfolios.
const	Constant threshold.

<code>order</code>	Order for the lower partial moment (should be 1 or 2).
<code>se.method</code>	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: "IFIid" (default), "IFcor" (default), "IFcorPW", "IFcorAdapt", "BOOTiid" or "BOOTcor".
<code>cleanOutliers</code>	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if FALSE.
<code>fitting.method</code>	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
<code>d.GLM.EN</code>	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
<code>freq.include</code>	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate".
<code>freq.par</code>	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.
<code>corOut</code>	Return correlation of the returns or the influence function transformed returns. Must be one of "retCor", "retIFCor" or "none" (default).
<code>return.coef</code>	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if FALSE.
<code>...</code>	Additional parameters.

Value

A vector or a list depending on `se.method`.

Author(s)

Xin Chen, <chenx26@uw.edu>

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
LPM.SE(edhec, se.method = c("IFIid", "IFcor"),
        cleanOutliers = FALSE,
        fitting.method = c("Exponential", "Gamma")[1])
```

Mean.SE*Standard Error Estimate for Mean of Returns*

Description

Mean.SE computes the standard error of the mean of the returns.

Usage

```
Mean.SE(
  data,
  se.method = c("IFiid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[c(1, 4)],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  corOut = c("none", "retCor", "retIFCor", "retIFCorPW")[1],
  return.coef = FALSE,
  ...
)
```

Arguments

data	Data of returns for one or multiple assets or portfolios.
se.method	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: "IFiid" (default), "IFcor", "IFcorPW", "IFcorAdapt" (default), "BOOTiid" or "BOOTcor".
cleanOutliers	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if FALSE.
fitting.method	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
d.GLM.EN	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
freq.include	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate."
freq.par	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.
corOut	Return correlation of the returns or the influence function transformed returns. Must be one of "retCor", "retIFCor" or "none" (default).
return.coef	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if FALSE.
...	Additional parameters.

Value

A vector or a list depending on se.method

Author(s)

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
Mean.SE(edhec, se.method = c("IFiid","IFcorAdapt"),
         cleanOutliers = FALSE,
         fitting.method = c("Exponential", "Gamma")[1])
```

Description

`OmegaRatio.SE` computes the standard error of the Omega ratio of the returns.

Usage

```
OmegaRatio.SE(
  data,
  const = 0,
  se.method = c("IFiid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[c(1, 4)],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  corOut = c("none", "retCor", "retIFCor", "retIFCorPW")[1],
  return.coef = FALSE,
  ...
)
```

Arguments

<code>data</code>	Data of returns for one or multiple assets or portfolios.
<code>const</code>	Constant threshold.
<code>se.method</code>	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: "IFiid" (default), "IFcor", "IFcorPW", "IFcorAdapt" (default), "BOOTiid", "BOOTcor".
<code>cleanOutliers</code>	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if FALSE.
<code>fitting.method</code>	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
<code>d.GLM.EN</code>	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
<code>freq.include</code>	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate".
<code>freq.par</code>	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.
<code>corOut</code>	Return correlation of the returns or the influence function transformed returns. Must be one of "retCor", "retIFCor" or "none" (default).
<code>return.coef</code>	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if FALSE.
<code>...</code>	Additional parameters.

Value

A vector or a list depending on `se.method`.

Author(s)

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
OmegaRatio.SE(edhec, se.method = c("IFiid", "IFcorAdapt")[1],
              cleanOutliers = FALSE,
              fitting.method = c("Exponential", "Gamma")[1])
```

printSE*Formatted Output for Standard Errors Functions in RPESE*

Description

printSE returns a formatted output from standard error functions from RPESE.

Usage

```
printSE(SE.data, round.digit = 3, round.out = TRUE)
```

Arguments

SE.data	Standard error estimates output from RPESE functions.
round.digit	Number of digits for rounding.
round.out	Round data (TRUE) with round.digit number of digits. Default is TRUE.

Value

A data frame with formatted output from standard error functions from RPESE.

Author(s)

Xin Chen, <chenx26@uw.edu>

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
ES.out <- ES.SE(edhec, se.method = c("IFiid","IFcor"),
                 cleanOutliers = FALSE,
                 fitting.method = c("Exponential", "Gamma")[1])
# Print the output
printSE(ES.out)
```

RachevRatio.SE*Standard Error Estimate for Rachev Ratio of Returns*

Description

RachevRatio.SE computes the standard error of the Rachev ratio of the returns.

Usage

```
RachevRatio.SE(
  data,
  alpha = 0.1,
  beta = 0.1,
  se.method = c("IFiid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[c(1, 4)],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  corOut = c("none", "retCor", "retIFCor", "retIFCorPW")[1],
  return.coef = FALSE,
  ...
)
```

Arguments

<code>data</code>	Data of returns for one or multiple assets or portfolios.
<code>alpha</code>	Lower tail probability.
<code>beta</code>	Upper tail probability.
<code>se.method</code>	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: "IFiid" (default), "IFcor", "IFcorPW", "IFcorAdapt" (default), "BOOTiid" or "BOOTcor".
<code>cleanOutliers</code>	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if FALSE.
<code>fitting.method</code>	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
<code>d.GLM.EN</code>	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
<code>freq.include</code>	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate."
<code>freq.par</code>	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.
<code>corOut</code>	Return correlation of the returns or the influence function transformed returns. Must be one of "retCor", "retIFCor" or "none" (default).

return.coef	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if FALSE.
...	Additional parameters.

Value

A vector or a list depending on se.method.

Author(s)

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
RachevRatio.SE(edhec, se.method = c("IFIid", "IFcorAdapt"),
               cleanOutliers = FALSE,
               fitting.method = c("Exponential", "Gamma")[1])
```

robMean.SE

Standard Error Estimate for Robust Location (Mean) M-Estimator of Returns

Description

robMean.SE computes the standard error of the robust location (mean) M-estimator of the returns.

Usage

```
robMean.SE(
  data,
  family = c("mopt", "opt", "bisquare")[1],
  eff = 0.95,
  se.method = c("IFIid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[c(1, 4)],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  corOut = c("none", "retCor", "retIFCor", "retIFCorPW")[1],
```

```

  return.coef = FALSE,
  ...
)

```

Arguments

<code>data</code>	Data of returns for one or multiple assets or portfolios.
<code>family</code>	Family for robust m-estimator of location. Must be one of "mopt" (default), "opt" or "bisquare".
<code>eff</code>	Tuning parameter for the normal distribution efficiency. Default is 0.99.
<code>se.method</code>	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: "IFiid" (default), "IFcor", "IFcorPW", "IFcorAdapt" (default), "BOOTiid" or "BOOTcor".
<code>cleanOutliers</code>	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if FALSE.
<code>fitting.method</code>	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
<code>d.GLM.EN</code>	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
<code>freq.include</code>	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate."
<code>freq.par</code>	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.
<code>corOut</code>	Return correlation of the returns or the influence function transformed returns. Must be one of "retCor", "retIFCor" or "none" (default).
<code>return.coef</code>	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if FALSE.
<code>...</code>	Additional parameters.

Value

A vector or a list depending on `se.method`.

Author(s)

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```

# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for

```

```
# the two influence functions based approaches
robMean.SE(edhec, se.method = c("IFIid", "IFcorAdapt"),
            fitting.method = c("Exponential", "Gamma")[1],
            family = "mopt", eff = 0.95)
```

SD.SE

Standard Error Estimate for Standard Deviation (SD) of Returns

Description

SD.SE computes the standard error of the standard deviation of the returns.

Usage

```
SD.SE(
  data,
  se.method = c("IFIid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[1:2],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  corOut = c("none", "retCor", "retIFCor", "retIFCorPW")[1],
  return.coef = FALSE,
  ...
)
```

Arguments

<code>data</code>	Data of returns for one or multiple assets or portfolios.
<code>se.method</code>	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: "IFIid" (default), "IFcor" (default), "IFcorPW", "IFcorAdapt" (default), "BOOTiid" or "BOOTcor".
<code>cleanOutliers</code>	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if FALSE.
<code>fitting.method</code>	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
<code>d.GLM.EN</code>	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
<code>freq.include</code>	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate."
<code>freq.par</code>	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.

corOut	Return correlation of the returns or the influence function transformed returns. Must be one of "retCor", "retIFCor" or "none" (default).
return.coef	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if FALSE.
...	Additional parameters.

Value

A vector or a list depending on se.method.

Author(s)

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
SD.SE(edhec, se.method = c("IFIid", "IFcor", "IFcorAdapt"),
       cleanOutliers = FALSE,
       fitting.method = c("Exponential", "Gamma")[1])
```

SemiSD.SE

Standard Error Estimate for Semi-Standared Deviation (SemiSD) of Returns

Description

SemiSD.SE computes the standard error of the SSD of the returns.

Usage

```
SemiSD.SE(
  data,
  se.method = c("IFIid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[1:2],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  corOut = c("none", "retCor", "retIFCor", "retIFCorPW")[1],
```

```

  return.coef = FALSE,
  ...
)

```

Arguments

<code>data</code>	Data of returns for one or multiple assets or portfolios.
<code>se.method</code>	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: "IFiid" (default), "IFcor" (default), "IFcorPW", "IFcorAdapt", "BOOTiid", "BOOTcor", or "none".
<code>cleanOutliers</code>	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if FALSE.
<code>fitting.method</code>	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
<code>d.GLM.EN</code>	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
<code>freq.include</code>	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate."
<code>freq.par</code>	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.
<code>corOut</code>	Return correlation of the returns or the influence function transformed returns. Must be one of "retCor", "retIFCor" or "none" (default).
<code>return.coef</code>	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if FALSE.
<code>...</code>	Additional parameters.

Value

A vector or a list depending on `se.method`.

Author(s)

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```

# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
SemiSD.SE(edhec, se.method = c("IFiid", "IFcor"),
           cleanOutliers = FALSE,
           fitting.method = c("Exponential", "Gamma")[1])

```

Description

SoR.SE computes the standard error of the Sortino ratio of the returns.

Usage

```
SoR.SE(
  data,
  const = 0,
  threshold = c("mean", "const")[1],
  se.method = c("IFiid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[c(1, 4)],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  corOut = c("none", "retCor", "retIFCor")[1],
  return.coef = FALSE,
  ...
)
```

Arguments

<code>data</code>	Data of returns for one or multiple assets or portfolios.
<code>const</code>	Minimum acceptable return for threshold.
<code>threshold</code>	Parameter to determine whether we use a "mean" or "const" threshold.
<code>se.method</code>	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: "IFiid" (default), "IFcor", "IFcorPW", "IFcorAdapt" (default), "BOOTiid" or "BOOTcor".
<code>cleanOutliers</code>	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if FALSE.
<code>fitting.method</code>	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
<code>d.GLM.EN</code>	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
<code>freq.include</code>	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate."
<code>freq.par</code>	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.
<code>corOut</code>	Return correlation of the returns or the influence function transformed returns. Must be one of "retCor", "retIFCor" or "none" (default).

return.coef	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if FALSE.
...	Additional parameters.

Value

A vector or a list depending on se.method.

Author(s)

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
SoR.SE(edhec, se.method = c("IFIid", "IFcorAdapt"),
        cleanOutliers = FALSE,
        fitting.method = c("Exponential", "Gamma")[1])
```

Description

SR.SE computes the standard error of the Sharpe ratio of the returns.

Usage

```
SR.SE(
  data,
  rf = 0,
  se.method = c("IFIid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[c(1, 4)],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  corOut = c("none", "retCor", "retIFCor", "retIFCorPW")[1],
  return.coef = FALSE,
  ...
)
```

Arguments

<code>data</code>	Data of returns for one or multiple assets or portfolios.
<code>rf</code>	Risk free rate.
<code>se.method</code>	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: "IFIid" (default), "IFcor", "IFcorPW", "IFcorAdapt" (default), "BOOTiid" or "BOOTcor".
<code>cleanOutliers</code>	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if FALSE.
<code>fitting.method</code>	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
<code>d.GLM.EN</code>	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
<code>freq.include</code>	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate".
<code>freq.par</code>	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.
<code>corOut</code>	Return correlation of the returns or the influence function transformed returns. Must be one of "retCor", "retIFCor" or "none" (default).
<code>return.coef</code>	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if FALSE.
<code>...</code>	Additional parameters.

Value

A vector or a list depending on `se.method`.

Author(s)

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
SR.SE(edhec, se.method = c("IFIid", "IFcorAdapt"),
      cleanOutliers = FALSE,
      fitting.method = c("Exponential", "Gamma")[1])
```

VaR.SE*Standard Error Estimate for Value-at-Risk (VaR) of Returns*

Description

VaR.SE computes the standard error of the value-at-risk of the returns.

Usage

```
VaR.SE(
  data = NULL,
  alpha = 0.95,
  se.method = c("IFiid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[1:2],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  corOut = c("none", "retCor", "retIFCor", "retIFCorPW")[1],
  return.coef = FALSE,
  ...
)
```

Arguments

data	Data of returns for one or multiple assets or portfolios.
alpha	Confidence level for calculation. Default is alpha=0.95.
se.method	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: "IFiid" (default), "IFcor" (default), "IFcorPW", "IFcorAdapt", "BOOTiid" or "BOOTcor".
cleanOutliers	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if FALSE.
fitting.method	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
d.GLM.EN	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
freq.include	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate".
freq.par	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.
corOut	Return correlation of the returns or the influence function transformed returns. Must be one of "retCor", "retIFCor" or "none" (default).
return.coef	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if FALSE.
...	Additional parameters.

Value

A vector or a list depending on se.method.

Author(s)

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
VaR.SE(edhec, se.method = c("IFiid","IFcor"),
       cleanOutliers = FALSE,
       fitting.method = c("Exponential", "Gamma")[1])
```

VaRratio.SE

Standard Error Estimate for Value-at-Risk Ratio (VaRratio) of Returns

Description

VaRratio.SE computes the standard error of the value-at-risk ratio of the returns.

Usage

```
VaRratio.SE(
  data,
  alpha = 0.1,
  rf = 0,
  se.method = c("IFiid", "IFcor", "IFcorAdapt", "IFcorPW", "BOOTiid", "BOOTcor")[c(1, 4)],
  cleanOutliers = FALSE,
  fitting.method = c("Exponential", "Gamma")[1],
  d.GLM.EN = 5,
  freq.include = c("All", "Decimate", "Truncate")[1],
  freq.par = 0.5,
  corOut = c("none", "retCor", "retIFCor", "retIFCorPW")[1],
  return.coef = FALSE,
  ...
)
```

Arguments

<code>data</code>	Data of returns for one or multiple assets or portfolios.
<code>alpha</code>	The tail probability of interest.
<code>rf</code>	Risk-free interest rate.
<code>se.method</code>	A character string indicating which method should be used to compute the standard error of the estimated standard deviation. One or a combination of: "IFIid" (default), "IFcor", "IFcorPW", "IFcorAdapt" (default), "BOOTiid" or "BOOTcor".
<code>cleanOutliers</code>	Boolean variable to indicate whether the pre-whitening of the influence functions TS should be done through a robust filter. Default if FALSE.
<code>fitting.method</code>	Distribution used in the standard errors computation. Should be one of "Exponential" (default) or "Gamma".
<code>d.GLM.EN</code>	Order of the polynomial for the Exponential or Gamma fitting. Default polynomial order of 5.
<code>freq.include</code>	Frequency domain inclusion criteria. Must be one of "All" (default), "Decimate" or "Truncate."
<code>freq.par</code>	Percentage of the frequency used if "freq.include" is "Decimate" or "Truncate." Default is 0.5.
<code>corOut</code>	Return correlation of the returns or the influence function transformed returns. Must be one of "retCor", "retIFCor" or "none" (default).
<code>return.coef</code>	Boolean variable to indicate whether the coefficients of the penalized GLM fit are returned. Default if FALSE.
<code>...</code>	Additional parameters.

Value

A vector or a list depending on `se.method`.

Author(s)

Anthony-Alexander Christidis, <anthony.christidis@stat.ubc.ca>

Examples

```
# Loading data
data(edhec, package = "PerformanceAnalytics")
# Changing the data colnames
names(edhec) = c("CA", "CTA", "DIS", "EM", "EMN",
                 "ED", "FIA", "GM", "LS", "MA",
                 "RV", "SS", "FOF")
# Computing the standard errors for
# the two influence functions based approaches
VaRratio.SE(edhec, se.method = c("IFIid", "IFcorAdapt"),
            cleanOutliers = FALSE,
            fitting.method = c("Exponential", "Gamma")[1])
```

Index

DSR.SE, 2
ES.SE, 3
ESratio.SE, 5
EstimatorSE, 6
LPM.SE, 8
Mean.SE, 10
OmegaRatio.SE, 11
printSE, 13
RachevRatio.SE, 14
robMean.SE, 15
SD.SE, 17
SemiSD.SE, 18
SoR.SE, 20
SR.SE, 21
VaR.SE, 23
VaRratio.SE, 24