

Package ‘Rosenbrock’

January 20, 2025

Type Package

Title Extended Rosenbrock-Type Densities for Markov Chain Monte Carlo (MCMC) Sampler Benchmarking

Version 0.1.0

Author Martin Wiegand

Imports MASS

Maintainer Martin Wiegand <Martin.Wiegand@mrc-bsu.cam.ac.uk>

Description New Markov chain Monte Carlo (MCMC) samplers new to be thoroughly tested and their performance accurately assessed. This requires densities that offer challenging properties to the novel sampling algorithms. One such popular problem is the Rosenbrock function. However, while its shape lends itself well to a benchmark problem, no codified multivariate expansion of the density exists. We have developed an extension to this class of distributions and supplied densities and direct sampler functions to assess the performance of novel MCMC algorithms. The functions are introduced in ``An n-dimensional Rosenbrock Distribution for MCMC Testing'' by Pagani, Wiegand and Nadarajah (2019) <[arXiv:1903.09556](https://arxiv.org/abs/1903.09556)>.

License GPL-2

Encoding UTF-8

LazyData true

NeedsCompilation no

Repository CRAN

Date/Publication 2020-03-15 10:30:02 UTC

Contents

deven	2
dfull	2
dhybrid	3
reven	4
rhybrid	5

Index

6

deven

*Density Function "Even Rosenbrock Function"***Description**

Density function for the full rosenbrock function, with two vector parameters a and b.

Usage

```
deven(x,a,b,mu)
```

Arguments

x	Input vector.
mu	Density shift.
a	Parameters for odd index input.
b	Parameters for even index input.

Value

Returns the density value of the "even" Rosenbrock distribution at point x for parameters mu, a and b.

Examples

```
x = rep(1,4)
a = b = rep(2,2)
mu = rep(1,2)

deven(x = x,a = a,b = b,mu = mu)
```

dfull

*Density Function "Full Rosenbrock Function"***Description**

Density function for the full rosenbrock function, with two vector parameters a and b.

Usage

```
dfull(x,a,b,mu)
```

Arguments

x	Input vector.
mu	Density shift.
a	First parameters.
b	Second parameters.

Value

Returns the density value of the "full" Rosenbrock distribution at point x for parameters mu, a and b.

Examples

```
x = rep(1,4)
a = b = rep(2,3)
mu = 1

dfull(x = x,mu = mu,a = a,b = b)
```

dhybrid

*Density Function "Hybrid Rosenbrock Function"***Description**

Density function for the hybrid rosenbrock function, with two list of vectors parameters b and input x/ xprime.

Usage

```
dhybrid(xprime,x,a,b,mu)
```

Arguments

xprime	Central input.
x	List of input vector blocks.
mu	Density shift.
a	Parameters for xprime.
b	List of parameters corresponding to input blocks.

Value

Returns the density value of the "hybrid" Rosenbrock distribution at point x/xprime for parameters mu, a and b.

Examples

```
a <- 1
xprime <- 1
mu <- -1

x <- list(c(1,2),
           c(2,3))

b <- list(c(3,2),
           c(2,2))

dhybrid(xprime = xprime,x = x,a = a,b = b,mu = mu)
```

reven

Random Sampler for the "Even Rosenbrock Function"

Description

Random sampler for the full Rosenbrock function, with two vector parameters a and b.

Usage

```
reven(n,a,b,mu)
```

Arguments

n	Sample size.
mu	Density shift.
a	Parameters for odd index input.
b	Parameters for even index input.

Value

Returns a sample of size n from the "full" Rosenbrock distribution.

Examples

```
n = 100
a = b = rep(2,2)
mu = rep(1,2)

reven(n = n,mu = mu,a = a,b = b)
```

rhybrid*Random Sampler for the "Hybrid Rosenbrock Function"*

Description

Random Sampler for the hybrid rosenbrock function, with two list of vectors parameters b and input x/ xprime.

Usage

```
rhybrid(n,a,b,mu)
```

Arguments

n	Sample size.
mu	Density shift.
a	Parameters for xprime.
b	List of parameters corresponding to input blocks.

Value

Returns a sample of size n from the "hybrid" Rosenbrock distribution.

Examples

```
a <- 1
mu <- -1

b <- list(c(3,2),
           c(2,2))

n <- 100

rhybrid(n = n,a = a,b = b,mu = mu)
```

Index

[deven, 2](#)
[dfull, 2](#)
[dhybrid, 3](#)

[reven, 4](#)
[rhybrid, 5](#)