

Package ‘ThomasJeffersonUniv’

July 1, 2024

Type Package

Title Handy Tools for TJU/TJUH Employees

Version 0.1.3

Date 2024-07-01

Description Functions for admin needs of employees of Thomas Jefferson University and Thomas Jefferson University Hospital, Philadelphia, PA.

License GPL-2

Encoding UTF-8

Imports lubridate, stringi, stringdist, survival, timeDate, utils, writexl, zoo

Language en-US

Depends R (>= 4.4.0)

RxygenNote 7.3.2

NeedsCompilation no

Author Tingting Zhan [aut, cre, cph] (<<https://orcid.org/0000-0001-9971-4844>>)

Maintainer Tingting Zhan <tingtingzhan@gmail.com>

Repository CRAN

Date/Publication 2024-07-01 17:50:09 UTC

Contents

| | |
|------------------------------|---|
| addProbs | 2 |
| anniversary | 3 |
| asDiffTime | 4 |
| bibentry2rmd | 5 |
| checkCount | 5 |
| checkDuplicated | 6 |
| date_diffTime_ | 7 |
| date_time_ | 8 |
| hexavigesimalExcel | 8 |

| | |
|---------------------------|----|
| matchDF | 10 |
| mergeDF | 11 |
| phone10 | 12 |
| rbinds | 13 |
| sample.by.int | 14 |
| sign2 | 15 |
| sourcePath | 16 |
| splitDF | 16 |
| subset_ | 17 |
| Surv_3Date | 18 |
| TJU_Cayuse | 19 |
| TJU_Fiscal_Year | 20 |
| TJU_SchoolTerm | 20 |
| TJU_Workday | 21 |
| trimws_ | 22 |
| zip5 | 23 |

| | |
|--------------|-----------|
| Index | 24 |
|--------------|-----------|

| | |
|-----------------|--|
| addProbs | <i>Conditional and/or Marginal Probabilities</i> |
|-----------------|--|

Description

Add conditional and/or marginal probabilities to a two-way contingency table.

Usage

```
addProbs(A, margin = seq_len(nd), fmt = "%d (%.1f%%)")
```

Arguments

| | |
|--------|--|
| A | matrix of typeof integer , two-dimensional contingency table. See addmargins |
| margin | integer scalar or vector , see addmargins |
| fmt | character scalar, C-style string format with a %d and an %f%% for the counts and proportions (order enforced). |

Details

Function [addProbs](#) provides the joint, marginal (using `margin = 1:2`) and conditional (using `margin = 1L` or `margin = 2L`) probabilities of a two-dimensional contingency table.

Value

Function [addProbs](#) returns an 'addProbs' object, which inherits from [table](#) and [noquote](#).

Note

`margin.table` (which is to be renamed as `marginSums`) is much slower than `colSums`.
The use of argument `margin` is the same as `addmargins`, and different from `proportions`!

See Also

`rowSums` `colSums` `proportions`

Examples

```
addProbs(table(warpbreaks$tension))

storage.mode(VADeaths) = 'integer'
addProbs(VADeaths)
addProbs(VADeaths, margin = 1L)
rowSums(proportions(VADeaths, margin = 1L))
addmargins(VADeaths, margin = 1L)
```

anniversary

Number of Anniversaries Between Two Dates

Description

Number of anniversaries between two dates.

Usage

```
anniversary(to, from)
```

Arguments

| | |
|-------------------|---|
| <code>to</code> | an R object convertible to <code>POSIXlt</code> , end date/time |
| <code>from</code> | an R object convertible to <code>POSIXlt</code> , start date/time |

Details

1. Year difference between `from` and `to` dates are calculated
2. In either situation below, subtract one (1) year from the year difference obtained in Step 1.
 - Month of `from` is later than month of `to`;
 - Months of `from` and `to` are the same, but day of `from` is later than day of `to`.In either of such situations, the anniversary of the current year has not been reached.
3. If any element from Step 2 is negative, `stop`.

Value

Function `anniversary` returns an `integer` scalar or `vector`.

asDiffTime*Create Time Differences, Extended***Description**

To create [difftime](#) object with additional time units 'months' and 'years'.

Usage

```
asDiffTime(
  tim,
  units = names(timeUnits()),
  negative_do = stop(sQuote(deparse1(substitute(tim))), " has negative value!"),
  ...
)
```

Arguments

| | |
|--------------------------|---|
| <code>tim</code> | numeric or difftime object, similar usage as in function as.difftime |
| <code>units</code> | character scalar, similar usage as in function as.difftime , but with additional options 'months' and 'years' |
| <code>negative_do</code> | exception handling if input <code>tim</code> has negative element(s). Default is to stop |
| ... | additional parameters, currently not in use |

Details

Function [asDiffTime](#) improves function [as.difftime](#) in terms that

- If input `tim` is a [difftime](#) object, function `units_difftime<-` is called and the unit of `tim` is updated. In function [as.difftime](#), `tim` is returned directly, i.e., parameter `units` is ignored
- Time units 'months' and 'years' are supported, in addition to 'secs', 'mins', 'hours', 'days', 'weeks' supported in function [as.difftime](#). Moreover, partial matching (via function `match.arg`) is allowed, while function [as.difftime](#) requires exact matching.
- End user may choose to [stop](#) if `tim` has negative values. Function [as.difftime](#) does not check for negative `tim`.

Value

Function [asDiffTime](#) returns a [difftime](#) object.

Note

Potential name clash with function [as_difftime](#)

bibentry2rmd*R Markdown Format of citation and/or bibentry*

Description

R markdown format of a [citation](#) and/or [bibentry](#) object.

Usage

```
bibentry2rmd(x = "R")
```

Arguments

x [character](#) scalar, 'R' (default) or name of an R package

Details

Function [bibentry2rmd](#) beautifies the output from function `utils:::format.bibentry` (with option `style = 'text'`) in the following ways.

- Line break '\n' is replaced by a white space;
- Fancy quotes “,”, ‘ and ’ are removed;
- doi entries are shown as URLs with labels (in R markdown grammar).

Value

Function [bibentry2rmd](#) returns a [character](#) scalar or [vector](#).

Examples

```
bibentry2rmd('survival')
if (FALSE) { # disabled for ?devtools::check
  ap = rownames(installed.packages())
  lapply(ap, FUN = bibentry2rmd)
}
```

checkCount*Positive Counts in a [logical](#) vector*

Description

Number and percentage of positive counts in a [logical](#) vector.

Usage

```
checkCount(x)
```

Arguments

| | |
|---|----------------|
| x | logical vector |
|---|----------------|

Value

Function `checkCount` returns a `character` scalar.

Examples

```
checkCount(as.logical(infert$case))
```

| | |
|-----------------|---|
| checkDuplicated | <i>Inspect Duplicated Records in a data.frame</i> |
|-----------------|---|

Description

To inspect duplicated records in a `data.frame`.

Usage

```
checkDuplicated(
  data,
  f,
  dontshow = character(length = 0L),
  file = tempfile(pattern = "checkDuplicated_", fileext = ".xlsx"),
  ...
)
```

Arguments

| | |
|----------|---|
| data | <code>data.frame</code> |
| f | <code>formula</code> , criteria of duplication, e.g., use $\sim \text{mrn}$ to identify duplicated <code>mrn</code> , or use $\sim \text{mrn} + \text{visitdt}$ to identify duplicated <code>mrn:visitdt</code> |
| dontshow | (optional) <code>character</code> scalar or <code>vector</code> , variable names to be omitted in output diagnosis file |
| file | <code>character</code> scalar, path of diagnosis file, print out of substantial duplicates |
| ... | additional parameters, currently not in use |

Value

Function `checkDuplicated` returns a `data.frame`.

Examples

```
(d1 = data.frame(A = c(1, 1), B = c(NA_character_, 'text')))

(d2 = data.frame(A = c(1, 2), B = c(NA_character_, 'text')))
```

date_difftime_ *Concatenate a Date and a difftime Object*

Description

..

Usage

```
date_difftime_(date_, difftime_, tz = "UTC", tol = sqrt(.Machine$double.eps))
```

Arguments

| | |
|-----------|--|
| date_ | an R object containing Date information |
| difftime_ | a difftime object |
| tz | character scalar, time zone, see as.POSIXlt.Date and ISOdatetime |
| tol | numeric scalar, tolerance in finding second. Default <code>sqrt(.Machine\$double.eps)</code> as in all.equal.numeric |

Value

Function `date_difftime_` returns a [POSIXct](#) object.

Note

For now, I do not know how to force function `readxl::read_excel` to read a column as [POSIXt](#). By default, such column will be read as [difftime](#).

See `lubridate:::date.default` for the handling of year and month!

Examples

```
(x = as.Date(c('2022-09-10', '2023-01-01', NA, '2022-12-31')))
y = as.difftime(c(47580.3, NA, 48060, 30660), units = 'secs')
units(y) = 'hours'
y
date_difftime_(x, y)
```

| | |
|-------------------------|----------------------------------|
| <code>date_time_</code> | <i>Concatenate Date and Time</i> |
|-------------------------|----------------------------------|

Description

Concatenate date and time information from two objects.

Usage

```
date_time_(date_, time_)
```

Arguments

| | |
|--------------------|---|
| <code>date_</code> | an R object containing Date information |
| <code>time_</code> | an R object containing time (POSIXt) information |

Details

Function `date_time_` is useful as clinicians may put date and time in different columns.

Value

Function `date_time_` returns a **POSIXct** object.

Examples

```
(today = Sys.Date())
(y = ISOdatetime(year = c(1899, 2010), month = c(12, 3), day = c(31, 22),
                 hour = c(15, 3), min = 2, sec = 1, tz = 'UTC'))
date_time_(today, y)
```

| | |
|---------------------------------|---|
| <code>hexavigesimalExcel</code> | <i>Hexavigesimal (Base 26L) and Excel Columns</i> |
|---------------------------------|---|

Description

Convert between decimal, hexavigesimal in C-style, and hexavigesimal in Excel-style.

Usage

```
Excel2int(x)
```

```
Excel2C(x)
```

Arguments

- `x` **character** scalar or **vector**, which consists of (except missingness) only letters A to Z and a to z.

Details

Convert between decimal, hexavigesimal in C-style, and hexavigesimal in Excel-style.

| | | | | | | | | | | |
|----------------------|---|---|----|----|----|----|----|-----|-----|-----|
| Decimal | 0 | 1 | 25 | 26 | 27 | 51 | 52 | 676 | 702 | 703 |
| Hexavigesimal; C | 0 | 1 | P | 10 | 11 | 1P | 20 | 100 | 110 | 111 |
| Hexavigesimal; Excel | 0 | A | Y | Z | AA | AY | AZ | YZ | ZZ | AAA |

Function `Excel2C` converts from hexavigesimal in Excel-style to hexavigesimal in C-style.

Function `Excel2int` converts from hexavigesimal in Excel-style to decimal, using function `Excel2C` and `strtoi`.

Value

Function `Excel2int` returns an **integer vector**.

Function `Excel2C` returns a **character vector**.

References

<http://mathworld.wolfram.com/Hexavigesimal.html>

See Also

[as.hexmode](#)

Examples

```
int1 = c(NA_integer_, 1L, 25L, 26L, 27L, 51L, 52L, 676L, 702L, 703L)
Excel1 = c(NA_character_, 'A', 'Y', 'Z', 'AA', 'AY', 'AZ', 'YZ', 'ZZ', 'AAA')
C1 = c(NA_character_, '1', 'P', '10', '11', '1P', '20', '100', '110', '111')
stopifnot(identical(int1, Excel2int(Excel1)), identical(int1, strtoi(C1, base = 26L)))

int2 = c(NA_integer_, 1L, 4L, 19L, 37L, 104L, 678L)
Excel2 = c(NA_character_, 'a', 'D', 's', 'aK', 'cZ', 'Zb')
stopifnot(identical(int2, Excel2int(Excel2)))
Excel2C(Excel2)

head(swiss[Excel2int('A')])
```

matchDF*Match Rows of One [data.frame](#) to Another*

Description

To **match** the rows of one [data.frame](#) to the rows of another [data.frame](#).

Usage

```
matchDF(
  x,
  table = unique.data.frame(x),
  by = names(x),
  by.x = character(),
  by.table = character(),
  view.table = character(),
  trace = FALSE,
  ...
)
```

Arguments

| | |
|-----------------------|--|
| x | data.frame , the rows of which to be matched. |
| table | data.frame , the rows of which to be matched <i>against</i> . |
| by | character scalar or vector |
| by.x, by.table | character scalar or vector |
| view.table | (optional) character scalar or vector , variable names of table to be printed in fuzzy suggestion (if applicable) |
| trace | logical scalar, to provide detailed diagnosis information, default FALSE |
| ... | additional parameters, currently not in use |

Value

Function **matchDF** returns a [integer](#) vector

Note

Unfortunately, R does not provide case-insensitive **match**. Only case-insensitive [grep](#) methods are available.

Examples

```
DF = swiss[sample(nrow(swiss), size = 55, replace = TRUE), ]
matchDF(DF)
```

mergeDF*An Alternative Merge Operation*

Description

..

Usage

```
mergeDF(
  x,
  table,
  by = character(),
  by.x = character(),
  by.table = character(),
  ...
)
```

Arguments

| | |
|----------------|---|
| x | <code>data.frame</code> , on which new columns will be added. All rows of x will be retained in the returned object, <i>in their original order</i> . |
| table | <code>data.frame</code> , columns of which will be added to x. Not all rows of table will be included in the returned object |
| by | <code>character</code> scalar or <code>vector</code> |
| by.x, by.table | <code>character</code> scalar or <code>vector</code> |
| ... | additional parameters of <code>matchDF</code> |

Value

Function `mergeDF` returns a `data.frame`.

Note

We avoid `merge.data.frame` as much as possible, because it's slow and even `sort = FALSE` may not completely retain the original order of input x.

Examples

```
# examples inspired by ?merge.data.frame

(authors = data.frame(
  surname = c('Tukey', 'Venables', 'Tierney', 'Ripley', 'McNeil'),
  nationality = c('US', 'Australia', 'US', 'UK', 'Australia'),
  deceased = c('yes', rep('no', 4))))
(books = data.frame(
  name = c('Tukey', 'Venables', 'Tierney', 'Ripley',
```

```
'Ripley', 'McNeil', 'R Core', 'Diggle'),
title = c(
  'Exploratory Data Analysis',
  'Modern Applied Statistics',
  'LISP-STAT', 'Spatial Statistics', 'Stochastic Simulation',
  'Interactive Data Analysis', 'An Introduction to R',
  'Analysis of Longitudinal Data'),
other.author = c(
  NA, 'Ripley', NA, NA, NA, NA, 'Venables & Smith',
  'Heagerty & Liang & Scott Zeger')))

(m = mergeDF(books, authors, by.x = 'name', by.table = 'surname'))
attr(m, 'nomatch')
```

phone10

*10-digit US phone number***Description**

..

Usage

phone10(x, sep = "")

Arguments

| | |
|-----|------------------|
| x | character vector |
| sep | character scalar |

DetailsFunction **phone10** converts all US and Canada (+1) phone numbers to 10-digit.**Value**Function **phone10** returns a character vector of nchar-10.**Examples**

```
x = c(
  '+1(800)275-2273', # Apple
  '1-888-280-4331', # Amazon
  '000-000-0000'
)
phone10(x)
phone10(x, sep = '-')
```

| | |
|--------|--------------------------------------|
| rbinds | <i>Row-Bind a list of data.frame</i> |
|--------|--------------------------------------|

Description

..

Usage

```
rbinds(x, make.row.names = FALSE, ..., .id = "idx")
```

Arguments

| | |
|---------------------|--|
| x | a list of named data.frame |
| make.row.names, ... | additional parameters of rbind.data.frame |
| .id | character value to specify the name of ID column, nomenclature follows rbindlist |

Details

Yet to look into `ggplot2:::rbind_dfs` closely.

Mine is slightly slower than the fastest alternatives, but I have more checks which are useful.

Value

Function `rbinds` returns a [data.frame](#).

References

<https://stackoverflow.com/questions/2851327/combine-a-list-of-data-frames-into-one-data-frame>

Examples

```
x = list(A = swiss[1:3, 1:2], B = swiss[5:9, 1:2]) # list of 'data.frame'  
rbinds(x)  
rbinds(x, make.row.names = TRUE)
```

`sample.by.int` *Indices of Stratified Sampling*

Description

Indices of Stratified Sampling

Usage

```
sample.by.int(f, ...)
```

Arguments

| | |
|------------------|---|
| <code>f</code> | <code>factor</code> |
| <code>...</code> | potential parameters of <code>sample.int</code> |

Details

End user should use `interaction` to combine multiple `factors`.

Value

Function `sample.by.int` returns an `integer vector`.

See Also

`dplyr::slice_sample`

Examples

```
id1 = sample.by.int(state.region, size = 2L)
state.region[id1]

id2 = sample.by.int(f = with(npk, interaction(N, P)), size = 2L)
npk[id2, c('N', 'P')] # each combination selected 2x
```

sign2

*Sign of Difference of Two Objects***Description**

..

Usage

```
sign2(
  e1,
  e2,
  name1 = substitute(e1),
  name2 = substitute(e2),
  na.detail = TRUE,
  ...
)
```

Arguments

| | |
|--------------|--|
| e1, e2 | two R objects, must be both numeric vectors , or ordered factors with the same levels |
| name1, name2 | two language objects, or character scalars |
| na.detail | logical scalar, whether to provide the missingness details of e1 and e2. Default TRUE . |
| ... | additional parameters, currently not in use |

Details

Function **sign2** extends **sign** in the following ways

- two **ordered factors** can be compared;
- (detailed) information on missingness are provided.

Value

Function **sign2** returns **character vector** when **na.detail = TRUE**, or **ordered factor** when **na.detail = FALSE**.

Examples

```
lv = letters[c(1,3,2)]
x0 = letters[1:3]
x = ordered(sample(x0, size = 100, replace = TRUE), levels = lv)
y = ordered(sample(x0, size = 50, replace = TRUE), levels = lv)
x < y # base R ok
pmax(x, y) # base R okay
```

```
pmin(x, y) # base R okay
x[c(1,3)] = NA
y[c(3,5)] = NA
table(sign(unclass(y) - unclass(x)))
table(sign2(x, y))
table(sign2(x, y, na.detail = FALSE), useNA = 'always')
```

sourcePath*Source All R Files under a Directory***Description**

source all *.R and *.r files under a directory.

Usage

```
sourcePath(path, ...)
```

Arguments

| | |
|------|---|
| path | character scalar, parent directory of .R files |
| ... | additional parameters of source |

Value

Function **sourcePath** does not have a returned value

splitDF*Split **data.frame** by Row***Description**

split.data.frame into individual rows.

Usage

```
splitDF(x)
```

Arguments

| | |
|---|-------------------|
| x | data.frame |
|---|-------------------|

Value

Function **splitDF** returns a **list** of **nrow-1** **data.frames**.

Note

We use `split.data.frame` with argument `f` being `attr(x, which = 'row.names')`, `exact = TRUE` instead of `seq_len(.row_names_info(x, type = 2L))`, not only because the former is faster, but also `.rowNamesDF<-` enforces that `row.names.data.frame` must be unique.

Examples

```
splitDF(head(mtcars)) # data.frame with rownames
splitDF(head(warpbreaks)) # data.frame without rownames
splitDF(data.frame()) # exception
```

subset_

*Inspect a Subset of data.frame***Description**

..

Usage

```
subset_(x, subset, select, select_pattern, avoid, avoid_pattern)
```

Arguments

| | |
|-----------------------------|---|
| <code>x</code> | a <code>data.frame</code> |
| <code>subset</code> | logical expression, see function <code>subset.data.frame</code> |
| <code>select</code> | character vector, columns to be selected, see function <code>subset.data.frame</code> |
| <code>select_pattern</code> | regular expression <code>regex</code> for multiple columns to be selected |
| <code>avoid</code> | character vector, columns to be avoided |
| <code>avoid_pattern</code> | regular expression <code>regex</code> , for multiple columns to be avoided |

Details

Function `subset_` is different from `subset.data.frame`, such that

- if both `select` and `select_pattern` are missing, only variables mentioned in `subset` are selected;
- be able to select all variables, except those in `avoid` and `avoid_pattern`;
- always returns `data.frame`, i.e., forces `drop = FALSE`

Value

Function `subset_` returns a `data.frame`, with additional attributes

`attr(,'vline')` integer scalar, position of a vertical line (see `?flextable::vline`)

`attr(,'jhighlight')` character vector, names of columns to be `flextable::highlighted`.

Examples

```
subset_(trees, Girth > 9 & Height < 70)
subset_(swiss, Fertility > 80, avoid = 'Catholic')
subset_(warpbreaks, wool == 'K')
```

Surv_3Date

Create Surv Object using Three Dates

Description

Create right-censored **Surv** object using start, stop and censoring dates.

Usage

```
Surv_3Date(start, stop, censor, units = "years", ...)
```

Arguments

| | |
|---------------------|---|
| start, stop, censor | Date , POSIXlt or POSIXct object |
| units | (optional) character scalar, time units |
| ... | potential parameters, currently not in use |

Value

Function **Surv_3Date** returns a **Surv** object.

Examples

```
library(survival)
d1 = within(survival::udca, expr = {
  edp_yr = Surv_3Date(entry.dt, death.dt, last.dt, units = 'years')
  edp_mon = Surv_3Date(entry.dt, death.dt, last.dt, units = 'months')
})
head(d1)

noout = within(survival::udca, expr = {
  edp_bug = Surv_3Date(entry.dt, death.dt, as.Date('1991-01-01'), units = 'months')
})
subset(survival::udca, subset = entry.dt > as.Date('1991-01-01')) # check error as suggested
```

TJU_Cayuse*Award & Effort from Cayuse*

Description

Print out grant and effort from Cayuse.

Usage

```
aggregateAwards(path = "~/Downloads", fiscal.year = year(Sys.Date()))
viewProposal(path = "~/Downloads", fiscal.year = year(Sys.Date()))
viewAward(path = "~/Downloads")
award2LaTeX(path = "~/Downloads")
```

Arguments

| | |
|-------------|---|
| path | character scalar, directory of downloaded award .csv file. Default is the download directory '~/Downloads' |
| fiscal.year | integer scalar |

Details

- go to <https://jefferson.cayuse424.com/sp/index.cfm>
- My Proposals -> Submitted Proposals. Lower-right corner of screen, 'Export to CSV'. Downloaded file has name pattern '^proposals_.*\\.csv'
- My Awards -> Awards (*not* 'Active Projects'). Lower-right corner of screen, 'View All', then 'Export to CSV'. Downloaded file has name pattern '^Awards_.*\\.csv'
- My Awards -> Awards. Click into each project, under 'People' tab to find my 'Sponsored Effort'

Function **aggregateAwards** aggregates grant over different period (e.g. from Axx-xx-001, Axx-xx-002, Axx-xx-003 to Axx-xx). Then we need to manually added in our 'Sponsored Effort' in the returned .csv file.

Value

..

Examples

```
if (FALSE) {
  aggregateAwards()
  viewAward()
  viewProposal()
```

```
award2LaTeX()
}
```

| | |
|-----------------|------------------------|
| TJU_Fiscal_Year | <i>TJU Fiscal Year</i> |
|-----------------|------------------------|

Description

..

Usage

`TJU_Fiscal_Year(x)`

Arguments

| | |
|---|-----------------------------|
| x | <code>integer</code> scalar |
|---|-----------------------------|

Value

Function `TJU_Fiscal_Year` returns a length-two `Date vector`, indicating the start (July 1 of the previous calendar year) and end date (June 30) of a fiscal year.

Examples

`TJU_Fiscal_Year(2022L)`

| | |
|----------------|------------------------|
| TJU_SchoolTerm | <i>TJU School Term</i> |
|----------------|------------------------|

Description

..

Usage

`TJU_SchoolTerm(x)`

Arguments

| | |
|---|--------------------------|
| x | <code>Date</code> object |
|---|--------------------------|

Value

`TJU_SchoolTerm` returns a `character vector`

Examples

```
TJU_SchoolTerm(as.Date(c('2021-03-14', '2022-01-01', '2022-05-01')))
```

TJU_Workday

Thomas Jefferson University Workdays

Description

To summarize the number of workdays, weekends, holidays and vacations in a given time-span (e.g., a month or a quarter of a year).

Usage

```
TJU_Workday(x, vacations)
```

Arguments

- x character scalar or vector (e.g., '2021-01' for January 2021, '2021 Q1' for 2021 Q1 (January to March)), or integer scalar or vector (e.g., 2021L for year 2021); The time-span to be summarized. Objects of classes `yearqtr` and `yearmon` are also accepted.
- vacations Date vector, vacation days

Details

Function `TJU_Workday` summarizes the workdays, weekends, Jefferson paid holidays (New Year's Day, Martin Luther King, Jr. Day, Memorial Day, Fourth of July, Labor Day, Thanksgiving and Christmas) and your vacation (e.g., sick, personal, etc.) days (if any), in a given time-span.

Per Jefferson policy (source needed), if a holiday is on Saturday, then the preceding Friday is considered to be a weekend day. If a holiday is on Sunday, then the following Monday is considered to be a weekend day.

Value

Function `TJU_Workday` returns a factor.

Examples

```
table(TJU_Workday(c('2021-01', '2021-02')))

tryCatch(TJU_Workday(c('2019-10', '2019-12')), error = identity)
table(c(TJU_Workday('2019-10'), TJU_Workday('2019-12'))) # work-around

table(TJU_Workday('2022-12'))

table(TJU_Workday('2022 Q1', vacations = seq.Date(
  from = as.Date('2022-03-14'), to = as.Date('2022-03-18'), by = 1)))
```

```
table(TJU_Workday('2022 Q2', vacations = as.Date(c(
  '2022-05-22', '2022-05-30', '2022-06-01', '2022-07-04'))))

table(TJU_Workday(2021L))
```

trimws_

Remove Leading/Trailing and Duplicated (Symbols that Look Like) White Spaces

Description

To remove leading/trailing and duplicated (symbols that look like) white spaces.
More aggressive than function [trimws](#).

Usage

```
trimws_(x)
```

Arguments

| | |
|----------------|--|
| <code>x</code> | an object with <code>typeof</code> being character |
|----------------|--|

Details

Function [trimws_](#) is more aggressive than [trimws](#), that it removes

- duplicated white spaces
- symbols that look like white space, such as \u00a0 (no-break space)

Value

Function [trimws_](#) returns an object of `typeof character`.

Note

`gsub` keeps [attributes](#)

Examples

```
(x = c(A = ' a  b  ', b = 'a .  s', ' a ,  b ; ', '\u00a0ab '))
base::trimws(x)
# raster::trim(x) # do not want to 'Suggests'
trimws_(x)

(xm = matrix(x, nrow = 2L))
trimws_(xm)
```

```
#library(microbenchmark)
#microbenchmark(trimws(x), trimws_(x))
```

zip5

5-digit US Zip Code

Description

..

Usage

zip5(x)

Arguments

x character vector

Details

Function `zip5` converts all US zip codes to 5-digit.

Value

Function `zip5` returns a character vector of nchar-5.

Examples

```
zip5(c('14901', '41452-1423'))
```

Index

.rowNamesDF<-, 17
addmargins, 2, 3
addProbs, 2, 2
aggregateAwards, 19
aggregateAwards (TJU_Cayuse), 19
all.equal.numeric, 7
anniversary, 3, 3
as.difftime, 4
as.hexmode, 9
as.POSIXlt.Date, 7
as_difftime, 4
asDifftime, 4, 4
attributes, 17, 22
award2LaTeX (TJU_Cayuse), 19
bibentry, 5
bibentry2rmd, 5, 5
character, 2, 4–7, 9–13, 15–23
checkCount, 5, 6
checkDuplicated, 6, 6
citation, 5
colSums, 3
data.frame, 6, 10, 11, 13, 16, 17
Date, 3, 7, 8, 18, 20, 21
date_difftime_, 7, 7
date_time_, 8, 8
difftime, 4, 7
Excel2C, 9
Excel2C (hexavigesimalExcel), 8
Excel2int, 9
Excel2int (hexavigesimalExcel), 8
expression, 17
factor, 14, 15, 21
formula, 6
grep, 10
gsub, 22
hexavigesimalExcel, 8
integer, 2, 3, 9, 10, 14, 17, 19–21
interaction, 14
ISOdatetime, 7
language, 15
levels, 15
list, 13, 16
logical, 5, 6, 10, 15, 17
margin.table, 3
marginSums, 3
match, 10
match.arg, 4
matchDF, 10, 10, 11
matrix, 2
merge.data.frame, 11
mergeDF, 11, 11
nchar, 12, 23
noquote, 2
nrow, 16
numeric, 4, 7, 15
ordered, 15
phone10, 12, 12
POSIXct, 7, 8, 18
POSIXlt, 3, 18
POSIXt, 7, 8
proportions, 3
rbind.data.frame, 13
rbindlist, 13
rbinds, 13, 13
regex, 17
row.names.data.frame, 17
rowSums, 3

sample.by.int, 14, 14
sample.int, 14
sign, 15
sign2, 15, 15
source, 16
sourcePath, 16, 16
split.data.frame, 16, 17
splitDF, 16, 16
stop, 3, 4
strtoi, 9
subset.data.frame, 17
subset_, 17, 17
Surv, 18
Surv_3Date, 18, 18

table, 2
TJU_Cayuse, 19
TJU_Fiscal_Year, 20, 20
TJU_SchoolTerm, 20, 20
TJU_Workday, 21, 21
trimws, 22
trimws_, 22, 22
typeof, 2, 22

units_difftime<-, 4

vector, 2, 3, 5, 6, 9–12, 14, 15, 17, 20, 21, 23
viewAward (TJU_Cayuse), 19
viewProposal (TJU_Cayuse), 19

yearmon, 21
yearqtr, 21

zip5, 23, 23