

# Package ‘aloom’

January 8, 2024

**Title** All Leave-One-Out Models

**Version** 0.1.1

**Description** Creates all leave-one-out models and produces predictions for test samples.

**Imports** glmnet, randomForest, stats, parallel

**License** GPL-2

**Encoding** UTF-8

**RoxygenNote** 7.2.3

**Suggests** testthat (>= 3.0.0)

**Config/testthat.edition** 3

**URL** <https://www.rcc.org.rs/aloom.html>

**NeedsCompilation** no

**Author** Damjan Krstajic [aut, cre] (<<https://orcid.org/0000-0002-7381-8570>>)

**Maintainer** Damjan Krstajic <Damjan.Krstajic@rcc.org.rs>

**Repository** CRAN

**Date/Publication** 2024-01-08 19:30:02 UTC

## R topics documented:

aloom	1
<b>Index</b>	<b>3</b>

---

aloom *All Leave-One-Out Models*

---

### Description

Creates a predictive model for a training set, as well as all leave-one-out predictive models. Produces predictions of all models (original and all leave one-out) for a test set.

**Usage**

```
aloom(train.x, train.y, test.x, method, model.params, mc.cores = 1, seed = 1)
```

**Arguments**

<code>train.x</code>	input matrix, of dimension nobs x nvars; each row is an observation vector.
<code>train.y</code>	response variable; binary factor of the same length as nrow( <code>train.x</code> )
<code>test.x</code>	Matrix of new values for <code>train.x</code> at which predictions are to be made. Must be a matrix.
<code>method</code>	name of the model. Currently allowed values are "rf" and "glmnet"
<code>model.params</code>	list of model parameters
<code>mc.cores</code>	number of cores
<code>seed</code>	seed number, default=1

**Value**

A list containing `predicted.y`, `predicted.prob.y` and `aloom.probs`

**Examples**

```
library(randomForest)
x1 <- matrix(rnorm(100 * 20), 100, 20)
x2 <- matrix(rnorm(30 * 20), 30, 20)
y1 <- as.factor(sample(c("POS","NEG"), 100, replace = TRUE))
vnames <- paste0("V",seq(20))
colnames(x1) <- vnames
colnames(x2) <- vnames
rownames(x1) <- paste0("train",seq(nrow(x1)))
rownames(x2) <- paste0("test",seq(nrow(x2)))
model.params <- list(ntree=100)
fit <- aloom(x1,y1,x2,method="rf",model.params)
```

# **Index**

aloom, 1