

Package ‘campsis’

April 4, 2025

Type Package

Title Generic PK/PD Simulation Platform CAMPSIS

Version 1.7.0

Description A generic, easy-to-use and intuitive

pharmacokinetic/pharmacodynamic (PK/PD) simulation platform based on R packages 'rxode2' and 'mrgsolve'. CAMPSIS provides an abstraction layer over the underlying processes of writing a PK/PD model, assembling a custom dataset and running a simulation. CAMPSIS has a strong dependency to the R package 'campsismod', which allows to read/write a model from/to files and adapt it further on the fly in the R environment. Package 'campsis' allows the user to assemble a dataset in an intuitive manner. Once the user's dataset is ready, the package is in charge of preparing the simulation, calling 'rxode2' or 'mrgsolve' (at the user's choice) and returning the results, for the given model, dataset and desired simulation settings.

License GPL (>= 3)

URL <https://github.com/Calvagone/campsis>,
<https://calvagone.github.io/>,
<https://calvagone.github.io/campsis.doc/>

BugReports <https://github.com/Calvagone/campsis/issues>

Depends campsismod (>= 1.2.0), R (>= 4.0.0)

Imports assertthat, digest, dplyr, furrr, future, ggplot2, MASS,
methods, progressr, purrr, rlang, stats, tibble, tidyverse

Suggests bookdown, devtools, gridExtra, knitr, mrgsolve, pkgdown,
rmarkdown, roxygen2, rxode2, stringr, testthat, tictoc, vdiffR,
xfun

VignetteBuilder knitr

Encoding UTF-8

Language en-US

LazyData true

RoxigenNote 7.3.2

Collate 'global.R' 'utilities.R' 'time_utilities.R' 'check.R'
 'generic.R' 'data.R' 'seed.R' 'distribution.R'
 'dataset_config.R' 'time_entry.R' 'repeated_schedule.R'
 'occasion.R' 'occasions.R' 'treatment_iv.R' 'treatment_ivs.R'
 'dose_adaptation.R' 'dose_adaptations.R' 'treatment_entry.R'
 'treatment.R' 'observations.R' 'observations_set.R'
 'covariate.R' 'covariates.R' 'bootstrap.R' 'protocol.R' 'arm.R'
 'arms.R' 'event.R' 'events.R' 'scenario.R' 'scenarios.R'
 'simulation_engine.R' 'dataset.R' 'event_logic.R'
 'dataset_summary.R' 'outfun.R' 'hardware_settings.R'
 'simulation_progress.R' 'solver_settings.R' 'nocb_settings.R'
 'declare_settings.R' 'progress_settings.R'
 'internal_settings.R' 'simulation_settings.R' 'plan_setup.R'
 'simulate_preprocess.R' 'simulate.R' 'results_processing.R'
 'default_plot.R'

NeedsCompilation no**Author** Nicolas Luyckx [aut, cre]**Maintainer** Nicolas Luyckx <nicolas.luyckx@calvagone.com>**Repository** CRAN**Date/Publication** 2025-04-04 17:10:02 UTC

Contents

applyCompartimentCharacteristics	5
Arm	6
arm-class	6
arms-class	7
BinomialDistribution	7
Bolus	7
bolus-class	8
bolus_wrapper-class	9
Bootstrap	9
bootstrap-class	10
BootstrapDistribution	10
bootstrap_distribution-class	11
campsis_handler	11
ConstantDistribution	11
constant_distribution-class	12
convertTime	12
Covariate	13
covariate-class	13
covariates-class	13
CyclicSchedule	14
cyclic_schedule-class	14
Dataset	15

dataset-class	15
DatasetConfig	16
dataset_config-class	16
days	17
Declare	17
declare_settings-class	18
DiscreteDistribution	18
distribution-class	18
DoseAdaptation	19
dose_adaptation-class	19
dose_adaptations-class	19
dosingOnly	20
EtaDistribution	20
Event	21
event-class	21
EventCovariate	22
Events	22
events-class	22
event_covariate-class	23
FixedDistribution	23
fixed_covariate-class	23
fixed_distribution-class	23
FunctionDistribution	24
function_distribution-class	24
generateIIV	25
generateIIV_	25
getAvailableTimeUnits	26
getCovariates	26
getEventCovariates	27
getFixedCovariates	27
getIOVs	28
getOccasions	29
getSeedForDatasetExport	29
getSeedForIteration	30
getSeedForParametersSampling	30
getSplittingConfiguration	31
getTimes	31
getTimeVaryingCovariates	32
Hardware	33
hardware_settings-class	34
hours	34
Infusion	35
infusion-class	36
infusion_wrapper-class	36
internal_settings-class	36
IOV	37
length,arm-method	37
length,cyclic_schedule-method	38

length,dataset-method	38
length,repeat_at_schedule-method	39
LogNormalDistribution	39
minutes	40
months	40
mrgsolve_engine-class	40
nhanes	41
NOCB	41
nocb_settings-class	42
NormalDistribution	42
Observations	43
observations-class	43
observations_set-class	43
obsOnly	44
Occasion	44
occasion-class	45
occasions-class	45
Outfun	45
output_function-class	46
ParameterDistribution	46
PI	47
Progress	47
progress_settings-class	48
protocol-class	48
RepeatAtSchedule	48
repeated_schedule-class	49
repeatSchedule	49
repeat_at_schedule-class	50
retrieveParameterValue	50
rnode_engine-class	51
sample	51
scatterPlot	52
Scenario	53
scenario-class	53
Scenarios	54
scenarios-class	54
seconds	54
setLabel	55
setSubjects	55
Settings	56
setupPlanDefault	56
setupPlanSequential	57
shadedPlot	57
simulate	58
SimulationProgress	62
simulation_engine-class	63
simulation_progress-class	63
simulation_settings-class	64

<i>applyCompartmentCharacteristics</i>	5
Solver	64
solver_settings-class	65
spaghettiPlot	65
standardiseTime	66
TimeVaryingCovariate	66
time_varying_covariate-class	67
treatment-class	67
treatment iov-class	67
treatment iovs-class	67
undefined_distribution-class	68
undefined_schedule-class	68
UniformDistribution	68
unwrapTreatment	69
updateADDL	70
updateAmount	71
updateII	72
updateRepeat	73
VPC	74
vpcPlot	74
weeks	75
years	75
Index	76

applyCompartmentCharacteristics

Apply compartment characteristics from model. In practice, only compartment infusion duration needs to be applied.

Description

Apply compartment characteristics from model. In practice, only compartment infusion duration needs to be applied.

Usage

```
applyCompartmentCharacteristics(table, properties)
```

Arguments

table	current dataset
properties	compartment properties from model

Value

updated dataset

Arm	<i>Create a treatment arm.</i>
------------	--------------------------------

Description

Create a treatment arm.

Usage

```
Arm(id = as.integer(NA), subjects = 1, label = as.character(NA))
```

Arguments

- | | |
|-----------------|---|
| id | unique identifier for this arm (available through dataset), integer. If NA (default), this identifier is auto-incremented. |
| subjects | number of subjects in arm, integer |
| label | arm label, single character string. If set, this label will be output in the ARM column of CAMPSIS instead of the identifier. |

Value

an arm

arm-class	<i>Arm class.</i>
------------------	-------------------

Description

Arm class.

Slots

- | | |
|-------------------|------------------------------------|
| id | arm unique ID, integer |
| subjects | number of subjects in arm, integer |
| label | arm label, single character string |
| protocol | protocol |
| covariates | covariates |
| bootstrap | covariates to be bootstrapped |

arms-class

Arms class.

Description

Arms class.

BinomialDistribution *Binomial distribution.*

Description

Binomial distribution.

Usage

`BinomialDistribution(trials, prob)`

Arguments

trials	number of Bernoulli trials per observation (=subject), integer
prob	probability of success for each trial

Value

a binomial distribution

Bolus

Create one or several bolus(es).

Description

Create one or several bolus(es).

Usage

```
Bolus(
  time,
  amount,
  compartment = NULL,
  f = NULL,
  lag = NULL,
  ii = NULL,
  addl = NULL,
  wrap = TRUE,
  ref = NULL,
  rep = NULL
)
```

Arguments

time	treatment time(s), numeric value or vector. First treatment time if used together with ii and addl.
amount	amount to give as bolus, single numeric value
compartment	compartment index or name to give the bolus(es). A vector of integers or names can be used for a complex model administration.
f	fraction of dose amount, list of distributions (one per compartment)
lag	dose lag time, list of distributions (one per compartment)
ii	inter-dose interval, requires argument 'time' to be a single numeric value
addl	number of additional doses, requires argument 'time' to be a single integer value
wrap	if TRUE, the bolus wrapper will be stored as is in the dataset, otherwise, it will be split into a list of boluses distinct in time. Default is TRUE.
ref	any reference name used to identify this bolus, single character value
rep	repeat the base dosing schedule several times, a 'repeated schedule' object is expected. Default is NULL (no repetition).

Value

a single bolus or a list of boluses

Description

Bolus class.

bolus_wrapper-class *Bolus wrapper class.*

Description

Bolus wrapper class.

Bootstrap *Create a bootstrap object.*

Description

Create a bootstrap object.

Usage

```
Bootstrap(  
  data,  
  id = "BS_ID",  
  replacement = FALSE,  
  random = FALSE,  
  export_id = FALSE  
)
```

Arguments

<code>data</code>	data frame to be bootstrapped. It must have a unique identifier column named according to the specified argument 'id' (default value is 'BS_ID'). Other columns are covariates to bootstrap. They must all be numeric. Whatever the configuration of the bootstrap, these covariates are always read row by row and belong to a same individual.
<code>id</code>	unique identifier column name in data
<code>replacement</code>	values can be reused or not when drawn, logical
<code>random</code>	values are drawn randomly, logical
<code>export_id</code>	tell CAMPSIS if the identifier 'BS_ID' must be output or not, logical

Value

a bootstrap object

bootstrap-class *Bootstrap class.*

Description

Bootstrap class.

Slots

data data frame to be bootstrapped. Column 'BS_ID' is mandatory and corresponds to the original row ID from the bootstrap. It must be numeric and unique. Other columns are covariates to be bootstrapped (row by row).

replacement values can be reused or not, logical

random values are drawn randomly, logical

export_id tell CAMPSIS if 'BS_ID' must be exported into the dataset, logical

BootstrapDistribution *Create a bootstrap distribution. During function sampling, CAMPSIS will generate values depending on the given data and arguments.*

Description

Create a bootstrap distribution. During function sampling, CAMPSIS will generate values depending on the given data and arguments.

Usage

```
BootstrapDistribution(data, replacement = FALSE, random = FALSE)
```

Arguments

data	values to draw, numeric vector
replacement	values can be reused or not, logical
random	values are drawn randomly, logical

Value

a bootstrap distribution

bootstrap_distribution-class
Bootstrap distribution class.

Description

Bootstrap distribution class.

Slots

`data` values to draw, numeric vector
`replacement` values can be reused or not, logical
`random` values are drawn randomly, logical

`campsis_handler` *Suggested Campsis handler for showing the progress bar.*

Description

Suggested Campsis handler for showing the progress bar.

Usage

`campsis_handler()`

Value

a progressr handler list

`ConstantDistribution` *Create a constant distribution. Its value will be constant across all generated samples.*

Description

Create a constant distribution. Its value will be constant across all generated samples.

Usage

`ConstantDistribution(value)`

Arguments

`value` covariate value, single numeric value

Value

a constant distribution (same value for all samples)

constant_distribution-class

Constant distribution class.

Description

Constant distribution class.

Slots

value covariate value, single numeric value

convertTime

Convert numeric time vector based on the provided units.

Description

Convert numeric time vector based on the provided units.

Usage

```
convertTime(x, from, to)
```

Arguments

x	numeric time vector
from	unit of x, single character value
to	destination unit, single character value

Value

numeric vector with the converted times

Covariate	<i>Create a non time-varying (fixed) covariate.</i>
-----------	---

Description

Create a non time-varying (fixed) covariate.

Usage

```
Covariate(name, distribution)
```

Arguments

name	covariate name, single character value
distribution	covariate distribution

Value

a fixed covariate

covariate-class	<i>Covariate class.</i>
-----------------	-------------------------

Description

Covariate class.

Slots

name	covariate name, single character value
distribution	covariate distribution

covariates-class	<i>Covariates class.</i>
------------------	--------------------------

Description

Covariates class.

CyclicSchedule *Cyclic schedule constructor.*

Description

Cyclic schedule constructor.

Usage

```
CyclicSchedule(duration, repetitions)
```

Arguments

duration	duration of the cycle, numeric value
repetitions	number of additional repetitions to the base pattern, integer value

Value

a cyclic schedule

cyclic_schedule-class *Cyclic schedule class.*

Description

Cyclic schedule class.

Slots

duration	duration of the cycle, numeric value
repetitions	number of additional repetitions to the base pattern, integer value

Dataset	<i>Create a dataset.</i>
---------	--------------------------

Description

Create a dataset.

Usage

```
Dataset(subjects = NULL, label = as.character(NA))
```

Arguments

subjects	number of subjects in the default arm
label	label of the default arm, NA by default

Value

a dataset

dataset-class	<i>Dataset class.</i>
---------------	-----------------------

Description

Dataset class.

Slots

arms	a list of treatment arms
config	dataset configuration for export
iiv	data frame containing the inter-individual variability (all ETAS) for the export

DatasetConfig	<i>Create a dataset configuration. This configuration allows CAMPSIS to know which are the default depot and observed compartments.</i>
---------------	---

Description

Create a dataset configuration. This configuration allows CAMPSIS to know which are the default depot and observed compartments.

Usage

```
DatasetConfig(
  defDepotCmt = 1,
  defObsCmt = 1,
  exportTSLD = FALSE,
  exportTDOS = FALSE,
  timeUnitDataset = "hour",
  timeUnitExport = "hour"
)
```

Arguments

defDepotCmt	default depot compartment, integer
defObsCmt	default observation compartment, integer
exportTSLD	export column TSLD (time since last dose), logical
exportTDOS	export column TDOS (time of last dose), logical
timeUnitDataset	unit of time in dataset, character ('hour' by default)
timeUnitExport	unit of time in export, character ('hour' by default)

Value

a dataset configuration

dataset_config-class *Dataset configuration class.*

Description

Dataset configuration class.

Slots

```
def_depot_cmt default depot compartment, integer  
def_obs_cmt default observation compartment, integer  
export_tsld export column TSLD, logical  
export_tdos export column TDOS, logical  
time_unit_dataset unit of time in dataset, character ('hour' by default)  
time_unit_export unit of time in export, character ('hour' by default)
```

days *Convert days to hours.*

Description

Convert days to hours.

Usage

```
days(x)
```

Arguments

x numeric vector in days

Value

numeric vector in hours

Declare *Create declare settings.*

Description

Create declare settings.

Usage

```
Declare(variables = character(0))
```

Arguments

variables uninitialized variables to be declared, only needed with mrgsolve

Value

Declare settings

`declare_settings-class`

Declare settings class.

Description

Declare settings class.

Slots

`variables` uninitialized variables to be declared, only needed with `mrgsolve`

`DiscreteDistribution` *Discrete distribution.*

Description

Discrete distribution.

Usage

`DiscreteDistribution(x, prob, replace = TRUE)`

Arguments

- `x` vector of one or more integers from which to choose
- `prob` a vector of probability weights for obtaining the elements of the vector being sampled
- `replace` should sampling be with replacement, default is TRUE

Value

a discrete distribution

`distribution-class` *Distribution class. See this class as an interface.*

Description

Distribution class. See this class as an interface.

DoseAdaptation *Create a dose adaptation.*

Description

Create a dose adaptation.

Usage

```
DoseAdaptation(formula, compartments = NULL)
```

Arguments

- formula formula to apply, single character string, e.g. "AMT*WT"
compartments compartment indexes or names where the formula needs to be applied, integer or character vector. Default is NULL (formula applied on all compartments)

Value

a fixed covariate

dose_adaptation-class *Dose adaptation class.*

Description

Dose adaptation class.

Slots

- formula formula to apply, single character string, e.g. "AMT*WT"
compartments compartment numbers where the formula needs to be applied

dose_adaptations-class
 Dose adaptations class.

Description

Dose adaptations class.

dosingOnly*Filter CAMPSIS output on dosing rows.***Description**

Filter CAMPSIS output on dosing rows.

Usage

```
dosingOnly(x)
```

Arguments

x	data frame, CAMPSIS output
---	----------------------------

Value

a data frame with the dosing rows

EtaDistribution

Create an ETA distribution. The resulting distribution is a normal distribution, with mean=0 and sd=sqrt(OMEGA).

Description

Create an ETA distribution. The resulting distribution is a normal distribution, with mean=0 and sd=sqrt(OMEGA).

Usage

```
EtaDistribution(model, omega)
```

Arguments

model	model
omega	corresponding THETA name, character

Value

an ETA distribution

Event	<i>Create an interruption event.</i>
-------	--------------------------------------

Description

Create an interruption event.

Usage

```
Event(name = NULL, times, fun, debug = FALSE)
```

Arguments

name	event name, character value
times	interruption times, numeric vector
fun	event function to apply at each interruption
debug	output the variables that were changed through this event

Value

an event definition

event-class	<i>Event class.</i>
-------------	---------------------

Description

Event class.

Slots

name	event name, character value
times	interruption times, numeric vector
fun	event function to apply at each interruption
debug	output the variables that were changed through this event

EventCovariate	<i>Create an event covariate. These covariates can be modified further in interruption events.</i>
----------------	--

Description

Create an event covariate. These covariates can be modified further in interruption events.

Usage

```
EventCovariate(name, distribution)
```

Arguments

name	covariate name, character
distribution	covariate distribution at time 0

Value

a time-varying covariate

Events	<i>Create a list of interruption events.</i>
--------	--

Description

Create a list of interruption events.

Usage

```
Events()
```

Value

a events object

events-class	<i>Events class.</i>
--------------	----------------------

Description

Events class.

event_covariate-class *Event covariate class.*

Description

Event covariate class.

FixedDistribution *Create a fixed distribution. Each sample will be assigned a fixed value coming from vector 'values'.*

Description

Create a fixed distribution. Each sample will be assigned a fixed value coming from vector 'values'.

Usage

FixedDistribution(values)

Arguments

values covariate values, numeric vector (1 value per sample)

Value

a fixed distribution (1 value per sample)

fixed_covariate-class *Fixed covariate class.*

Description

Fixed covariate class.

fixed_distribution-class
 Fixed distribution class.

Description

Fixed distribution class.

Slots

values covariate values, numeric vector (1 value per sample)

FunctionDistribution *Create a function distribution. During distribution sampling, the provided function will be responsible for generating values for each sample. If first argument of this function is not the size (n), please tell which argument corresponds to the size 'n' (e.g. list(size="n")).*

Description

Create a function distribution. During distribution sampling, the provided function will be responsible for generating values for each sample. If first argument of this function is not the size (n), please tell which argument corresponds to the size 'n' (e.g. list(size="n")).

Usage

```
FunctionDistribution(fun, args)
```

Arguments

fun	function name, character (e.g. 'rnorm')
args	list of arguments (e.g list(mean=70, sd=10))

Value

a function distribution

function_distribution-class
Function distribution class.

Description

Function distribution class.

Slots

fun	function name, character (e.g. 'rnorm')
args	list of arguments (e.g list(mean=70, sd=10))

generateIIV*Generate IIV matrix for the given Campsis model.*

Description

Generate IIV matrix for the given Campsis model.

Usage

```
generateIIV(model, n, offset = 0)
```

Arguments

model	Campsis model
n	number of subjects
offset	if specified, resulting ID will be ID + offset

Value

IIV data frame with ID column

generateIIV_*Generate IIV matrix for the given OMEGA matrix.*

Description

Generate IIV matrix for the given OMEGA matrix.

Usage

```
generateIIV_(omega, n)
```

Arguments

omega	omega matrix
n	number of subjects

Value

IIV data frame

`getAvailableTimeUnits` *Return the list of available time units.*

Description

Return the list of available time units.

Usage

```
getAvailableTimeUnits()
```

Value

character vector

`getCovariates` *Get all covariates (fixed / time-varying / event covariates).*

Description

Get all covariates (fixed / time-varying / event covariates).

Usage

```
getCovariates(object)

## S4 method for signature 'covariates'
getCovariates(object)

## S4 method for signature 'arm'
getCovariates(object)

## S4 method for signature 'arms'
getCovariates(object)

## S4 method for signature 'dataset'
getCovariates(object)
```

Arguments

`object` any object

Value

all covariates from object

getEventCovariates *Get all event-related covariates.*

Description

Get all event-related covariates.

Usage

```
getEventCovariates(object)

## S4 method for signature 'covariates'
getEventCovariates(object)

## S4 method for signature 'arm'
getEventCovariates(object)

## S4 method for signature 'arms'
getEventCovariates(object)

## S4 method for signature 'dataset'
getEventCovariates(object)
```

Arguments

object any object

Value

all event-related covariates from object

getFixedCovariates *Get all fixed covariates.*

Description

Get all fixed covariates.

Usage

```
getFixedCovariates(object)

## S4 method for signature 'covariates'
getFixedCovariates(object)

## S4 method for signature 'arm'
```

```
getFixedCovariates(object)

## S4 method for signature 'arms'
getFixedCovariates(object)

## S4 method for signature 'dataset'
getFixedCovariates(object)
```

Arguments

object any object

Value

all fixed covariates from object

getIOVs

Get all IOV objects.

Description

Get all IOV objects.

Usage

```
getIOVs(object)

## S4 method for signature 'arm'
getIOVs(object)

## S4 method for signature 'arms'
getIOVs(object)

## S4 method for signature 'dataset'
getIOVs(object)
```

Arguments

object any object

Value

all IOV's from object

getOccasions	<i>Get all occasions.</i>
--------------	---------------------------

Description

Get all occasions.

Usage

```
getOccurrences(object)

## S4 method for signature 'arm'
getOccurrences(object)

## S4 method for signature 'arms'
getOccurrences(object)

## S4 method for signature 'dataset'
getOccurrences(object)
```

Arguments

object	any object
--------	------------

Value

all occasions from object

getSeedForDatasetExport	<i>Get seed for dataset export.</i>
-------------------------	-------------------------------------

Description

Get seed for dataset export.

Usage

```
getSeedForDatasetExport(seed, progress)
```

Arguments

seed	original seed
progress	simulation progress

Value

the seed value used to export the dataset

`getSeedForIteration` *Get seed for iteration.*

Description

Get seed for iteration.

Usage

`getSeedForIteration(seed, progress)`

Arguments

seed	original seed
progress	simulation progress

Value

the seed value to be used for the given replicate number and iteration

`getSeedForParametersSampling`
 Get seed for parameter uncertainty sampling.

Description

Get seed for parameter uncertainty sampling.

Usage

`getSeedForParametersSampling(seed)`

Arguments

seed	original seed
------	---------------

Value

the seed value used to sample parameter uncertainty

getSplittingConfiguration

Get splitting configuration for parallel export.

Description

Get splitting configuration for parallel export.

Usage

```
getSplittingConfiguration(dataset, hardware)
```

Arguments

dataset	Campsis dataset to export
hardware	hardware configuration

Value

splitting configuration list (if 'parallel_dataset' is enabled) or NA (if 'parallel_dataset' disabled or if the length of the dataset is less than the dataset export slice size)

getTimes

Get all distinct times for the specified object.

Description

Get all distinct times for the specified object.

Usage

```
getTimes(object)

## S4 method for signature 'observations_set'
getTimes(object)

## S4 method for signature 'arm'
getTimes(object)

## S4 method for signature 'arms'
getTimes(object)

## S4 method for signature 'events'
getTimes(object)

## S4 method for signature 'dataset'
getTimes(object)
```

Arguments

<code>object</code>	any object
---------------------	------------

Value

numeric vector with all unique times, sorted

`getTimeVaryingCovariates`

Get all time-varying covariates.

Description

Get all time-varying covariates.

Usage

```
getTimeVaryingCovariates(object)

## S4 method for signature 'covariates'
getTimeVaryingCovariates(object)

## S4 method for signature 'arm'
getTimeVaryingCovariates(object)

## S4 method for signature 'arms'
getTimeVaryingCovariates(object)

## S4 method for signature 'dataset'
getTimeVaryingCovariates(object)
```

Arguments

<code>object</code>	any object
---------------------	------------

Value

all time-varying covariates from object

Hardware	<i>Create hardware settings.</i>
----------	----------------------------------

Description

Create hardware settings.

Usage

```
Hardware(  
  cpu = 1,  
  replicate_parallel = FALSE,  
  scenario_parallel = FALSE,  
  slice_parallel = FALSE,  
  slice_size = NULL,  
  dataset_parallel = FALSE,  
  dataset_slice_size = 500,  
  auto_setup_plan = NULL  
)
```

Arguments

cpu	number of CPU cores to use, default is 1
replicate_parallel	enable parallel computing for replicates, default is FALSE
scenario_parallel	enable parallel computing for scenarios, default is FALSE
slice_parallel	enable parallel computing for slices, default is FALSE
slice_size	number of subjects per simulated slice, default is NULL (auto-configured by Campsis depending on the specified engine)
dataset_parallel	enable parallelisation when exporting dataset into a table, default is FALSE
dataset_slice_size	dataset slice size when exporting subjects to a table, default is 500. Only applicable if 'dataset_parallel' is enabled.
auto_setup_plan	auto-setup plan with the library future, if not set (i.e. =NULL), plan will be setup automatically if the number of CPU's > 1.

Value

hardware settings

hardware_settings-class
Hardware settings class.

Description

Hardware settings class.

Slots

cpu number of CPU cores to use, default is 1
replicate_parallel enable parallel computing for replicates, default is FALSE
scenario_parallel enable parallel computing for scenarios, default is FALSE
slice_parallel enable parallel computing for slices, default is FALSE
slice_size number of subjects per simulated slice, default is NULL (auto-configured by Campsis depending on the specified engine)
dataset_parallel enable parallelisation when exporting dataset into a table, default is FALSE
dataset_slice_size dataset slice size when exporting subjects to a table, default is 500. Only applicable if 'dataset_parallel' is enabled.
auto_setup_plan auto-setup plan with the library future, default is FALSE

hours *Convert hours to hours (do nothing).*

Description

Convert hours to hours (do nothing).

Usage

`hours(x)`

Arguments

x numeric vector in hours

Value

numeric vector in hours

Infusion	<i>Create one or several infusion(s).</i>
----------	---

Description

Create one or several infusion(s).

Usage

```
Infusion(
  time,
  amount,
  compartment = NULL,
  f = NULL,
  lag = NULL,
  duration = NULL,
  rate = NULL,
  ii = NULL,
  addl = NULL,
  wrap = TRUE,
  ref = NULL,
  rep = NULL
)
```

Arguments

time	treatment time(s), numeric value or vector. First treatment time if used together with ii and addl.
amount	amount to infuse, single numeric value
compartment	compartment index or name to give the infusion(s). A vector of integers or names can be used for a complex model administration.
f	fraction of infusion amount, list of distributions (one per compartment)
lag	infusion lag time, , list of distributions (one per compartment)
duration	infusion duration, list of distributions (one per compartment)
rate	infusion rate, list of distributions (one per compartment)
ii	inter-dose interval, requires argument 'time' to be a single numeric value
addl	number of additional doses, requires argument 'time' to be a single integer value
wrap	if TRUE, the infusion wrapper will be stored as is in the dataset, otherwise, it will be split into a list of infusions distinct in time. Default is TRUE.
ref	any reference name used to identify this infusion, single character value
rep	repeat the base dosing schedule several times, a 'repeated schedule' object is expected. Default is NULL (no repetition).

Value

a single infusion or a list of infusions.

infusion-class

Infusion class.

Description

Infusion class.

Slots

duration infusion duration, distribution list

rate infusion rate, distribution list

infusion_wrapper-class

Infusion wrapper class.

Description

Infusion wrapper class.

internal_settings-class

Internal settings class (transient object from the simulation settings).

Description

Internal settings class (transient object from the simulation settings).

Slots

dataset_summary dataset summary

progress simulation progress

iterations list of event iterations

IOV	<i>Define inter-occasion variability (IOV) into the dataset. A new variable of name 'colname' will be output into the dataset and will vary at each dose number according to the given distribution.</i>
-----	--

Description

Define inter-occasion variability (IOV) into the dataset. A new variable of name 'colname' will be output into the dataset and will vary at each dose number according to the given distribution.

Usage

```
IOV(colname, distribution, doseNumbers = NULL)
```

Arguments

colname	name of the column that will be output in dataset
distribution	distribution
doseNumbers	dose numbers, if provided, IOV is generated at these doses only. By default, IOV is generated for all doses.

Value

an IOV object

length,arm-method	<i>Return the number of subjects contained in this arm.</i>
-------------------	---

Description

Return the number of subjects contained in this arm.

Usage

```
## S4 method for signature 'arm'  
length(x)
```

Arguments

x	arm
---	-----

Value

a number

```
length,cyclic_schedule-method
```

Return the number of repetition cycles.

Description

Return the number of repetition cycles.

Usage

```
## S4 method for signature 'cyclic_schedule'  
length(x)
```

Arguments

x schedule object

Value

a number

```
length,dataset-method  Return the number of subjects contained in this dataset.
```

Description

Return the number of subjects contained in this dataset.

Usage

```
## S4 method for signature 'dataset'  
length(x)
```

Arguments

x dataset

Value

a number

`length,repeat_at_schedule-method`

Return the number of repetition cycles.

Description

Return the number of repetition cycles.

Usage

```
## S4 method for signature 'repeat_at_schedule'  
length(x)
```

Arguments

<code>x</code>	schedule object
----------------	-----------------

Value

a number

`LogNormalDistribution` *Create a log normal distribution.*

Description

Create a log normal distribution.

Usage

```
LogNormalDistribution(meanlog, sdlog)
```

Arguments

<code>meanlog</code>	mean value of distribution in log domain
<code>sdlog</code>	standard deviation of distribution in log domain

Value

a log normal distribution

minutes	<i>Convert minutes to hours.</i>
---------	----------------------------------

Description

Convert minutes to hours.

Usage

```
minutes(x)
```

Arguments

x	numeric vector in minutes
---	---------------------------

Value

numeric vector in hours

months	<i>Convert pharma months (1 month = 4 weeks) to hours.</i>
--------	--

Description

Convert pharma months (1 month = 4 weeks) to hours.

Usage

```
months(x)
```

Arguments

x	numeric vector in months
---	--------------------------

Value

numeric vector in hours

mrgsolve_engine-class	<i>mrgsolve engine class.</i>
-----------------------	-------------------------------

Description

mrgsolve engine class.

nhanes	<i>NHANES database (demographics and body measure data combined, from 2017-2018).</i>
--------	---

Description

NHANES database (demographics and body measure data combined, from 2017-2018).

Usage

```
nhanes
```

Format

data frame

BS_ID Original identifier

SEX Sex: 1 for males, 2 for females

AGE Age in years

BW Body weight in kg

BMI Body mass index

HT Height in cm

Source

https://wwwn.cdc.gov/Nchs/Nhanes/2017-2018/DEMO_J.XPT

https://wwwn.cdc.gov/Nchs/Nhanes/2017-2018/BMX_J.XPT

NOCB	<i>Create NOCB settings.</i>
------	------------------------------

Description

Create NOCB settings.

Usage

```
NOCB(enable = NULL, variables = character(0))
```

Arguments

enable	enable/disable next-observation carried backward mode (NOCB), default value is TRUE for mrgsolve, FALSE for RxODE
variables	variable names subject to NOCB behavior (see vignette for more info)

Value

NOCB settings

`nocb_settings-class` *NOCB settings class.*

Description

NOCB settings class.

Slots

`enable` enable/disable next-observation carried backward mode (NOCB), default value is TRUE for mrgsolve, FALSE for RxODE
`variables` variable names subject to NOCB behavior (see vignette for more info)

`NormalDistribution` *Create a normal distribution.*

Description

Create a normal distribution.

Usage

`NormalDistribution(mean, sd)`

Arguments

<code>mean</code>	mean value of distribution
<code>sd</code>	standard deviation of distribution

Value

a normal distribution

Observations	<i>Create an observations list. Please note that the provided 'times' will automatically be sorted. Duplicated times will be removed.</i>
--------------	---

Description

Create an observations list. Please note that the provided 'times' will automatically be sorted. Duplicated times will be removed.

Usage

```
Observations(times, compartment = NA)
```

Arguments

- | | |
|-------------|---|
| times | observation times, numeric vector |
| compartment | compartment index (integer) or name (character) |

Value

an observations list

observations-class	<i>Observations class.</i>
--------------------	----------------------------

Description

Observations class.

Slots

- | | |
|-------------|--|
| times | observation times, numeric vector |
| compartment | compartment index (integer) or name (character) |
| dv | observed values, numeric vector (FOR EXTERNAL USE) |

observations_set-class	<i>Observations set class.</i>
------------------------	--------------------------------

Description

Observations set class.

obsOnly	<i>Filter CAMPSIS output on observation rows.</i>
---------	---

Description

Filter CAMPSIS output on observation rows.

Usage

```
obsOnly(x)
```

Arguments

x	data frame, CAMPSIS output
---	----------------------------

Value

a data frame with the observation rows

Occasion	<i>Define a new occasion. Occasions are defined by mapping occasion values to dose numbers. A new column will automatically be created in the exported dataset.</i>
----------	---

Description

Define a new occasion. Occasions are defined by mapping occasion values to dose numbers. A new column will automatically be created in the exported dataset.

Usage

```
Occasion(colname, values, doseNumbers)
```

Arguments

colname	name of the column that will be output in dataset
values	the occasion numbers, any integer vector
doseNumbers	the related dose numbers, any integer vector of same length as 'values'

Value

occasion object

occasion-class	<i>Occasion class.</i>
----------------	------------------------

Description

Occasion class.

Slots

colname	single character value representing the column name related to this occasion
values	occasion values, integer vector, same length as dose_numbers
dose_numbers	associated dose numbers, integer vector, same length as values

occasions-class	<i>Occurrences class.</i>
-----------------	---------------------------

Description

Occurrences class.

Outfun	<i>Create a new output function</i>
--------	-------------------------------------

Description

Create a new output function

Usage

```
Outfun(
  fun = function(x, ...) {
    x
  },
  args = list(),
  packages = NULL,
  level = "scenario"
)
```

Arguments

fun	function or purrr-style lambda formula, first argument 'x' must be the results
args	extra arguments, named list
packages	packages that must be loaded to execute the given function, character vector
level	either 'scenario' or 'replicate'. Default is 'scenario'.

Value

an output function

output_function-class *Output function class.*

Description

Output function class.

Slots

fun function or purrr-style lambda formula, first argument 'x' must be the results
 args extra arguments, named list
 packages packages that must be loaded to execute the given function, character vector
 level either 'scenario' or 'replicate'. Default is 'scenario'.

ParameterDistribution *Create a parameter distribution. The resulting distribution is a log-normal distribution, with meanlog=log(THETA) and sdlog=sqrt(OMEGA).*

Description

Create a parameter distribution. The resulting distribution is a log-normal distribution, with meanlog=log(THETA) and sdlog=sqrt(OMEGA).

Usage

```
ParameterDistribution(model, theta, omega = NULL)
```

Arguments

model	model
theta	corresponding THETA name, character
omega	corresponding OMEGA name, character, NULL if not defined

Value

a parameter distribution

PI

Compute the prediction interval summary over time.

Description

Compute the prediction interval summary over time.

Usage

```
PI(x, output, scenarios = NULL, level = 0.9, gather = TRUE)
```

Arguments

x	data frame
output	variable to show, character value
scenarios	scenarios, character vector, NULL is default
level	PI level, default is 0.9 (90% PI)
gather	FALSE: med, low & up columns, TRUE: metric column

Value

a summary table

Progress

Create progress settings.

Description

Create progress settings.

Usage

```
Progress(tick_slice = TRUE)
```

Arguments

tick_slice	tick() is called after each simulated slice, default is TRUE. In some cases, when the number of subjects per slice is low, it may be useful disable this flag, to improve performance issues.
------------	---

Value

progress settings

progress_settings-class

Progress settings class.

Description

Progress settings class.

Slots

`tick_slice` `tick()` is called after each simulated slice, default is TRUE. In some cases, when the number of subjects per slice is low, it may be useful disable this flag, to improve performance issues.

protocol-class

Protocol class.

Description

Protocol class.

RepeatAtSchedule

'Repeat at' schedule constructor. Note that the time 0 for the base pattern will be added by default if not provided.

Description

'Repeat at' schedule constructor. Note that the time 0 for the base pattern will be added by default if not provided.

Usage

`RepeatAtSchedule(times)`

Arguments

`times` times at which the original schedule must be repeated, numeric vector

Value

a 'repeat-at' schedule

repeated_schedule-class

Repeated schedule class. See this class as an interface.

Description

Repeated schedule class. See this class as an interface.

repeatSchedule

Repeat schedule.

Description

Repeat schedule.

Usage

```
repeatSchedule(x, schedule)

## S4 method for signature 'numeric,cyclic_schedule'
repeatSchedule(x, schedule)

## S4 method for signature 'numeric,repeat_at_schedule'
repeatSchedule(x, schedule)

## S4 method for signature 'numeric,undefined_schedule'
repeatSchedule(x, schedule)
```

Arguments

x	object to repeat the schedule
schedule	initial times vector

Value

resulting times vector

repeat_at_schedule-class

'Repeat at' schedule class.

Description

'Repeat at' schedule class.

Slots

times times at which the event is repeated, numeric vector

retrieveParameterValue

Retrieve the parameter value (standardized) for the specified parameter name.

Description

Retrieve the parameter value (standardized) for the specified parameter name.

Usage

```
retrieveParameterValue(model, paramName, default = NULL, mandatory = FALSE)
```

Arguments

model	model
paramName	parameter name
default	default value if not found
mandatory	must be in model or not

Value

the standardized parameter value or the given default value if not found

rxode_engine-class *RxODE/rxode2 engine class.*

Description

RxODE/rxode2 engine class.

Slots

rxode2 logical field to indicate if CAMPSIS should use rxode2 (field set to TRUE) or RxODE (field set to FALSE). Default is TRUE.

sample *Sample generic object.*

Description

Sample generic object.

Usage

```
sample(object, n, ...)

## S4 method for signature 'constant_distribution,integer'
sample(object, n)

## S4 method for signature 'fixed_distribution,integer'
sample(object, n)

## S4 method for signature 'function_distribution,integer'
sample(object, n)

## S4 method for signature 'bootstrap_distribution,integer'
sample(object, n)

## S4 method for signature 'bolus,integer'
sample(object, n, ...)

## S4 method for signature 'infusion,integer'
sample(object, n, ...)

## S4 method for signature 'observations,integer'
sample(object, n, ...)

## S4 method for signature 'covariate,integer'
```

```
sample(object, n)

## S4 method for signature 'bootstrap,integer'
sample(object, n)
```

Arguments

- `object` generic object
- `n` number of samples required
- `...` extra arguments

Value

sampling result

<code>scatterPlot</code>	<i>Scatter plot (or X vs Y plot).</i>
--------------------------	---------------------------------------

Description

Scatter plot (or X vs Y plot).

Usage

```
scatterPlot(x, output, colour = NULL, time = NULL)
```

Arguments

- `x` data frame
- `output` the 2 variables to show, character vector
- `colour` variable(s) to colour
- `time` the time to look at those 2 variables, if NULL, min time is used (usually 0)

Value

a ggplot object

Scenario	<i>Create an scenario.</i>
----------	----------------------------

Description

Create an scenario.

Usage

```
Scenario(name = NULL, model = NULL, dataset = NULL)
```

Arguments

name	scenario name, single character string
model	either a CAMPSIS model, a function or lambda-style formula
dataset	either a CAMPSIS dataset, a function or lambda-style formula

Value

a new scenario

scenario-class	<i>Scenario class.</i>
----------------	------------------------

Description

Scenario class.

Slots

name	scenario name, single character string
model	either a CAMPSIS model, a function or lambda-style formula
dataset	either a CAMPSIS dataset, a function or lambda-style formula

Scenarios	<i>Create a list of scenarios.</i>
-----------	------------------------------------

Description

Create a list of scenarios.

Usage

`Scenarios()`

Value

a scenarios object

scenarios-class	<i>Scenarios class.</i>
-----------------	-------------------------

Description

Scenarios class.

seconds	<i>Convert seconds to hours.</i>
---------	----------------------------------

Description

Convert seconds to hours.

Usage

`seconds(x)`

Arguments

x	numeric vector in seconds
---	---------------------------

Value

numeric vector in hours

setLabel	<i>Set the label.</i>
----------	-----------------------

Description

Set the label.

Usage

```
setLabel(object, x)

## S4 method for signature 'arm,character'
setLabel(object, x)
```

Arguments

object	any object that has a label
x	the new label

Value

the updated object

setSubjects	<i>Set the number of subjects.</i>
-------------	------------------------------------

Description

Set the number of subjects.

Usage

```
setSubjects(object, x)

## S4 method for signature 'arm,integer'
setSubjects(object, x)

## S4 method for signature 'dataset,integer'
setSubjects(object, x)
```

Arguments

object	any object
x	the new number of subjects

Value

the updated object

Settings

Create advanced simulation settings.

Description

Create advanced simulation settings.

Usage

`Settings(...)`

Arguments

...	any user-required settings: see ?Hardware, ?Solver, ?NOCB, ?Declare, ?Progress or ?AutoReplicationSettings
-----	--

Value

advanced simulation settings

setupPlanDefault

Setup default plan for the given simulation or hardware settings. This plan will prioritise the distribution of workers in the following order: 1) Replicates (if 'replicate_parallel' is enabled) 2) Scenarios (if 'scenario_parallel' is enabled) 3) Dataset export / slices (if 'dataset_export' or 'slice_parallel' is enabled)

Description

Setup default plan for the given simulation or hardware settings. This plan will prioritise the distribution of workers in the following order: 1) Replicates (if 'replicate_parallel' is enabled) 2) Scenarios (if 'scenario_parallel' is enabled) 3) Dataset export / slices (if 'dataset_export' or 'slice_parallel' is enabled)

Usage

`setupPlanDefault(object)`

Arguments

object	simulation or hardware settings
--------	---------------------------------

Value

nothing

setupPlanSequential *Setup plan as sequential (i.e. no parallelisation).*

Description

Setup plan as sequential (i.e. no parallelisation).

Usage

```
setupPlanSequential()
```

Value

nothing

shadedPlot *Shaded plot (or prediction interval plot).*

Description

Shaded plot (or prediction interval plot).

Usage

```
shadedPlot(  
  x,  
  output,  
  colour = NULL,  
  strat_extra = NULL,  
  level = 0.9,  
  alpha = 0.25  
)
```

Arguments

x	data frame
output	variable to show
colour	variable(s) to colour
strat_extra	variable(s) to stratify, but not to colour (useful for use with facet_wrap)
level	PI level, default is 0.9 (90% PI)
alpha	alpha parameter (transparency) given to geom_ribbon

Value

a ggplot object

simulate *Simulate function.*

Description

Simulate function.

Usage

```
simulate(  
  model,  
  dataset,  
  dest = NULL,  
  events = NULL,  
  scenarios = NULL,  
  tablefun = NULL,  
  outvars = NULL,  
  outfun = NULL,  
  seed = NULL,  
  replicates = 1,  
  dosing = FALSE,  
  settings = NULL  
)  
  
## S4 method for signature  
## 'replicated_campsis_model,'  
##   dataset,  
##   character,  
##   events,  
##   scenarios,  
##   function,  
##   character,  
##   output_function,  
##   integer,  
##   integer,  
##   logical,  
##   simulation_settings'  
simulate(  
  model,  
  dataset,  
  dest = NULL,  
  events = NULL,  
  scenarios = NULL,  
  tablefun = NULL,  
  outvars = NULL,  
  outfun = NULL,  
  seed = NULL,
```

```
replicates = 1,
dosing = FALSE,
settings = NULL
)

## S4 method for signature
## 'campsis_model,
##   dataset,
##   character,
##   events,
##   scenarios,
##   function,
##   character,
##   output_function,
##   integer,
##   integer,
##   logical,
##   simulation_settings'
simulate(
  model,
  dataset,
  dest = NULL,
  events = NULL,
  scenarios = NULL,
  tablefun = NULL,
  outvars = NULL,
  outfun = NULL,
  seed = NULL,
  replicates = 1,
  dosing = FALSE,
  settings = NULL
)

## S4 method for signature
## 'campsis_model,
##   tbl_df,
##   character,
##   events,
##   scenarios,
##   function,
##   character,
##   output_function,
##   integer,
##   integer,
##   logical,
##   simulation_settings'
simulate(
  model,
```

```
dataset,
dest = NULL,
events = NULL,
scenarios = NULL,
tablefun = NULL,
outvars = NULL,
outfun = NULL,
seed = NULL,
replicates = 1,
dosing = FALSE,
settings = NULL
)

## S4 method for signature
## 'campsis_model,
##   data.frame,
##   character,
##   events,
##   scenarios,
##   function,
##   character,
##   output_function,
##   integer,
##   integer,
##   logical,
##   simulation_settings'
simulate(
  model,
  dataset,
  dest = NULL,
  events = NULL,
  scenarios = NULL,
  tablefun = NULL,
  outvars = NULL,
  outfun = NULL,
  seed = NULL,
  replicates = 1,
  dosing = FALSE,
  settings = NULL
)

## S4 method for signature
## 'campsis_model,
##   tbl_df,
##   rkode_engine,
##   events,
##   scenarios,
##   function,
```

```
##   character,
##   output_function,
##   integer,
##   integer,
##   logical,
##   simulation_settings'
simulate(
  model,
  dataset,
  dest = NULL,
  events = NULL,
  scenarios = NULL,
  tablefun = NULL,
  outvars = NULL,
  outfun = NULL,
  seed = NULL,
  replicates = 1,
  dosing = FALSE,
  settings = NULL
)

## S4 method for signature
## 'campsis_model,
##   tbl_df,
##   mrgsolve_engine,
##   events,
##   scenarios,
##   function,
##   character,
##   output_function,
##   integer,
##   integer,
##   logical,
##   simulation_settings'
simulate(
  model,
  dataset,
  dest = NULL,
  events = NULL,
  scenarios = NULL,
  tablefun = NULL,
  outvars = NULL,
  outfun = NULL,
  seed = NULL,
  replicates = 1,
  dosing = FALSE,
  settings = NULL
)
```

Arguments

model	generic CAMPSIS model
dataset	CAMPSIS dataset or 2-dimensional table
dest	destination simulation engine, default is 'RxODE'
events	interruption events
scenarios	list of scenarios to be simulated
tablefun	function or lambda formula to apply on exported 2-dimensional dataset
outvars	variables to output in resulting dataframe
outfun	an output function to apply on the simulation results. Type ?Outfun for more info.
seed	seed value
replicates	number of replicates, default is 1
dosing	output dosing information, default is FALSE
settings	advanced simulation settings

Value

dataframe with all results

SimulationProgress

Create a simulation progress object.

Description

Create a simulation progress object.

Usage

```
SimulationProgress(
  replicates = 1,
  scenarios = 1,
  progressor = NULL,
  hardware = NULL
)
```

Arguments

replicates	total number of replicates to simulate
scenarios	total number of scenarios to simulate
progressor	progressr progressor
hardware	hardware settings

Value

a progress bar

simulation_engine-class

Simulation engine class.

Description

Simulation engine class.

simulation_progress-class

Simulation progress class.

Description

Simulation progress class.

Arguments

replicates	total number of replicates to simulate
scenarios	total number of scenarios to simulate
iterations	total number of iterations to simulate
slices	total number of slices to simulate
replicate	current replicate number being simulated
scenario	current scenario number being simulated
iteration	current iteration number being simulated
slice	current slice number being simulated
progressor	progressr progressor
hardware	hardware settings

simulation_settings-class*Simulation settings class.***Description**

Simulation settings class.

Slots

hardware hardware settings object
 solver solver settings object
 nocb NOCB settings object
 declare declare settings (mrgsolve only)
 progress progress settings
 replication replication settings
 internal internal settings

Solver*Create solver settings.***Description**

Create solver settings.

Usage

```
Solver(  
  atol = 1e-08,  
  rtol = 1e-08,  
  hmax = NA,  
  maxsteps = 70000L,  
  method = "liblsoda"  
)
```

Arguments

atol	absolute solver tolerance, default is 1e-08
rtol	relative solver tolerance, default is 1e-08
hmax	limit how big a solver step can be, default is NA
maxsteps	max steps between 2 integration times (e.g. when observations records are far apart), default is 70000
method	solver method, for RxODE/rxode2 only: 'liblsoda' (default), 'lsoda', 'dop853', 'indLin'. Mrgsolve's method is always 'lsoda'.

Value

solver settings

`solver_settings-class` *Solver settings class. See ?mrgsolve::update. See ?rxode2::rxSolve.*

Description

Solver settings class. See ?mrgsolve::update. See ?rxode2::rxSolve.

Slots

`atol` absolute solver tolerance, default is 1e-08
`rtol` relative solver tolerance, default is 1e-08
`hmax` limit how big a solver step can be, default is NA
`maxsteps` max steps between 2 integration times (e.g. when observations records are far apart), default is 70000
`method` solver method, for RxODE/rxode2 only: 'liblsoda' (default), 'lsoda', 'dop853', 'indLin'. Mrgsolve's method is always 'lsoda'.

`spaghettiPlot` *Spaghetti plot.*

Description

Spaghetti plot.

Usage

```
spaghettiPlot(x, output, colour = NULL)
```

Arguments

<code>x</code>	data frame
<code>output</code>	variable to show
<code>colour</code>	variable(s) to colour

Value

plot

`standardiseTime` *Standardise time to hours.*

Description

Standardise time to hours.

Usage

```
standardiseTime(x, unit)
```

Arguments

<code>x</code>	numeric time vector
<code>unit</code>	unit of <code>x</code> , single character value

Value

numeric vector with the times converted to hours

`TimeVaryingCovariate` *Create a time-varying covariate. This covariate will be implemented using EVID=2 rows in the exported dataset and will not use interruption events.*

Description

Create a time-varying covariate. This covariate will be implemented using EVID=2 rows in the exported dataset and will not use interruption events.

Usage

```
TimeVaryingCovariate(name, table)
```

Arguments

<code>name</code>	covariate name, character
<code>table</code>	data.frame, must contain the mandatory columns 'TIME' and 'VALUE'. An 'ID' column may also be specified. In that case, ID's between 1 and the max number of subjects in the dataset/arm can be used. All ID's must have a VALUE defined for TIME 0.

Value

a time-varying covariate

time_varying_covariate-class

Time-varying covariate class.

Description

Time-varying covariate class.

treatment-class

Treatment class.

Description

Treatment class.

treatment_iov-class

Treatment IOV class.

Description

Treatment IOV class.

Slots

`colname` name of the column that will be output in dataset

`distribution` distribution

`dose_numbers` associated dose numbers, integer vector, same length as values

treatment_iovs-class

Treatment IOV's class.

Description

Treatment IOV's class.

undefined_distribution-class

Undefined distribution class. This type of object is automatically created in method toExplicitDistribution() when the user does not provide a concrete distribution. This is because S4 objects do not accept NULL values.

Description

Undefined distribution class. This type of object is automatically created in method toExplicitDistribution() when the user does not provide a concrete distribution. This is because S4 objects do not accept NULL values.

undefined_schedule-class

Undefined schedule class.

Description

Undefined schedule class.

UniformDistribution *Create an uniform distribution.***Description**

Create an uniform distribution.

Usage

`UniformDistribution(min, max)`

Arguments

<code>min</code>	min value
<code>max</code>	max value

Value

an uniform distribution

unwrapTreatment *Unwrap treatment.*

Description

Unwrap treatment.

Usage

```
unwrapTreatment(object)

## S4 method for signature 'bolus'
unwrapTreatment(object)

## S4 method for signature 'infusion'
unwrapTreatment(object)

## S4 method for signature 'bolus_wrapper'
unwrapTreatment(object)

## S4 method for signature 'infusion_wrapper'
unwrapTreatment(object)

## S4 method for signature 'treatment'
unwrapTreatment(object)

## S4 method for signature 'arm'
unwrapTreatment(object)

## S4 method for signature 'arms'
unwrapTreatment(object)

## S4 method for signature 'dataset'
unwrapTreatment(object)
```

Arguments

object any object

Value

updated object

`updateADDL`*Update the number of additional doses (ADDL).*

Description

Update the number of additional doses (ADDL).

Usage

```
updateADDL(object, addl, ref = NULL)

## S4 method for signature 'bolus_wrapper,integer,character'
updateADDL(object, addl, ref = NULL)

## S4 method for signature 'infusion_wrapper,integer,character'
updateADDL(object, addl, ref = NULL)

## S4 method for signature 'bolus,integer,character'
updateADDL(object, addl, ref = NULL)

## S4 method for signature 'infusion,integer,character'
updateADDL(object, addl, ref = NULL)

## S4 method for signature 'treatment,integer,character'
updateADDL(object, addl, ref = NULL)

## S4 method for signature 'arm,integer,character'
updateADDL(object, addl, ref = NULL)

## S4 method for signature 'arms,integer,character'
updateADDL(object, addl, ref = NULL)

## S4 method for signature 'dataset,integer,character'
updateADDL(object, addl, ref = NULL)
```

Arguments

object	generic object
addl	new number of additional doses
ref	reference treatment name

Value

updated object

updateAmount	<i>Update amount.</i>
--------------	-----------------------

Description

Update amount.

Usage

```
updateAmount(object, amount, ref)

## S4 method for signature 'bolus,numeric,character'
updateAmount(object, amount, ref)

## S4 method for signature 'infusion,numeric,character'
updateAmount(object, amount, ref)

## S4 method for signature 'bolus_wrapper,numeric,character'
updateAmount(object, amount, ref)

## S4 method for signature 'infusion_wrapper,numeric,character'
updateAmount(object, amount, ref)

## S4 method for signature 'treatment,numeric,character'
updateAmount(object, amount, ref)

## S4 method for signature 'arm,numeric,character'
updateAmount(object, amount, ref)

## S4 method for signature 'arms,numeric,character'
updateAmount(object, amount, ref)

## S4 method for signature 'dataset,numeric,character'
updateAmount(object, amount, ref)
```

Arguments

object	generic object
amount	new amount
ref	reference treatment name

Value

updated object

updateII

*Update the inter-dose interval (II).***Description**

Update the inter-dose interval (II).

Usage

```
updateII(object, ii, ref = NULL)

## S4 method for signature 'bolus_wrapper,numeric,character'
updateII(object, ii, ref = NULL)

## S4 method for signature 'infusion_wrapper,numeric,character'
updateII(object, ii, ref = NULL)

## S4 method for signature 'bolus,numeric,character'
updateII(object, ii, ref = NULL)

## S4 method for signature 'infusion,numeric,character'
updateII(object, ii, ref = NULL)

## S4 method for signature 'treatment,numeric,character'
updateII(object, ii, ref = NULL)

## S4 method for signature 'arm,numeric,character'
updateII(object, ii, ref = NULL)

## S4 method for signature 'arms,numeric,character'
updateII(object, ii, ref = NULL)

## S4 method for signature 'dataset,numeric,character'
updateII(object, ii, ref = NULL)
```

Arguments

object	generic object
ii	new inter-dose interval
ref	reference treatment name

Value

updated object

updateRepeat	<i>Update the repeat field (argument 'rep' in Bolus and Infusion constructors).</i>
--------------	---

Description

Update the repeat field (argument 'rep' in Bolus and Infusion constructors).

Usage

```
updateRepeat(object, rep, ref = NULL)

## S4 method for signature 'bolus_wrapper,repeated_schedule,character'
updateRepeat(object, rep, ref = NULL)

## S4 method for signature 'infusion_wrapper,repeated_schedule,character'
updateRepeat(object, rep, ref = NULL)

## S4 method for signature 'bolus,repeated_schedule,character'
updateRepeat(object, rep, ref = NULL)

## S4 method for signature 'infusion,repeated_schedule,character'
updateRepeat(object, rep, ref = NULL)

## S4 method for signature 'treatment,repeated_schedule,character'
updateRepeat(object, rep, ref = NULL)

## S4 method for signature 'arm,repeated_schedule,character'
updateRepeat(object, rep, ref = NULL)

## S4 method for signature 'arms,repeated_schedule,character'
updateRepeat(object, rep, ref = NULL)

## S4 method for signature 'dataset,repeated_schedule,character'
updateRepeat(object, rep, ref = NULL)
```

Arguments

object	generic object
rep	repeated dosing schedule (definition) object
ref	reference treatment name

Value

updated object

VPC	<i>Compute the VPC summary. Input data frame must contain the following columns:</i> - replicate: replicate number - low: low percentile value in replicate (and in scenario if present) - med: median value in replicate (and in scenario if present) - up: up percentile value in replicate (and in scenario if present) - any scenario column
-----	--

Description

Compute the VPC summary. Input data frame must contain the following columns: - replicate: replicate number - low: low percentile value in replicate (and in scenario if present) - med: median value in replicate (and in scenario if present) - up: up percentile value in replicate (and in scenario if present) - any scenario column

Usage

```
VPC(x, scenarios = NULL, level = 0.9)
```

Arguments

x	data frame
scenarios	scenarios, character vector, NULL is default
level	PI level, default is 0.9 (90% PI)

Value

VPC summary with columns TIME, <scenarios> and all combinations of low, med, up (i.e. low_low, low_med, low_up, etc.)

vpcPlot

*VPC plot.***Description**

VPC plot.

Usage

```
vpcPlot(x, scenarios = NULL, level = 0.9, alpha = 0.15)
```

Arguments

x	data frame, output of CAMPSIS with replicates
scenarios	scenarios, character vector, NULL is default
level	PI level, default is 0.9 (90% PI)
alpha	alpha parameter (transparency) given to geom_ribbon

Value

a ggplot object

weeks	<i>Convert weeks to hours.</i>
-------	--------------------------------

Description

Convert weeks to hours.

Usage

`weeks(x)`

Arguments

x	numeric vector in weeks
---	-------------------------

Value

numeric vector in hours

years	<i>Convert pharma years (1 year = 12*4 weeks) to hours.</i>
-------	---

Description

Convert pharma years (1 year = 12*4 weeks) to hours.

Usage

`years(x)`

Arguments

x	numeric vector in years
---	-------------------------

Value

numeric vector in hours

Index

* datasets
 nhanes, 41

applyCompartmentCharacteristics, 5

Arm, 6

arm-class, 6

arms-class, 7

BinomialDistribution, 7

Bolus, 7

bolus-class, 8

bolus_wrapper-class, 9

Bootstrap, 9

bootstrap-class, 10

bootstrap_distribution-class, 11

BootstrapDistribution, 10

campsis_handler, 11

constant_distribution-class, 12

ConstantDistribution, 11

convertTime, 12

Covariate, 13

covariate-class, 13

covariates-class, 13

cyclic_schedule-class, 14

CyclicSchedule, 14

Dataset, 15

dataset-class, 15

dataset_config-class, 16

DatasetConfig, 16

days, 17

Declare, 17

declare_settings-class, 18

DiscreteDistribution, 18

distribution-class, 18

dose_adaptation-class, 19

dose_adaptations-class, 19

DoseAdaptation, 19

dosingOnly, 20

EtaDistribution, 20

Event, 21

event-class, 21

event_covariate-class, 23

EventCovariate, 22

Events, 22

events-class, 22

fixed_covariate-class, 23

fixed_distribution-class, 23

FixedDistribution, 23

function_distribution-class, 24

FunctionDistribution, 24

generateIIV, 25

generateIIV_, 25

getAvailableTimeUnits, 26

getCovariates, 26

getCovariates, arm-method
 (getCovariates), 26

getCovariates, arms-method
 (getCovariates), 26

getCovariates, covariates-method
 (getCovariates), 26

getCovariates, dataset-method
 (getCovariates), 26

getEventCovariates, 27

getEventCovariates, arm-method
 (getEventCovariates), 27

getEventCovariates, arms-method
 (getEventCovariates), 27

getEventCovariates, covariates-method
 (getEventCovariates), 27

getEventCovariates, dataset-method
 (getEventCovariates), 27

getFixedCovariates, 27

getFixedCovariates, arm-method
 (getFixedCovariates), 27

getFixedCovariates, arms-method
 (getFixedCovariates), 27

getFixedCovariates, covariates-method
 (getFixedCovariates), 27
getFixedCovariates, dataset-method
 (getFixedCovariates), 27
getIOVs, 28
getIOVs, arm-method (getIOVs), 28
getIOVs, arms-method (getIOVs), 28
getIOVs, dataset-method (getIOVs), 28
getOccasions, 29
getOccasions, arm-method (getOccasions),
 29
getOccasions, arms-method
 (getOccasions), 29
getOccasions, dataset-method
 (getOccasions), 29
getSeedForDatasetExport, 29
getSeedForIteration, 30
getSeedForParametersSampling, 30
getSplittingConfiguration, 31
getTimes, 31
getTimes, arm-method (getTimes), 31
getTimes, arms-method (getTimes), 31
getTimes, dataset-method (getTimes), 31
getTimes, events-method (getTimes), 31
getTimes, observations_set-method
 (getTimes), 31
getTimeVaryingCovariates, 32
getTimeVaryingCovariates, arm-method
 (getTimeVaryingCovariates), 32
getTimeVaryingCovariates, arms-method
 (getTimeVaryingCovariates), 32
getTimeVaryingCovariates, covariates-method
 (getTimeVaryingCovariates), 32
getTimeVaryingCovariates, dataset-method
 (getTimeVaryingCovariates), 32

Hardware, 33
hardware_settings-class, 34
hours, 34

Infusion, 35
infusion-class, 36
infusion_wrapper-class, 36
internal_settings-class, 36
IOV, 37

length, arm-method, 37
length, cyclic_schedule-method, 38
length, dataset-method, 38

length, repeat_at_schedule-method, 39
LogNormalDistribution, 39

minutes, 40
months, 40
mrgsolve_engine-class, 40

nhanes, 41
NOCB, 41
nocb_settings-class, 42
NormalDistribution, 42

Observations, 43
observations-class, 43
observations_set-class, 43
obsOnly, 44
Occasion, 44
occasion-class, 45
occasions-class, 45
Outfun, 45
output_function-class, 46

ParameterDistribution, 46
PI, 47
Progress, 47
progress_settings-class, 48
protocol-class, 48

repeat_at_schedule-class, 50
RepeatAtSchedule, 48
repeated_schedule-class, 49
repeatSchedule, 49
repeatSchedule, numeric, cyclic_schedule-method
 (repeatSchedule), 49
repeatSchedule, numeric, repeat_at_schedule-method
 (repeatSchedule), 49
repeatSchedule, numeric, undefined_schedule-method
 (repeatSchedule), 49
retrieveParameterValue, 50
rxode_engine-class, 51

sample, 51
sample, bolus, integer-method (sample), 51
sample, bootstrap, integer-method
 (sample), 51
sample, bootstrap_distribution, integer-method
 (sample), 51
sample, constant_distribution, integer-method
 (sample), 51

sample,covariate,integer-method
 (sample), 51
 sample,fixed_distribution,integer-method
 (sample), 51
 sample,function_distribution,integer-method
 (sample), 51
 sample,infusion,integer-method
 (sample), 51
 sample,observations,integer-method
 (sample), 51
 scatterPlot, 52
 Scenario, 53
 scenario-class, 53
 Scenarios, 54
 scenarios-class, 54
 seconds, 54
 setLabel, 55
 setLabel,arm,character-method
 setLabel), 55
 setSubjects, 55
 setSubjects,arm,integer-method
 (setSubjects), 55
 setSubjects,dataset,integer-method
 (setSubjects), 55
 Settings, 56
 setupPlanDefault, 56
 setupPlanSequential, 57
 shadedPlot, 57
 simulate, 58
 simulate,campsis_model,data.frame,character,event
 (simulate), 58
 simulate,campsis_model,dataset,character,events
 (simulate), 58
 simulate,campsis_model,tbl_df,character,events
 (simulate), 58
 simulate,campsis_model,tbl_df,mrgsolve_engine
 (simulate), 58
 simulate,campsis_model,tbl_df,rxode_engine,events
 (simulate), 58
 simulate,replicated_campsis_model,dataset,character
 (simulate), 58
 simulation_engine-class, 63
 simulation_progress-class, 63
 simulation_settings-class, 64
 SimulationProgress, 62
 Solver, 64
 solver_settings-class, 65
 spaghettiPlot, 65
 standardiseTime, 66
 time_varying_covariate-class, 67
 TimeVaryingCovariate, 66
 treatment-class, 67
 treatment iov-class, 67
 treatment iovs-class, 67
 undefined_distribution-class, 68
 undefined_schedule-class, 68
 UniformDistribution, 68
 unwrapTreatment, 69
 unwrapTreatment,arm-method
 (unwrapTreatment), 69
 unwrapTreatment,arms-method
 (unwrapTreatment), 69
 unwrapTreatment,bolus-method
 (unwrapTreatment), 69
 unwrapTreatment,bolus_wrapper-method
 (unwrapTreatment), 69
 unwrapTreatment,dataset-method
 (unwrapTreatment), 69
 unwrapTreatment,infusion-method
 (unwrapTreatment), 69
 unwrapTreatment,infusion_wrapper-method
 (unwrapTreatment), 69
 unwrapTreatment,treatment-method
 (unwrapTreatment), 69
 updateADDL, 70
 updateADDL,events
 (updateADDL), 70
 updateADDL,events,character
 (updateADDL), 70
 updateADDL,infusion
 (updateADDL), 70
 updateADDL,treatment,integer,character-method
 (updateADDL), 70
 updateAmount, 71
 updateAmount,arm,numeric,character-method
 (updateAmount), 71

updateAmount, arms, numeric, character-method VPC, 74
 (updateAmount), 71 vpcPlot, 74

updateAmount, bolus, numeric, character-method weeks, 75
 (updateAmount), 71 years, 75

updateAmount, dataset, numeric, character-method

 (updateAmount), 71

updateAmount, infusion, numeric, character-method

 (updateAmount), 71

updateAmount, infusion_wrapper, numeric, character-method

 (updateAmount), 71

updateAmount, treatment, numeric, character-method

 (updateAmount), 71

updateII, 72

updateII, arm, numeric, character-method

 (updateII), 72

updateII, arms, numeric, character-method

 (updateII), 72

updateII, bolus, numeric, character-method

 (updateII), 72

updateII, bolus_wrapper, numeric, character-method

 (updateII), 72

updateII, dataset, numeric, character-method

 (updateII), 72

updateII, infusion, numeric, character-method

 (updateII), 72

updateII, infusion_wrapper, numeric, character-method

 (updateII), 72

updateII, treatment, numeric, character-method

 (updateII), 72

updateRepeat, 73

updateRepeat, arm, repeated_schedule, character-method

 (updateRepeat), 73

updateRepeat, arms, repeated_schedule, character-method

 (updateRepeat), 73

updateRepeat, bolus, repeated_schedule, character-method

 (updateRepeat), 73

updateRepeat, bolus_wrapper, repeated_schedule, character-method

 (updateRepeat), 73

updateRepeat, dataset, repeated_schedule, character-method

 (updateRepeat), 73

updateRepeat, infusion, repeated_schedule, character-method

 (updateRepeat), 73

updateRepeat, infusion_wrapper, repeated_schedule, character-method

 (updateRepeat), 73

updateRepeat, treatment, repeated_schedule, character-method

 (updateRepeat), 73