

Package ‘difffdfs’

October 13, 2022

Title Compute the Difference Between Data Frames

Version 0.9.0

Description Shows you which rows have changed between two data frames with the same column structure. Useful for diffing slowly mutating data.

License MIT + file LICENSE

Imports arrow, dplyr, janitor, rlang

BugReports <https://github.com/riazarbi/difffdfs>

Encoding UTF-8

RoxygenNote 7.2.1

Suggests testthat (>= 3.0.0)

Config/testthat.edition 3

NeedsCompilation no

Author Riaz Arbi [aut, cre]

Maintainer Riaz Arbi <difffdfs@arbidata.com>

Repository CRAN

Date/Publication 2022-08-09 13:50:06 UTC

R topics documented:

| | |
|----------|---|
| checkkey | 2 |
| difffdfs | 2 |

Index

4

checkkey

*Check That A Dataframe Key Col Set Is Unique***Description**

Checks that a provided vector of column names constitute a unique key (that is, no rows are duplicated) for a dataframe.

Usage

```
checkkey(df, key_cols, verbose = FALSE)
```

Arguments

| | |
|----------|---------------------------------------|
| df | a dataframe |
| key_cols | vector of column names |
| verbose | TRUE/FALSE should we print a message? |

Value

TRUE if key cols have unique rows; FALSE if not

Examples

```
irisint = iris
irisint$rownum = 1:nrow(irisint)
key_cols = c("rownum")
checkkey(irisint, key_cols, TRUE)
checkkey(irisint, "Species", TRUE)
```

diffdfs

*Compute the Difference Between Dataframes***Description**

Returns a dataframe describing the modifications required to transform old_df into new_df. The dataframes needBugReports: <https://github.com/tidyverse/dplyr/issues> to have identical columns and column types and share unique index columns.

Usage

```
diffdfs(new_df, old_df = NA, key_cols = NA, verbose = FALSE)
```

Arguments

| | |
|----------|---|
| new_df | A dataframe of new data. |
| old_df | A dataframe of old data. new_df and old_df can (and usually do) have overlapping data. |
| key_cols | optional vector of column names that constitute a unique table key. If NA, colnames(old_df) will be used. |
| verbose | logical, default FALSE. Should the processing be chatty? |

Value

a dataframe.

Examples

```
iris$key <- 1:nrow(iris)

old_df <- iris[1:100,]
old_df[75,1] <- 100
new_df <- iris[50:150,]
diffdfs(new_df, old_df, key_cols = "key")
```

Index

`checkkey`, [2](#)

`diffdfs`, [2](#)