

Package ‘dmetatools’

May 30, 2023

Type Package

Title Computational Tools for Meta-Analysis of Diagnostic Accuracy Test

Version 1.1.1

Date 2023-05-27

Maintainer Hisashi Noma <noma@ism.ac.jp>

Description Computational tools for meta-analysis of diagnostic accuracy test. Bootstrap-based computational methods of the confidence interval for AUC of summary ROC curve and some related AUC-based inference methods are available (Noma et al. (2021) <doi:10.1080/23737484.2021.1894408>).

Imports MASS, mada

License GPL-3

Encoding UTF-8

LazyData true

NeedsCompilation no

Author Hisashi Noma [aut, cre] (<<https://orcid.org/0000-0002-2520-9949>>)

Repository CRAN

Date/Publication 2023-05-30 10:50:10 UTC

R topics documented:

| | |
|------------------------------|---|
| dmetatools-package | 2 |
| asthma | 2 |
| AUC_boot | 3 |
| AUC_comparison | 4 |
| AUC_IF | 6 |
| cervical | 8 |

Index

9

dmetatools-package *The 'dmetatools' package.*

Description

Computational tools for meta-analysis of diagnostic accuracy test. Bootstrap-based computational methods of the confidence interval for AUC of summary ROC curve and some related AUC-based inference methods are available.

Author(s)

Hisashi Noma <noma@ism.ac.jp>

References

Noma, H., Matsushima, Y., and Ishii, R. (2021). Confidence interval for the AUC of SROC curve and some related methods using bootstrap for meta-analysis of diagnostic accuracy studies. *Communications in Statistics: Case Studies and Data Analysis* 7: 344-358. doi:10.1080/23737484.2021.1894408

asthma *Korevaar et al. (2015)'s data of minimally invasive markers for detection of airway eosinophilia in asthma*

Description

- TP: A vector of the number of true positives (TP)
- FP: A vector of the number of false positives (FP)
- FN: A vector of the number of false negatives (FN)
- TN: A vector of the number of true negatives (TN)

Usage

```
data(asthma)
```

Format

A data frame with 12 rows and 4 variables

References

- Korevaar, D. A., Westerhof, G. A., Wang, J., et al. (2015). Diagnostic accuracy of minimally invasive markers for detection of airway eosinophilia in asthma: a systematic review and meta-analysis. *Lancet Respiratory Medicine*. 3: 290-300. doi:10.1016/S22132600(15)000508
- Noma, H., Matsushima, Y., and Ishii, R. (2021). Confidence interval for the AUC of SROC curve and some related methods using bootstrap for meta-analysis of diagnostic accuracy studies. *Communications in Statistics: Case Studies and Data Analysis* 7: 344-358. doi:10.1080/23737484.2021.1894408

AUC_boot

Confidence interval for AUC of summary ROC curve

Description

Calculating the confidence interval for AUC of summary ROC curve by parametric bootstrap.

Usage

```
AUC_boot(TP, FP, FN, TN, B=2000, alpha=0.95)
```

Arguments

| | |
|-------|--|
| TP | A vector of the number of true positives (TP) |
| FP | A vector of the number of false positives (FP) |
| FN | A vector of the number of false negatives (FN) |
| TN | A vector of the number of true negatives (TN) |
| B | The number of bootstrap resampling (default: 2000) |
| alpha | The confidence level (default: 0.95) |

Value

The confidence interval for AUC of summary ROC curve is calculated.

- AUC: The AUC of the summary ROC curve.
- AUC_CI: The 95% confidence interval for the AUC of the summary ROC curve (the confidence level can be changed by alpha).

Author(s)

Hisashi Noma <noma@ism.ac.jp>

References

- Noma, H., Matsushima, Y., and Ishii, R. (2021). Confidence interval for the AUC of SROC curve and some related methods using bootstrap for meta-analysis of diagnostic accuracy studies. *Communications in Statistics: Case Studies and Data Analysis* 7: 344-358. doi:10.1080/23737484.2021.1894408

Examples

```

require(mada)

data(cervical)

CT <- cervical[cervical$method==1,]
LAG <- cervical[cervical$method==2,]
MRI <- cervical[cervical$method==3,]

fit1 <- reitsma(CT)      # DTA meta-analysis using the Reitsma model
summary(fit1)
fit2 <- reitsma(LAG)
summary(fit2)
fit3 <- reitsma(MRI)
summary(fit3)

plot(fit1)    # Plot the SROC curves
lines(sroc(fit2), lty=2, col="blue")
ROCellipse(fit2, lty=2, pch=2, add=TRUE, col="blue")
lines(sroc(fit3), lty=3, col="red")
ROCellipse(fit3, lty=3, pch=3, add=TRUE, col="red")
points(fpr(CT), sens(CT), cex = .5)
points(fpr(LAG), sens(LAG), pch = 2, cex = 0.5, col="blue")
points(fpr(MRI), sens(MRI), pch = 3, cex = 0.5, col="red")
legend("bottomright", c("CT", "LAG", "MRI"), pch = 1:3, lty = 1:3, col=c("black","blue","red"))

AUC_boot(CT$TP,CT$FP,CT$FN,CT$TN,B=5)
AUC_boot(LAG$TP,LAG$FP,LAG$FN,LAG$TN,B=5)
AUC_boot(MRI$TP,MRI$FP,MRI$FN,MRI$TN,B=5)
# These are example commands for illustration. B should be >= 1000.

```

AUC_comparison

Bootstrap test for the difference of AUCs of summary ROC curves for multiple diagnostic tests

Description

Calculating the difference of AUCs of summary ROC curves (dAUC) and its confidence interval, and the p-value for the test of "dAUC=0" by parametric bootstrap.

Usage

```
AUC_comparison(TP1, FP1, FN1, TN1, TP2, FP2, FN2, TN2, B=2000, alpha=0.05)
```

Arguments

| | |
|-----|--|
| TP1 | A vector of the number of true positives (TP) of test 1 |
| FP1 | A vector of the number of false positives (FP) of test 1 |

| | |
|-------|--|
| FN1 | A vector of the number of false negatives (FN) of test 1 |
| TN1 | A vector of the number of true negatives (TN) of test 1 |
| TP2 | A vector of the number of true positives (TP) of test 2 |
| FP2 | A vector of the number of false positives (FP) of test 2 |
| FN2 | A vector of the number of false negatives (FN) of test 2 |
| TN2 | A vector of the number of true negatives (TN) of test 2 |
| B | The number of bootstrap resampling (default: 2000) |
| alpha | The significance level (default: 0.05) |

Value

The AUCs of the summary ROC curves and their confidence intervals are calculated. Also, the difference of the AUCs (dAUC) and its confidence interval, and the p-value for the test of "dAUC=0" are provided.

- AUC1: The AUC of the summary ROC curve for test 1.
- AUC1_CI: The 95% confidence interval for the AUC of the summary ROC curve for test 1 (the confidence level can be changed by alpha).
- AUC2: The AUC of the summary ROC curve for test 2.
- AUC2_CI: The 95% confidence interval for the AUC of the summary ROC curve for test 2 (the confidence level can be changed by alpha).
- dAUC: The difference of the AUC1 and AUC2.
- dAUC_CI: The 95% confidence interval for dAUC (the confidence level can be changed by alpha).
- pvalue: The p-value of the test of dAUC=0.

Author(s)

Hisashi Noma <noma@ism.ac.jp>

References

Noma, H., Matsushima, Y., and Ishii, R. (2021). Confidence interval for the AUC of SROC curve and some related methods using bootstrap for meta-analysis of diagnostic accuracy studies. *Communications in Statistics: Case Studies and Data Analysis* 7: 344-358. doi:10.1080/23737484.2021.1894408

Examples

```
require(mada)

data(cervical)

CT <- cervical[cervical$method==1,]
LAG <- cervical[cervical$method==2,]
MRI <- cervical[cervical$method==3,]
```

```

fit1 <- reitsma(CT)      # DTA meta-analysis using the Reitsma model
summary(fit1)
fit2 <- reitsma(LAG)
summary(fit2)
fit3 <- reitsma(MRI)
summary(fit3)

plot(fit1)    # Plot the SROC curves
lines(sroc(fit2), lty=2, col="blue")
ROCellipse(fit2, lty=2, pch=2, add=TRUE, col="blue")
lines(sroc(fit3), lty=3, col="red")
ROCellipse(fit3, lty=3, pch=3, add=TRUE, col="red")
points(fpr(CT), sens(CT), cex = .5)
points(fpr(LAG), sens(LAG), pch = 2, cex = 0.5, col="blue")
points(fpr(MRI), sens(MRI), pch = 3, cex = 0.5, col="red")
legend("bottomright", c("CT", "LAG", "MRI"), pch = 1:3, lty = 1:3, col=c("black","blue","red"))

AUC_comparison(CT$TP,CT$FP,CT$FN,CT$TN,LAG$TP,LAG$FP,LAG$FN,LAG$TN,B=5)
AUC_comparison(MRI$TP,MRI$FP,MRI$FN,MRI$TN,LAG$TP,LAG$FP,LAG$FN,LAG$TN,B=5)
AUC_comparison(MRI$TP,MRI$FP,MRI$FN,MRI$TN,CT$TP,CT$FP,CT$FN,CT$TN,B=5)
# These are example commands for illustration. B should be >= 1000.

```

AUC_IF*Influence diagnostics based on the AUC of summary ROC curve***Description**

Influence diagnostics based on AUC of the summary ROC curve by leave-one-out analysis. The threshold to determine influential outlying study is computed by parametric bootstrap.

Usage

```
AUC_IF(TP, FP, FN, TN, B=2000, alpha=0.95)
```

Arguments

| | |
|-------|---|
| TP | A vector of the number of true positives (TP) |
| FP | A vector of the number of false positives (FP) |
| FN | A vector of the number of false negatives (FN) |
| TN | A vector of the number of true negatives (TN) |
| B | The number of bootstrap resampling (default: 2000) |
| alpha | The error level to be calculated for the bootstrap interval of deltaAUC (default: 0.95) |

Value

Influence diagnostic statistics based on the AUC of the summary ROC curve. The output is sorted by the absolute size of deltaAUC.

- AUC: The AUC of the summary ROC curve.
- id: identification number.
- AUC(-i): The AUC estimate if ith study is excluded.
- deltaAUC: The difference of AUC estimates for all study and for the subpopulation that ith study is excluded.
- Q1: Default 2.5th percentile of the bootstrap distribution of deltaAUC (can be changed by alpha).
- Q2: Default 97.5th percentile of the bootstrap distribution of deltaAUC (can be changed by alpha).

Author(s)

Hisashi Noma <noma@ism.ac.jp>

References

Noma, H., Matsushima, Y., and Ishii, R. (2021). Confidence interval for the AUC of SROC curve and some related methods using bootstrap for meta-analysis of diagnostic accuracy studies. *Communications in Statistics: Case Studies and Data Analysis* 7: 344-358. doi:[10.1080/23737484.2021.1894408](https://doi.org/10.1080/23737484.2021.1894408)

Examples

```
require(mada)

data(asthma)

fit1 <- reitsma(asthma)      # DTA analysis using the Reitsma model
summary(fit1)

plot(fit1) # Plot the SROC curves
points(fpr(asthma), sens(asthma), cex = .5)

attach(asthma)
AUC_IF(TP, FP, FN, TN, B=2)    # Influential analysis based on the AUC
detach(asthma)
# This is an example command for illustration. B should be >= 1000.
```

cervical

Scheidler et al. (1997)'s cervical cancer data

Description

- id: identification number
- author: The first author name of the corresponding study
- year: The published year of the corresponding study
- method: The diagnostic method; 1=CT (computed tomography), 2=LAG (lymphangiography), 3=MRI (magnetic resonance imaging)
- TP: A vector of the number of true positives (TP)
- FP: A vector of the number of false positives (FP)
- FN: A vector of the number of false negatives (FN)
- TN: A vector of the number of true negatives (TN)

Usage

```
data(cervical)
```

Format

A data frame with 44 rows and 8 variables

References

- Scheidler, J., Hricak, H., Yu, K. K., Subak, L., and Segal, M. R. (1997). Radiological evaluation of lymph node metastases in patients with cervical cancer. A meta-analysis. *JAMA* **278**: 1096-1101.
- Reitsma, J. B., Glas, A. S., Rutjes, A. W., Scholten, R. J., Bossuyt, P. M., and Zwinderman, A. H. (2005). Bivariate analysis of sensitivity and specificity produces informative summary measures in diagnostic reviews. *Journal of Clinical Epidemiology* **58**: 982-990. doi:[10.1016/j.jclinepi.2005.02.022](https://doi.org/10.1016/j.jclinepi.2005.02.022)
- Noma, H., Matsushima, Y., and Ishii, R. (2021). Confidence interval for the AUC of SROC curve and some related methods using bootstrap for meta-analysis of diagnostic accuracy studies. *Communications in Statistics: Case Studies and Data Analysis* **7**: 344-358. doi:[10.1080/23737484.2021.1894408](https://doi.org/10.1080/23737484.2021.1894408)

Index

* datasets

 asthma, [2](#)

 cervical, [8](#)

 asthma, [2](#)

 AUC_boot, [3](#)

 AUC_comparison, [4](#)

 AUC_IF, [6](#)

 cervical, [8](#)

dmetatools-package, [2](#)