

Package ‘enerscape’

January 29, 2024

Type Package

Title Compute Energy Landscapes

Version 1.1.0

Author Emilio Berti

Maintainer Emilio Berti <emilio.berti@idiv.de>

Description

Compute energy landscapes using a digital elevation model raster and body mass of animals.

License GPL-3

Encoding UTF-8

LazyData true

Imports Rcpp, methods, terra

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

LinkingTo Rcpp

RoxygenNote 7.2.0

Depends R (>= 2.10)

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation yes

Repository CRAN

Date/Publication 2024-01-29 13:20:02 UTC

R topics documented:

circuitscape_skeleton	2
distances	2
energy	3
energyscape	3
enerscape	4
neighbours	5
omniscape_skeleton	5

pontzer	6
sirente	6
slope	7

Index**8**

circuitscape_skeleton *Create the initialization file for the julia package Circuitscape*

Description

This creates the init file for the julia package Circuitscape: <https://juliapackages.com/p/circuitscape>.

Usage

```
circuitscape_skeleton(en = NULL, path = NULL, points = NULL)
```

Arguments

- | | |
|--------|---|
| en | an enerscape object. |
| path | full path where to write the .ini file. |
| points | data.frame with origin and destination coordinates. |

Value

Nothing, only write the circuitscape.ini file to disk.

distances *Spatial distances*

Description

Spatial distances

Usage

```
distances(x, center, res)
```

Arguments

- | | |
|--------|--|
| x | matrix with values |
| center | numeric value (double) with the value of the focal cell |
| res | numeric value (double) of the spatial resolution of the matrix |

Value

Vector with values the distances between x and center

energy

Energy Landscape

Description

Energy Landscape

Usage

```
energy(slope, distance, mass, res, kcal = TRUE)
```

Arguments

slope	vector with slopes
distance	vector with distances
mass	body mass of species (kg)
res	numeric value (double) of the spatial resolution of the matrix
kcal	(boolean) if to return the result in kCal (true) or J (false)

Value

Vector with the energy cost of locomotion (EnergyScape)

energyscape

Energy Landscape

Description

Energy Landscape

Usage

```
energyscape(x, n = 4L, mass = 0, res = 0, kcal = TRUE)
```

Arguments

x	matrix with values the elevation.
n	(integer) number of neighbours to consider (either 4 or 8).
mass	body mass of species (kg).
res	numeric value (double) of the spatial resolution of the matrix.
kcal	(boolean) if to return the result in kCal (true) or J (false).

Value

Matrix with the energy cost of locomotion (EnergyScape).

enerscape*Compute Energy Landscapes*

Description

This is the main function to compute energy landscapes from a digital elevation model and body mass of animals based on the model from Pontzer (2016). The core of the computations are done using the *gdistance* (Etten, 2017) package.

Usage

```
enerscape(dem, m, unit = "joule", neigh = 8)
```

Arguments

dem	raster file of the digital elevation model, either a raster or a full path location of the file.
m	species body mass (kg).
unit	if joules ('joule') or kilocalories ('kcal').
neigh	number of neighbor cells that are connected together.

Details

From the digital elevation model, transition slopes, energy costs and conductances (1 / work) are computed based on the model described in Pontzer (2016).

Value

A list with elements a rasterStack of the digital elevation model, slope, energy landscape, and conductance and the conductance as a transitionLayer for path analysis.

References

Pontzer, H. (2016). A unified theory for the energy cost of legged locomotion. *Biology Letters*, 12(2), 20150935. doi:[10.1098/rsbl.2015.0935](https://doi.org/10.1098/rsbl.2015.0935).

Examples

```
library(terra)
library(enerscape)

data("volcano")
dem <- rast(volcano)
en <- enerscape(dem, 10, unit = "kcal", neigh = 16)
```

neighbours	<i>Neighbours</i>
------------	-------------------

Description

Neighbours

Usage

```
neighbours(i, j, n, x)
```

Arguments

i	row index
j	column index
n	number of neighbours (4 or 8)
x	matrix with values

Value

Vector with values the neighbours of x

omniscape_skeleton	<i>Create the initialization file for the julia package Omniscape</i>
--------------------	---

Description

This creates the init file for the julia package Omniscape: <https://juliapackages.com/p/omniscape>.

Usage

```
omniscape_skeleton(en = NULL, path = NULL, radius = NULL, aggr_fact = 1)
```

Arguments

en	an enerscape object.
path	full path where to write the .ini file.
radius	radius in pixels of the moving window.
aggr_fact	the block size to compute the Omniscape.

Value

Nothing, only write the omniscape.ini file to disk.

pontzer

*Energy cost of transport from Pontzer (2016)***Description**

Energy cost of transport from Pontzer (2016)

Usage

```
pontzer
```

Format

A data frame with 92 rows and 5 variables:

Species species name

Incline incline of movement

Mass species body mass

Cost.of.Transport cost of transport

Source original source of data

Source

[doi:10.1098/rsbl.2015.0935](https://doi.org/10.1098/rsbl.2015.0935)

References

#' Pontzer, H. (2016). A unified theory for the energy cost of legged locomotion. *Biology Letters*, 12(2), 20150935.

sirente

*Monte Sirente Digital Elevation Model***Description**

A matrix with the digital elevation mode of the Monte Sirente (Central Italy).

Usage

```
sirente
```

Format

An object of class `matrix` (inherits from `array`) with 393 rows and 594 columns.

slope	<i>Slopes</i>
-------	---------------

Description

Slopes

Usage

```
slope(x, center, res)
```

Arguments

x	matrix with values
center	numeric value (double) with the value of the focal cell
res	numeric value (double) of the spatial resolution of the matrix

Value

Vector with values the slopes (degrees) between x and center

Index

* datasets

pontzer, [6](#)
sirente, [6](#)

[circuitscape_skeleton](#), [2](#)

[distances](#), [2](#)

[energy](#), [3](#)

[energyscape](#), [3](#)

[enerscape](#), [4](#)

[neighbours](#), [5](#)

[omniscape_skeleton](#), [5](#)

[pontzer](#), [6](#)

[sirente](#), [6](#)

[slope](#), [7](#)