

Package ‘fslr’

May 10, 2024

Type Package

Title Wrapper Functions for 'FSL' ('FMRIB' Software Library) from
Functional MRI of the Brain ('FMRIB')

Version 2.25.3

Maintainer John Muschelli <muschelli2@gmail.com>

Description Wrapper functions that interface with 'FSL'
<<http://fsl.fmrib.ox.ac.uk/fsl/fslwiki/>>, a powerful and commonly-
used 'neuroimaging'
software, using system commands. The goal is to be able to interface with 'FSL'
completely in R, where you pass R objects of class 'nifti', implemented by
package 'oro.nifti', and the function executes an 'FSL' command and returns an R
object of class 'nifti' if desired.

Imports methods, R.utils, graphics, grDevices, stats, utils

Depends oro.nifti (>= 0.5.0), neurobase (>= 1.32.0), R (>= 3.2.0)

License GPL-3

VignetteBuilder knitr

Suggests knitr, rmarkdown, covr

BugReports <https://github.com/muschelli2/fslr/issues>

SystemRequirements FSL

Encoding UTF-8

RoxygenNote 7.3.1

NeedsCompilation no

Author John Muschelli [aut, cre] (<<https://orcid.org/0000-0001-6469-1750>>)

Repository CRAN

Date/Publication 2024-05-10 04:20:02 UTC

R topics documented:

| | |
|----------------------------|---|
| applytopup | 6 |
| aux.file-methods | 7 |

| | |
|-------------------------|----|
| bitpix-methods | 7 |
| cal.max-methods | 7 |
| cal.min-methods | 8 |
| checkout | 8 |
| check_file | 9 |
| datatype-methods | 9 |
| data_type-methods | 10 |
| descrip-methods | 10 |
| dim_-methods | 10 |
| download_fsl | 11 |
| dtifit | 11 |
| eddy | 12 |
| eddy_correct | 14 |
| enforce_form | 14 |
| face_removal_mask | 15 |
| fast | 16 |
| fast.help | 17 |
| flirt | 18 |
| flirt.help | 19 |
| flirt_apply | 19 |
| fnirt | 20 |
| fnirt.help | 21 |
| fnirt_with_affine | 21 |
| fnirt_with_affine_apply | 22 |
| fslabs.help | 24 |
| fslacos.help | 24 |
| fsladd.help | 25 |
| fsland | 25 |
| fslasin.help | 26 |
| fslatan.help | 26 |
| fslbet.help | 27 |
| fslbin.help | 28 |
| fslbinv.help | 28 |
| fslchfiletype | 29 |
| fslchfiletype.help | 30 |
| fslcmd | 30 |
| fslcog | 31 |
| fslcos.help | 32 |
| fslcpgeom | 33 |
| fslcpgeom.help | 34 |
| fsldir | 34 |
| fsldiv.help | 35 |
| fsledge.help | 35 |
| fslentropy | 36 |
| fslspi_reg | 36 |
| fslerode.help | 38 |
| fslexp.help | 38 |
| fslfill.help | 39 |

| | |
|----------------------|----|
| fslfill2 | 39 |
| fslgetorient | 40 |
| fslhd | 41 |
| fslhd.help | 41 |
| fslhd.parse | 42 |
| fslhelp | 42 |
| fslindex.help | 43 |
| fsllog.help | 44 |
| fslmask.help | 44 |
| fslmaths.help | 45 |
| fslmax | 45 |
| fslmean | 46 |
| fslmerge.help | 46 |
| fslmul.help | 47 |
| fslnan.help | 47 |
| fslnanm.help | 48 |
| fslor | 49 |
| fslorient | 50 |
| fslorient.help | 50 |
| fslorienter | 51 |
| fslrand.help | 51 |
| fslrandn.help | 52 |
| fslrange | 52 |
| fslrecip.help | 53 |
| fslrem.help | 54 |
| fslreorient2std | 54 |
| fslreorient2std.help | 55 |
| fslrobustfov | 56 |
| fslrobustfov.help | 57 |
| fslroi | 57 |
| fslsd | 58 |
| fslsin | 59 |
| fslsin.help | 60 |
| fslslicetimer | 60 |
| fslsmooth.help | 61 |
| fslsmooth_in_mask | 62 |
| fslsplit | 63 |
| fslsplit.help | 64 |
| fslsqr.help | 64 |
| fslsqrt.help | 65 |
| fslstats | 65 |
| fslstats.help | 66 |
| fslsub.help | 66 |
| fslsub2.help | 67 |
| fslsum | 68 |
| fslswapdim.help | 68 |
| fsltan.help | 69 |
| fslthresh.help | 69 |

| | |
|------------------------------|-----|
| fslval | 70 |
| fslval.help | 70 |
| fslview | 71 |
| fslview.help | 72 |
| fslvol | 72 |
| fslvolume | 73 |
| fslxor | 73 |
| fsl_abs | 74 |
| fsl_acos | 75 |
| fsl_add | 76 |
| fsl_anat | 77 |
| fsl_anat.help | 78 |
| fsl_applywarp | 79 |
| fsl_applywarp.help | 80 |
| fsl_asin | 80 |
| fsl_atan | 81 |
| fsl_atlas_dir | 82 |
| fsl_avscale | 82 |
| fsl_bet | 83 |
| fsl_biascorrect | 84 |
| fsl_bin | 85 |
| fsl_binv | 86 |
| fsl_bin_tab | 87 |
| fsl_cluster | 87 |
| fsl_cos | 89 |
| fsl_data_dir | 90 |
| fsl_deface | 91 |
| fsl_dice | 92 |
| fsl_dilate | 92 |
| fsl_div | 94 |
| fsl_edge | 95 |
| fsl_erode | 96 |
| fsl_exp | 97 |
| fsl_fill | 98 |
| fsl_index | 99 |
| fsl_log | 100 |
| fsl_mask | 101 |
| fsl_maths | 102 |
| fsl_merge | 103 |
| fsl_mul | 104 |
| fsl_nan | 105 |
| fsl_nanm | 106 |
| fsl_rand | 107 |
| fsl_randn | 108 |
| fsl_recip | 109 |
| fsl_rem | 110 |
| fsl_resample | 111 |
| fsl_smooth | 112 |

| | |
|------------------------|-----|
| fsl_smoothest | 113 |
| fsl_sqr | 114 |
| fsl_sqrt | 115 |
| fsl_std_dir | 116 |
| fsl_sub | 116 |
| fsl_sub2 | 117 |
| fsl_swapdim | 118 |
| fsl_tan | 119 |
| fsl_thresh | 120 |
| fsl_tsplot | 122 |
| fsl_version | 123 |
| get.fsl | 124 |
| get.fsloutput | 125 |
| get.imgext | 125 |
| getForms | 126 |
| get_quickshear_mask | 126 |
| have.fsl | 127 |
| intent_code-methods | 128 |
| intent_name-methods | 128 |
| intent_p1-methods | 129 |
| intent_p2-methods | 129 |
| intent_p3-methods | 129 |
| invert_xfm | 130 |
| magic-methods | 131 |
| mcflirt | 131 |
| mcflirt.help | 132 |
| melodic | 132 |
| melodic.help | 133 |
| mid_sagittal_align | 134 |
| mni_fname | 134 |
| mni_img | 135 |
| mridefacer | 136 |
| parse_avscale | 137 |
| pixdim-methods | 137 |
| probtrackx | 138 |
| qform,character-method | 140 |
| qform_code-methods | 141 |
| readrpi | 141 |
| read_xfm | 142 |
| reverse_rpi_orient | 142 |
| rpi_orient | 143 |
| run_first_all | 144 |
| run_first_all.help | 145 |
| scl_inter-methods | 146 |
| scl_slope-methods | 146 |
| sform_code-methods | 146 |
| sizeof_hdr-methods | 147 |
| slice_code-methods | 147 |

| | |
|----------------------------------|-----|
| slice_duration-methods | 148 |
| slice_end-methods | 148 |
| slice_start-methods | 149 |
| susan | 149 |
| susan.help | 150 |
| toffset-methods | 151 |
| topup | 151 |
| vox_offset-methods | 153 |
| xfibres | 153 |

| | |
|--------------|------------|
| Index | 155 |
|--------------|------------|

| | |
|------------|--|
| applytopup | <i>applytopup - calling FSL applytopup</i> |
|------------|--|

Description

A tool for applying and correcting estimated susceptibility induced distortions

Usage

```

applytopup(
  infile,
  datain,
  index,
  topup_files,
  out = NULL,
  method = c("lsr", "jac"),
  interp = c("spline", "trilinear"),
  verbose = TRUE
)

apply_topup(...)

fsl_applytopup(...)

```

Arguments

| | |
|-------------|---|
| infile | list of names of input image (to be corrected) |
| datain | name of text file with PE directions/times |
| index | list of indices into -datain of the input image (to be corrected) |
| topup_files | name of field/movements (from topup) |
| out | basename for output (warped) image |
| method | Use jacobian modulation (jac) or least-squares resampling (lsr), default=lsr. |
| interp | Image interpolation model, trilinear or spline. Default spline |
| verbose | Print diagnostic information while running |
| ... | arguments passed to topup if using fsl_topup |

aux.file-methods *Extract Image aux.file attribute*

Description

aux_file method for character types

Usage

```
## S4 method for signature 'character'  
aux.file(object)
```

Arguments

object is a filename to pass to [fslval](#)

bitpix-methods *Extract Image bitpix attribute*

Description

bitpix method for character types

Usage

```
## S4 method for signature 'character'  
bitpix(object)
```

Arguments

object is a filename to pass to [fslval](#)

cal.max-methods *Extract Image cal.max attribute*

Description

cal_max method for character types

Usage

```
## S4 method for signature 'character'  
cal.max(object)
```

Arguments

object is a filename to pass to [fslval](#)

| | |
|-----------------|--|
| cal.min-methods | <i>Extract Image cal.min attribute</i> |
|-----------------|--|

Description

cal_min method for character types

Usage

```
## S4 method for signature 'character'
cal.min(object)
```

Arguments

object is a filename to pass to [fslval](#)

| | |
|----------|--|
| checkout | <i>Determine if Q and S forms are consistent</i> |
|----------|--|

Description

This function determines if the determinants of the sform and qform have the same sign

Usage

```
checkout(hd)
```

Arguments

hd (list) sforms from [getForms](#)

Value

logical indicating if sform and qform consistent

Examples

```
if (have.fsl()){
  mnifile = file.path(fsldir(), "data", "standard",
    "MNI152_T1_2mm.nii.gz")
  forms = getForms(mnifile)
  checkout(forms)
}
```

| | |
|------------|---|
| check_file | <i>Wrapper for getForms with filename</i> |
|------------|---|

Description

Checking the q/s-forms for a header

Usage

```
check_file(file, ...)
```

Arguments

| | |
|------|---|
| file | (character) filename of image to be checked |
| ... | options passed to checking |

Value

result of [checkout](#)

Examples

```
library(fslr)
if (have.fsl()){
  mnifile = mni_fname("2")
  check_file(mnifile)
}
```

| | |
|------------------|---|
| datatype-methods | <i>Extract Image datatype attribute</i> |
|------------------|---|

Description

datatype method for character types

Usage

```
## S4 method for signature 'character'
datatype(object)
```

Arguments

| | |
|--------|---|
| object | is a filename to pass to fslval |
|--------|---|

data_type-methods *Extract Image data_type attribute*

Description

data_type method for character types

Usage

```
## S4 method for signature 'character'  
data_type(object)
```

Arguments

object is a filename to pass to [fslval](#)

descrip-methods *Extract Image descrip attribute*

Description

descrip method for character types

Usage

```
## S4 method for signature 'character'  
descrip(object)
```

Arguments

object is a filename to pass to [fslval](#)

dim_-methods *Extract Image dim_ attribute*

Description

dim_ method for class character

Usage

```
## S4 method for signature 'character'  
dim_(object)
```

Arguments

object is a filename to pass to [fslval](#)

| | |
|--------------|---------------------|
| download_fsl | <i>Download FSL</i> |
|--------------|---------------------|

Description

Download FSL Tarball

Usage

```
download_fsl(
  os = c("macosx", "redhat5", "redhat6", "centos5", "centos6", "debian", "ubuntu"),
  outdir = tempdir(),
  overwrite = TRUE,
  ...
)
```

Arguments

| | |
|-----------|--|
| os | Operating system |
| outdir | Output directory for tarball |
| overwrite | If file.path(outdir, tarball_name) exists, should it be overwritten? |
| ... | Arguments to pass to download.file |

Value

Filename of destination file

| | |
|--------|---------------------------------------|
| dtifit | <i>DTI Fitting Procedure from FSL</i> |
|--------|---------------------------------------|

Description

Calls dtifit from FSL

Usage

```
dtifit(
  infile,
  bvecs,
  bvals,
  mask = NULL,
  outprefix = NULL,
  opts = "",
  bet.opts = "",
  verbose = TRUE,
```

```

    sse = FALSE,
    save_tensor = FALSE,
    grad_image = NULL
)

```

Arguments

| | |
|-------------|---|
| infile | Input filename |
| bvecs | b-vectors: matrix of 3 columns or filename of ASCII text file |
| bvals | b-values: vector of same length as number of rows of b-vectors or filename of ASCII text file |
| mask | Mask filename |
| outprefix | Output prefix |
| opts | Additional options for dtifit |
| bet.opts | Options for <code>fs1bet</code> if mask is not supplied |
| verbose | print diagnostic messages |
| sse | Save sum of squared errors |
| save_tensor | Save tensor file out |
| grad_image | Gradient Nonlinearity Tensor file |

Value

Vector of character filenames of output. See Note

Note

On successful completion of the command, the following files will be output, which are: mask - the mask used in the analysis outprefix_V1 - 1st eigenvector outprefix_V2 - 2nd eigenvector outprefix_V3 - 3rd eigenvector outprefix_L1 - 1st eigenvalue outprefix_L2 - 2nd eigenvalue outprefix_L3 - 3rd eigenvalue outprefix_MD - mean diffusivity outprefix_FA - fractional anisotropy outprefix_MO - mode of the anisotropy (oblate ~ -1; isotropic ~ 0; prolate ~ 1) outprefix_S0 - raw T2 signal with no diffusion weighting optional output If sse = TRUE, then the additional file will be present: outprefix_sse - Sum of squared error If save_tensor = TRUE, then the additional file will be present: outprefix_tensor - tensor as a 4D file in this order: Dxx,Dxy,Dxz,Dyy,Dyz,Dzz

eddy

Eddy Current Correction

Description

This function calls eddy from FSL for DTI Processing

Usage

```

eddy(
  infile,
  mask,
  acq_file,
  index_file,
  bvecs,
  bvals,
  topup = NULL,
  outfile = NULL,
  retimg = TRUE,
  opts = "",
  verbose = TRUE,
  eddy_cmd = c("eddy", "eddy_openmp", "eddy_cuda"),
  ...
)

```

Arguments

| | |
|-------------------------|---|
| <code>infile</code> | input filename of 4D image. |
| <code>mask</code> | Mask filename (or class nifti) |
| <code>acq_file</code> | A text-file describing the acquisition parameters for the different images in <code>infile</code> . The format of this file is identical to that used by <code>topup</code> (though the parameter is called <code>--datain</code> there). |
| <code>index_file</code> | A text-file that determines the relationship between on the one hand the images in <code>infile</code> and on the other hand the acquisition parameters in <code>acq_file</code> . |
| <code>bvecs</code> | A text file with normalised vectors describing the direction of the diffusion weighting. |
| <code>bvals</code> | A text file with b-values describing the "amount of" diffusion weighting |
| <code>topup</code> | This should only be specified if you have previously run 'topup' on your data and should be the same name that you gave as an argument to the <code>--out</code> parameter when you ran <code>topup</code> , aka the base name for output files from <code>topup</code> . |
| <code>outfile</code> | Output file basename |
| <code>retimg</code> | (logical) return image of class nifti |
| <code>opts</code> | Additional options to pass to arguments passed to eddy |
| <code>verbose</code> | print diagnostic messages |
| <code>eddy_cmd</code> | The version of <code>eddy</code> to run. |
| <code>...</code> | Not currently used |

Value

Result from system command currently

| | |
|--------------|--------------------------------|
| eddy_correct | <i>Eddy Current Correction</i> |
|--------------|--------------------------------|

Description

This function calls eddy_correct from FSL for DTI Processing

Usage

```
eddy_correct(infile, outfile = NULL, retimg = TRUE, reference_no = 0, ...)
```

Arguments

| | |
|--------------|---|
| infile | input filename of 4D image. |
| outfile | Output filename |
| retimg | (logical) return image of class nifti |
| reference_no | Set the volume number for the reference volume that will be used as a target to register all other volumes to. (default=0, i.e. the first volume) |
| ... | Additional arguments passed to fslcmd |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

| | |
|--------------|---|
| enforce_form | <i>Enforce Either Qform or Sform is set</i> |
|--------------|---|

Description

Enforce Either Qform or Sform is set

Usage

```
enforce_form(file, ...)
```

Arguments

| | |
|------|--|
| file | (character) image filename or character of class nifti |
| ... | additional arguments to pass to getForms |

Value

A character filename

Examples

```
if (have_fsl()) {
  res = enforce_form(mni_fname())
}
```

| | |
|-------------------|--------------------------|
| face_removal_mask | <i>Face Removal Mask</i> |
|-------------------|--------------------------|

Description

Face Removal Mask

Usage

```
face_removal_mask(
  file,
  template = mni_fname(mm = "1"),
  face_mask = mni_face_fname(mm = "1"),
  outfile = NULL,
  dof = 12,
  cost = "mutualinfo",
  retimg = FALSE
)

deface_image(file, ...)
```

Arguments

| | |
|-----------|---|
| file | input image |
| template | Template image to register input image to. Set to NULL (recommended) if want to use from https://github.com/poldracklab/pydeface . Alternatively, use mni_fname . |
| face_mask | Mask of image, in same space as template. Set to NULL (recommended) if want to use from https://github.com/poldracklab/pydeface . Alternatively, use mni_face_fname . |
| outfile | Output file name |
| dof | (numeric) degrees of freedom (default 6 - rigid body) |
| cost | Cost function passed to flirt |
| retimg | (logical) return image of class nifti |
| ... | not used |

Value

An image or filename depending on retimg

Examples

```

if (have_fsl()) {
  file = "~/Downloads/sample_T1_input.nii.gz"
  if (file.exists(file)) {
    mask = face_removal_mask(file = file,
                             template = NULL, face_mask = NULL)
    image = fslmask(file, mask)
  }
}

```

fast

FSL FAST

Description

This function calls fast from FSL

Usage

```

fast(
  file,
  outfile = NULL,
  bias_correct = TRUE,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  type = c("T1", "T2", "PD"),
  out_type = c("seg", "mixeltype", "pve_0", "pve_1", "pve_2", "pveseg"),
  verbose = TRUE,
  all_images = FALSE,
  ...
)

fast_all(..., all_images = TRUE)

fast_nobias_all(..., bias_correct = FALSE, all_images = FALSE)

fsl_fast(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)

fslfast(...)

fsl_fast_nobias(
  ...,
  bias_correct = FALSE,

```

```

    outfile = tempfile(fileext = ".nii.gz"),
    retimg = FALSE
)

fast_nobias(..., bias_correct = FALSE)

fslfast_nobias(..., bias_correct = FALSE)

```

Arguments

| | |
|--------------|--|
| file | (character) image to be manipulated |
| outfile | (character) resultant image name (optional) |
| bias_correct | (logical) if FALSE, then "--nobias" is passed to FAST. Additional options can be sent using opts, but this is the most commonly one changed. |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to fast |
| type | type of image T1, T2, or PD. |
| out_type | (character) Suffix to grab from outfile. For example, output filename is paste0(outfile, "_", out_type) |
| verbose | (logical) print out command before running |
| all_images | If retimg |
| ... | additional arguments passed to readnii . |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fast.help

FAST help

Description

This function calls fast's help

Usage

```
fast.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fast.help()
}
```

 flirt

Register using FLIRT

Description

This function calls `flirt` to register `infile` to `reffile` and either saves the image or returns an object of class `nifti`, along with the transformation matrix `omat`

Usage

```
flirt(
  infile,
  reffile,
  omat = NULL,
  dof = 6,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|-----------------------|--|
| <code>infile</code> | (character) input filename |
| <code>reffile</code> | (character) reference image to be registered to |
| <code>omat</code> | (character) Output matrix name |
| <code>dof</code> | (numeric) degrees of freedom (default 6 - rigid body) |
| <code>outfile</code> | (character) output filename |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) pass to system |
| <code>opts</code> | (character) additional options to FLIRT |
| <code>verbose</code> | (logical) print out command before running |
| <code>...</code> | additional arguments passed to readnii . |

Value

character or logical depending on intern

flirt.help

FLIRT help

Description

This function calls `flirt`'s help

Usage

```
flirt.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  flirt.help()
}
```

flirt_apply

Apply Warp from FLIRT

Description

This function applies a matrix from `flirt` to other images

Usage

```
flirt_apply(
  infile,
  reffile,
  initmat,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|----------|--|
| infile | (character) input filename |
| reffile | (character) reference image to be registered to |
| initmat | (character) Matrix of transformation |
| outfile | (character) output filename |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) pass to system |
| opts | (character) additional options to FLIRT |
| verbose | (logical) print out command before running |
| ... | additional arguments passed to readnii . |

Value

character or logical depending on intern

| | |
|-------|-----------------------------|
| fnirt | <i>Register using FNIRT</i> |
|-------|-----------------------------|

Description

This function calls `fnirt` to register `infile` to `reffile` and either saves the image or returns an object of class `nifti`

Usage

```
fnirt(
  infile,
  reffile,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|----------|--|
| infile | (character) input filename |
| reffile | (character) reference image to be registered to |
| outfile | (character) output filename |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) pass to system |
| opts | (character) additional options to FLIRT |
| verbose | (logical) print out command before running |
| ... | additional arguments passed to readnii . |

Value

character or logical depending on intern

fnirt.help

FNIRT help

Description

This function calls fnirt's help

Usage

fnirt.help()

Value

Prints help output and returns output as character vector

fnirt_with_affine

Register using FNIRT, but doing Affine Registration as well

Description

This function calls fnirt to register infile to reffile and either saves the image or returns an object of class nifti, but does the affine registration first

Usage

```
fnirt_with_affine(
  infile,
  reffile,
  flirt.omat = NULL,
  flirt.outfile = NULL,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  flirt.opts = "",
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|---------------|--|
| infile | (character) input filename |
| reffile | (character) reference image to be registered to |
| flirt.omat | (character) Filename of output affine matrix |
| flirt.outfile | (character) Filename of output affine-registered image |
| outfile | (character) output filename |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) pass to system |
| flirt.opts | (character) additional options to FLIRT |
| opts | (character) additional options to FNIRT |
| verbose | (logical) print out command before running |
| ... | additional arguments passed to readnii . |

Value

character or logical depending on intern

fnirt_with_affine_apply

Applies FLIRT then FNIRT transformations

Description

Applies an affine transformation with FLIRT then the warp image with FNIRT

Usage

```
fnirt_with_affine_apply(  
  infile,  
  reffile,  
  flirt.omat = NULL,  
  flirt.outfile = NULL,  
  fnirt.warpfile = NULL,  
  outfile = NULL,  
  retimg = TRUE,  
  reorient = FALSE,  
  intern = FALSE,  
  flirt.opts = "",  
  opts = "",  
  verbose = TRUE,  
  ...  
)
```

Arguments

| | |
|-----------------------------|--|
| <code>infile</code> | (character) input filename |
| <code>reffile</code> | (character) reference image to be registered to |
| <code>flirt.omat</code> | (character) Filename of output affine matrix |
| <code>flirt.outfile</code> | (character) Filename of output affine-registered image |
| <code>fnirt.warpfile</code> | (character) Filename of warp image from fnirt |
| <code>outfile</code> | (character) output filename |
| <code>retimg</code> | (logical) return image of class nifti |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) pass to system |
| <code>flirt.opts</code> | (character) additional options to FLIRT |
| <code>opts</code> | (character) additional options to FNIRT |
| <code>verbose</code> | (logical) print out command before running |
| <code>...</code> | additional arguments passed to readnii . |

Value

character or logical depending on `intern`

See Also

[fnirt_with_affine](#)

fslabs.help

fslabs Help

Description

This function calls fslmaths's help, as fslabs is a wrapper for fslmaths

Usage

```
fslabs.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslabs.help()  
}
```

fslacos.help

fslacos Help

Description

This function calls fslmaths's help, as fslacos is a wrapper for fslmaths

Usage

```
fslacos.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslacos.help()  
}
```

`fsladd.help`*fsladd Help*

Description

This function calls `fslmaths`'s help, as `fsladd` is a wrapper for `fslmaths`

Usage

```
fsladd.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fsladd.help()  
}
```

`fsland`*Logical AND with Images using FSL*

Description

This function multiplies two images using [fslmul](#)) after binarizing the images (using [fslbin](#)

Usage

```
fsland(file, file2, ...)
```

```
fsl_and(file, file2, ...)
```

Arguments

`file` (character) input image

`file2` (character) image to be multiplied

... additional arguments passed to [fslmul](#).

Value

If `retimg` then object of class `nifti`. Otherwise, result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

| | |
|--------------|---------------------|
| fslasin.help | <i>fslasin Help</i> |
|--------------|---------------------|

Description

This function calls `fslmaths`'s `help`, as `fslasin` is a wrapper for `fslmaths`

Usage

```
fslasin.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslasin.help()
}
```

| | |
|--------------|---------------------|
| fslatan.help | <i>fslatan Help</i> |
|--------------|---------------------|

Description

This function calls `fslmaths`'s `help`, as `fslatan` is a wrapper for `fslmaths`

Usage

```
fslatan.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslatan.help()  
}
```

fslbet.help

Help for FSL BET

Description

This function calls bet's help

Usage

```
fslbet.help(betcmd = c("bet2", "bet"))
```

Arguments

betcmd (character) Get help for bet or bet2 function

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslbet.help()  
  fslbet.help("bet")  
}
```

fslbin.help

fslbin Help

Description

This function calls fslmaths's help, as fslbin is a wrapper for fslmaths

Usage

```
fslbin.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslbin.help()  
}
```

fslbinv.help

fslbinv Help

Description

This function calls fslmaths's help, as fslbinv is a wrapper for fslmaths

Usage

```
fslbinv.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslbinv.help()  
}
```

| | |
|---------------|-----------------------------|
| fslchfiletype | <i>FSL Change file type</i> |
|---------------|-----------------------------|

Description

This function calls `fslchfiletype`

Usage

```
fslchfiletype(  
  file,  
  filetype = "NIFTI_GZ",  
  outfile = NULL,  
  retimg = TRUE,  
  reorient = FALSE,  
  intern = FALSE,  
  verbose = TRUE,  
  ...  
)
```

Arguments

| | |
|-----------------------|--|
| <code>file</code> | (character) image to be manipulated |
| <code>filetype</code> | filetype to change image to |
| <code>outfile</code> | Output filename. If NULL, will overwrite input file |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>verbose</code> | (logical) print out command before running |
| <code>...</code> | additional arguments passed to readnii . |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is TRUE or FALSE.

fslchfiletype.help *fslchfiletype help*

Description

This function calls fslchfiletype's help

Usage

```
fslchfiletype.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslchfiletype.help()
}
```

fslcmd *FSL Command Wrapper*

Description

This function calls fsl command passed to func

Usage

```
fslcmd(
  func,
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  verbose = TRUE,
  samefile = FALSE,
  opts_after_outfile = FALSE,
  frontopts = "",
  no.outfile = FALSE,
  trim_front = FALSE,
  run = TRUE,
  ...
)
```

Arguments

| | |
|--------------------|--|
| func | (character) FSL function |
| file | (character) image to be manipulated |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to func |
| verbose | (logical) print out command before running |
| samefile | (logical) is the output the same file? |
| opts_after_outfile | (logical) should opts come after the outfile in the FSL command? |
| frontopts | (character) options/character to put in before filename |
| no.outfile | (logical) is there an output file in the arguments of the FSL function? |
| trim_front | trim the whitespace from the front of the command. |
| run | (logical) Should the command just be printed (if FALSE)? |
| ... | additional arguments passed to readnii . |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

| | |
|--------|--------------------------------------|
| fslcog | <i>Image Center of Gravity (FSL)</i> |
|--------|--------------------------------------|

Description

Find Center of Gravity of Image from FSL

Usage

```
fslcog(img, mm = TRUE, verbose = TRUE, ts = FALSE)
```

Arguments

| | |
|---------|--|
| img | Object of class nifti, or path of file |
| mm | Logical if the center of gravity (COG) would be in mm (default TRUE) or voxels (FALSE) |
| verbose | (logical) print out command before running |
| ts | (logical) is the series a timeseries (4D), invoking -t option |

Value

Vector of length 3 unless ts option invoked

Note

FSL uses a 0-based indexing system, which will give you a different answer compared to cog, but `fslcog(img, mm = FALSE) + 1` should be relatively close to `cog(img)`

Examples

```
if (have.fsl()){
  x = array(rnorm(1e6), dim = c(100, 100, 100))
  img = nifti(x, dim= c(100, 100, 100),
  datatype = convert.datatype()$FLOAT32, cal.min = min(x),
  cal.max = max(x), pixdim = rep(1, 4))
  fslcog(img)
}
```

fslcos.help

fslcos Help

Description

This function calls `fslmaths`'s help, as `fslcos` is a wrapper for `fslmaths`

Usage

```
fslcos.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslcos.help()
}
```

`fslcpgeom`*FSL Copy Geometry*

Description

This function calls `fslcpgeom`

Usage

```
fslcpgeom(  
  file,  
  file_with_header,  
  retimg = TRUE,  
  reorient = FALSE,  
  intern = FALSE,  
  opts = "",  
  verbose = TRUE,  
  ...  
)
```

Arguments

| | |
|-------------------------------|--|
| <code>file</code> | (character) image to be manipulated |
| <code>file_with_header</code> | image with header to be copied over |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>opts</code> | (character) operations to be passed to <code>fslmaths</code> |
| <code>verbose</code> | (logical) print out command before running |
| <code>...</code> | additional arguments passed to readnii . |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is TRUE or FALSE.

| | |
|----------------|-----------------------|
| fslcpgeom.help | <i>fslcpgeom help</i> |
|----------------|-----------------------|

Description

This function calls fslcpgeom's help

Usage

```
fslcpgeom.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslcpgeom.help()  
}
```

| | |
|---------|----------------------------|
| fsl_dir | <i>Get FSL's Directory</i> |
|---------|----------------------------|

Description

Finds the FSLDIR from system environment or getOption("fsl.path") for location of FSL functions and returns it

Usage

```
fsl_dir()  
  
fsl_dir()
```

Value

Character path

`fsldiv.help`*fsldiv Help*

Description

This function calls `fslmaths`'s `help`, as `fsldiv` is a wrapper for `fslmaths`

Usage

```
fsldiv.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fsldiv.help()  
}
```

`fsledge.help`*fsledge Help*

Description

This function calls `fslmaths`'s `help`, as `fsledge` is a wrapper for `fslmaths`

Usage

```
fsledge.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fsledge.help()  
}
```

| | |
|------------|---------------------------|
| fslentropy | <i>Image Mean Entropy</i> |
|------------|---------------------------|

Description

Estimates Mean Entropy of Image from FSL

Usage

```
fslentropy(img, nonzero = FALSE, verbose = TRUE, ts = FALSE)
```

Arguments

| | |
|---------|---|
| img | Object of class nifti, or path of file |
| nonzero | (logical) Should the statistic be taken over non-zero voxels |
| verbose | (logical) print out command before running |
| ts | (logical) is the series a timeseries (4D), invoking -t option |

Value

Vector of unless ts option invoked, then matrix

Note

This uses option -e or -E in [fslstats](#)

| | |
|------------|--|
| fslepi_reg | <i>Register EPI images to Structural image</i> |
|------------|--|

Description

This function calls `epi_reg`, designed to register EPI images (typically functional or diffusion) to structural (e.g. T1-weighted) image.

Usage

```
fslepi_reg(
  epi,
  t1,
  t1_brain,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  fmap = NULL,
```

```

    fmap_mag = NULL,
    fmap_mag_brain = NULL,
    echo_spacing = NA,
    phase_enc_dir = c("x", "y", "z", "-x", "-y", "-z"),
    weight = NULL,
    verbose = TRUE,
    opts = "",
    ...
)

fsl_epi_reg(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)

epi_reg(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)

```

Arguments

| | |
|----------------|--|
| epi | EPI image, character or nifti object |
| t1 | whole head T1 image , character or nifti object |
| t1_brain | brain extracted T1 image |
| outfile | output registered image filename |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| fmap | fieldmap image (in rad/s) |
| fmap_mag | fieldmap magnitude image - whole head extracted |
| fmap_mag_brain | fieldmap magnitude image - brain extracted |
| echo_spacing | Effective EPI echo spacing (sometimes called dwell time) - in seconds |
| phase_enc_dir | phase encoding direction, dir = x/y/z/-x/-y/-z |
| weight | weighting image (in T1 space) |
| verbose | (logical) print out command before running |
| opts | (character) operations to be passed to fslmaths |
| ... | additional arguments passed to readnii . |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fslerode.help

fslerode Help

Description

This function calls `fslmaths`'s `help`, as `fslerode` is a wrapper for `fslmaths`

Usage

```
fslerode.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslerode.help()  
}
```

fslexp.help

fslexp Help

Description

This function calls `fslmaths`'s `help`, as `fslexp` is a wrapper for `fslmaths`

Usage

```
fslexp.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslexp.help()  
}
```

`fslfill.help`*fslfill Help*

Description

This function calls `fslmaths`'s help, as `fslfill` is a wrapper for `fslmaths`

Usage

```
fslfill.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslfill.help()
}
```

`fslfill2`*Fill image holes with dilation then erosion*

Description

This function calls `fslmaths` to dilate an image, then calls it again to erode it.

Usage

```
fslfill2(
  file,
  outfile = NULL,
  kopts = "",
  remove.ends = TRUE,
  refill = TRUE,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|-------------|---|
| file | (character) filename of image to be filled |
| outfile | (character) name of resultant filled file |
| kopts | (character) Options passed for kernel before erosion/dilation |
| remove.ends | (logical) Remove top and bottom dilation. |
| refill | (logical) Run <code>fslfill</code> after dilation/erosion. |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to <code>readnii</code> . |
| intern | (logical) pass to <code>system</code> |
| verbose | (logical) print out command before running |
| ... | additional arguments passed to <code>readnii</code> . |

Value

character or logical depending on intern

Note

This function binarizes the image before running.

fslgetorient

FSL Orientation Wrappers

Description

This function calls `fslorient -get*` and is a simple wrapper of `fslorient`

Usage

```
fslgetorient(file, verbose = TRUE)
fslgetsform(file, verbose = TRUE)
fslgetqform(file, verbose = TRUE)
fslgetsformcode(file, verbose = TRUE)
fslgetqformcode(file, verbose = TRUE)
```

Arguments

| | |
|---------|--|
| file | (character) image to be manipulated |
| verbose | (logical) print out command before running |

Value

Result from system command, output from FSL

| | |
|-------|-----------------------------------|
| fslhd | <i>Get NIfTI header using FSL</i> |
|-------|-----------------------------------|

Description

This function calls `fslhd` to obtain a nifti header

Usage

```
fslhd(file, opts = "", verbose = TRUE, ...)
```

Arguments

| | |
|----------------------|---|
| <code>file</code> | (character) image filename or character of class nifti |
| <code>opts</code> | (character) additional options to be passed to <code>fslhd</code> |
| <code>verbose</code> | (logical) print out command before running |
| <code>...</code> | options passed to checking |

Value

Character of information from `fslhd`

Examples

```
if (have.fsl()){  
  mnifile = file.path(fsldir(), "data", "standard",  
    "MNI152_T1_2mm.nii.gz")  
  fslhd(mnifile)  
}
```

| | |
|------------|-------------------|
| fslhd.help | <i>FSLhd help</i> |
|------------|-------------------|

Description

This function calls `fslhd`'s help

Usage

```
fslhd.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslhd.help()
}
```

fslhd.parse

Parse FSL Header

Description

This function takes in a FSL header and parses the components

Usage

```
fslhd.parse(hd)
```

Arguments

hd (character) header from [fslhd](#)

Value

data.frame of information from FSL header

Examples

```
if (have.fsl()){
  mnifile = mni_fname("2")
  hd = fslhd(mnifile)
  fslhd.parse(hd)
}
```

fslhelp

Wrapper for getting fsl help

Description

This function takes in the function and returns the help from FSL for that function

Usage

```
fslhelp(func_name, help.arg = "--help", extra.args = "")
```

Arguments

| | |
|------------|--|
| func_name | FSL function name |
| help.arg | Argument to print help, usually "--help" |
| extra.args | Extra arguments to be passed other than --help |

Value

Prints help output and returns output as character vector

| | |
|---------------|----------------------|
| fslindex.help | <i>fslindex Help</i> |
|---------------|----------------------|

Description

This function calls fslmaths's help, as fslindex is a wrapper for fslmaths

Usage

```
fslindex.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslindex.help()  
}
```

fsllog.help

fsllog Help

Description

This function calls fslmaths's help, as fsllog is a wrapper for fslmaths

Usage

```
fsllog.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fsllog.help()  
}
```

fslmask.help

fslmask Help

Description

This function calls fslmaths's help, as fslmask is a wrapper for fslmaths

Usage

```
fslmask.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslmask.help()  
}
```

`fslmaths.help`*FSL Maths Help*

Description

This function calls fslmaths's help

Usage

```
fslmaths.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslmaths.help()  
}
```

`fslmax`*Get min/max of an image*

Description

This function calls the range or robust range functions from FSL and then extracts the min/max

Usage

```
fslmax(file, ...)
```

```
fslmin(file, ...)
```

Arguments

`file` (character) filename of image to be checked

`...` options passed to [fslrange](#)

Value

Numeric vector of mins/maxs or just one depending if `ts = TRUE`

Examples

```

if (have.fsl()){
  mnifile = file.path(fsldir(), "data", "standard",
    "MNI152_T1_2mm.nii.gz")
  fslmax(mnifile)
}

```

| | |
|---------|-------------------|
| fslmean | <i>Image Mean</i> |
|---------|-------------------|

Description

Estimates Mean of Image from FSL

Usage

```
fslmean(img, nonzero = FALSE, verbose = TRUE, ts = FALSE)
```

Arguments

| | |
|---------|---|
| img | Object of class nifti, or path of file |
| nonzero | (logical) Should the statistic be taken over non-zero voxels |
| verbose | (logical) print out command before running |
| ts | (logical) is the series a timeseries (4D), invoking -t option |

Value

Vector of unless ts option invoked, then matrix

Note

This uses option -m or -M in [fslstats](#)

| | |
|---------------|----------------------|
| fslmerge.help | <i>FSLMerge help</i> |
|---------------|----------------------|

Description

This function calls fslmerge's help

Usage

```
fslmerge.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslmerge.help()  
}
```

fslmul.help

fslmul Help

Description

This function calls fslmaths's help, as fslmul is a wrapper for fslmaths

Usage

```
fslmul.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslmul.help()  
}
```

fslnan.help

fslnan Help

Description

This function calls fslmaths's help, as fslnan is a wrapper for fslmaths

Usage

```
fslnan.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslnan.help()  
}
```

fslnanm.help

fslnanm Help

Description

This function calls `fslmaths`'s `help`, as `fslnanm` is a wrapper for `fslmaths`

Usage

```
fslnanm.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslnanm.help()  
}
```

fslor

Perform OR/Union operation on Images using FSL

Description

This function calls `fslmaths file -add file2 -bin` after binarizing `file` and `file2` using [fslbin](#).

Usage

```
fslor(
  file,
  file2,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  ...
)
```

```
fsl_or(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

Arguments

| | |
|-----------------------|---|
| <code>file</code> | (character) input image |
| <code>file2</code> | (character) image to be unioned |
| <code>outfile</code> | (character) resultant image name (optional) |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>reorient</code> | (logical) If <code>retimg</code> , should <code>file</code> be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>...</code> | additional arguments passed to readnii . |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

 fslorient

FSL Orient

Description

This function calls `fslorient`

Usage

```
fslorient(
  file,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|-----------------------|--|
| <code>file</code> | (character) image to be manipulated |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>opts</code> | (character) operations to be passed to <code>fslorient</code> |
| <code>verbose</code> | (logical) print out command before running |
| <code>...</code> | additional arguments passed to readnii . |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

 fslorient.help

fslorient help

Description

This function calls `fslorient`'s help

Usage

```
fslorient.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslorient.help()
}
```

 fslorienter

Wrapper for FSL Get Orientation

Description

This function calls `fslorient -getorient` and is a simple wrapper of [fslorient](#)

Usage

```
fslorienter(file, opts = "", verbose = TRUE)
```

Arguments

| | |
|---------|--|
| file | (character) image to be manipulated |
| opts | option to send to fslorient |
| verbose | (logical) print out command before running |

Value

Result from system command, output from FSL

 fslrand.help

fslrand Help

Description

This function calls `fslmaths`'s help, as `fslrand` is a wrapper for `fslmaths`

Usage

```
fslrand.help(...)
```

Arguments

| | |
|-----|---|
| ... | passed to fslmaths.help |
|-----|---|

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslrandn.help()
}
```

| | |
|---------------|----------------------|
| fslrandn.help | <i>fslrandn Help</i> |
|---------------|----------------------|

Description

This function calls `fslmaths`'s `help`, as `fslrandn` is a wrapper for `fslmaths`

Usage

```
fslrandn.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslrandn.help()
}
```

| | |
|----------|------------------------------|
| fslrange | <i>Get range of an image</i> |
|----------|------------------------------|

Description

This function calls `fslstats -R` to get the range of an image or `fslstats -r` to get the robust range

Usage

```
fslrange(file, robust = FALSE, verbose = TRUE, ts = FALSE, ...)
```

Arguments

| | |
|---------|---|
| file | (character) filename of image to be checked |
| robust | (logical) Should the range be robust (-r) |
| verbose | (logical) print out command before running |
| ts | (logical) is the series a timeseries (4D), invoking -t option |
| ... | options passed to checking |

Value

numeric vector of length 2

Examples

```
if (have.fsl()){
  mnifile = file.path(fsldir(), "data", "standard",
    "MNI152_T1_2mm.nii.gz")
  fslrange(mnifile)
}
```

fslrecip.help

fslrecip Help

Description

This function calls `fslmaths`'s help, as `fslrecip` is a wrapper for `fslmaths`

Usage

```
fslrecip.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslrecip.help()
}
```

 fslrem.help

fslrem Help

Description

This function calls fslmaths's help, as fslrem is a wrapper for fslmaths

Usage

```
fslrem.help(...)
```

Arguments

```
...           passed to fslmaths.help
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslrem.help()
}
```

 fslreorient2std

FSL Orient to MNI

Description

This function calls fslreorient2std

Usage

```
fslreorient2std(
  file,
  reting = TRUE,
  reorient = FALSE,
  intern = FALSE,
  verbose = TRUE,
  opts = "",
  ...
)

fslreorient2std_mat(
  file,
```

```

    matfile = tempfile(fileext = ".mat"),
    verbose = TRUE,
    ...
)

```

Arguments

| | |
|----------|--|
| file | (character) image to be manipulated |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| verbose | (logical) print out command before running |
| opts | additional options to pass to fslreorient2std |
| ... | additional arguments passed to readnii . |
| matfile | Output file for the matrix for reorientation |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

fslreorient2std.help *fslreorient2std help*

Description

This function calls fslreorient2std's help

Usage

```
fslreorient2std.help()
```

Value

Prints help output and returns output as character vector

Examples

```

if (have.fsl()){
  fslreorient2std.help()
}

```

 fslrobustfov

FSL Robust Field of View

Description

This function calls `robustfov` to automatically crop the image

Usage

```
fslrobustfov(
  file,
  brain_size = NULL,
  mat_name = NULL,
  roi_name = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  verbose = TRUE,
  ...
)

fsl_robustfov(retimg = FALSE, ...)
```

Arguments

| | |
|-------------------------|---|
| <code>file</code> | (character) image to be manipulated |
| <code>brain_size</code> | size of brain in z-dimension (default 150mm) |
| <code>mat_name</code> | matrix output name |
| <code>roi_name</code> | ROI volume output name |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to <code>readnii</code> . |
| <code>intern</code> | (logical) to be passed to <code>system</code> |
| <code>verbose</code> | (logical) print out command before running |
| <code>...</code> | additional arguments passed to <code>readnii</code> . |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is TRUE or FALSE.

| | |
|-------------------|--------------------------------------|
| fslrobustfov.help | <i>FSL Robust Field of View Help</i> |
|-------------------|--------------------------------------|

Description

This function calls robustfov help

Usage

```
fslrobustfov.help()
```

| | |
|--------|----------------|
| fslroi | <i>FSL ROI</i> |
|--------|----------------|

Description

This function calls fslroi

Usage

```
fslroi(  
  file,  
  xmin = 0,  
  xsize = -1,  
  ymin = 0,  
  ysize = -1,  
  zmin = 0,  
  zsize = -1,  
  tmin = NULL,  
  tsize = NULL,  
  outfile = NULL,  
  retimg = TRUE,  
  reorient = FALSE,  
  intern = FALSE,  
  verbose = TRUE,  
  ...  
)  
  
fsl_roi(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)  
  
fslroi_time(file, tmin = NULL, tsize = NULL, ...)
```

Arguments

| | |
|----------|--|
| file | (character) image to be manipulated |
| xmin | Minimum index for x-dimension |
| xsize | Size of ROI in x-dimension |
| ymin | Minimum index for y-dimension |
| ysize | Size of ROI in y-dimension |
| zmin | Minimum index for z-dimension |
| zsize | Size of ROI in z-dimension |
| tmin | Minimum index for t-dimension |
| tsize | Size of ROI in t-dimension |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| verbose | (logical) print out command before running |
| ... | additional arguments passed to readnii . |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

Note

Indexing (in both time and space) starts with 0 not 1! Inputting -1 for a size will set it to the full image extent for that dimension.

fslsd

Image Standard Deviation

Description

Estimates Standard Deviation of Image from FSL

Usage

```
fslsd(img, nonzero = FALSE, verbose = TRUE, ts = FALSE)
```

Arguments

| | |
|---------|---|
| img | Object of class nifti, or path of file |
| nonzero | (logical) Should the statistic be taken over non-zero voxels |
| verbose | (logical) print out command before running |
| ts | (logical) is the series a timeseries (4D), invoking -t option |

Value

Vector of unless ts option invoked, then matrix

Note

This uses option -s or -S in [fslstats](#)

| | |
|--------|---------------------------------------|
| fslsin | <i>Sine Transform Image using FSL</i> |
|--------|---------------------------------------|

Description

This function calls `fslmaths -sin`. The R functions wraps `fslmaths`

Usage

```
fslsin(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|-----------------------|--|
| <code>file</code> | (character) input image to sine transform |
| <code>outfile</code> | (character) resultant image name (optional) |
| <code>retimg</code> | (logical) return image of class nifti |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>opts</code> | (character) operations to be passed to <code>fslmaths</code> |
| <code>...</code> | additional arguments passed to readnii . |

Value

If `retimg` then object of class nifti. Otherwise, Result from system command, depends if `intern` is TRUE or FALSE.

`fslsin.help`*fslsin Help*

Description

This function calls `fslmaths`'s help, as `fslsin` is a wrapper for `fslmaths`

Usage

```
fslsin.help(...)
```

Arguments

```
...           passed to fslmaths.help
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslsin.help()  
}
```

`fslslicetimer`*FSL Slice Timing Correction*

Description

This function calls `slicetimer` and performs slice timing correction for fMRI data

Usage

```
fslslicetimer(  
  file,  
  outfile = NULL,  
  retimg = TRUE,  
  reorient = FALSE,  
  intern = FALSE,  
  tr = 3,  
  direction = "z",  
  indexing = c("up", "down"),  
  acq_order = c("contiguous", "interleaved"),  
  verbose = TRUE,  
  ...  
)
```

```
)
fsl_slicetimer(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

Arguments

| | |
|-----------|--|
| file | (character) image to be manipulated |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| tr | (numeric) Repeat time in seconds |
| direction | (character) Direction of acquisition |
| indexing | (character) Whether indexing was bottom up (default) or down using --down option |
| acq_order | (character) Order of acquisition, either contiguous or interleaved |
| verbose | (logical) print out command before running |
| ... | additional arguments passed to readnii . |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

| | |
|----------------|-----------------------|
| fslsmooth.help | <i>fslsmooth Help</i> |
|----------------|-----------------------|

Description

This function calls [fslmaths](#)'s help, as [fslsmooth](#) is a wrapper for [fslmaths](#)

Usage

```
fslsmooth.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslsmooth.help()
}
```

| | |
|-------------------|--|
| fslsmooth_in_mask | <i>Smooth Image Within a Mask Only</i> |
|-------------------|--|

Description

This function smooth an image within a mask and replaces the values of the original image with the smoothed values.

Usage

```
fslsmooth_in_mask(file, sigma = 10, mask = NULL, ...)
```

```
fsl_smooth_in_mask(...)
```

Arguments

| | |
|-------|--|
| file | (character) image to be smoothed |
| sigma | (numeric) sigma (in mm) of Gaussian kernel for smoothing |
| mask | (character) optional mask given for image |
| ... | additional arguments passed to fslsmooth . |

Value

Object of class `nifti`

Examples

```
if (have.fsl()){
  system.time({
    dims = c(50, 50, 20)
    x = array(rnorm(prod(dims)), dim = dims)
    img = nifti(x, dim= dims,
    datatype = convert.datatype()$FLOAT32, cal.min = min(x),
    cal.max = max(x), pixdim = rep(1, 4))
    mask = abs(img ) > 1
    s.img = fslsmooth_in_mask(img, mask = mask)
  })
}
```

`fslsplit`*Split images using FSL*

Description

This function calls `fslsplit` to merge files on some dimension and either saves the image or returns an object of class `nifti`

Usage

```
fslsplit(  
  infile,  
  direction = c("t", "x", "y", "z"),  
  output_basename = NULL,  
  retimg = TRUE,  
  reorient = FALSE,  
  verbose = TRUE  
)  
  
fsl_split(..., retimg = FALSE)
```

Arguments

| | |
|------------------------------|--|
| <code>infile</code> | (character) input filename |
| <code>direction</code> | (character) direction to split over: t (time), x, y, z |
| <code>output_basename</code> | (character) prefix to have for output |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>verbose</code> | (logical) print out command before running |
| <code>...</code> | not used |

Value

List of output files

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fslsplit.help

FSL Split help

Description

This function calls fslsplit's help

Usage

```
fslsplit.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslsplit.help()  
}
```

fslsqr.help

fslsqr Help

Description

This function calls fslmaths's help, as fslsqr is a wrapper for fslmaths

Usage

```
fslsqr.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslsqr.help()  
}
```

| | |
|-------------|--------------------|
| fslsqr.help | <i>fslsqr Help</i> |
|-------------|--------------------|

Description

This function calls `fslmaths`'s help, as `fslsqr` is a wrapper for `fslmaths`

Usage

```
fslsqr.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslsqr.help()
}
```

| | |
|----------|------------------|
| fslstats | <i>FSL Stats</i> |
|----------|------------------|

Description

This function calls `fslstats`

Usage

```
fslstats(file, opts = "", verbose = TRUE, ts = FALSE, ...)
```

Arguments

| | |
|---------|--|
| file | (character) filename of image to be checked |
| opts | (character) operation passed to <code>fslstats</code> |
| verbose | (logical) print out command before running |
| ts | (logical) is the series a timeseries (4D), invoking <code>-t</code> option |
| ... | options passed to checking |

Value

Result of fslstats command

Examples

```
if (have.fsl()){
  system.time({
    x = array(rnorm(1e6), dim = c(100, 100, 100))
    img = nifti(x, dim= c(100, 100, 100),
    datatype = convert.datatype($FLOAT32, cal.min = min(x),
    cal.max = max(x), pixdim = rep(1, 4))
    entropy = fslstats(img, opts='-E')
  })
}
```

fslstats.help

FSL Stats Help

Description

This function calls fslstats's help

Usage

```
fslstats.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslstats.help()
}
```

fslsub.help

fslsub Help

Description

This function calls fslmaths's help, as fslsub is a wrapper for fslmaths

Usage

```
fslsub.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslsub2.help()  
}
```

fslsub2.help

fslsub2 Help

Description

This function calls fslmaths's help, as fslsub2 is a wrapper for fslmaths

Usage

```
fslsub2.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslsub2.help()  
}
```

| | |
|--------|----------------|
| fslsum | <i>FSL Sum</i> |
|--------|----------------|

Description

This function calls `fslstats -M -V` to get product, aka the approximate sum.

Usage

```
fslsum(file, opts = "", ts = FALSE, ...)
```

Arguments

| | |
|------|--|
| file | (character) filename of image to be checked |
| opts | Additional options to pass to fslstats |
| ts | (logical) is the series a timeseries (4D), invoking <code>-t</code> option |
| ... | options passed to fslstats |

Value

Numeric value

Note

This may be approximate due to rounding

| | |
|-----------------|------------------------|
| fslswapdim.help | <i>fslswapdim help</i> |
|-----------------|------------------------|

Description

This function calls `fslswapdim`'s help

Usage

```
fslswapdim.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fslswapdim.help()
}
```

`fsltan.help`*fsltan Help*

Description

This function calls `fslmaths`'s `help`, as `fsltan` is a wrapper for `fslmaths`

Usage

```
fsltan.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fsltan.help()  
}
```

`fslthresh.help`*fslthresh Help*

Description

This function calls `fslmaths`'s `help`, as `fslthresh` is a wrapper for `fslmaths`

Usage

```
fslthresh.help(...)
```

Arguments

... passed to [fslmaths.help](#)

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslthresh.help()  
}
```

fslval

Get value from FSL header

Description

This function calls `fslval` to obtain a nifti header

Usage

```
fslval(file, keyword = "", verbose = TRUE, ...)
```

Arguments

| | |
|----------------------|--|
| <code>file</code> | (character) image filename or character of class nifti |
| <code>keyword</code> | (character) keyword to be taken from fslhd |
| <code>verbose</code> | (logical) print out command before running |
| <code>...</code> | options passed to checking |

Value

Character of information from fslhd field specified in keyword

Examples

```
if (have.fsl()){  
  mnifile = file.path(fsldir(), "data", "standard",  
    "MNI152_T1_2mm.nii.gz")  
  fslval(mnifile, keyword = "dim1")  
}
```

fslval.help*fslval help*

Description

This function calls `fslval`'s help

Usage

```
fslval.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  fslval.help()  
}
```

fslview

Open image in FSLView

Description

This function calls `fslview` to view an image in the FSL viewer

Usage

```
fslview(file, intern = TRUE, opts = "", verbose = TRUE, ...)
```

```
fsleyes(file, intern = TRUE, opts = "", verbose = TRUE, ...)
```

Arguments

| | |
|----------------------|---|
| <code>file</code> | (character) filename of image to be thresholded |
| <code>intern</code> | (logical) pass to <code>system</code> |
| <code>opts</code> | (character) options for FSLView |
| <code>verbose</code> | (logical) print out command before running |
| <code>...</code> | options passed to <code>checking</code> |

Value

character or logical depending on `intern`

Note

As of FSL version 5.0.10, this is deprecated: <https://fsl.fmrib.ox.ac.uk/fsl/fslwiki/WhatsNew>

fslview.help

FSLView help

Description

This function calls `fslview`'s help

Usage

```
fslview.help()
```

Value

Prints help output and returns output as character vector

Examples

```
library(fslr)
if (have.fsl()){
  print(fsl_version())
  in_ci <- function() {
    nzchar(Sys.getenv("CI"))
  }
  if (!in_ci()) {
    fslview.help()
  }
}
```

fslvol

FSL Volume in mL (or cubic centimeters)

Description

This function wraps `fslsum` and `voxdim`

Usage

```
fslvol(file, ...)
```

Arguments

`file` (character) filename of image to be checked
`...` options passed to `fslsum`

Value

Numeric value of volume in mL

Note

This may be approximate due to rounding

| | |
|-----------|---------------------|
| fslvolume | <i>Image Volume</i> |
|-----------|---------------------|

Description

Estimates Volume of Image from FSL

Usage

```
fslvolume(img, nonzero = FALSE, verbose = TRUE, ts = FALSE)
```

Arguments

| | |
|---------|---|
| img | Object of class nifti, or path of file |
| nonzero | (logical) Should the statistic be taken over non-zero voxels |
| verbose | (logical) print out command before running |
| ts | (logical) is the series a timeseries (4D), invoking -t option |

Value

Vector of unless ts option invoked, then matrix

Note

This uses option -v or -V in [fslstats](#)

| | |
|--------|---|
| fslxor | <i>Perform XOR/Exclusive Or operation on Images using FSL</i> |
|--------|---|

Description

This function calls `fslmaths file -add file2 -bin` after binarizing file and file2 using [fslbin](#) and then uses [fsl_thresh](#) to threshold any values greater than 1 back to zero.

Usage

```
fslxor(
  file,
  file2,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  ...
)

fsl_xor(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

Arguments

| | |
|----------|--|
| file | (character) input image |
| file2 | (character) image to be XOR'd |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| ... | additional arguments passed to readnii . |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fsl_abs

Absolute Value Image using FSL

Description

This function calls `fslmaths -abs`. The R functions wraps `fslmaths`

Usage

```
fsl_abs(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)

fslabs(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| file | (character) input image to absolute value |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to fslmaths |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fsl_acos

Arc Cosine Transform Image using FSL

Description

This function calls `fslmaths -acos`. The R functions wraps `fslmaths`

Usage

```
fsl_acos(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)

fslacos(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| file | (character) input image to arc cosine transform |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to fslmaths |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fsl_add

Add Images using FSL

Description

This function calls `fslmaths -add`. The R functions wraps `fslmaths`

Usage

```
fsl_add(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)

fsladd(
  file,
  file2,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| file | (character) input image |
| file2 | (character) image to be added |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to fslmaths |

Value

If `retimg` then object of class nifti. Otherwise, Result from system command, depends if `intern` is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

Description

This function calls `fsl_anat` from FSL

Usage

```
fsl_anat(
  file,
  modality = c("T1", "T2", "PD"),
  outdir = NULL,
  intern = FALSE,
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|----------|--|
| file | (character) image to be manipulated, should be full path |
| modality | (character) Modality of Image to be run |
| outdir | (character) output directory, if none specified, will default to dirname(file) |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to fsl_anat |
| verbose | (logical) print out command before running |
| ... | options passed to checking |

Value

Result from system command, depends if intern is TRUE or FALSE.

fsl_anat.help

fsl_anat help

Description

This function calls fsl_anat's help

Usage

```
fsl_anat.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){
  fsl_anat.help()
}
```

`fsl_applywarp`*Apply Warp from FNIRT*

Description

This function applies a coefficient map from `fnirt` to other images

Usage

```
fsl_applywarp(  
  infile,  
  reffile,  
  warpfile,  
  outfile = NULL,  
  retimg = TRUE,  
  reorient = FALSE,  
  intern = FALSE,  
  opts = "",  
  verbose = TRUE,  
  ...  
)
```

Arguments

| | |
|-----------------------|---|
| <code>infile</code> | (character) input filename |
| <code>reffile</code> | (character) reference image to be registered to |
| <code>warpfile</code> | (character) reference image to be registered to |
| <code>outfile</code> | (character) output filename |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to <code>readnii</code> . |
| <code>intern</code> | (logical) pass to <code>system</code> |
| <code>opts</code> | (character) additional options to FLIRT |
| <code>verbose</code> | (logical) print out command before running |
| <code>...</code> | additional arguments passed to <code>readnii</code> . |

Value

character or logical depending on `intern`

fsl_applywarp.help *FSL applywarp help*

Description

This function calls applywarp's help

Usage

```
fsl_applywarp.help()
```

Value

Prints help output and returns output as character vector

fsl_asin *Arc Sine Transform Image using FSL*

Description

This function calls fslmaths -asin. The R functions wraps fslmaths

Usage

```
fsl_asin(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslasin(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| file | (character) input image to arc sine transform |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to fslmaths |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

 fsl_atan

Arc Tangent Transform Image using FSL

Description

This function calls `fslmaths -atan`. The R functions wraps `fslmaths`

Usage

```
fsl_atan(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslatan(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|-----------------------|--|
| <code>...</code> | additional arguments passed to readnii . |
| <code>outfile</code> | (character) resultant image name (optional) |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>file</code> | (character) input image to arc tangent transform |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>opts</code> | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

| | |
|---------------|--|
| fsl_atlas_dir | <i>Get FSL's Standard Data Directory</i> |
|---------------|--|

Description

Finds the FSLDIR from system environment or `getOption("fsl.path")` and pastes on "data/standard"

Usage

```
fsl_atlas_dir()
```

Value

Character path

| | |
|-------------|--|
| fsl_avscale | <i>Scale Affine Matrix using avscale</i> |
|-------------|--|

Description

This function calls `avscale` to get individual matrices for FSL

Usage

```
fsl_avscale(file, volume = NULL, parsed = TRUE, verbose = TRUE)
```

```
avscale(...)
```

Arguments

| | |
|---------|--|
| file | (character) matrix filename |
| volume | (character) non-reference volume filename or nifti image |
| parsed | (logical) should <code>parse_avscale</code> be run after? |
| verbose | (logical) print out command before running |
| ... | not used, but used for duplicating <code>avscale</code> as alias |

Value

Character of information from `avscale`

fsl_bet

Use FSL's Brain Extraction Tool (BET)

Description

This function calls bet to extract a brain from an image, usually for skull stripping.

Usage

```
fsl_bet(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslbet(
  infile,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  betcmd = c("bet2", "bet"),
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) output filename |
| retimg | (logical) return image of class nifti |
| infile | (character) input filename |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) pass to system |
| opts | (character) additional options to bet |
| betcmd | (character) Use bet or bet2 function |
| verbose | (logical) print out command before running |

Value

character or logical depending on intern

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fsl_biascorrect *FSL Bias Correct*

Description

This function wraps a call to fast that performs bias correction

Usage

```
fsl_biascorrect(  
  file,  
  outfile = NULL,  
  retimg = TRUE,  
  reorient = FALSE,  
  intern = FALSE,  
  opts = "",  
  verbose = TRUE,  
  remove.seg = TRUE,  
  ...  
)
```

Arguments

| | |
|------------|--|
| file | (character) image to be manipulated |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to fast |
| verbose | (logical) print out command before running |
| remove.seg | (logical) Should segmentation from FAST be removed? |
| ... | additional arguments passed to readnii . |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

`fsl_bin`*Binarize Image using FSL*

Description

This function calls `fslmaths -bin`. The R functions wraps `fslmaths`

Usage

```
fsl_bin(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslbin(  
  file,  
  outfile = NULL,  
  retimg = TRUE,  
  reorient = FALSE,  
  intern = FALSE,  
  opts = "",  
  ...  
)
```

Arguments

| | |
|-----------------------|--|
| <code>...</code> | additional arguments passed to readnii . |
| <code>outfile</code> | (character) resultant image name (optional) |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>file</code> | (character) image to be binarized |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>opts</code> | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

Examples

```

set.seed(5)
dims = rep(10, 3)
arr = array(rnorm(prod(dims)), dim = dims)
nim = oro.nifti::nifti(arr)
if (have.fsl()){
  fslbin(nim)
  fsl_bin(nim)
}

```

fsl_binv

*Binarized Inverse Image using FSL***Description**

This function calls `fslmaths -binv`. The R functions wraps `fslmaths`

Usage

```
fsl_binv(..., outfile = tempfile(fileext = ".nii.gz"), reting = FALSE)
```

```

fslbinv(
  file,
  outfile = NULL,
  reting = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)

```

Arguments

| | |
|-----------------------|--|
| <code>...</code> | additional arguments passed to readnii . |
| <code>outfile</code> | (character) resultant image name (optional) |
| <code>reting</code> | (logical) return image of class nifti |
| <code>file</code> | (character) input image to take the binarized inverse |
| <code>reorient</code> | (logical) If <code>reting</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>opts</code> | (character) operations to be passed to <code>fslmaths</code> |

Value

If `reting` then object of class nifti. Otherwise, Result from system command, depends if `intern` is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

| | |
|-------------|--|
| fsl_bin_tab | <i>Quick Tabulation for logical images</i> |
|-------------|--|

Description

Creates a 2 by 2 table for

Usage

```
fsl_bin_tab(x, y, dnames = c("x", "y"), verbose = FALSE)
```

Arguments

| | |
|---------|----------------------------------|
| x | filename of logical or 0/1 image |
| y | filename of logical or 0/1 image |
| dnames | names for table |
| verbose | Should fsl commands be printed? |

Value

table of x vs y

Note

fsl_bin will be run to make these images binary before running

| | |
|-------------|---|
| fsl_cluster | <i>Form clusters, report information about clusters and/or perform cluster-based inference. Wrapper for cluster</i> |
|-------------|---|

Description

Form clusters, report information about clusters and/or perform cluster-based inference. Wrapper for cluster

Usage

```
fsl_cluster(
  file,
  threshold,
  retimg = FALSE,
  reorient = FALSE,
  opts = "",
  cope_image = NULL,
  pthresh = NULL,
  peakdist = 0,
  volume = FALSE,
  smooth_est = NULL,
  voxel_rese1 = NULL,
  fractional = FALSE,
  connectivity = 26,
  mm = FALSE,
  find_minima = FALSE,
  standard_image = NULL,
  verbose = TRUE,
  ...
)

fslcluster(..., retimg = TRUE)

read_cluster_table(file)
```

Arguments

| | |
|----------------|--|
| file | filename of input volume |
| threshold | threshold for input volume |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| opts | (character) operations to be passed to <code>cluster</code> |
| cope_image | filename of input cope volume |
| pthresh | p-threshold |
| peakdist | minimum distance between local maxima/minima, in mm (default 0) |
| volume | number of voxels in the mask |
| smooth_est | smoothness estimate = $\sqrt{\det(\text{Lambda})}$ |
| voxel_rese1 | Size of one resel in voxel units |
| fractional | interprets the threshold as a fraction of the robust range |
| connectivity | the connectivity of voxels (default 26) |
| mm | use mm, not voxel, coordinates |
| find_minima | find minima instead of maxima |
| standard_image | filename for standard-space volume |

verbose (logical) print out command before running
 ... additional arguments to pass to `fslcmd`

Value

A list of filenames of outputs and tables:

- opvals filename for image output of log pvals
- oindex filename for output of cluster index (in size order)
- othresh filename for output of thresholded image
- olmax filename for output of local maxima text file
- olmaxim filename for output of local maxima volume
- osize filename for output of size image
- omax filename for output of max image
- omean filename for output of mean image

Examples

```
if (have_fsl()) {
  file = mni_fname(brain = TRUE, mask = FALSE)
  threshold = 6000
  clus = fsl_cluster(file, threshold)
}
```

fsl_cos

Cosine Transform Image using FSL

Description

This function calls `fslmaths -cos`. The R functions wraps `fslmaths`

Usage

```
fsl_cos(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslcos(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|----------|---|
| ... | additional arguments passed to <code>readnii</code> . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| file | (character) input image to cosine transform |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to <code>readnii</code> . |
| intern | (logical) to be passed to <code>system</code> |
| opts | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class nifti. Otherwise, Result from system command, depends if `intern` is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fsl_data_dir

Get FSL's Data Directory

Description

Finds the FSLDIR from system environment or `getOption("fsl.path")` and pastes on "data"

Usage

```
fsl_data_dir()
```

Value

Character path

| | |
|------------|---|
| fsl_deface | <i>Tool to deface a structural T1w image.</i> |
|------------|---|

Description

Tool to deface a structural T1w image.

Usage

```
fsl_deface(
  file,
  outfile = NULL,
  retimg = TRUE,
  opts = "",
  deface_cropped = FALSE,
  bet_fractional_intensity = NULL,
  bias_correct = FALSE,
  shift_xyz = NULL,
  cog_xyz = NULL,
  reorient = FALSE,
  intern = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|--------------------------|--|
| file | (character) input image to estimate edge strength |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| opts | (character) operations to be passed to fsl_deface |
| deface_cropped | apply the defacing to the cropped image instead of the original image |
| bet_fractional_intensity | fractional intensity for bet (0->1); default=0.5; |
| bias_correct | Bias-correct the input image (with fast); |
| shift_xyz | Shift, in mm, x-, y- and z-directions, to shift face mask by; |
| cog_xyz | centre-of-gravity for bet (voxels, not mm); |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| verbose | print diagnostic messages |
| ... | additional arguments passed to fslcmd . |

Examples

```

if (have_fsl()) {
  file = mni_fname(mm = 1, brain = FALSE)
  out = fsl_deface(file, retimg = FALSE)
}

```

| | |
|----------|--|
| fsl_dice | <i>Calculate Dice Coefficient of 2 Binary images</i> |
|----------|--|

Description

Creates a 2 by 2 table for

Usage

```
fsl_dice(x, y, ...)
```

Arguments

| | |
|-----|---|
| x | filename of logical or 0/1 image |
| y | filename of logical or 0/1 image |
| ... | arguments passed to fsl_bin_tab |

Value

Single number of the dice coefficient

| | |
|------------|-------------------------------|
| fsl_dilate | <i>Dilate image using FSL</i> |
|------------|-------------------------------|

Description

This function calls `fslmaths -ero` after inverting the image to dilate an image with either the default FSL kernel or the kernel specified in `kopts`. The function either saves the image or returns an object of class `nifti`.

Usage

```
fsl_dilate(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fsldilate(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  kopts = "",
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) resultant dilated image name |
| retimg | (logical) return image of class nifti |
| file | (character) image to be dilated |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| kopts | (character) options for kernel |
| opts | (character) additional options to be passed to fslmaths |
| verbose | (logical) print out command before running |

Value

Result from system command, depends if intern is TRUE or FALSE. If retimg is TRUE, then the image will be returned.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

Examples

```
if (have.fsl()){
  system.time({
    dims = c(50, 50, 20)
    x = array(rnorm(prod(dims)), dim = dims)
    img = nifti(x, dim= dims,
    datatype = convert.datatype())$FLOAT32, cal.min = min(x),
    cal.max = max(x), pixdim = rep(1, 4))
    mask = img > .5
```

```
dilated = fsldilate(mask, kopts = "-kernel boxv 5", retimg=TRUE)
})
}
```

fsl_div

Divide Images using FSL

Description

This function calls `fslmaths -div`. The R functions wraps `fslmaths`

Usage

```
fsl_div(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fsldiv(
  file,
  file2,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| file | (character) input image |
| file2 | (character) image to be divided |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

Description

This function calls `fslmaths -edge`. The R functions wraps `fslmaths`

Usage

```
fsl_edge(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fsledge(  
  file,  
  outfile = NULL,  
  retimg = TRUE,  
  reorient = FALSE,  
  intern = FALSE,  
  opts = "",  
  ...  
)
```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class <code>nifti</code> |
| file | (character) input image to estimate edge strength |
| reorient | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fsl_erode

*Erode image using FSL***Description**

This function calls `fslmaths -ero` to erode an image with either the default FSL kernel or the kernel specified in `kopts`. The function either saves the image or returns an object of class `nifti`.

Usage

```
fsl_erode(..., outfile = tempfile(fileext = ".nii.gz"), reting = FALSE)
```

```
fsl_erode(
  file,
  outfile = NULL,
  reting = TRUE,
  reorient = FALSE,
  intern = FALSE,
  kopts = "",
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|-----------------------|--|
| <code>...</code> | additional arguments passed to readnii . |
| <code>outfile</code> | (character) resultant eroded image name |
| <code>reting</code> | (logical) return image of class <code>nifti</code> |
| <code>file</code> | (character) image to be eroded |
| <code>reorient</code> | (logical) If <code>reting</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>kopts</code> | (character) options for kernel |
| <code>opts</code> | (character) additional options to be passed to <code>fslmaths</code> |
| <code>verbose</code> | (logical) print out command before running |

Value

Result from system command, depends if `intern` is `TRUE` or `FALSE`. If `reting` is `TRUE`, then the image will be returned.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

Examples

```

if (have.fsl()){
  system.time({
    dims = c(50, 50, 20)
    x = array(rnorm(prod(dims)), dim = dims)
    img = nifti(x, dim= dims,
    datatype = convert.datatype()$FLOAT32, cal.min = min(x),
    cal.max = max(x), pixdim = rep(1, 4))
    mask = img > .5
    eroded = fslerode(mask, kopts = "-kernel boxv 5", retimg=TRUE)
  })
}

```

fsl_exp

*Exponentiate Image using FSL***Description**

This function calls `fslmaths -exp`. The R functions wraps `fslmaths`

Usage

```
fsl_exp(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```

fslexp(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)

```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| file | (character) input image to exponentiated |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

| | |
|-----------------------|-------------------------|
| <code>fsl_fill</code> | <i>Fill image holes</i> |
|-----------------------|-------------------------|

Description

This function calls `fslmaths -fillh` to fill in image holes and either saves the image or returns an object of class `nifti`

Usage

```
fsl_fill(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslfill(
  file,
  outfile = NULL,
  bin = TRUE,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|-----------------------|--|
| <code>...</code> | additional arguments passed to readnii . |
| <code>outfile</code> | (character) name of resultant filled file |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>file</code> | (character) filename of image to be filled |
| <code>bin</code> | (logical) binarize the image before filling |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) pass to system |
| <code>verbose</code> | (logical) print out command before running |

Value

character or logical depending on `intern`

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

Examples

```
if (have.fsl()){
  system.time({
    dims = c(50, 50, 20)
    x = array(rnorm(prod(dims)), dim = dims)
    img = nifti(x, dim= dims,
    datatype = convert.datatype()$FLOAT32, cal.min = min(x),
    cal.max = max(x), pixdim = rep(1, 4))
    mask = img > .5
    eroded = fslerode(mask, kopts = "-kernel boxv 5", retimg=TRUE)
    filled = fslfill(eroded, retimg= TRUE)
  })
}
```

fsl_index

*Index Image using FSL***Description**

This function calls `fslmaths -index`. The R functions wraps `fslmaths`

Usage

```
fsl_index(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslindex(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| file | (character) input image to have non-zero entries replaced with index |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |

intern (logical) to be passed to [system](#)
 opts (character) operations to be passed to fslmaths

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fsl_log *Log Transform Image using FSL*

Description

This function calls `fslmaths -log`. The R functions wraps `fslmaths`

Usage

```
fsl_log(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fsllog(  
  file,  
  outfile = NULL,  
  retimg = TRUE,  
  reorient = FALSE,  
  intern = FALSE,  
  opts = "",  
  ...  
)
```

Arguments

... additional arguments passed to [readnii](#).
 outfile (character) resultant image name (optional)
 retimg (logical) return image of class `nifti`
 file (character) input image to log transform
 reorient (logical) If `retimg`, should file be reoriented when read in? Passed to [readnii](#).
 intern (logical) to be passed to [system](#)
 opts (character) operations to be passed to `fslmaths`

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

 fsl_mask

Mask image using FSL

Description

This function calls `fslmaths -mas` to mask an image from an image mask and either saves the image or returns an object of class `nifti`

Usage

```
fsl_mask(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslmask(
  file,
  mask,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|-----------------------|--|
| <code>...</code> | additional arguments passed to readnii . |
| <code>outfile</code> | (character) resultant masked image name |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>file</code> | (character) image to be masked |
| <code>mask</code> | (character) mask given for image |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>opts</code> | (character) additional options to be passed to <code>fslmask</code> |
| <code>verbose</code> | (logical) print out command before running |

Value

Result from system command, depends if intern is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

Examples

```
if (have.fsl()){
  system.time({
    x = array(rnorm(1e5), dim = c(100, 100, 10))
    img = nifti(x, dim= c(100, 100, 10),
    datatype = convert.datatype())$FLOAT32, cal.min = min(x),
    cal.max = max(x), pixdim = rep(1, 4))
    mask = img > .5
    masked = fslmask(img, mask = mask, reting=TRUE)
  })
}
```

 fsl_maths

FSL Maths

Description

This function calls fslmaths

Usage

```
fsl_maths(..., outfile = tempfile(fileext = ".nii.gz"), reting = FALSE)
```

```
fslmaths(
  file,
  outfile = NULL,
  reting = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

... additional arguments passed to [readnii](#).
 outfile (character) resultant image name (optional)

| | |
|----------|--|
| retimg | (logical) return image of class nifti |
| file | (character) image to be manipulated |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to fslmaths |
| verbose | (logical) print out command before running |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

| | |
|-----------|-------------------------------|
| fsl_merge | <i>Merge images using FSL</i> |
|-----------|-------------------------------|

Description

This function calls `fslmerge` to merge files on some dimension and either saves the image or returns an object of class nifti

Usage

```
fsl_merge(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslmerge(
  infiles,
  direction = c("x", "y", "z", "t", "a"),
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|---------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) output filename |
| retimg | (logical) return image of class nifti |

| | |
|-----------|--|
| infile | (character) input filenames |
| direction | (character) direction to merge over, x, y, z, t (time), a (auto) |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) pass to system |
| verbose | (logical) print out command before running |

Value

character or logical depending on intern

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

| | |
|---------|----------------------------------|
| fsl_mul | <i>Multiply Images using FSL</i> |
|---------|----------------------------------|

Description

This function calls `fslmaths -mul`. The R functions wraps `fslmaths`

Usage

```
fsl_mul(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslmul(
  file,
  file2,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| file | (character) input image |
| file2 | (character) image to be multiplied |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

 fsl_nan

Replace NaNs in Image using FSL

Description

This function calls `fslmaths -nan`. The R functions wraps `fslmaths`

Usage

```
fsl_nan(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslnan(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|-----------------------|--|
| <code>...</code> | additional arguments passed to readnii . |
| <code>outfile</code> | (character) resultant image name (optional) |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>file</code> | (character) input image to replace NaNs (improper numbers) with 0 |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>opts</code> | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fsl_nanm

Mask NaNs in Image using FSL

Description

This function calls `fslmaths -nanm`. The R functions wraps `fslmaths`

Usage

```
fsl_nanm(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslnanm(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| file | (character) input image to set to 1 for NaN voxels, 0 otherwise |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class nifti. Otherwise, Result from system command, depends if `intern` is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

`fsl_rand`*Add Random Uniform Noise Image using FSL*

Description

This function calls `fslmaths -rand`. The R functions wraps `fslmaths`

Usage

```
fsl_rand(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslrand(  
  file,  
  outfile = NULL,  
  retimg = TRUE,  
  reorient = FALSE,  
  intern = FALSE,  
  opts = "",  
  ...  
)
```

Arguments

| | |
|-----------------------|--|
| <code>...</code> | additional arguments passed to readnii . |
| <code>outfile</code> | (character) resultant image name (optional) |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>file</code> | (character) input image to add random uniform noise to |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>opts</code> | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fsl_randn

*Add Random Standard Gaussian Noise Image using FSL***Description**

This function calls `fslmaths -randn`. The R functions wraps `fslmaths`

Usage

```
fsl_randn(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslrandn(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|-----------------------|--|
| <code>...</code> | additional arguments passed to readnii . |
| <code>outfile</code> | (character) resultant image name (optional) |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>file</code> | (character) input image to add random standard to Gaussian noise |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>opts</code> | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

`fsl_recip`*Reciprocal Image using FSL*

Description

This function calls `fslmaths -recip`. The R functions wraps `fslmaths`

Usage

```
fsl_recip(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslrecip(  
  file,  
  outfile = NULL,  
  retimg = TRUE,  
  reorient = FALSE,  
  intern = FALSE,  
  opts = "",  
  ...  
)
```

Arguments

| | |
|-----------------------|--|
| <code>...</code> | additional arguments passed to readnii . |
| <code>outfile</code> | (character) resultant image name (optional) |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>file</code> | (character) input image to take the reciprocal (1/image) |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>opts</code> | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fsl_rem

*Modulus Remainder of 2 Images using FSL***Description**

This function calls `fslmaths -rem`. The R functions wraps `fslmaths`

Usage

```
fsl_rem(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslrem(
  file,
  file2,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|-----------------------|--|
| <code>...</code> | additional arguments passed to readnii . |
| <code>outfile</code> | (character) resultant image name (optional) |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>file</code> | (character) input image |
| <code>file2</code> | (character) image to divide the current image by and take remainder |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>opts</code> | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

`fsl_resample`*Resample an Image to Specific Voxel Size*

Description

Resample an Image to Specific Voxel Size

Usage

```
fsl_resample(  
  file,  
  voxel_size,  
  outfile = NULL,  
  retimg = TRUE,  
  reorient = FALSE,  
  opts = NULL,  
  verbose = TRUE  
)
```

Arguments

| | |
|-------------------------|--|
| <code>file</code> | Input file to resample |
| <code>voxel_size</code> | Voxel size (in mm). This should be a scalar number. |
| <code>outfile</code> | (character) output filename |
| <code>retimg</code> | (logical) return image of class nifti |
| <code>reorient</code> | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| <code>opts</code> | options to pass to <code>flirt</code> |
| <code>verbose</code> | (logical) print out command before running |

Value

If `retimg` then object of class `nifti`. Otherwise, the output file.

Examples

```
if (have_fsl()) {  
  file = mni_fname(mm = 1, brain = TRUE)  
  est2 = fsl_resample(file = file, voxel_size = 1, retimg = FALSE)  
  pixdim(est2)  
  est = fsl_resample(file = file, voxel_size = 1)  
  pixdim(est)  
}
```

fsl_smooth

*Gaussian smooth image using FSL***Description**

This function calls `fslmaths -s` to smooth an image and either saves the image or returns an object of class `nifti`

Usage

```
fsl_smooth(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslsmooth(
  file,
  sigma = 10,
  mask = NULL,
  smooth_mask = TRUE,
  smoothed_mask = NULL,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|----------------------------|---|
| <code>...</code> | additional arguments passed to <code>readnii</code> . |
| <code>outfile</code> | (character) resultant smoothed image name (optional) if not give, will be the stub of the filename then <code>_sigma</code> |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>file</code> | (character or <code>nifti</code>) image to be smoothed |
| <code>sigma</code> | (numeric) sigma (in mm) of Gaussian kernel for smoothing |
| <code>mask</code> | (character) optional mask given for image |
| <code>smooth_mask</code> | (logical) Smooth mask? If TRUE, the masked image will be divided by the smoothed mask. |
| <code>smoothed_mask</code> | (character or <code>nifti</code>) If specified and <code>smooth_mask = TRUE</code> , then will use this as the smoothed mask for division. |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to <code>readnii</code> . |
| <code>intern</code> | (logical) to be passed to <code>system</code> |
| <code>verbose</code> | (logical) print out command before running |

Value

Result from system command, depends if intern is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

Examples

```
if (have.fsl()){
  system.time({
    dims = c(50, 50, 20)
    x = array(rnorm(prod(dims)), dim = dims)
    img = nifti(x, dim= dims,
    datatype = convert.datatype()$FLOAT32, cal.min = min(x),
    cal.max = max(x), pixdim = rep(1, 4))
    s.img = fslsmooth(img, retimg=TRUE)
  })
}
```

fsl_smoothest

Smoothness Estimation using smoothest

Description

Smoothness Estimation using smoothest

Usage

```
fsl_smoothest(
  file,
  residual_image,
  z_image,
  dof = NULL,
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|----------------|---|
| file | filename of input brain mask |
| residual_image | 4d residual image. If specified, then dof must be specified. |
| z_image | z-statistic image. Cannot be specified if residual_image is specified |
| dof | number of degrees of freedom |
| opts | (character) operations to be passed to smoothest |

verbose (logical) print out command before running
 ... additional arguments to pass to `fslcmd`

Value

An output of smoothness estimate

Examples

```
if (have_fsl()) {
  file = mni_fname(mm = 2, brain = TRUE, mask = TRUE)
  img = mni_img(mm = 2, brain = TRUE, mask = FALSE)
  mask = mni_img(mm = 2, brain = TRUE, mask = TRUE)
  img = zscore_img(img = img, mask = mask)
  est = fsl_smoothest(file = file, z_image = img)
}
```

fsl_sqr

Square Image using FSL

Description

This function calls `fslmaths -sqr`. The R functions wraps `fslmaths`

Usage

```
fsl_sqr(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslsqr(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

... additional arguments passed to `readnii`.
 outfile (character) resultant image name (optional)
 retimg (logical) return image of class `nifti`
 file (character) input image to square
 reorient (logical) If `retimg`, should file be reoriented when read in? Passed to `readnii`.
 intern (logical) to be passed to `system`
 opts (character) operations to be passed to `fslmaths`

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

| | |
|----------|------------------------------------|
| fsl_sqrt | <i>Square Root Image using FSL</i> |
|----------|------------------------------------|

Description

This function calls `fslmaths -sqrt`. The R functions wraps `fslmaths`

Usage

```
fsl_sqrt(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslsqrt(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|-----------------------|--|
| <code>...</code> | additional arguments passed to readnii . |
| <code>outfile</code> | (character) resultant image name (optional) |
| <code>retimg</code> | (logical) return image of class <code>nifti</code> |
| <code>file</code> | (character) input image to square root |
| <code>reorient</code> | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| <code>intern</code> | (logical) to be passed to system |
| <code>opts</code> | (character) operations to be passed to <code>fslmaths</code> |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is `TRUE` or `FALSE`.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

| | |
|-------------|--|
| fsl_std_dir | <i>Get FSL's Standard Data Directory</i> |
|-------------|--|

Description

Finds the FSLDIR from system environment or `getOption("fsl.path")` and pastes on "data/standard"

Usage

```
fsl_std_dir()
fsl_std_file(file = NULL)
```

Arguments

file A file from the standard data file

Value

Character path

| | |
|---------|----------------------------------|
| fsl_sub | <i>Subtract Images using FSL</i> |
|---------|----------------------------------|

Description

This function calls `fslmaths -sub`. The R functions wraps `fslmaths`

Usage

```
fsl_sub(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)

fslsub(
  file,
  file2,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|----------|---|
| ... | additional arguments passed to <code>readnii</code> . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| file | (character) input image |
| file2 | (character) image to be subtracted |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to <code>readnii</code> . |
| intern | (logical) to be passed to <code>system</code> |
| opts | (character) operations to be passed to <code>fslmaths</code> |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

| | |
|----------|---------------------------------------|
| fsl_sub2 | <i>Subsample image by factor of 2</i> |
|----------|---------------------------------------|

Description

This function calls `fslmaths -subsamp2` to subsample an image and either saves the image or returns an object of class nifti

Usage

```
fsl_sub2(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)

fslsub2(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|----------|---|
| ... | additional arguments passed to <code>readnii</code> . |
| outfile | (character) name of resultant subsampled file |
| retimg | (logical) return image of class nifti |
| file | (character) filename of image to be subsampled |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to <code>readnii</code> . |
| intern | (logical) pass to <code>system</code> |
| verbose | (logical) print out command before running |

Value

character or logical depending on intern

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

Examples

```
if (have.fsl()){
  system.time({
    x = array(rnorm(1e6), dim = c(100, 100, 100))
    img = nifti(x, dim= c(100, 100, 100),
    datatype = convert.datatype())$FLOAT32, cal.min = min(x),
    cal.max = max(x), pixdim = rep(1, 4))
    subsamp = fslsub2(img, retimg=TRUE)
    print(voxdim(subsamp))
  })
}
```

fsl_swapdim

FSL Swap Dimensions

Description

This function calls `fslswapdim`

Usage

```
fsl_swapdim(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslswapdim(
  file,
  outfile = NULL,
  retimg = TRUE,
```

```

    reorient = FALSE,
    intern = FALSE,
    a = "x",
    b = "y",
    c = "z",
    verbose = TRUE,
    ...
)

```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| file | (character) image to be manipulated |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| a | (character) Option for x domain in fslswapdim |
| b | (character) Option for y domain in fslswapdim |
| c | (character) Option for z domain in fslswapdim |
| verbose | (logical) print out command before running |

Value

If `retimg` then object of class `nifti`. Otherwise, Result from system command, depends if `intern` is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fsl_tan

Tangent Transform Image using FSL

Description

This function calls `fslmaths -tan`. The R functions wraps `fslmaths`

Usage

```
fsl_tan(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)

fsltan(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  ...
)
```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| file | (character) input image to tangent transform |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to <code>fslmaths</code> |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

fsl_thresh

Threshold an image

Description

This function calls `fslmaths -thr -uthr` to threshold an image and either saves the image or returns an object of class nifti

Usage

```
fsl_thresh(..., outfile = tempfile(fileext = ".nii.gz"), retimg = FALSE)
```

```
fslthresh(
  file,
  outfile = NULL,
  thresh = 0,
  uthresh = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|----------|--|
| ... | additional arguments passed to readnii . |
| outfile | (character) name of resultant thresholded file |
| retimg | (logical) return image of class nifti |
| file | (character) filename of image to be thresholded |
| thresh | (numeric) threshold (anything below set to 0) |
| uthresh | (numeric) upper threshold (anything above set to 0) |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) pass to system |
| opts | (character) additional options to be passed to fslmaths |
| verbose | (logical) print out command before running |

Value

character or logical depending on intern

Note

Functions with underscores have different defaults and will return an output filename, so to be used for piping

Examples

```
if (have.fsl()){
  system.time({
    x = array(rnorm(1e6), dim = c(100, 100, 100))
    img = nifti(x, dim= c(100, 100, 100),
    datatype = convert.datatype())$FLOAT32, cal.min = min(x),
    cal.max = max(x), pixdim = rep(1, 4))
    thresh = fslthresh(img, thresh=0, uthresh = 2, retimg=TRUE)
```

```

    })
  }

```

fsl_tsplot

FSL Timeseries Plot using 'fsl_tsplot' (not 'tsplot')

Description

FSL Timeseries Plot using 'fsl_tsplot' (not 'tsplot')

Usage

```

fsl_tsplot(
  infile,
  outfile = tempfile(fileext = ".png"),
  plot_title = NULL,
  legend = NULL,
  labels = NULL,
  ymin = NULL,
  ymax = NULL,
  xlabel = NULL,
  ylabel = NULL,
  height = NULL,
  width = NULL,
  precision = NULL,
  unit = NULL,
  scientific_notation = FALSE,
  start_position = NULL,
  end_position = NULL,
  ...
)

fsl_tsplot.help()

```

Arguments

| | |
|------------|---|
| infile | comma-separated list of input file names (ASCII text matrix, one column per timecourse) |
| outfile | output filename for the PNG file |
| plot_title | plot title |
| legend | file name of ASCII text file, one row per legend entry |
| labels | comma-separated list of labels |
| ymin | minimum y-value |
| ymax | maximum y-value |
| xlabel | X-axis label |

| | |
|---------------------|---|
| ylabel | Y-axis label |
| height | plot height in pixels (default 150) |
| width | plot width in pixels (default 600) |
| precision | precision of x-axis labels |
| unit | scaling units for x-axis (default 1...length of infile) |
| scientific_notation | switch on scientific notation |
| start_position | Position of first column to plot |
| end_position | Position of final column to plot |
| ... | additional options to pass to <code>fslcmd</code> |

Value

Name of PNG file

| | |
|-------------|-------------------------|
| fsl_version | <i>Find FSL Version</i> |
|-------------|-------------------------|

Description

Finds the FSL version from `FSLDIR/etc/fslversion`

Usage

```
fsl_version(full = FALSE)
```

```
fslversion()
```

```
fsl_version_gt5()
```

Arguments

`full` provide the full version, versus the numeric version

Value

If the version file does not exist, it will throw a warning, but it will return an empty string. Otherwise it will be a string of the version.

Note

This will use `fsldir()` to get the directory

Examples

```
if (have_fsl()) {  
    fslversion()  
    fsl_version()  
}
```

get.fsl

Create command declaring FSLDIR

Description

Finds the FSLDIR from system environment or `getOption("fsl.path")` for location of FSL functions

Usage

```
get.fsl(add_bin = TRUE)
```

```
get_fsl(add_bin = TRUE)
```

Arguments

`add_bin` Should bin be added to the fsl path? All executables are assumed to be in FSLDIR/bin/. If not, and `add_bin = FALSE`, they will be assumed to be in FSLDIR/.

Value

NULL if FSL in path, or bash code for setting up FSL DIR

Note

This will use `Sys.getenv("FSLDIR")` before `getOption("fsl.path")`. If the directory is not found for FSL in `Sys.getenv("FSLDIR")` and `getOption("fsl.path")`, it will try the default directory `/usr/local/fsl`.

| | |
|---------------|----------------------------------|
| get.fsloutput | <i>Determine FSL output type</i> |
|---------------|----------------------------------|

Description

Finds the FSLOUTPUTTYPE from system environment or getOption("fsl.outputtype") for output type (nii.gz, nii, ANALYZE,etc)

Usage

```
get.fsloutput()
```

Value

FSLOUTPUTTYPE, such as NIFTI_GZ. If none found, uses NIFTI_GZ as default

| | |
|------------|--|
| get.imgext | <i>Determine extension of image based on FSLOUTPUTTYPE</i> |
|------------|--|

Description

Runs get.fsloutput() to extract FSLOUTPUTTYPE and then gets corresponding extension (such as .nii.gz)

Usage

```
get.imgext()
```

Value

Extension for output type

| | |
|----------|--|
| getForms | <i>Get Q and S Forms of orientation matrix</i> |
|----------|--|

Description

This function obtains the s and q forms of an image transformation matrix

Usage

```
getForms(file, verbose = FALSE, ...)
```

Arguments

| | |
|---------|---|
| file | (character) filename of image to pass to header |
| verbose | (logical) passed to <code>fslhd</code> |
| ... | options passed to <code>checking</code> |

Value

list with elements of sform and qform and their respective codes

Examples

```
if (have.fsl()){
  mnifile = mni_fname("2")
  getForms(mnifile)
}
```

| | |
|---------------------|--|
| get_quickshear_mask | <i>Face Removal Mask using "Quickshear Defacing for Neuroimages" (Schimke et al. 2011)</i> |
|---------------------|--|

Description

Face Removal Mask using "Quickshear Defacing for Neuroimages" (Schimke et al. 2011)

Usage

```
get_quickshear_mask(brain_mask, buffer = 10, verbose = TRUE)

quickshear_deface_image(
  file,
  brain_mask = NULL,
  buffer = 10,
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|------------|---|
| brain_mask | Brain mask image. If NULL, then <code>fslbet</code> will be run |
| buffer | buffer to add to intercept for face mask equation |
| verbose | print diagnostic messages |
| file | input image - same orientation as brain mask |
| ... | additional arguments passed to <code>fslmask</code> |

Value

A binary image of the non-face areas

Note

adapted from <https://github.com/nipy/quickshear/blob/master/quickshear.py>

Examples

```

if (have_fsl()) {
  file = "~/Downloads/sample_T1_input.nii.gz"
  if (file.exists(file)) {
    res = quickshear_deface_image(file)
    brain_mask = fslbet(file) > 0
    mask = get_quickshear_mask(brain_mask)
    image = fslmask(file, mask)
  }
}

```

| | |
|----------|---|
| have.fsl | <i>Logical check if FSL is accessible</i> |
|----------|---|

Description

Uses `get.fsl` to check if FSLDIR is accessible or the option `fsl.path` is set and returns logical

Usage

```
have.fsl(...)
```

```
have_fsl(...)
```

Arguments

... options to pass to `get.fsl`

Value

Logical TRUE is FSL is accessible, FALSE if not

Examples

```
have.fsl()
```

intent_code-methods *Extract Image intent_code attribute*

Description

intent_code method for character types

Usage

```
## S4 method for signature 'character'  
intent_code(object)
```

Arguments

object is a filename to pass to [fslval](#)

intent_name-methods *Extract Image intent_name attribute*

Description

intent_name method for character types

Usage

```
## S4 method for signature 'character'  
intent_name(object)
```

Arguments

object is a filename to pass to [fslval](#)

intent_p1-methods *Extract Image intent_p1 attribute*

Description

intent_p1 method for character types

Usage

```
## S4 method for signature 'character'  
intent_p1(object)
```

Arguments

object is a filename to pass to [fslval](#)

intent_p2-methods *Extract Image intent_p2 attribute*

Description

intent_p2 method for character types

Usage

```
## S4 method for signature 'character'  
intent_p2(object)
```

Arguments

object is a filename to pass to [fslval](#)

intent_p3-methods *Extract Image intent_p3 attribute*

Description

intent_p3 method for character types

Usage

```
## S4 method for signature 'character'  
intent_p3(object)
```

Arguments

object is a filename to pass to [fslval](#)

`invert_xfm`*Convert a Transformation*

Description

Convert a Transformation

Usage

```
invert_xfm(inmat, omat = tempfile(fileext = ".mat"), verbose = TRUE)

concat_xfm(inmat, inmat2, omat = tempfile(fileext = ".mat"), verbose = TRUE)

fixscaleskew_xfm(
  inmat,
  inmat2,
  omat = tempfile(fileext = ".mat"),
  verbose = TRUE
)
```

Arguments

| | |
|----------------------|--|
| <code>inmat</code> | input matrix transformation |
| <code>omat</code> | output matrix transformation |
| <code>verbose</code> | print diagnostic messages |
| <code>inmat2</code> | second matrix filename to be concatenated or fixscaleskew to first |

Value

A filename of the output matrix file

Examples

```
if (have_fsl()) {
  img = mni_fname()
  mat = fslreorient2std_mat(img)
  inverted = invert_xfm(mat)
  readLines(inverted)
  catted = concat_xfm(mat, mat)
  readLines(catted)
  fixed = fixscaleskew_xfm(mat, mat)
  readLines(fixed)
}
```

| | |
|---------------|--------------------------------------|
| magic-methods | <i>Extract Image magic attribute</i> |
|---------------|--------------------------------------|

Description

magic method for character types

Usage

```
## S4 method for signature 'character'
magic(object)
```

Arguments

object is a filename to pass to [fslval](#)

| | |
|---------|------------------------------|
| mcflirt | <i>FSL Motion Correction</i> |
|---------|------------------------------|

Description

This function calls `mcflirt`

Usage

```
mcflirt(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|----------|--|
| file | (character) image to be manipulated |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class <code>nifti</code> |
| reorient | (logical) If <code>retimg</code> , should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| opts | (character) operations to be passed to <code>mcflirt</code> . Cannot use <code>-o</code> or <code>-verbose</code> , as output file should be specified in <code>outfile</code> . |
| verbose | (logical) print out command before running |
| ... | additional arguments passed to readnii . |

Value

If `returning` then object of class `nifti`. Otherwise, it will have additional attributes in the `additional_files` field.

`mcflirt.help`

MCFLIRT help

Description

This function calls `mcflirt`'s help

Usage

```
mcflirt.help()
```

Value

Prints help output and returns output as character vector

Examples

```
library(fslr)
if (have.fsl()){
  mcflirt.help()
}
```

`melodic`

Run MELODIC ICA

Description

This function calls `melodic`

Usage

```
melodic(
  file,
  outdir = dirname(file),
  intern = FALSE,
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|---------|---|
| file | (character) image to be run |
| outdir | (character) output directory. (Default dirname(file)) |
| intern | (logical) pass to system |
| opts | (character) options for melodic |
| verbose | (logical) print out command before running |
| ... | arguments passed to checking |

Value

character or logical depending on intern

| | |
|--------------|---------------------|
| melodic.help | <i>MELODIC help</i> |
|--------------|---------------------|

Description

This function calls melodic's help

Usage

```
melodic.help()
```

Value

Prints help output and returns output as character vector

Examples

```
if (have.fsl()){  
  melodic.help()  
}
```

mid_sagittal_align *Mid-Sagittal Plane Alignment*

Description

This function takes in an image, flips the image over the left/right plane, registers that flipped image to the original image, then applies the half transformation

Usage

```
mid_sagittal_align(
    file,
    outfile = NULL,
    retimg = TRUE,
    opts = "",
    translation = TRUE,
    force_rpi = TRUE,
    verbose = TRUE
)
```

Arguments

| | |
|-------------|--|
| file | (character) input filename or class nifti |
| outfile | (character) output filename |
| retimg | (logical) return image of class nifti |
| opts | (character) options passed to flirt |
| translation | (logical) should the translation parameters be preserved (TRUE) or set to zero (FALSE) |
| force_rpi | Should rpi_orient_file be run? |
| verbose | (logical) print diagnostic messages |

Value

Filename of output or nifti depending on retimg

mni_fname *Construct MNI Filename*

Description

Finds the standard data directory for FSL and pastes together the string for an MNI template image

Usage

```
mni_fname(mm = c("1", "0.5", "2"), brain = FALSE, linear = FALSE, mask = FALSE)
mni_face_fname(mm = c("1", "0.5", "2"))
```

Arguments

| | |
|--------|--|
| mm | Resolution (in mm) of the brain image (isotropic) |
| brain | Should the brain be returned (default) or the T1 with the skull |
| linear | Should the linearized MNI template be used |
| mask | should the mask be given? Generally, only MNI152_T1_1mm_brain_mask exists. |

Value

Character path of filename, warning if that file does not exist

mni_img

Read MNI Filename

Description

Simple wrapper for reading in the MNI image constructed from [mni_fname](#)

Usage

```
mni_img(...)
```

Arguments

... Arguments passed to [mni_fname](#)

Value

Object of class [nifti](#)

 mridefacer

MRI Defacer

Description

MRI Defacer

Usage

```
mridefacer(file, ..., verbose = TRUE)
```

```
get_mridefacer_mask(
  file,
  brain_mask = NULL,
  bet_opts = "-f 0.5",
  search_radius = 90,
  opts = NULL,
  template_brain = NULL,
  template_brain_weight = NULL,
  template_biometric_mask = NULL,
  verbose = TRUE
)
```

Arguments

| | |
|-------------------------|---|
| file | input file image to remove face/ears |
| ... | not used |
| verbose | print diagnostic messages. If > 1, more verbose |
| brain_mask | brain mask of file. If NULL, <code>fslbet</code> will be applied |
| bet_opts | options to pass to <code>fslbet</code> if applied |
| search_radius | search radius option to pass to <code>flirt</code> |
| opts | additional options to pass to <code>flirt</code> |
| template_brain | template brain image, may be NULL |
| template_brain_weight | template brain weight image, used for registration may be NULL |
| template_biometric_mask | template biometric mask. Everything that is wanted should be 1, may be NULL |

Value

A character filename of the output image

Note

Adapted from <https://github.com/mih/mridefacer>

Examples

```

if (have_fsl()) {
file = "~/Downloads/sample_T1_input.nii.gz"
if (file.exists(file)) {
  res = mridefacer(file)
}
}

```

| | |
|---------------|----------------------------------|
| parse_avscale | <i>Parse output from avscale</i> |
|---------------|----------------------------------|

Description

This function parses the output from [fsl_avscale](#) into something more manageable

Usage

```
parse_avscale(av_out)
```

Arguments

av_out output from [fsl_avscale](#), character vector

Value

List of output values

| | |
|----------------|---------------------------------------|
| pixdim-methods | <i>Extract Image pixdim attribute</i> |
|----------------|---------------------------------------|

Description

Gets pixdim from a character

Usage

```

## S4 method for signature 'character'
pixdim(object)

```

Arguments

object is a filename to pass to [fslval](#)

probtrackx

Probabilistic diffusion tractography with multiple fibre orientations

Description

This function wraps probtrackx from FSL

Usage

```
probtrackx(  
  samples = "merged",  
  mask,  
  seed,  
  outdir = "fdt_paths",  
  verbose = TRUE,  
  mode = NULL,  
  targetmasks = NULL,  
  mask2 = NULL,  
  waypoints = NULL,  
  network = FALSE,  
  mesh = NULL,  
  seedref = NULL,  
  dir = FALSE,  
  forcedir = FALSE,  
  opd = FALSE,  
  pd = FALSE,  
  os2t = FALSE,  
  avoid = NULL,  
  stop = NULL,  
  xfm = NULL,  
  invxfm = NULL,  
  nsamples = 5000,  
  nsteps = 2000,  
  distthresh = 0,  
  cthr = 0.2,  
  fibthresh = 0.01,  
  sampvox = FALSE,  
  steplength = 0.5,  
  loopcheck = FALSE,  
  usef = FALSE,  
  randfib = c(0, 1, 2, 3),  
  fibst = 1,  
  modeuler = FALSE,  
  rseed = NULL,  
  s2tastext = FALSE,  
  opts = ""  
)
```

Arguments

| | |
|-------------|--|
| samples | (nifti/character) Basename for samples files |
| mask | (nifti/character) Bet binary mask file in diffusion space |
| seed | (nifti/character) Seed volume, or voxel, or ascii file with multiple volumes, or freesurfer label file |
| outdir | (character) Output file (default='fdt_paths') |
| verbose | (logical/numeric) Verbose level, [0-2] |
| mode | (character) Use -mode=simple for single seed voxel |
| targetmasks | (character) File containing a list of target masks - required for seeds_to_targets classification |
| mask2 | (nifti/character) Second mask in twomask_symm mode. |
| waypoints | (nifti/character) Waypoint mask or ascii list of waypoint masks - only keep paths going through ALL the masks |
| network | (logical) Activate network mode - only keep paths going through at least one seed mask (required if multiple seed masks) |
| mesh | (character) Freesurfer-type surface descriptor (in ascii format) |
| seedref | (nifti/character) Reference vol to define seed space in simple mode - diffusion space assumed if absent |
| dir | (logical) Directory to put the final volumes in - code makes this directory - default='logdir' |
| forcedir | (logical) Use the actual directory name given - i.e. don't add + to make a new directory |
| opd | (logical) Output path distribution |
| pd | (logical) Correct path distribution for the length of the pathways |
| os2t | (logical) Output seeds to targets |
| avoid | (nifti/character) Reject pathways passing through locations given by this mask |
| stop | (nifti/character) Stop tracking at locations given by this mask file |
| xfm | (character) Transform taking seed space to DTI space (either FLIRT matrix or FNIRT warpfield) - default is identity |
| invxfm | (character) Transform taking DTI space to seed space (compulsory when using a warpfield for seeds_to_dti) |
| nsamples | (numeric) Number of samples - default=5000 |
| nsteps | (numeric) Number of steps per sample - default=2000 |
| distthresh | (numeric) Discards samples shorter than this threshold (in mm - default=0) |
| cthr | (numeric) Curvature threshold - default=0.2 |
| fibthresh | (numeric) Volume fraction before subsidiary fibre orientations are considered - default=0.01 |
| sampvox | (logical) Sample random points within seed voxels |
| steplength | (numeric) Steplength in mm - default=0.5 |

| | |
|-----------|--|
| loopcheck | (logical) Perform loopchecks on paths - slower, but allows lower curvature threshold |
| usef | (logical) Use anisotropy to constrain tracking |
| randfib | (numeric) Default 0. Set to 1 to randomly sample initial fibres (with $f > \text{fibthresh}$). Set to 2 to sample in proportion fibres (with $f > \text{fibthresh}$) to f . Set to 3 to sample ALL populations at random (even if $f < \text{fibthresh}$) |
| fibst | (numeric) Force a starting fibre for tracking - default=1, i.e. first fibre orientation. Only works if $\text{randfib} == 0$ |
| modeuler | (logical) Use modified euler streamlining |
| rseed | (numeric) Random seed |
| s2tastext | (logical) Output seed-to-target counts as a text file (useful when seeding from a mesh) |
| opts | Additional options or way to specify things instead of command line arguments |

Value

A filename of the output file

qform,character-method

Extract NIfTI 3D Image Orientation

Description

Gets q/s-forms from a character

Usage

```
## S4 method for signature 'character'
qform(object)
```

```
## S4 method for signature 'character'
sform(object)
```

Arguments

object is a nifti object

qform_code-methods *Extract Image qform_code attribute*

Description

qform_code method for character types

Usage

```
## S4 method for signature 'character'
qform_code(object)
```

Arguments

object is a filename to pass to [fslval](#)

readrpi *Read NIfTI file reoriented to RPI*

Description

This function calls the [readnii](#) function after calling [rpi_orient_file](#) to force RPI orientation.

Usage

```
readrpi(file, ..., verbose = TRUE)
```

Arguments

file file name of the NIfTI file.
 ... Arguments to pass to [readnii](#)
 verbose print diagnostics, passed to [rpi_orient_file](#)

Examples

```
if (have.fsl()){
  print(fsl_version())
  in_ci <- function() {
    nzchar(Sys.getenv("CI"))
  }
  if (in_ci()) {
    destfile = tempfile(fileext = ".nii.gz")
    url = paste0("https://ndownloader.figshare.com/",
      "files/18068546")
    old_url = paste0("https://github.com/muschellij2/",
      "Neurohacking/files/3454385/113-01-MPRAGE2.nii.gz")
```

```

dl = tryCatch(download.file(url,
destfile = destfile))
if (inherits(dl, "try-error") || dl != 0) {
dl = download.file(old_url, destfile = destfile)
}
res = readrpi(destfile)
}
}

```

read_xfm

Read FSL Transformation

Description

Read FSL Transformation

Usage

```
read_xfm(file)
```

Arguments

file transformation file from [flirt](#), usually ending in `.mat`

Value

A numeric matrix of numeric class

reverse_rpi_orient

Reverse Reorientation an Image to RPI orientation

Description

This function uses `fslswapdim` to reorient an image

Usage

```

reverse_rpi_orient(
  file,
  convention = c("NEUROLOGICAL", "RADIOLOGICAL"),
  orientation,
  verbose = TRUE
)

reverse_rpi_orient_file(
  file,

```

```

    convention = c("NEUROLOGICAL", "RADIOLOGICAL"),
    orientation,
    verbose = TRUE
)

```

Arguments

| | |
|-------------|--|
| file | Object of class <code>nifti</code> or character path |
| convention | Convention of original image (usually from <code>rpi_orient</code>) |
| orientation | Vector of length 3 from original image (usually from <code>rpi_orient</code>) |
| verbose | print diagnostic messages |

Value

Object of class `nifti`

| | |
|------------|---|
| rpi_orient | <i>Reorient an Image to RPI orientation</i> |
|------------|---|

Description

This function uses `fs1swpdim` to reorient an image

Usage

```

rpi_orient(file, verbose = TRUE)

rpi_orient_file(file, verbose = TRUE)

is_rpi(file, verbose = FALSE)

is.rpi(file, verbose = FALSE)

```

Arguments

| | |
|---------|--|
| file | Object of class <code>nifti</code> or character path |
| verbose | print diagnostic messages |

Value

List of 3 elements

- `img`: Reoriented image of class `nifti`
- `convention`: Convention (Neurological/Radiological) of original image
- `orientation`: Original image orientations

Note

'orient_rpi' and 'orient_rpi_file' uses 'RNifti' to ensure the reading orientation

Examples

```
lr_fname = system.file( "nifti", "mniLR.nii.gz", package = "oro.nifti")
img = readnii(lr_fname)

rl_fname = system.file( "nifti", "mniRL.nii.gz", package = "oro.nifti")
rl_img = readnii(rl_fname)
stopifnot(all(rl_img[nrow(rl_img):1,,] == img))

## Not run:
if (have_fsl()) {

reor = rpi_orient(rl_fname)
rev = reverse_rpi_orient(reor$img, convention = reor$convention,
orientation = reor$orientation)
stopifnot(all(rev == rl_img))
}

## End(Not run)

reor = orient_rpi(rl_fname)
stopifnot(all(img == reor$img))

rev = reverse_orient_rpi(reor$img, convention = reor$convention,
orientation = reor$orientation)
stopifnot(all(rev == rl_img))
```

run_first_all

Run FIRST All

Description

Wrapper for run_first_all from FSL for FIRST analysis segmentation of subcortical structures

Usage

```
run_first_all(
  img,
  oprefix = tempfile(),
  brain_extracted = FALSE,
  structures = NULL,
  affine = NULL,
  opts = "",
  verbose = TRUE
)
```

Arguments

| | |
|-----------------|--|
| img | specifies the input image (T1-weighted) |
| oprefix | specifies the output image basename (extensions will be added to this) |
| brain_extracted | specifies that the input image has been brain extracted |
| structures | a restricted set of structures to be segmented |
| affine | specifies the affine registration matrix to standard space (optional) |
| opts | (character) operations to be passed to run_first_all |
| verbose | (logical) print out command before running |

Value

List of results, including result of [system](#) and some output files

run_first_all.help *Run FIRST All Help*

Description

This function calls run_first_all's help

Usage

```
run_first_all.help()
```

Value

Prints help output and returns output as character vector

Examples

```
library(fslr)

if (have.fsl()){
  run_first_all.help()
}
```

scl_inter-methods *Extract Image scl_inter attribute*

Description

scl_inter method for character types

Usage

```
## S4 method for signature 'character'  
scl_inter(object)
```

Arguments

object is a filename to pass to [fslval](#)

scl_slope-methods *Extract Image scl_slope attribute*

Description

scl_slope method for character types

Usage

```
## S4 method for signature 'character'  
scl_slope(object)
```

Arguments

object is a filename to pass to [fslval](#)

sform_code-methods *Extract Image sform_code attribute*

Description

sform_code method for character types

Usage

```
## S4 method for signature 'character'  
sform_code(object)
```

Arguments

object is a filename to pass to [fslval](#)

sizeof_hdr-methods *Extract Image sizeof_hdr attribute*

Description

'sizeof_hdr' method for character types

Usage

```
## S4 method for signature 'character'  
sizeof_hdr(object)
```

Arguments

object is a filename to pass to [fslval](#)

slice_code-methods *Extract Image slice_code attribute*

Description

slice_code method for character types

Usage

```
## S4 method for signature 'character'  
slice_code(object)
```

Arguments

object is a filename to pass to [fslval](#)

slice_duration-methods

Extract Image slice_duration attribute

Description

slice_duration method for character types

Usage

```
## S4 method for signature 'character'  
slice_duration(object)
```

Arguments

object is a filename to pass to [fslval](#)

slice_end-methods

Extract Image slice_end attribute

Description

slice_end method for character types

Usage

```
## S4 method for signature 'character'  
slice_end(object)
```

Arguments

object is a filename to pass to [fslval](#)

slice_start-methods *Extract Image slice_start attribute*

Description

slice_start method for character types

Usage

```
## S4 method for signature 'character'
slice_start(object)
```

Arguments

object is a filename to pass to [fslval](#)

susan *FSL SUSAN noise reduction*

Description

Implements Smallest Univalued Segment Assimilating Nucleus (SUSAN) noise reduction technique from FSL

Usage

```
susan(
  file,
  outfile = NULL,
  retimg = TRUE,
  reorient = FALSE,
  intern = FALSE,
  bthresh = 0.1,
  sigma = 3,
  dimg = c(3, 2),
  use_median = FALSE,
  n_usans = c(0, 1, 2),
  extra.scans = list(),
  opts = "",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|-------------|---|
| file | (character) image to be manipulated |
| outfile | (character) resultant image name (optional) |
| retimg | (logical) return image of class nifti |
| reorient | (logical) If retimg, should file be reoriented when read in? Passed to readnii . |
| intern | (logical) to be passed to system |
| bthresh | brightness threshold and should be greater than noise level and less than contrast of edges to be preserved. |
| sigma | spatial size (sigma i.e. half-width) of smoothing in mm. |
| dimg | dimensionality (2 or 3) depending on whether smoothing is to be within-plane (2) or fully 3D (3). |
| use_median | determines whether to use a local median filter in the cases where single-point noise is detected (0 or 1). |
| n_usans | determines whether the smoothing area (USAN) is to be found from secondary images (0 1 or 2). |
| extra.scans | List of extra scans for USAN. List of n_usans elements, where each element has 2 named objects bthresh and filename |
| opts | (character) operations to be passed to susan, not currently used. |
| verbose | (logical) print out command before running |
| ... | additional arguments passed to fslcmd . |

Value

If retimg then object of class nifti. Otherwise, Result from system command, depends if intern is TRUE or FALSE.

References

S.M. Smith and J.M. Brady. SUSAN -a new approach to low level image processing. International Journal of Computer Vision, 23(1):45-78, May 1997.

susan.help

FSL SUSAN Help

Description

This function calls susan's help

Usage

```
susan.help()
```

Value

Prints help output and returns output as character vector

Examples

```
library(fslr)
if (have.fsl()){
  susan.help()
}
```

| | |
|-----------------|--|
| toffset-methods | <i>Extract Image toffset attribute</i> |
|-----------------|--|

Description

Gets toffset from a character

Usage

```
## S4 method for signature 'character'
toffset(object)
```

Arguments

object is a filename to pass to [fslval](#)

| | |
|-------|----------------------------------|
| topup | <i>topup - calling FSL topup</i> |
|-------|----------------------------------|

Description

A tool for estimating and correcting susceptibility induced distortions

Usage

```
topup(
  infile,
  datain,
  out = NULL,
  fout = NULL,
  iout = NULL,
  logout = NULL,
  warpres = 10,
  subsamp = 1,
  fwhm = 8,
  config = NULL,
```

```

    miter = 5,
    lambda = NULL,
    sslambda = 1,
    regmod = c("bending_energy", "membrane_energy"),
    estmov = 1,
    minmet = c(0, 1),
    splineorder = c(3, 2),
    numprec = c("double", "float"),
    interp = c("spline", "linear"),
    scale = c(0, 1),
    regrid = c(0, 1),
    verbose = TRUE
)

fsl_topup(...)

```

Arguments

| | |
|-------------|--|
| infile | name of 4D file with images |
| datain | name of text file with PE directions/times |
| out | base-name of output files (spline coefficients (Hz) and movement parameters) |
| fout | name of image file with field (Hz) |
| iout | name of 4D image file with unwarped images |
| logout | Name of log-file |
| warpres | (approximate) resolution (in mm) of warp basis for the different sub-sampling levels, default 10 |
| subsamp | sub-sampling scheme, default 1 |
| fwhm | FWHM (in mm) of gaussian smoothing kernel, default 8 |
| config | Name of config file specifying command line arguments |
| miter | Max # of non-linear iterations, default 5 |
| lambda | Weight of regularisation, default depending on sslambda and regmod switches. See user documentation. |
| sslambda | If set (=1), lambda is weighted by current ssq, default 1 |
| regmod | Model for regularisation of warp-field [membrane_energy bending_energy], default bending_energy |
| estmov | Estimate movements if set, default 1 (true) |
| minmet | Minimisation method 0=Levenberg-Marquardt, 1=Scaled Conjugate Gradient, default 0 (LM) |
| splineorder | Order of spline, 2->Quadratic spline, 3->Cubic spline. Default=3 |
| numprec | Precision for representing Hessian, double or float. Default double |
| interp | Image interpolation model, linear or spline. Default spline |
| scale | If set (=1), the images are individually scaled to a common mean, default 0 (false) |

| | |
|---------|--|
| regrid | If set (=1), the calculations are done in a different grid, default 1 (true) |
| verbose | Print diagnostic information while running |
| ... | arguments passed to topup if using fsl_topup |

| | |
|--------------------|---|
| vox_offset-methods | <i>Extract Image vox_offset attribute</i> |
|--------------------|---|

Description

vox_offset method for character types

Usage

```
## S4 method for signature 'character'
vox_offset(object)
```

Arguments

| | |
|--------|---|
| object | is a filename to pass to fslval |
|--------|---|

| | |
|---------|--|
| xfibres | <i>Bayesian Estimation of Diffusion Parameters Obtained using Sampling Techniques with Crossing Fibers</i> |
|---------|--|

Description

Calls xfibres from FSL to fit, also known as bedpostx

Usage

```
xfibres(
  infile,
  bvecs,
  bvals,
  mask = NULL,
  nfibres = 1,
  bet.opts = "",
  verbose = TRUE,
  njumps = NULL,
  burnin = NULL,
  burnin_noard = NULL,
  sampleevery = NULL,
  updateproposalevery = NULL,
  seed = NULL,
  noard = FALSE,
```

```

    allard = FALSE,
    nospat = FALSE,
    nonlinear = FALSE,
    cnonlinear = FALSE,
    rician = FALSE,
    f0 = FALSE,
    ardf0 = FALSE,
    opts = ""
)

```

Arguments

| | |
|----------------------------------|---|
| <code>infile</code> | Input filename |
| <code>bvecs</code> | b-vectors: matrix of 3 columns or filename of ASCII text file |
| <code>bvals</code> | b-values: vector of same length as number of rows of b-vectors or filename of ASCII text file |
| <code>mask</code> | Mask filename |
| <code>nfibres</code> | Maximum number of fibres to fit in each voxel (default 1) |
| <code>bet.opts</code> | Options for <code>fs1bet</code> if mask is not supplied |
| <code>verbose</code> | print diagnostic messages |
| <code>njumps</code> | num of jumps to be made by MCMC (default is 5000) |
| <code>burnin</code> | Total num of jumps at start of MCMC to be discarded (default is 0) |
| <code>burnin_noard</code> | num of burnin jumps before the ard is imposed (default is 0) |
| <code>sampleevery</code> | num of jumps for each sample (MCMC) (default is 1) |
| <code>updateproposalevery</code> | num of jumps for each update to the proposal density std (MCMC) (default is 40) |
| <code>seed</code> | for pseudo random number generator |
| <code>noard</code> | Turn ARD off on all fibres |
| <code>allard</code> | Turn ARD on on all fibres |
| <code>nospat</code> | Initialise with tensor, not spatially |
| <code>nonlinear</code> | Initialise with nonlinear fitting |
| <code>cnonlinear</code> | Initialise with constrained nonlinear fitting |
| <code>rician</code> | Use Rician noise modelling |
| <code>f0</code> | Add to the model an unattenuated signal compartment |
| <code>ardf0</code> | Use ard on f0 |
| <code>opts</code> | Additional options for <code>xfibres</code> . There should not be any left out in the current arguments, but <code>opts</code> may be a way some prefer to input options. |

Value

Output from `system`

Index

apply_topup (applytopup), 6
applytopup, 6
aux.file, character-method
 (aux.file-methods), 7
aux.file-methods, 7
avscale (fsl_avscale), 82

bedpostx (xfibres), 153
bitpix, character-method
 (bitpix-methods), 7
bitpix-methods, 7

cal.max, character-method
 (cal.max-methods), 7
cal.max-methods, 7
cal.min, character-method
 (cal.min-methods), 8
cal.min-methods, 8
check_file, 9
checking, 9, 41, 53, 65, 70, 71, 78, 126, 133
checkout, 8, 9
concat_xfm (invert_xfm), 130

data_type, character-method
 (data_type-methods), 10
data_type-methods, 10
datatype, character-method
 (datatype-methods), 9
datatype-methods, 9
deface_image (face_removal_mask), 15
descrip, character-method
 (descrip-methods), 10
descrip-methods, 10
dim_, character-method (dim_-methods), 10
dim_-methods, 10
download.file, 11
download_fsl, 11
dtifit, 11

eddy, 12, 13

eddy_correct, 14
enforce_form, 14
epi_reg (fslepi_reg), 36

face_removal_mask, 15
fast, 16
fast.help, 17
fast_all (fast), 16
fast_nobias (fast), 16
fast_nobias_all (fast), 16
fixscaleskew_xfm (invert_xfm), 130
flirt, 18, 19, 134, 136, 142
flirt.help, 19
flirt_apply, 19
flirt_apply.help (flirt.help), 19
fnirt, 20, 23, 79
fnirt.help, 21
fnirt_with_affine, 21
fnirt_with_affine_apply, 22
fsl_abs, 74
fsl_acos, 75
fsl_add, 76
fsl_anat, 77
fsl_anat.help, 78
fsl_and (fsland), 25
fsl_applytopup (applytopup), 6
fsl_applywarp, 79
fsl_applywarp.help, 80
fsl_asin, 80
fsl_atan, 81
fsl_atlas_dir, 82
fsl_avscale, 82, 137
fsl_bet, 83
fsl_biascorrect, 84
fsl_bin, 85
fsl_bin_tab, 87, 92
fsl_binv, 86
fsl_cluster, 87
fsl_cos, 89
fsl_data_dir, 90

- fsl_deface, 91
- fsl_dice, 92
- fsl_dilate, 92
- fsl_dir (fsldir), 34
- fsl_div, 94
- fsl_edge, 95
- fsl_epi_reg (fslepi_reg), 36
- fsl_erode, 96
- fsl_exp, 97
- fsl_fast (fast), 16
- fsl_fast_nobias (fast), 16
- fsl_fill, 98
- fsl_index, 99
- fsl_log, 100
- fsl_mask, 101
- fsl_maths, 102
- fsl_merge, 103
- fsl_mul, 104
- fsl_nan, 105
- fsl_nanm, 106
- fsl_or (fslor), 49
- fsl_rand, 107
- fsl_randn, 108
- fsl_recip, 109
- fsl_rem, 110
- fsl_resample, 111
- fsl_robustfov (fslrobustfov), 56
- fsl_roi (fslroi), 57
- fsl_slicetimer (fslslicetimer), 60
- fsl_smooth, 112
- fsl_smooth_in_mask (fslsmooth_in_mask), 62
- fsl_smoothest, 113
- fsl_split (fslsplit), 63
- fsl_sqr, 114
- fsl_sqrt, 115
- fsl_std_dir, 116
- fsl_std_file (fsl_std_dir), 116
- fsl_sub, 116
- fsl_sub2, 117
- fsl_swapdim, 118
- fsl_tan, 119
- fsl_thresh, 73, 120
- fsl_topup (topup), 151
- fsl_tsplot, 122
- fsl_version, 123
- fsl_version_gt5 (fsl_version), 123
- fsl_xor (fslxor), 73
- fslabs (fsl_abs), 74
- fslabs.help, 24
- fslacos (fsl_acos), 75
- fslacos.help, 24
- fsladd (fsl_add), 76
- fsladd.help, 25
- fsland, 25
- fslasin (fsl_asin), 80
- fslasin.help, 26
- fslatan (fsl_atan), 81
- fslatan.help, 26
- fslbet, 12, 127, 136, 154
- fslbet (fsl_bet), 83
- fslbet.help, 27
- fslbin, 25, 49, 73
- fslbin (fsl_bin), 85
- fslbin.help, 28
- fslbinv (fsl_binv), 86
- fslbinv.help, 28
- fslchfiletype, 29
- fslchfiletype.help, 30
- fslcluster (fsl_cluster), 87
- fslcmd, 14, 30, 89, 91, 114, 123, 150
- fslcog, 31
- fslcos (fsl_cos), 89
- fslcos.help, 32
- fslcpgeom, 33
- fslcpgeom.help, 34
- fsl_dilate (fsl_dilate), 92
- fsldir, 34
- fsldiv (fsl_div), 94
- fsldiv.help, 35
- fsledge (fsl_edge), 95
- fsledge.help, 35
- fslentropy, 36
- fslentropy.help (fslstats.help), 66
- fslepi_reg, 36
- fsl_erode (fsl_erode), 96
- fsl_erode.help, 38
- fsl_exp (fsl_exp), 97
- fsl_exp.help, 38
- fsleyes (fslview), 71
- fslfast (fast), 16
- fslfast_nobias (fast), 16
- fslfill, 40
- fslfill (fsl_fill), 98
- fslfill.help, 39
- fslfill2, 39

- fslgetorient, 40
- fslgetqform (fslgetorient), 40
- fslgetqformcode (fslgetorient), 40
- fslgetsform (fslgetorient), 40
- fslgetsformcode (fslgetorient), 40
- fslhd, 41, 42, 126
- fslhd.help, 41
- fslhd.parse, 42
- fslhelp, 42
- fslindex (fsl_index), 99
- fslindex.help, 43
- fsllog (fsl_log), 100
- fsllog.help, 44
- fslmask, 127
- fslmask (fsl_mask), 101
- fslmask.help, 44
- fslmaths (fsl_maths), 102
- fslmaths.help, 24–28, 32, 35, 38, 39, 43, 44, 45, 47, 48, 51–54, 60, 61, 64, 65, 67, 69
- fslmax, 45
- fslmean, 46
- fslmean.help (fslstats.help), 66
- fslmerge (fsl_merge), 103
- fslmerge.help, 46
- fslmin (fslmax), 45
- fslmul, 25
- fslmul (fsl_mul), 104
- fslmul.help, 47
- fslnan (fsl_nan), 105
- fslnan.help, 47
- fslnanm (fsl_nanm), 106
- fslnanm.help, 48
- fslor, 49
- fslorient, 40, 50, 51
- fslorient.help, 50
- fslorienter, 51
- fslrand (fsl_rand), 107
- fslrand.help, 51
- fslrandn (fsl_randn), 108
- fslrandn.help, 52
- fslrange, 45, 52
- fslrange.help (fslstats.help), 66
- fslrecip (fsl_recip), 109
- fslrecip.help, 53
- fslrem (fsl_rem), 110
- fslrem.help, 54
- fslreorient2std, 54, 55
- fslreorient2std.help, 55
- fslreorient2std_mat (fslreorient2std), 54
- fslrobustfov, 56
- fslrobustfov.help, 57
- fslroi, 57
- fslroi_time (fslroi), 57
- fslsd, 58
- fslsd.help (fslstats.help), 66
- fslsin, 59
- fslsin.help, 60
- fslslicetimer, 60
- fslsmooth, 62
- fslsmooth (fsl_smooth), 112
- fslsmooth.help, 61
- fslsmooth_in_mask, 62
- fslsplit, 63
- fslsplit.help, 64
- fslsqr (fsl_sqr), 114
- fslsqr.help, 64
- fslsqrt (fsl_sqrt), 115
- fslsqrt.help, 65
- fslstats, 36, 46, 59, 65, 68, 73
- fslstats.help, 66
- fslsub (fsl_sub), 116
- fslsub.help, 66
- fslsub2 (fsl_sub2), 117
- fslsub2.help, 67
- fslsum, 68, 72
- fslswapdim (fsl_swapdim), 118
- fslswapdim.help, 68
- fsltan (fsl_tan), 119
- fsltan.help, 69
- fslthresh (fsl_thresh), 120
- fslthresh.help, 69
- fslval, 7–10, 70, 128, 129, 131, 137, 141, 146–149, 151, 153
- fslval.help, 70
- fslversion (fsl_version), 123
- fslview, 71
- fslview.help, 72
- fslvol, 72
- fslvolume, 73
- fslxor, 73
- get.fsl, 124, 127
- get.fsloutput, 125
- get.imgext, 125
- get_fsl (get.fsl), 124

- get_mridefacer_mask (mridefacer), 136
- get_quickshear_mask, 126
- getForms, 8, 14, 126
- have.fsl, 127
- have_fsl (have.fsl), 127
- intent_code, character-method
 - (intent_code-methods), 128
- intent_code-methods, 128
- intent_name, character-method
 - (intent_name-methods), 128
- intent_name-methods, 128
- intent_p1, character-method
 - (intent_p1-methods), 129
- intent_p1-methods, 129
- intent_p2, character-method
 - (intent_p2-methods), 129
- intent_p2-methods, 129
- intent_p3, character-method
 - (intent_p3-methods), 129
- intent_p3-methods, 129
- invert_xfm, 130
- is.rpi (rpi_orient), 143
- is_rpi (rpi_orient), 143
- magic, character-method (magic-methods),
 - 131
- magic-methods, 131
- mcflirt, 131
- mcflirt.help, 132
- melodic, 132
- melodic.help, 133
- mid_sagittal_align, 134
- mni_face_fname, 15
- mni_face_fname (mni_fname), 134
- mni_fname, 15, 134, 135
- mni_img, 135
- mridefacer, 136
- nifti, 135
- parse_avscale, 82, 137
- pixdim, character-method
 - (pixdim-methods), 137
- pixdim-methods, 137
- probtrackx, 138
- qform, character
 - (qform, character-method), 140
- qform, character-method, 140
- qform_code, character-method
 - (qform_code-methods), 141
- qform_code-methods, 141
- quickshear_deface_image
 - (get_quickshear_mask), 126
- read_cluster_table (fsl_cluster), 87
- read_xfm, 142
- readnii, 17, 18, 20–23, 29, 31, 33, 37, 40, 49,
 - 50, 55, 56, 58, 59, 61, 63, 74–77,
 - 79–81, 83–86, 88, 90, 91, 93–112,
 - 114, 115, 117–121, 131, 141, 150
- readrpi, 141
- reverse_rpi_orient, 142
- reverse_rpi_orient_file
 - (reverse_rpi_orient), 142
- rpi_orient, 143, 143
- rpi_orient_file, 134, 141
- rpi_orient_file (rpi_orient), 143
- run_first_all, 144
- run_first_all.help, 145
- scl_inter, character-method
 - (scl_inter-methods), 146
- scl_inter-methods, 146
- scl_slope, character-method
 - (scl_slope-methods), 146
- scl_slope-methods, 146
- sform, character
 - (qform, character-method), 140
- sform, character-method
 - (qform, character-method), 140
- sform_code, character-method
 - (sform_code-methods), 146
- sform_code-methods, 146
- sizeof_hdr, character-method
 - (sizeof_hdr-methods), 147
- sizeof_hdr-methods, 147
- slice_code, character-method
 - (slice_code-methods), 147
- slice_code-methods, 147
- slice_duration, character-method
 - (slice_duration-methods), 148
- slice_duration-methods, 148
- slice_end, character-method
 - (slice_end-methods), 148
- slice_end-methods, 148

slice_start,character-method
 (slice_start-methods), 149
slice_start-methods, 149
susan, 149
susan.help, 150
system, 17, 18, 20–23, 29, 31, 33, 37, 40, 49,
 50, 55, 56, 58, 59, 61, 71, 74–81,
 83–86, 90, 91, 93–98, 100, 101,
 103–110, 112, 114, 115, 117–121,
 131, 133, 145, 150, 154

toffset,character-method
 (toffset-methods), 151
toffset-methods, 151
topup, 151

vox_offset,character-method
 (vox_offset-methods), 153
vox_offset-methods, 153
voxdim, 72

xfibres, 153