

Package ‘geoFKF’

October 13, 2022

Title Kriging Method for Spatial Functional Data

Version 0.1.1

Maintainer Gilberto Sassi <sassi.pereira.gilberto@gmail.com>

Description A Kriging method for functional datasets with spatial dependency.

This functional Kriging method avoids the need to estimate the trace-variogram, and the curve is estimated by minimizing a quadratic form. The curves in the functional dataset are smoothed using Fourier series. The functional Kriging of this package is a modification of the method proposed by Giraldo (2011) <[doi:10.1007/s10651-010-0143-y](https://doi.org/10.1007/s10651-010-0143-y)>.

Imports numDeriv, stats, Rcpp

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.1.2

URL <https://github.com/gilberto-sassi/geoFKF>

BugReports <https://github.com/gilberto-sassi/geoFKF/issues>

LinkingTo Rcpp, RcppArmadillo

NeedsCompilation yes

Author Gilberto Sassi [aut, cre]

Repository CRAN

Date/Publication 2022-08-12 19:50:02 UTC

R topics documented:

coef_fourier	2
datasetCanada	2
fourier_b	3
geo_fkf	3
logLikMultiNorm	4
log_lik_rf	5

Index

6

coef_fourier *Computing coefficients Fourier.*

Description

This function computes minimum square estimates for Fourier coefficients.

Usage

```
coef_fourier(f, m)
```

Arguments

- | | |
|----------|---|
| f | A time series to be smoothed. |
| m | Order of the Fourier polynomial. Default value is computed using the Sturge's rule. |

Value

A vector with the fourier coefficients.

Examples

```
x <- seq(from = -pi, to = pi, by = 0.01)
y <- x^2 + rnorm(length(x), sd = 0.1)
v_coef <- coef_fourier(y)
```

datasetCanada *Temperature datasets from Canada.*

Description

Temperature time series from 35 weather stations from Canada. This dataset is a classic one and was used in famous package fda. We have made a few changes in this dataset.

Usage

```
data("datasetCanada")
```

Format

A list with two entries: **m_cood** and **m_data**.

m_cood a tibble with latitude, logitude and the name of stations.

m_data a tibble where each column is the time series from a weather station.

Source

the CanadianWeather dataset from the R package fda.

fourier_b

Smoothed curve in Fourier Series.

Description

This function computes the smoothed curve using Fourier coefficients.

Usage

```
fourier_b(coef, x)
```

Arguments

- | | |
|------|---|
| coef | Fourier coefficients. |
| x | a time series to evaluate the smoothed curve. |

Value

a time series with the smoothed curve.

Examples

```
v_coef <- rnorm(23)
fourier_b(v_coef)
```

geo_fkf

Kriging method for Spatial Functional Data.

Description

geo_fkf implements the kriging method for spatial functional datasets.

Usage

```
geo_fkf(m_data, m_coord, new_loc, p, t = seq(from = -pi, to = pi, by = 0.01))
```

Arguments

- | | |
|---------|--|
| m_data | a tibble where each column or variable is data from a station |
| m_coord | a tibble with two columns: latitude and longitude |
| new_loc | a tble with one observation, where the columns or variables are latitude and longitude |
| p | order in the Fourier Polynomial |
| t | a time series with values belonging to $[-\pi, \pi]$ to evaluate the estimate curve |

Value

a list with three entries: **estimates**, **Theta** and **cov_params**

estimates the estimate curve

Theta weights (matrices) of the linear combination

cov_params estimate σ^2 , ϕ and ρ

Examples

```
data("datasetCanada")

m_data <- as.matrix(datasetCanada$m_data)
m_coord <- as.matrix(datasetCanada$m_coord[, 1:2])
pos <- sample.int(nrow(m_coord), 1)
log_pos <- !(seq_len(nrow(m_coord)) %in% pos)
new_loc <- m_coord[pos, ]
m_coord <- m_coord[log_pos, ]
m_data <- m_data[, log_pos]

geo_fkf(m_data, m_coord, new_loc)
```

logLikMultiNorm

Log likelihood function for multivariate normal with spatial dependency.

Description

Log likelihood function for multivariate normal with spatial dependency.

Arguments

mCoef	coefficient matrix. Each column is the coefficient from a curve;
mDist	distance matrix;
s2	variance from the covariance model;
phi	variance from the covariance model;
rho	variance from the covariance model;

<code>log_lik_rf</code>	<i>Maximum likelihood estimate for σ^2, ϕ and ρ.</i>
-------------------------	--

Description

This function maximum likelihood estimate for σ^2 , ϕ and ρ in the random field model for the covariance.

Usage

```
log_lik_rf(m_coef, m_coord)
```

Arguments

<code>m_coef</code>	Matrix where each column is an observed vector
<code>m_coord</code>	Matrix where each observation contains the latitude and longitude

Value

Return a list with

par A vector with the estimates of σ^2 , ϕ and ρ .

m_cov A matrix of covariances of the estimates.

Examples

```
data("datasetCanada")

m_data <- as.matrix(datasetCanada$m_data)
m_coord <- as.matrix(datasetCanada$m_coord[, 1:2])

p <- ceiling(1 + log2(nrow(m_data)))
m_coef <- sapply(seq_len(nrow(m_coord)), function(i) {
  coef_fourier(m_data[, i], p)
})
log_lik_rf(m_coef, m_coord)
```

Index

* datasets

datasetCanada, [2](#)

coef_fourier, [2](#)

datasetCanada, [2](#)

fourier_b, [3](#)

geo_fkf, [3](#)

log_lik_rf, [5](#)

logLikMultiNorm, [4](#)