

Package ‘gglyph’

September 24, 2025

Title Network-Style Visualization of Directed Pairwise Relationships

Version 0.2.0

Description Create network-style visualizations of pairwise relationships using custom edge glyphs built on top of 'ggplot2'. The package supports both statistical and non-statistical data and allows users to represent directed relationships. This enables clear, publication-ready graphics for exploring and communicating relational structures in a wide range of domains. The method was first used in Abu-Akel et al. (2021) <[doi:10.1371/journal.pone.0245100](https://doi.org/10.1371/journal.pone.0245100)>. Code is released under the MIT License; included datasets are licensed under the Creative Commons Attribution 4.0 International (CC BY 4.0).

License MIT + file LICENSE

URL <https://valentinsvelev.github.io/gglyph/>

BugReports <https://github.com/valentinsvelev/gglyph/issues/>

Depends R (>= 4.1.0)

Imports dplyr, ggplot2, ggtext, grid, magrittr, rlang, stats, tibble, tidyverse, utils

Suggests ggthemes, haven, kableExtra, knitr, patchwork, psych, purrr, readr, rmarkdown, rstatix, spelling, svglite, testthat (>= 3.0.0), tidyverse, viridis, viridisLite

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

Language en-US

RoxygenNote 7.3.2

NeedsCompilation no

Author Valentin Velev [cre, aut],
Andreas Spitz [ctb]

Maintainer Valentin Velev <valentin.velev@uni-konstanz.de>

Repository CRAN

Date/Publication 2025-09-24 08:20:02 UTC

Contents

generate_mock_data	2
geom_glyph	3
pisa_2022	5
process_data_general	6
process_data_statistical	7
sipri_milex_1995_2023	8

Index	10
--------------	-----------

generate_mock_data *Generate mock data for gglyph::geom_glyph()*

Description

Generates custom mock data to be passed to gglyph::geom_glyph().

Usage

```
generate_mock_data(
  n_nodes = 5,
  n_edges = 7,
  n_groups = 1,
  statistical = FALSE,
  p_threshold = 0.05
)
```

Arguments

n_nodes	Number of nodes in the graph. Default is 5.
n_edges	Number of edges to generate. Default is 7.
n_groups	Number of groups (for faceting). Default is 1 (ungrouped).
statistical	If TRUE, generates mock p-values for edges. Default is FALSE.
p_threshold	The significance threshold for filtering edges. Default is 0.05.

Value

A data frame with mock data for nodes and edges.

Examples

```
# For non-grouped data
mock_data <- generate_mock_data(
  n_nodes = 5,
  n_edges = 7,
  n_groups = 1,
  statistical = FALSE,
```

```
p_threshold = 0.05
)

# For grouped data
mock_data <- generate_mock_data(
  n_nodes = 5,
  n_edges = 7,
  n_groups = 3,
  statistical = TRUE,
  p_threshold = 0.05
)
```

geom_glyph

Create a directed network-style graph

Description

Create a network-style graph that illustrates directed pairwise relationships using custom edges.

Usage

```
geom_glyph(
  mapping = NULL,
  data = NULL,
  edge_size = 1,
  edge_colour = "grey",
  edge_fill = NULL,
  edge_alpha = 1,
  node_size = 1,
  node_colour = "black",
  node_fill = NULL,
  node_alpha = 1,
  node_shape = 21,
  node_spacing = 1,
  label_size = 12,
  group_label_size = 13,
  legend_title = NULL,
  legend_subtitle = NULL,
  ...,
  stat = "identity",
  position = "identity",
  na.rm = FALSE,
  show.legend = TRUE,
  inherit.aes = TRUE
)
```

Arguments

<code>mapping</code>	Set of aesthetic mappings created by <code>aes()</code> . You must supply mapping if there is no plot mapping.
<code>data</code>	A DataFrame with preprocessed data from either <code>gglyph::preprocess_data_general()</code> or <code>gglyph::preprocess_data_statistical()</code> . To be passed to <code>ggplot2::ggplot()</code> .
<code>edge_size</code>	A numeric scaling factor indicating the size/width of the edges. Default is 1.
<code>edge_colour</code>	Color(s) of the edge outlines. Can be a single string (for non-grouped data) or a vector of strings or a function (for grouped data). Default is "grey".
<code>edge_fill</code>	Color(s) for the edge fill. Can be a single string, a vector of strings, or a color function. If <code>NULL</code> , defaults to <code>edge_colour</code> .
<code>edge_alpha</code>	A numeric value indicating the transparency of the edges. Default is 1.
<code>node_size</code>	A numeric value indicating the size of the nodes. Default is 8.
<code>node_colour</code>	Color(s) of the node outlines. Can be a single string (for non-grouped data) or a vector of strings or a function (for grouped data). Default is "black".
<code>node_fill</code>	Color for the node fill. If <code>NULL</code> , defaults to <code>node_colour</code> .
<code>node_alpha</code>	A numeric value indicating the transparency of the nodes. Default is 1.
<code>node_shape</code>	A numeric value specifying the shape of the nodes, following <code>ggplot2</code> 's shape specifications. Default is 21 (a circle with a border).
<code>node_spacing</code>	A numeric scaling factor for the distance between nodes. Values > 1 will push nodes further apart, while values < 1 will bring them closer. Default is 1.
<code>label_size</code>	A numeric value indicating the size of the node labels. Default is 12.
<code>group_label_size</code>	A numeric value indicating the size of group label. Default is 13.
<code>legend_title</code>	Title for the legend as a string.
<code>legend_subtitle</code>	Subtitle for the legend as a string.
<code>...</code>	Additional arguments passed to <code>ggplot2</code> layer.
<code>stat</code>	The statistical transformation to use on the data for this layer.
<code>position</code>	A position adjustment to use on the data for this layer.
<code>na.rm</code>	If <code>FALSE</code> , the default, missing values are removed with a warning. If <code>TRUE</code> , missing values are silently removed.
<code>show.legend</code>	Should this layer be included in the legends? Default is <code>TRUE</code> .
<code>inherit.aes</code>	If <code>FALSE</code> , overrides the default aesthetics, rather than combining with them. Default is <code>FALSE</code> .

Value

A `ggplot2` layer with custom network-based graph.

See Also

[ggplot2::ggsave\(\)](#)

Examples

```
# For non-grouped/-facetted plot
data <- gglyph::generate_mock_data(n_groups = 1)

ggplot2::ggplot(data = data) +
  gglyph::geom_glyph()

ggplot2::ggplot(data = data) +
  gglyph::geom_glyph(edge_colour = "purple", node_colour = "blue")

ggplot2::ggplot(data = data) +
  gglyph::geom_glyph(edge_colour = "purple", node_colour = "blue") +
  ggplot2::labs(title = "A beautiful glyph")

# For grouped/facetted plot
data <- gglyph::generate_mock_data(n_groups = 3)

ggplot2::ggplot(data = data) +
  gglyph::geom_glyph() +
  ggplot2::facet_wrap(~ group)

ggplot2::ggplot(data = data) +
  gglyph::geom_glyph(edge_colour = viridis::viridis, node_colour = viridis::viridis) +
  ggplot2::facet_wrap(~ group)

ggplot2::ggplot(data = data) +
  gglyph::geom_glyph(edge_colour = viridis::viridis, node_colour = viridis::viridis) +
  ggplot2::facet_wrap(~ group) +
  ggplot2::labs(title = "Beautiful glyphs")
```

pisa_2022

PISA 2022 data

Description

Results of pairwise t-tests (with Bonferroni correction) performed on a subset from the PISA 2022 data.

Usage

```
data(pisa_2022)
```

Format

A data frame with 492 rows and 3 variables:

from Category A of educational level (ISCED) attained by the parents of the respondent (character).
to Category B of educational level (ISCED) attained by the parents of the respondent (character).

`group` Country of the respondent (character).
`sig` p-value of the pairwise t-test (numeric).

Source

Data obtained from:

- OECD (2023). *PISA 2022 Database* [Data Set]. Zenodo. doi:10.5281/zenodo.13382904

Licensed under CC BY 4.0: <https://creativecommons.org/licenses/by/4.0/>

References

Additional reference(s) for further reading:

- OECD (2024). *PISA 2022 Technical Report*. OECD Publishing, Paris. doi:10.1787/01820d6d-en

Examples

```
data(pisa_2022)
head(pisa_2022)
```

`process_data_general` *Process general/non-statistical data*

Description

Prepare general/non-statistical data for plotting with `gglyph::geom_glyph()`.

Usage

```
process_data_general(data, from = "from", to = "to", group = NULL)
```

Arguments

<code>data</code>	A DataFrame or tibble containing the input data to be processed.
<code>from</code>	A string indicating the column name for the start nodes.
<code>to</code>	A string indicating the column name for the end nodes.
<code>group</code>	A string indicating the column name for the grouping variable.

Value

A DataFrame with the preprocessed data that is to be passed to `gglyph::geom_glyph()`.

Examples

```
data(sipri_milex_1995_2023)

# For non-grouped data
processed_data <- process_data_general(
  data = sipri_milex_1995_2023,
  from = "from",
  to = "to"
)

# For grouped data
processed_data <- process_data_general(
  data = sipri_milex_1995_2023,
  from = "from",
  to = "to",
  group = "group"
)
```

process_data_statistical
Process statistical data

Description

Prepare statistical data for plotting with `gglyph::geom_glyph()`.

Usage

```
process_data_statistical(
  data,
  from = "from",
  to = "to",
  group = NULL,
  sig = "sig",
  thresh = 0.05
)
```

Arguments

<code>data</code>	A DataFrame or tibble containing the input data to be processed.
<code>from</code>	A string indicating the column name for the start nodes.
<code>to</code>	A string indicating the column name for the end nodes.
<code>group</code>	A string indicating the column name for the grouping variable.
<code>sig</code>	A string indicating the column name for the significance level.
<code>thresh</code>	A single number indicating the significance threshold. Default is 0.05.

Value

A DataFrame with the preprocessed data that is to be passed to `gglyph::geom_glyph()`.

Examples

```
data(pisa_2022)

# For non-grouped data
processed_data <- process_data_statistical(
  data = pisa_2022,
  from = "from",
  to = "to",
  sig = "sig",
  thresh = 0.05
)

# For grouped data
processed_data <- process_data_statistical(
  data = pisa_2022,
  from = "from",
  to = "to",
  sig = "sig",
  group = "group",
  thresh = 0.05
)
```

`sipri_milex_1995_2023` *SIPRI Military Expenditure 1995-2023 data*

Description

A subset of the SIPRI Military Expenditure 1949-2023 data.

Usage

```
data(sipri_milex_1995_2023)
```

Format

A data frame with 77 rows and 3 variables:

`from` Name of country A (character).
`to` Name of country B (character).
`group` Year (numeric).

Source

Data obtained from:

- SIPRI (2025). *SIPRI Military Expenditure Database* [Data Set]. doi:10.55163/CQGC9685

Licensed under CC BY 4.0: <https://creativecommons.org/licenses/by/4.0/>

Examples

```
data(sipri_milex_1995_2023)
head(sipri_milex_1995_2023)
```

Index

* **dataset**
 pisa_2022, [5](#)
 sipri_milex_1995_2023, [8](#)

generate_mock_data, [2](#)
geom_glyph, [3](#)
ggplot2::ggsave(), [4](#)

 pisa_2022, [5](#)
 process_data_general, [6](#)
 process_data_statistical, [7](#)

 sipri_milex_1995_2023, [8](#)