

## Package ‘snem’

October 14, 2022

## Type Package

## Title EM Algorithm for Multivariate Skew-Normal Distribution with Overparametrization

Version 0.1.1

Date 2020-03-02

**Author** Toshihiro Abe <abetosh@ss.nanzan-u.ac.jp>, Hironori Fujisawa <fujisawa@ism.ac.jp>, Takayuki Kawashima <kawashima@c.titech.ac.jp>

**Maintainer** Takayuki Kawashima <kawashima@c.titech.ac.jp>

## Imports mvtnorm

**Description** Efficient estimation of multivariate skew-normal distribution in closed form.

**License** GPL (>= 2)

## Encoding UTF-8

**LazyData** true

**Suggests sn**

**RoxxygenNote** 7.0.1

## NeedsCompilation no

Repository CRAN

**Date/Publication** 2020-03-16 12:30:02 UTC

## R topics documented:

Index	3
-------	---

snem

*EM algorithm for multivariate skew normal distribution.*

## Description

EM algorithm in closed form.

## Usage

```
snem(
  x,
  eps = 0.9,
  iter.eps = 10^-6,
  stop.rule = c("parameter", "log-likelihood")
)
```

## Arguments

<code>x</code>	A data matrix. Each row is an observation vector.
<code>eps</code>	Weight parameter with $0 \leq \text{eps} < 1$ . Default is 0.9.
<code>iter.eps</code>	Convergence threshold. Default is $10^{-6}$ .
<code>stop.rule</code>	"parameter": The difference of the parameter is used as a stopping rule. "log-likelihood" The difference of the log-likelihood is used as a stopping rule.

## Details

The parameter `eps` is a tuning parameter which ensures that an initial covariance matrix is positive semi-definite.

## Value

Location parameter (`mu`), covariance matrix (`omega`), skewness parameter (`delta`), and another expression of skewness parameter (`lambda`).

## References

Abe, T., Fujisawa, H., and Kawashima, T. (2019) *EM algorithm using overparametrization for multivariate skew-normal distribution, in preparation.*

## Examples

```
library(sn)
data(ais, package="sn")
x <- ais[c("BMI")]
snem(x, stop.rule ="log-likelihood")
```

# **Index**

`snem`, 2