

Package ‘spatialwidget’

January 22, 2024

Type Package

Title Formats Spatial Data for Use in Htmlwidgets

Version 0.2.5

Date 2024-01-22

Description

Many packages use 'htmlwidgets' <<https://CRAN.R-project.org/package=htmlwidgets>> for interactive plotting of spatial data.

This package provides functions for converting R objects, such as simple features, into structures suitable for use in 'htmlwidgets' mapping libraries.

URL <https://symbolixau.github.io/spatialwidget/articles/spatialwidget.html>

License MIT + file LICENSE

Depends R (>= 3.3.0)

Encoding UTF-8

LazyData true

SystemRequirements C++14

Imports Rcpp

LinkingTo BH (>= 1.84.0), colourvalues (>= 0.3.9), geojsonsf (>= 2.0.3), geometries (>= 0.2.4), interleave (>= 0.1.2), jsonify (>= 1.2.2), rapidjsonr, Rcpp (>= 0.12.18), sfheaders (>= 0.4.4)

RoxxygenNote 7.2.3

Suggests colourvalues, covr, geojsonsf, jsonify, sfheaders, knitr, rmarkdown, testthat

VignetteBuilder knitr

NeedsCompilation yes

Author David Cooley [aut, cre]

Maintainer David Cooley <dcooley@symbolix.com.au>

Repository CRAN

Date/Publication 2024-01-22 14:10:02 UTC

R topics documented:

widget_arcs	2
widget_capitals	3
widget_line	3
widget_melbourne	4
widget_od	5
widget_point	6
widget_polygon	7
widget_roads	8

Index	9
--------------	----------

widget_arcs	<i>Origin Destination points between Sydney, Australia and other capitals cities</i>
--------------------	--

Description

A simple feature sf object with two sfc columns, "origin" and "destination"

Usage

```
widget_arcs
```

Format

A sf object with 199 observations and 6 variables

country_from origin country
capital_from origin capital
country_to destination country
capital_to destination capital
origin sfc geometry column
destination sfc geometry column

widget_capitals	<i>Capital cities for each country</i>
-----------------	--

Description

A simple feature sf object containing the coordinates of 200 capital cities in the world

Usage

```
widget_capitals
```

Format

A sf object with 200 observations and 4 variables

country country name

capital capital name

geometry sfc geometry column

widget_line	<i>Widget Line</i>
-------------	--------------------

Description

Converts an ‘sf’ object with LINESTRING geometries into JSON for plotting in an htmlwidget

Usage

```
widget_line(  
  data,  
  stroke_colour = NULL,  
  stroke_opacity = NULL,  
  stroke_width = NULL,  
  legend = TRUE,  
  json_legend = TRUE,  
  digits = 6  
)
```

Arguments

data	sf object
stroke_colour	string specifying column of sf to use for the stroke colour, or a single value to apply to all rows of data
stroke_opacity	string specifying column of sf to use for the stroke opacity, or a single value to apply to all rows of data
stroke_width	string specifying column of sf to use for the stroke width, or a single value to apply to all rows of data
legend	logical indicating if legend data will be returned
json_legend	logical indicating if the legend will be returned as json
digits	number of decimal places for rounding lon & lat coordinates. Default 6

Examples

```
## use default stroke options
l <- widget_line( widget_roads, legend = TRUE )
```

widget_melbourne *Melbourne*

Description

A simple feature sf object of Polygons for Melbourne and the surrounding area

Usage

widget_melbourne

Format

A data frame with 397 observations and 7 variables

SA2_NAME statistical area 2 name of the polygon

SA3_NAME statistical area 3 name of the polygon

AREASQKM area of the SA2 polygon

geometry sfc geometry column

Details

This data set is a subset of the Statistical Area Level 2 (SA2) ASGS Edition 2016 data released by the Australian Bureau of Statistics <https://www.abs.gov.au/>

The data is realeased under a Creative Commons Attribution 2.5 Australia licence <https://creativecommons.org/licenses/by/2.5/au/>

The data has been down-cast from MULTIPOLYGONS to POLYGONS.

`widget_od`*Widget OD*

Description

Converts an ‘sf‘ object with two POINT geometries into JSON for plotting in an htmlwidget

Usage

```
widget_od(  
  data,  
  origin,  
  destination,  
  fill_colour = NULL,  
  fill_opacity = NULL,  
  legend = TRUE,  
  json_legend = TRUE,  
  digits = 6  
)
```

Arguments

<code>data</code>	<code>sf</code> object
<code>origin</code>	string specifying the column of data containing the origin geometry
<code>destination</code>	string specifying the column of data containing the destination geometry
<code>fill_colour</code>	string specifying column of <code>sf</code> to use for the fill colour, or a single value to apply to all rows of data
<code>fill_opacity</code>	string specifying column of <code>sf</code> to use for the fill opacity, or a single value to apply to all rows of data
<code>legend</code>	logical indicating if legend data will be returned
<code>json_legend</code>	logical indicating if the legend will be returned as json
<code>digits</code>	number of decimal places for rounding lon & lat coordinates. Default 6

Examples

```
l <- widget_od( data = widget_arcs, origin = "origin", destination = "destination", legend = FALSE )
```

widget_point	<i>Widget Point</i>
--------------	---------------------

Description

Converts an ‘sf‘ object with POINT geometries into JSON for plotting in an htmlwidget

Usage

```
widget_point(
  data,
  fill_colour = NULL,
  fill_opacity = NULL,
  lon = NULL,
  lat = NULL,
  legend = TRUE,
  json_legend = TRUE,
  digits = 6
)
```

Arguments

data	<code>sf</code> object
fill_colour	string specifying column of <code>sf</code> to use for the fill colour, or a single value to apply to all rows of data
fill_opacity	string specifying column of <code>sf</code> to use for the fill opacity, or a single value to apply to all rows of data
lon	string specifying the column of data containing the longitude. Ignored if using an <code>sf</code> object
lat	string specifying the column of data containing the latitude. Ignored if using an <code>sf</code> object
legend	logical indicating if legend data will be returned
json_legend	logical indicating if the legend will be returned as json
digits	number of decimal places for rounding lon & lat coordinates. Default 6

Examples

```
1 <- widget_point( data = widget_capitals, legend = FALSE )
```

widget_polygon	<i>Widget Polygon</i>
----------------	-----------------------

Description

Converts an ‘sf‘ object with POLYGON geometries into JSON for plotting in an htmlwidget

Usage

```
widget_polygon(  
  data,  
  stroke_colour = NULL,  
  stroke_opacity = NULL,  
  stroke_width = NULL,  
  fill_colour = NULL,  
  fill_opacity = NULL,  
  legend = TRUE,  
  json_legend = TRUE,  
  digits = 6  
)
```

Arguments

data	sf object
stroke_colour	string specifying column of sf to use for the stroke colour, or a single value to apply to all rows of data
stroke_opacity	string specifying column of sf to use for the stroke opacity, or a single value to apply to all rows of data
stroke_width	string specifying column of sf to use for the stroke width, or a single value to apply to all rows of data
fill_colour	string specifying column of sf to use for the fill colour, or a single value to apply to all rows of data
fill_opacity	string specifying column of sf to use for the fill opacity, or a single value to apply to all rows of data
legend	logical indicating if legend data will be returned
json_legend	logical indicating if the legend will be returned as json
digits	number of decimal places for rounding lon & lat coordinates. Default 6

Examples

```
1 <- widget_polygon( widget_melbourne, legend = FALSE )  
1 <- widget_polygon( widget_melbourne, fill_colour = "AREASQKM16", legend = TRUE )
```

`widget_roads` *Roads in central Melbourne*

Description

A simple feature sf object of roads in central Melbourne

Usage

`widget_roads`

Format

An sf and data frame object with 18286 observations and 16 variables

Details

Obtained from <https://www.data.gov.au/> and distributed under the Creative Commons 4 License <https://creativecommons.org/licenses/by/4.0/>

Index

* datasets

- widget_arcs, [2](#)
- widget_capitals, [3](#)
- widget_melbourne, [4](#)
- widget_roads, [8](#)

- widget_arcs, [2](#)
- widget_capitals, [3](#)
- widget_line, [3](#)
- widget_melbourne, [4](#)
- widget_od, [5](#)
- widget_point, [6](#)
- widget_polygon, [7](#)
- widget_roads, [8](#)