

# Package ‘survC’

October 29, 2025

**Title** Survival Model Validation Utilities

**Version** 0.1.0

**Author** Minhyuk Kim [aut, cre] (ORCID: <<https://orcid.org/0009-0000-8083-5099>>)

**Maintainer** Minhyuk Kim <[mhkim@zarathu.com](mailto:mhkim@zarathu.com)>

**Description** Provides helper functions to compute linear predictors, time-dependent ROC curves, and Harrell's concordance index for Cox proportional hazards models as described in Therneau (2024) <<https://CRAN.R-project.org/package=survival>>, Therneau and Grambsch (2000, ISBN:0-387-98784-3), Hung and Chiang (2010) <[doi:10.1002/cjs.10046](https://doi.org/10.1002/cjs.10046)>, Uno et al. (2007) <[doi:10.1198/016214507000000149](https://doi.org/10.1198/016214507000000149)>, Blanche, Dartigues, and Jacqmin-Gadda (2013) <[doi:10.1002/sim.5958](https://doi.org/10.1002/sim.5958)>, Blanche, Latouche, and Viallon (2013) <[doi:10.1007/978-1-4614-8981-8\\_11](https://doi.org/10.1007/978-1-4614-8981-8_11)>, Harrell et al. (1982) <[doi:10.1001/jama.1982.03320430047030](https://doi.org/10.1001/jama.1982.03320430047030)>, Peto and Peto (1972) <[doi:10.2307/2344317](https://doi.org/10.2307/2344317)>, Schemper and Uno et al. (2011) <[doi:10.1002/sim.4154](https://doi.org/10.1002/sim.4154)>.

**Imports** survival, stats, timeROC, officer, rvg

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**URL** <https://newjoseph.github.io/survC/>

**Suggests** magrittr, jstable, testthat (>= 3.0.0)

**Config/testthat/edition** 3

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2025-10-29 19:40:02 UTC

## Contents

calc_risk_score . . . . .	2
cindex_calc . . . . .	3
tdroc_calc . . . . .	3
validation_report . . . . .	4

<b>Index</b>	<b>5</b>
--------------	----------

---

calc_risk_score	<i>Compute risk scores from a fitted survival model</i>
-----------------	---

---

### Description

This helper wraps `stats::predict()` for `coxph` objects so that package users can easily obtain linear predictors (default) or risk scores to feed into downstream metrics such as time-dependent ROC or Harrell's C-index.

### Usage

```
calc_risk_score(model, data = NULL, type = "lp", ...)
```

### Arguments

<code>model</code>	A fitted <code>coxph</code> object.
<code>data</code>	Optional dataset on which to score the model. Defaults to the training data stored within <code>model</code> .
<code>type</code>	Scale of the predictions to return. Either "lp" (linear predictor, the default) or "risk". If NULL or omitted, "lp" is used.
<code>...</code>	Additional arguments passed to <code>stats::predict()</code> .

### Value

A numeric vector containing the requested risk scores.

### Examples

```
if (requireNamespace("survival", quietly = TRUE)) {  
  fit <- survival::coxph(survival::Surv(time, status) ~ age, data = survival::lung)  
  # Linear predictor on the training data  
  calc_risk_score(fit)  
  
  # Risk scale predictions on new data  
  calc_risk_score(fit, survival::lung, type = "risk")  
}
```

---

cindex_calc	<i>Calculate Harrell's C-index with 95% CI</i>
-------------	--

---

**Description**

Calculate Harrell's C-index with 95% CI

**Usage**

```
cindex_calc(model, newdata = NULL, digits = 3)
```

**Arguments**

model	a 'coxph' object
newdata	optional validation dataset
digits	number of decimal places for rounding (default 3).

**Value**

numeric vector of C-index (lower, upper)

**Examples**

```
library(survival)
fit <- coxph(Surv(time, status) ~ age + sex, data = lung)
cindex_calc(fit)
```

---

tdroc_calc	<i>Calculate time-dependent ROC and AUC</i>
------------	---

---

**Description**

Calculate time-dependent ROC and AUC

**Usage**

```
tdroc_calc(time, status, marker, times)
```

**Arguments**

time	Survival time vector
status	Event indicator (1 = event, 0 = censor)
marker	Risk score or linear predictor
times	Vector of time points (e.g., c(365, 730, 1095))

**Value**

A data.frame with AUCs for each time

---

validation_report	<i>Generate survival model validation report</i>
-------------------	--

---

**Description**

Generate survival model validation report

**Usage**

```
validation_report(  
  train_data,  
  val_data,  
  model,  
  time_col,  
  status_col,  
  times = c(365, 730, 1095),  
  time_unit = "days",  
  output = NULL  
)
```

**Arguments**

train_data	training dataset containing survival outcomes.
val_data	validation dataset containing survival outcomes.
model	fitted 'coxph'
time_col	name of the survival time column present in both datasets
status_col	name of the event indicator column present in both datasets
times	follow-up timepoints
time_unit	character label for the time axis (default = "days")
output	file path (.pptx or .html). Defaults to a temporary file.

**Value**

Invisibly returns the file path containing the validation report

# Index

`calc_risk_score`, 2  
`cindex_calc`, 3  
`stats::predict()`, 2  
`tdroc_calc`, 3  
`validation_report`, 4