

Package ‘tfrmt’

October 15, 2024

Title Applies Display Metadata to Analysis Results Datasets

Version 0.1.3

Description Creates a framework to store and apply display metadata to Analysis Results Datasets (ARDs). The use of 'tfrmt' allows users to define table format and styling without the data, and later apply the format to the data.

Language en-GB

License Apache License (>= 2)

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

Suggests covr, testthat (>= 3.0.0), knitr, rmarkdown, patchwork,
survival, ggfortify

Imports magrittr, dplyr, purrr, rlang, stringr, stringi, tidyverse, gt (>= 0.6.0), tidyselect,forcats, tibble, ggplot2, jsonlite, glue

Config/testthat/edition 3

URL <https://GSK-Biostatistics.github.io/tfrmt/>,
<https://github.com/GSK-Biostatistics/tfrmt>

BugReports <https://github.com/GSK-Biostatistics/tfrmt/issues>

Depends R (>= 2.10)

NeedsCompilation no

Author Becca Krouse [aut, cre],
Christina Fillmore [aut] (<<https://orcid.org/0000-0003-0595-2302>>),
GlaxoSmithKline Research & Development Limited [cph, fnd],
Atorus Research LLC [cph, fnd],
Ellis Hughes [aut] (<<https://orcid.org/0000-0003-0637-4436>>),
Karima Ahmad [aut] (<<https://orcid.org/0000-0002-8784-1712>>),
Shannon Haughton [aut]

Maintainer Becca Krouse <becca.z.krouse@gsk.com>

Repository CRAN

Date/Publication 2024-10-15 21:30:02 UTC

Contents

apply_fmt	2
big_n_structure	4
body_plan	5
col_plan	6
col_style_plan	8
col_style_structure	9
data_ae	10
data_demog	11
data_efficacy	11
data_labs	12
display_row_frmcts	13
display_val_frmcts	14
element_block	15
element_row_grp_loc	16
footnote_plan	17
footnote_structure	18
frm	19
frm_structure	21
is_frm	22
json_to_tfrm	23
layer_tfrm	24
make_mock_data	25
page_plan	25
page_structure	26
param_set	27
print_mock_gt	28
print_to_ggplot	29
print_to_gt	30
row_grp_plan	31
row_grp_structure	32
tfrm	33
tfrm_n_pct	37
tfrm_sigdig	38
tfrm_to_json	39
update_group	40

Index

42

apply_fmt	<i>Apply formatting</i>
-----------	-------------------------

Description

Apply formatting

Usage

```
apply_fmt(fmt_def, .data, value, mock = FALSE, ...)

## S3 method for class 'fmt'
apply_fmt(fmt_def, .data, value, mock = FALSE, ...)

## S3 method for class 'fmt_combine'
apply_fmt(
  fmt_def,
  .data,
  value,
  mock = FALSE,
  param,
  column,
  label,
  group,
  ...
)

## S3 method for class 'fmt_when'
apply_fmt(fmt_def, .data, value, mock = FALSE, ...)
```

Arguments

fmt_def	formatting to be applied
.data	data, but only what is getting changed
value	value symbol should only be one
mock	Logical value is this is for a mock or not. By default FALSE
...	additional arguments for methods
param	param column as a quosure
column	column columns as a list of quosures
label	label column as a quosure
group	group column as a list of quosures

Value

formatted dataset

Examples

```
library(tibble)
library(dplyr)
# Set up data
df <- tibble(x = c(20.12,34.54,12.34))

apply_fmt(
  fmt_def = fmt("XX.X"),
```

```
.data=df,
value=quo(x))
```

big_n_structure *Big N Structure*

Description

Big N structure allows you to specify which values should become the subject totals ("big N" values) and how they should be formatted in the table's column labels. Values are specified by providing the value(s) of the `param` column for which the values are big N's. This will remove these from the body of the table and place them into columns matching the values in the `column` column(s). The default formatting is `N = xx`, on its own line, but that can be changed by providing a different `frmt()` to `n_frmt`

Usage

```
big_n_structure(param_val, n_frmt = frmt("\nN = xx"), by_page = FALSE)
```

Arguments

<code>param_val</code>	row value(s) of the parameter column for which the values are big n's
<code>n_frmt</code>	<code>frmt()</code> to control the formatting of the big n's
<code>by_page</code>	Option to include different big Ns for each group-defined set of pages (defined by any variables set to ".default" in the <code>page_plan</code>). Default is FALSE, meaning only the overall Ns are applied

Value

`big_n_structure` object

See Also

[Link to related article](#)

body_plan*Table Body Plan*

Description

Define the formatting of the body contents of the table through a series of frmt_structures. Structures get applied in order from bottom up, so the last added structure is the first applied.

Usage

```
body_plan(...)
```

Arguments

...	list of frmt_structures defining the body formatting
-----	--

Value

body_plan object

See Also

[frmt_structure\(\)](#) defines which rows the formats will be applied to, and [frmt\(\)](#), [frmt_combine\(\)](#), and [frmt_when\(\)](#) define the format semantics.

[Link to related article](#)

Examples

```
tfrmt_spec<- tfrmt(
  title = "Table Title",
  body_plan = body_plan(
    frmt_structure(
      group_val = c("group1"),
      label_val = ".default",
      frmt("XXX")
    )
  )
)
```

col_plan*Define the Column Plan & Span Structures*

Description

Using <[tidy-select](#)> expressions and a series span_structures, define the order of the columns. The selection follows "last selected" principals, meaning columns are moved to the *last* selection as opposed to preserving the first location.

Usage

```
col_plan(..., .drop = FALSE)

span_structure(...)
```

Arguments

...	For a col_plan and span_structure, < tidy-select > arguments, unquoted expressions separated by commas, and span_structures. span_structures must have the arguments named to match the name the column in the input data has to identify the correct columns. See the examples
.drop	Boolean. Should un-listed columns be dropped from the data. Defaults to FALSE.

Details**Column Selection:**

When col_plan gets applied and is used to create the output table, the underlying logic sorts out which column specifically is being selected. If a column is selected twice, the *last* instance in which the column is selected will be the location it gets rendered.

Avoid beginning the col_plan() column selection with a deselection (i.e. col_plan(-col1), col_plan(-starts_with("value"))). This will result in the table preserving all columns not "de-selected" in the statement, and the order of the columns not changed. It is preferred when creating the col_plan() to identify all the columns planned on preserving in the order they are wished to appear, or if <[tidy-select](#)> arguments - such as [everything](#)- are used, identify the de-selection after the positive-selection.

Alternatively, once the gt table is produced, use the [cols_hide](#) function to remove un-wanted columns.

Value

col_plan object
span_structure object

Images

Here are some example outputs:

See Also

[Link to related article](#)

Examples

```
library(dplyr)

## select col_1 as the first column, remove col_last, then create spanning
## structures that have multiple levels
##
## examples also assume the tfrmt has the column argument set to c(c1, c2, c3)
##
spanning_col_plan_ex <- col_plan(
  col_1,
  -col_last,
  span_structure(
    c1 = "Top Label Level 1",
    c2 = "Second Label Level 1.1",
    c3 = c(col_3, col_4)
  ),
  span_structure(
    c1 = "Top Label Level 1",
    c2 = "Second Label Level 1.2",
    c3 = starts_with("B")
  ),
  span_structure(
    c1 = "Top Label Level 1",
    c3 = col_5
  ),
  span_structure(
    c2 = "Top Label Level 2",
    c3 = c(col_6, col_7)
  )
)

## select my_col_1 as the first column, then
## rename col_2 to new_col_1 and put as the
## second column, then select the rest of the columns
renaming_col_plan_ex <- col_plan(
  my_col_1,
  new_col_1 = col_2,
  everything()
)

renaming_col_plan_ex2 <- col_plan(
  my_col_1,
  new_col_1 = col_2,
  span_structure(
    c1 = c(`My Favorite span name` = "Top Label Level 1"),
    c3 = c(`the results column` = col_5)
  )
)
```

col_style_plan*Column Style Plan*

Description

Define how the columns of the table body should be aligned, whether left, right or on a specific character(s).

Usage

```
col_style_plan(...)
```

Arguments

...	series of col_style_structure objects
-----	---------------------------------------

Value

```
col_style_plan object
```

See Also

[col_style_structure\(\)](#) for more information on how to specify how to and which columns to align.

[Link to related article](#)

Examples

```
plan <- col_style_plan(  
  col_style_structure(col = "my_var", align = "left", width = 100),  
  col_style_structure(col = vars(four), align = "right"),  
  col_style_structure(col = vars(two, three), align = c(".", ",", " ")))  
)
```

col_style_structure *Column Style Structure*

Description

Column Style Structure

Usage

```
col_style_structure(  
  col,  
  align = NULL,  
  type = c("char", "pos"),  
  width = NULL,  
  ...  
)
```

Arguments

col	Column value to align on from <code>column</code> variable. May be a quoted or unquoted column name, a tidyselect semantic, or a <code>span_structure</code> .
align	Alignment to be applied to column. Defaults to <code>left</code> alignment. See details for acceptable values.
type	Type of alignment: <code>"char"</code> or <code>"pos"</code> , for character alignment (default), and positional alignment, respectively. Positional alignment allows for aligning over multiple positions in the column.
width	Width to apply to the column in number of characters. Acceptable values include a numeric value, or a character string of a number.
...	These dots are for future extensions and must be empty

Details

Supports alignment and width setting of data value columns (values found in the `column` column). Row group and label columns are left-aligned by default. Acceptable input values for `align` differ by `type = "char"` or `"pos"`:

Character alignment (`type = "char"`):

- `"left"` for left alignment
- `"right"` for right alignment
- supply a vector of character(s) to align on. If more than one character is provided, alignment will be based on the first occurrence of any of the characters. For alignment based on white space, leading white spaces will be ignored.

Positional alignment (`type = "pos"`):

supply a vector of strings covering all formatted cell values, with numeric values represented as `x`'s. These values can be created manually or obtained by utilizing the helper `display_val_fmts()`.

Alignment positions will be represented by vertical bars. For example, with starting values: c("12.3", "(5%)", "2.35 (10.23)") we can align all of the first sets of decimals and parentheses by providing align = c("xx.l.x", "|(x%)", "xl.xx |")

Value

col_style_structure object

See Also

[col_style_plan\(\)](#) for more information on how to combine col_style_structure()'s together to form a plan.

[Link to related article](#)

Examples

```
plan <- col_style_plan(
  col_style_structure(col = "my_var",
    align = c("xx| |(xx%)",
              "xx|.x |(xx.x - xx.x)"),
    type = "pos", width = 100),
  col_style_structure(col = vars(four), align = "right", width = 200),
  col_style_structure(col = vars(two, three), align = c(".", ", ", " ")),
  col_style_structure(col = c(two, three), width = 25),
  col_style_structure(col = two, width = 25),
  col_style_structure(col = span_structure(span = value, col = val2),
    width = 25)
)
```

data_ae

Adverse Events Analysis Results Data

Description

A dataset containing the results needed for an AE table. Using the CDISC pilot data.

Usage

data_ae

Format

A data frame with 2,794 rows and 8 variables:

AEBODSYS highest level row labels: System Organ Class

AETERM more specific row labels: Preferred Term

col2 higher level column names (spanners)

col1 lower level column names
param parameter to explain each value
value values to put in a table
ord1 controls ordering
ord2 more ordering controls

data_demog*Demography Analysis Results Data*

Description

A dataset containing the results needed for a demography table. Using the CDISC pilot data.

Usage

```
data_demog
```

Format

A data frame with 386 rows and 7 variables:

rowlbl1 highest level row labels
rowlbl2 more specific row labels
param parameter to explain each value
grp grouping column used to distinguish continuous and categorical
ord1 controls ordering
ord2 more ordering controls
column column names
value values to put in a table

data_efficacy*Efficacy Analysis Results Data*

Description

A dataset containing the results needed for an Efficacy table. Using the CDISC pilot data for ADAS-Cog(11).

Usage

```
data_efficacy
```

Format

A data frame with 70 rows and 7 variables:

group highest level row labels
label more specific row labels
column column names
param parameter to explain each value
value values to put in a table
ord1 controls ordering
ord2 more ordering controls

data_labs

Labs Analysis Results Data

Description

A dataset containing the results needed for an labs results table. Using the CDISC pilot data.

Usage

`data_labs`

Format

A data frame with 4,950 rows and 7 variables:

group1 highest level row labels: Lab value class
group2 more specific row labels: Lab parameter
rowlbl most specific row labels: Study visit
col1 higher level column names (spanners)
col2 lower level column names
param parameter to explain each value
value values to put in a table
ord1 controls ordering
ord2 more ordering controls
ord3 more ordering controls

<code>display_row_frmts</code>	<i>Display formatting applied to each row</i>
--------------------------------	---

Description

Used when debugging formatting, it is an easy way to allow you to see which formats are applied to each row in your dataset.

Used when debugging formatting, it is an easy way to allow you to see which formats are applied to each row in your dataset.

Usage

```
display_row_frmts(tfrmt, .data, convert_to_txt = TRUE)

display_row_frmts(tfrmt, .data, convert_to_txt = TRUE)
```

Arguments

<code>tfrmt</code>	tfrmt object to apply to the data
<code>.data</code>	Data to apply the tfrmt to
<code>convert_to_txt</code>	Logical value converting formatting to text, by default TRUE

Value

formatted tibble	
formatted tibble	

Examples

```
library(dplyr)
library(tidyr)

tfrmt_spec <- tfrmt(
  label = label,
  column = column,
  param = param,
  value=value,
  body_plan = body_plan(
    frmt_structure(group_val = ".default", label_val = ".default",
      frmt_combine(
        "{count} {percent}",
        count = frmt("xxx"),
        percent = frmt_when("==100" ~ frmt(""),
          "==0" ~ "",
          "TRUE" ~ frmt("(xx.x%)))))))
  ))

# Create data
```

```

df <- crossing(label = c("label 1", "label 2"),
               column = c("placebo", "trt1"),
               param = c("count", "percent")) %>%
  mutate(value=c(24,19,2400/48,1900/38,5,1,500/48,100/38))

display_row_frmts(tfrmt_spec,df)
library(dplyr)
library(tidyr)

tfrmt_spec <- tfrmt(
  label = label,
  column = column,
  param = param,
  value=value,
  body_plan = body_plan(
    frmt_structure(group_val = ".default", label_val = ".default",
                   frmt_combine(
                     "{count} {percent}",
                     count = frmt("xxx"),
                     percent = frmt_when("==100"~ frmt(""),
                                         "==0"~ "",
                                         "TRUE" ~ frmt("(xx.x%)))))))
  ))

# Create data
df <- crossing(label = c("label 1", "label 2"),
               column = c("placebo", "trt1"),
               param = c("count", "percent")) %>%
  mutate(value=c(24,19,2400/48,1900/38,5,1,500/48,100/38))

display_row_frmts(tfrmt_spec,df)

```

display_val_frmts *Display formatted values*

Description

A helper for creating positional-alignment specifications for the col_style_plan. Returns all unique formatted values to appear in the column(s) specified. Numeric values are represented by x's.

Usage

```
display_val_frmts(tfrmt, .data, mock = FALSE, col = NULL)
```

Arguments

tfrmt	tfrmt object to apply to the data
.data	Data to apply the tfrmt to
mock	Mock table? TRUE or FALSE (default)

col	Column value to align on from <code>column</code> variable. May be a quoted or unquoted column name, a tidyselect semantic, or a <code>span_structure</code> .
-----	--

Value

text representing character vector of formatted values to be copied and modified in the `col_style_plan`

Examples

```
tf_spec <- tfrmt(
  group = c(rowlbl1, grp),
  label = rowlbl2,
  column = column,
  param = param,
  value = value,
  sorting_cols = c(ord1, ord2),
  body_plan = body_plan(
    frmt_structure(group_val = ".default", label_val = ".default", frmt_combine("{n} ({pct} %)",
      n = frmt("xxx"),
      pct = frmt("xx.x"))),
    frmt_structure(group_val = ".default", label_val = "n", frmt("xxx")),
    frmt_structure(group_val = ".default", label_val = c("Mean", "Median", "Min", "Max"),
      frmt("xxx.x")),
    frmt_structure(group_val = ".default", label_val = "SD", frmt("xxx.xx")),
    frmt_structure(group_val = ".default", label_val = ".default",
      p = frmt_when(">0.99" ~ ">0.99",
        "<0.15" ~ "<0.15",
        TRUE ~ frmt("x.xxx", missing = "")))
  )))
display_val_frmnts(tf_spec, data_demog, col = vars(everything()))
display_val_frmnts(tf_spec, data_demog, col = "p-value")
```

Description

Element block

Usage

```
element_block(post_space = c(NULL, " ", "-"), fill = TRUE)
```

Arguments

post_space	Values to show in a new line created after the group block
fill	Whether to recycle the value of <code>post_space</code> to match width of the data. Defaults to <code>TRUE</code>

Value

element block object

See Also

[row_grp_plan\(\)](#) for more details on how to group row group structures, [row_grp_structure\(\)](#) for more details on how to specify row group structures, [element_row_grp_loc\(\)](#) for more details on how to specify whether row titles span the entire table or collapse.

Examples

```
tfrmt_spec <- tfrmt(
  group = grp1,
  label = label,
  param = param,
  value = value,
  column = column,
  row_grp_plan = row_grp_plan(
    row_grp_structure(group_val = ".default", element_block(post_space = "  "))
  ),
  body_plan = body_plan(
    frmt_structure(group_val = ".default", label_val = ".default", frmt("xx"))
  )
)
```

element_row_grp_loc *Element Row Group Location*

Description

Element Row Group Location

Usage

```
element_row_grp_loc(
  location = c("indented", "spanning", "column", "noprint", "gtdefault"),
  indent = "  "
)
```

Arguments

location	Location of the row group labels. Specifying 'indented' combines all group and label variables into a single column with each sub-group indented under its parent. 'spanning' and 'column' retain the highest level group variable in its own column and combine all remaining group and label variables into a single column with sub-groups indented. The highest level group column will either be printed as a spanning header or in its own column in the gt. The 'noprint' option allows the user to suppress group values from being printed. Finally, the
-----------------	---

'gtdefault' option allows users to use the 'gt' defaults for styling multiple group columns.

indent	A string of the number of spaces you want to indent
--------	---

Value

element_row_grp_loc object

Images

Here are some example outputs:

See Also

[row_grp_plan\(\)](#) for more details on how to group row group structures, [row_grp_structure\(\)](#) for more details on how to specify row group structures, [element_block\(\)](#) for more details on how to specify spacing between each group.

[Link to related article](#)

Examples

```
tfrmt_spec <- tfrmt(
  group = c(grp1, grp2),
  label = label,
  param = param,
  value = value,
  column = column,
  row_grp_plan = row_grp_plan(label_loc = element_row_grp_loc(location = "noprint")),
  body_plan = body_plan(
    frmt_structure(group_val = ".default", label_val = ".default", frmt("xx"))
  )
)
```

Description

Defining the location and content of footnotes with a series of footnote structures. Each structure is a footnote and can be applied in multiple locations.

Usage

```
footnote_plan(..., marks = c("numbers", "letters", "standard", "extended"))
```

Arguments

...	a series of <code>footnote_structure()</code> separated by commas
marks	type of marks required for footnotes, properties inherited from <code>tab_footnote</code> in 'gt'. Available options are "numbers", "letters", "standard" and "extended" (standard for a traditional set of 4 symbols, extended for 6 symbols). The default option is set to "numbers".

Value

footnote plan object

Examples

```
# Adds a footnote indicated by letters rather than numbers to Group 1
footnote_plan <- footnote_plan(
  footnote_structure(footnote_text = "Source Note", group_val = "Group 1"),
  marks="letters")

# Adds a footnote to the 'Placebo' column
footnote_plan <- footnote_plan(
  footnote_structure(footnote_text = "footnote", column_val = "Placebo"),
  marks="numbers")
```

`footnote_structure` *Footnote Structure*

Description

Footnote Structure

Usage

```
footnote_structure(
  footnote_text,
  column_val = NULL,
  group_val = NULL,
  label_val = NULL
)
```

Arguments

footnote_text	string with text for footnote
column_val	string or a named list of strings which represent the column to apply the footnote to
group_val	string or a named list of strings which represent the value of group to apply the footnote to
label_val	string which represents the value of label to apply the footnote to

Value

footnote structure object

Examples

```
# Adds a source note aka a footnote without a symbol in the table
footnote_structure <- footnote_structure(footnote_text = "Source Note")

# Adds a footnote to the 'Placebo' column
footnote_structure <- footnote_structure(footnote_text = "Text",
                                         column_val = "Placebo")

# Adds a footnote to either 'Placebo' or 'Treatment groups' depending on which
# which is last to appear in the column vector
footnote_structure <- footnote_structure(footnote_text = "Text",
                                         column_val = list(col1 = "Placebo", col2= "Treatment groups"))

# Adds a footnote to the 'Adverse Event' label
footnote_structure <- footnote_structure("Text", label_val = "Adverse Event")
```

Description

These functions provide an abstracted way to approach to define formatting of table contents. By defining in this way, the formats can be layered to be more specific and general cell styling can be done first.

`frmt()` is the base definition of a format. This defines spacing, rounding, and missing behaviour.

`frmt_combine()` is used when two or more rows need to be combined into a single cell in the table. Each of the rows needs to have a defined `frmt()` and need to share a label.

`frmt_when()` is used when a rows format behaviour is dependent on the value itself and is written similarly to `dplyr::case_when()`. The left hand side of the equation is a "TRUE"for the default case or the right hand side of a boolean expression ">50".

Usage

```
frmt(expression, missing = NULL, scientific = NULL, transform = NULL, ...)

frmt_combine(expression, ..., missing = NULL)

frmt_when(..., missing = NULL)
```

Arguments

expression	this is the string representing the intended format. See details: expression for more a detailed description.
missing	when a value is missing that is intended to be formatted, what value to place. See details: missing for more a detailed description.
scientific	a string representing the intended scientific notation to be appended to the expression. Ex. "e^XX" or "x10^XX".
transform	this is what should happen to the value prior to formatting, It should be a formula or function. Ex. ~.*100if you want to convert a percent from a decimal prior to rounding
...	See details: ... for a detailed description.

Details

expression:

- `frmt()` All numbers are represented by "x". Any additional character are printed as-is. If additional X's present to the left of the decimal point than the value, they will be represented as spaces.
- `frmt_combine()` defines how the parameters will be combined as a `glue::glue()` statement. Parameters need to be equal to the values in the param column and defined in the expression as "{param1} {param2}".

missing:

- `frmt()` Value to enter when the value is missing. When NULL, the value is "".
- `frmt_combine()` defines how when all values to be combined are missing. When NULL the value is "".

...:

- `frmt()` These dots are for future extensions and must be empty.
- `frmt_combine()` accepts named arguments defining the `frmt()` to be applied to which parameters before being combined.
- `frmt_when()` accepts a series of equations separated by commas, similar to `dplyr::case_when()`. The left hand side of the equation is a "TRUE" for the default case or the right hand side of a boolean expression ">50". The right hand side of the equation is the `frmt()` to apply when the left side evaluates to TRUE.

Value

frmt object

See Also

`body_plan()` combines the frmt_structures to be applied to the table body, and `frmt_structure()` defines which rows the formats will be applied to.

[Link to related article](#)

Examples

```

frmt("XXX %")

frmt("XX.XXX")

frmt("xx.xx", scientific = "x10^xx")

frmt_combine(
  "{param1} {param2}",
  param1 = frmt("XXX %"),
  param2 = frmt("XX.XXX")
)

frmt_when(
  ">3" ~ frmt("(X.X%"),
  "<=3" ~ frmt("Undetectable")
)

frmt_when(
  "==100"~ frmt(""),
  "==0"~ "",
  "TRUE" ~ frmt("(XXX.X%")
)

```

frmt_structure *Format Structure Object*

Description

Function needed to create a `frmt_structure` object, which is a building block of `body_plan()`. This specifies the rows the format will be applied to.

Usage

```
frmt_structure(group_val = ".default", label_val = ".default", ...)
```

Arguments

<code>group_val</code>	A string or a named list of strings which represent the value of group should be when the given <code>frmt</code> is implemented
<code>label_val</code>	A string which represent the value of label should be when the given <code>frmt</code> is implemented
<code>...</code>	either a <code>frmt()</code> , <code>frmt_combine()</code> , or a <code>frmt_when()</code> object. This can be named to also specify the parameter value

Value

`frmt_structure` object

Images

Here are some example outputs:

See Also

`body_plan()` combines the `frmt_structures` to be applied to the table body, and `frmt()`, `frmt_combine()`, and `frmt_when()` define the format semantics.

[Link to related article](#)

Examples

```
sample_structure <- frmt_structure(
  group_val = c("group1"),
  label_val = ".default",
  frmt("XXX")
)
## multiple group columns
sample_structure <- frmt_structure(
  group_val = list(grp_col1 = "group1", grp_col2 = "subgroup3"),
  label_val = ".default",
  frmt("XXX")
)
```

is_fmt

Check if input is a frmt

Description

Check if input is a `frmt`
 Check if input is a `frmt_combine`
 Check if input is a `frmt_when`
 Check if input is a `frmt_structure`
 Check if input is a `row_grp_structure`

Usage

```
is_fmt(x)

is_fmt_combine(x)

is_fmt_when(x)

is_fmt_structure(x)

is_row_grp_structure(x)
```

Arguments

x	Object to check
---	-----------------

Value

'TRUE' if yes, 'FALSE' if no

Examples

```
x1 <- frmt("XXX.XX")
is_frmt(x1)

x2 <- frmt_combine("XXX %", "XX,XXX")
is_frmt_combine(x2)

x2 <- frmt_when(
  ">3" ~ frmt("(X.X%)"),
  "<=3" ~ frmt("Undetectable")
)
is_frmt_when(x2)

x3 <- frmt_structure(
  group_val = c("group1"),
  label_val = ".default",
  frmt("XXX")
)
is_frmt_structure(x3)

x4 <- row_grp_structure(group_val = c("A", "C"), element_block(post_space = "---"))
is_row_grp_structure(x4)
```

json_to_tfrmt

json to tfrmt

Description

Reader to read JSON files/objects into tfrmt objects

Usage

```
json_to_tfrmt(path = NULL, json = NULL)
```

Arguments

path	location of the json file to read in
json	json object to read in. By default this is null. This function will read in json object preferentially. So if both a path and a json object are supplied the json object will be read in.

`layer_tfrm`*Layer tfrm objects together*

Description

Provide utility for layering tfrm objects together. If both tfrm's have values, it will preferentially choose the second tfrm by default. This is an alternative to piping together tfrm's

Usage

```
layer_tfrm(x, y, ..., join_body_plans = TRUE)
```

Arguments

<code>x, y</code>	tfrm objects that need to be combined
<code>...</code>	arguments passed to <code>layer_tfrm_arg</code> functions for combining different tfrm elements
<code>join_body_plans</code>	should the <code>body_plans</code> be combined, or just keep styling in <code>y</code> . See details: <code>join_body_plans</code> for more details.

Details

`join_body_plan`:

When combining two `body_plans`, the body plans will stack together, first the body plan from `x` tfrm then `y` tfrm. This means that `frmt_structures` in `y` will take priority over those in `x`.

Combining two tfrm with large `body_plans` can lead to slow table evaluation. Consider setting `join_body_plan` to `FALSE`. Only the `y` body_plan will be preserved.

Value

tfrm object

Examples

```
tfrm_1 <- tfrm(title = "title1")
tfrm_2 <- tfrm(title = "title2", subtitle = "subtitle2")
layered_table_format <- layer_tfrm(tfrm_1, tfrm_2)
```

make_mock_data	<i>Make mock data for display shells</i>
----------------	--

Description

Make mock data for display shells

Usage

```
make_mock_data(tfrm, .default = 1:3, n_cols = NULL)
```

Arguments

tfrm	tfrm object
.default	Number of unique levels to create for group/label values set to ".default"
n_cols	Number of columns in the output table (not including group/label variables). If not supplied it will default to using the col_plan from the tfrm. If neither are available it will use 3.

Value

tibble containing mock data

Examples

```
tfrm_spec <- tfrm(  
  label = label,  
  column = column,  
  param = param,  
  value=value,  
  body_plan = body_plan(  
    frmt_structure(group_val=".default", label_val=".default", frmt("xx.x"))  
  )  
)  
  
make_mock_data(tfrm_spec)
```

page_plan	<i>Page Plan</i>
-----------	------------------

Description

Defining the location and/or frequency of page splits with a series of page_structure's and the row_every_n argument, respectively.

Usage

```
page_plan(
  ...,
  note_loc = c("noprint", "preheader", "subtitle", "source_note"),
  max_rows = NULL
)
```

Arguments

...	a series of <code>page_structure()</code> separated by commas
note_loc	Location of the note describing each table's subset value(s). Useful if the <code>page_structure</code> contains only ".default" values (meaning the table is split by every unique level of a grouping variable), and that variable is dropped in the <code>col_plan</code> . <code>preheader</code> only available for rtf output.
max_rows	Option to set a maximum number of rows per page. Takes a numeric value.

Value

page_plan object

Examples

```
# use of page_struct
page_plan(
  page_structure(group_val = "grp1", label_val = "lbl1")
)

# use of # rows
page_plan(
  max_rows = 5
)
```

Description

Page structure

Usage

```
page_structure(group_val = NULL, label_val = NULL)
```

Arguments

group_val	string or a named list of strings which represent the value of group to split after. Set to ".default" if the split should occur after every unique value of the variable.
label_val	string which represents the value of label to split after. Set to ".default" if the split should occur after every unique value of the variable.

Value

page structure object

Examples

```
# split page after every unique level of the grouping variable
page_structure(group_val = ".default", label_val = NULL)

# split page after specific levels
page_structure(group_val = "grp1", label_val = "lbl3")
```

param_set

Set custom parameter-level significant digits rounding

Description

Set custom parameter-level significant digits rounding

Usage

param_set(...)

Arguments

...	Series of name-value pairs, optionally formatted using glue::glue() syntax (note glue syntax is required for combined parameters). The name represents the parameter and the value represents the number of places to round the parameter to. For combined parameters (e.g., "{min}, {max}"), value should be a vector of the same length (e.g., c(1,1)).
-----	---

Details

Type param_set() in console to view package defaults. Use of the function will add to the defaults and/or override included defaults of the same name. For values that are integers, use NA so no decimal places will be added.

Value

list of default parameter-level significant digits rounding

Examples

```
# View included defaults
param_set()

# Update the defaults
param_set("{mean} ({sd})" = c(2,3), "pct" = 1)

# Separate mean and SD to different lines
param_set("mean" = 2, "sd" = 3)

# Add formatting using the glue syntax
param_set("{pct} %" = 1)
```

print_mock_gt *Print mock table to GT*

Description

Print mock table to GT

Usage

```
print_mock_gt(
  tfrm,
  .data = NULL,
  .default = 1:3,
  n_cols = NULL,
  .unicode_ws = TRUE
)
```

Arguments

<code>tfrm</code>	tfrm the mock table will be based off of
<code>.data</code>	Optional data. If this is missing, group values, labels values and parameter values will be estimated based on the tfrm
<code>.default</code>	sequence to replace the default values if a dataset isn't provided
<code>n_cols</code>	the number of columns. This will only be used if mock data isn't provided. If not supplied, it will default to using the col_plan from the tfrm. If neither are available it will use 3.
<code>.unicode_ws</code>	Whether to convert white space to unicode in preparation for output

Value

a stylized gt object

Examples

```
# Create tfrmt specification
tfrmt_spec <- tfrmt( label = label, column =
  column, param = param, body_plan = body_plan( frmt_structure(group_val =
  ".default", label_val = ".default", frmt_combine( "{count} {percent}",
  count = frmt("xxx"), percent = frmt_when("==100"~ frmt(""), "==0"~ "",
  "TRUE" ~ frmt("(xx.x%)))) ) )

# Print mock table using default
print_mock_gt(tfrmt = tfrmt_spec)

# Create mock data
df <- crossing(label = c("label 1", "label 2",
  "label 3"), column = c("placebo", "trt1", "trt2"), param = c("count",
  "percent"))

# Print mock table using mock data
print_mock_gt(tfrmt_spec, df)
```

print_to_ggplot *Print to ggplot*

Description

Print to ggplot

Usage

```
print_to_ggplot(tfrmt, .data, ...)
```

Arguments

- tfrmt tfrmt object that will dictate the structure of the ggplot object
- .data Data to style in order to make the ggplot object
- ... Inputs to geom_text to modify the style of the table body

Value

a stylized ggplot object

Examples

```
# Create data
risk<-tibble(time=c(rep(c(0,1000,2000,3000),3)),
              label=c(rep("Obs",4),rep("Lev",4),rep("Lev+5FU",4)),
              value=c(630,372,256,11,620,360,266,8,608,425,328,14),
              param=rep("n",12))

table<-tfrmt(
  label = label ,
  column = time,
  param = param,
  value = value) %>%
  print_to_ggplot(risk)

table
```

print_to_gt*Print to gt***Description**

Print to gt

Usage

```
print_to_gt(tfrmt, .data, .unicode_ws = TRUE)
```

Arguments

<code>tfrmt</code>	tfrmt object that will dictate the structure of the table
<code>.data</code>	Data to style in order to make the table
<code>.unicode_ws</code>	Whether to convert white space to unicode in preparation for output

Value

a stylized gt object

Examples

```
library(dplyr)
# Create tfrmt specification
tfrmt_spec <- tfrmt(
  label = label,
  column = column,
  param = param,
```

```

    value=value,
    body_plan = body_plan(
      frmt_structure(group_val = ".default", label_val = ".default",
                     frmt_combine(
                       "{count} {percent}",
                       count = frmt("xxx"),
                       percent = frmt_when("==100"~ frmt(""),
                                         "==0"~ "",
                                         "TRUE" ~ frmt("(xx.x%))))))
  )))
# Create data
df <- crossing(label = c("label 1", "label 2"),
                column = c("placebo", "trt1"),
                param = c("count", "percent")) %>%
  mutate(value=c(24,19,2400/48,1900/38,5,1,500/48,100/38))

print_to_gt(tfrmt_spec,df)

```

row_grp_plan*Row Group Plan***Description**

Define the look of the table groups on the output. This function allows you to add spaces after blocks and allows you to control how the groups are viewed whether they span the entire table or are nested as a column.

Usage

```
row_grp_plan(..., label_loc = element_row_grp_loc(location = "indented"))
```

Arguments

...	Row group structure objects separated by commas
label_loc	element_row_grp_loc() object specifying location

Value

row_grp_plan object

See Also

[row_grp_structure\(\)](#) for more details on how to specify row group structures, [element_block\(\)](#) for more details on how to specify spacing between each group, [element_row_grp_loc\(\)](#) for more details on how to specify whether row group titles span the entire table or collapse.

[Link to related article](#)

Examples

```
## single grouping variable example
sample_grp_plan <- row_grp_plan(
  row_grp_structure(group_val = c("A", "C"), element_block(post_space = "---")),
  row_grp_structure(group_val = c("B"), element_block(post_space = " ")),
  label_loc = element_row_grp_loc(location = "column")
)

## example with multiple grouping variables
sample_grp_plan <- row_grp_plan(
  row_grp_structure(group_val = list(grp1 = "A", grp2 = "b"), element_block(post_space = " ")),
  label_loc = element_row_grp_loc(location = "spanning")
)
```

row_grp_structure *Row Group Structure Object*

Description

Function needed to create a `row_grp_structure` object, which is a building block of `row_grp_plan()`

Usage

```
row_grp_structure(group_val = ".default", element_block)
```

Arguments

- | | |
|----------------------------|---|
| <code>group_val</code> | A string or a named list of strings which represent the value of group should be when the given frmt is implemented |
| <code>element_block</code> | <code>element_block()</code> object to define the block styling |

Value

`row_grp_structure` object

See Also

[row_grp_plan\(\)](#) for more details on how to group row group structures, [element_block\(\)](#) for more details on how to specify spacing between each group.

[Link to related article](#)

Examples

```
## single grouping variable example
row_grp_structure(group_val = c("A","C"), element_block(post_space = "---"))

## example with multiple grouping variables
row_grp_structure(group_val = list(grp1 = "A", grp2 = "b"), element_block(post_space = " "))
```

tfrmt

Table Format

Description

tfrmt, or "table format" is a way to pre-define the non-data components of your tables, and how the data will be handled once added: i.e. title, footers, headers, span headers, and cell formats. In addition, tfrmt's can be layered, building from one table format to the next. For cases where only one value can be used, the newly defined tfrmt accepts the latest tfrmt

Usage

```
tfrmt(
  tfrmt_obj,
  group = vars(),
  label = quo(),
  param = quo(),
  value = quo(),
  column = vars(),
  title,
  subtitle,
  row_grp_plan,
  body_plan,
  col_style_plan,
  col_plan,
  sorting_cols,
  big_n,
  footnote_plan,
  page_plan,
  ...
)
```

Arguments

tfrmt_obj	a tfrmt object to base this new format off of
group	what are the grouping vars of the input dataset
label	what is the label column of the input dataset
param	what is the param column of the input dataset

<code>value</code>	what is the value column of the input dataset
<code>column</code>	what is the column names column in the input dataset
<code>title</code>	title of the table
<code>subtitle</code>	subtitle of the table
<code>row_grp_plan</code>	plan of the row groups blocking. Takes a row_grp_plan()
<code>body_plan</code>	combination and formatting of the input data. Takes a body_plan()
<code>col_style_plan</code>	how to style columns including alignment (left, right, character) and width. Takes a col_style_plan()
<code>col_plan</code>	a col_plan object which is used to select, rename, and nest columns. Takes a col_plan()
<code>sorting_cols</code>	which columns determine sorting of output
<code>big_n</code>	how to format subject totals ("big Ns") for inclusion in the column labels. Takes a big_n_structure()
<code>footnote_plan</code>	footnotes to be added to the table. Takes a footnote_plan()
<code>page_plan</code>	pagination splits to be applied to the table. Takes a page_plan()
<code>...</code>	These dots are for future extensions and must be empty.

Details

NSE and Argument Evaluation:

- *tfrm* allows users to pass `vars`, `quo`, and unquoted expressions to a variety of arguments, such as `group`, `label`, `param`, `value`, `column`, and `sorting_cols`. Users accustomed to tidyverse semantics should be familiar with this behaviour. However, there is an important behaviour difference between *tfrm* and normal tidyverse functions. Because the data are not a part of *tfrm*, it does not know when a value being passed to it is intended to be an unquoted expression representing a column name or an object from the environment. As such, it preferentially uses the value from the environment over preserving the entry as an expression. For example, if you have an object "my_object" in your environment with the value "Hello world", and try to create a *tfrm* as `tfrm(column = my_object)`, it will take the value of "my_object" over assuming the `column` argument is an unquoted expression and view the entry to `column` as "Hello World". To pass "my_object" to *tfrm* as a column name, use quotes around the value: `tfrm(column = "my_object")`.
- Additionally, unquoted expressions that match *tfrm*'s other argument names can cause unexpected results. It is recommended to put quotes around the value as such: `tfrm(label = "group")`. In this case, the quoting will prevent *tfrm* from assigning its `group` input value to the `label` value.

Value

tfrm object

Images

Here are some example outputs:

See Also

[Link to related article](#)

Examples

```
tfrmt_spec <- tfrmt(
  label = label,
  column = column,
  param = param,
  value=value)

tfrmt_spec <- tfrmt(
  label = label,
  column = column,
  param = param,
  value=value,
  # Set the formatting for values
  body_plan = body_plan(
    frmt_structure(
      group_val = ".default",
      label_val = ".default",
      frmt_combine("{n} {pct}",
        n = frmt("xxx"),
        pct = frmt_when(
          "==100" ~ "(100%)",
          "==" ~ "",
          TRUE ~ frmt("(xx.x %)")
        )
      )
    ),
    # Specify column styling plan
    col_style_plan = col_style_plan(
      col_style_structure(col = vars(everything()), align = c(".", ",",""))
    )
  )

tfrmt_spec <- tfrmt(
  group = group,
  label = label,
  column = column,
  param = param,
  value=value,
  sorting_cols = c(ord1, ord2),
  # specify value formatting
  body_plan = body_plan(
    frmt_structure(
      group_val = ".default",
      label_val = ".default",
      frmt_combine("{n} {pct}",
        n = frmt("xxx"),
        pct = frmt_when(
          "==100" ~ "(100%)",
          "==" ~ ""
```

```

"==0" ~ """",
TRUE ~ frmt("(xx.x %)")
)
)
),
frmt_structure(
  group_val = ".default",
  label_val = "n",
  frmt("xxx")
),
frmt_structure(
  group_val = ".default",
  label_val = c("Mean", "Median", "Min", "Max"),
  frmt("xxx.x")
),
frmt_structure(
  group_val = ".default",
  label_val = "SD",
  frmt("xxx.xx")
),
frmt_structure(
  group_val = ".default",
  label_val = ".default",
  p = frmt("")
),
frmt_structure(
  group_val = ".default",
  label_val = c("n", "<65 yrs", "<12 months", "<25"),
  p = frmt_when(
    ">0.99" ~ ">0.99",
    "<0.001" ~ "<0.001",
    TRUE ~ frmt("x.xxx", missing = "")
  )
),
# remove extra cols
col_plan = col_plan(-grp,
  -starts_with("ord") ),
# Specify column styling plan
col_style_plan = col_style_plan(
  col_style_structure(col = vars(everything()), align = c(".", ","," ")))
),
# Specify row group plan
row_grp_plan = row_grp_plan(
  row_grp_structure(
    group_val = ".default",
    element_block(post_space = " ")
  ),
  label_loc = element_row_grp_loc(location = "column")
)
)
```

tfrmt_n_pct*N Percent Template*

Description

This function creates an tfrmt for an n % table, so count based table. The parameter values for n and percent can be provided (by default it will assume n and pct). Additionally the frmt_when for formatting the percent can be specified. By default 100% and 0% will not appear and everything between 99% and 100% and 0% and 1% will be rounded using greater than (>) and less than (<) signs respectively.

Usage

```
tfrmt_n_pct(
  n = "n",
  pct = "pct",
  pct_frmt_when = frmt_when("==100" ~ frmt(""), ">99" ~ frmt("(>99%)"), "==0" ~ "", "<1"
    ~ frmt("(<1%)"), "TRUE" ~ frmt("(xx.x%"))),
  tfrmt_obj = NULL
)
```

Arguments

n	name of count (n) value in the parameter column
pct	name of percent (pct) value in the parameter column
pct_frmt_when	formatting to be used on the the percent values
tfrmt_obj	an optional tfrmt object to layer

Value

tfrmt object

Examples

```
print_mock_gt(tfrmt_n_pct())
```

tfrm_t_sigdig*Create tfrm_t object from significant digits spec*

Description

This function creates a tfrm_t based on significant digits specifications for group/label values. The input data spec provided to sigdig_df will contain group/label value specifications. tfrm_t_sigdig assumes that these columns are group columns unless otherwise specified. The user may optionally choose to pass the names of the group and/or label columns as arguments to the function.

Usage

```
tfrmt_sigdig(
  sigdig_df,
  group = vars(),
  label = quo(),
  param_defaults = param_set(),
  missing = NULL,
  tfrmt_obj = NULL,
  ...
)
```

Arguments

sigdig_df	data frame containing significant digits formatting spec. Has 1 record per group/label value, and columns for relevant group and/or label variables, as well as a numeric column sigdig containing the significant digits rounding to be applied in addition to the default. If unique group/label values are represented in multiple rows, this will result in only one of the sigdig values being carried through in implementation.
group	what are the grouping vars of the input dataset
label	what is the label column of the input dataset
param_defaults	Option to override or add to default parameters.
missing	missing option to be included in all frmts
tfrm _t _obj	an optional tfrm _t object to layer
...	These dots are for future extensions and must be empty.

Details**Formats covered:**

Currently covers specifications for frmt and frmt_combine. frmt_when not supported and must be supplied in additional tfrm_t that is layered on.

Group/label variables:

If the group/label variables are not provided to the arguments, the body_plan will be constructed from the input data with the following behaviour:

- If no group or label are supplied, it will be assumed that all columns in the input data are group columns.
- If a label variable is provided, but nothing is specified for group, any leftover columns (i.e. not matching `sigdig` or the supplied label variable name) in the input data will be assumed to be group columns.
- If any group variable is provided, any leftover columns (i.e. not matching `sigdig` or the supplied group/label variable) will be disregarded.

Value

`tfrmt` object with a `body_plan` constructed based on the significant digits data spec and param-level significant digits defaults.

Examples

```
sig_input <- tibble::tribble(
  ~group1,    ~group2, ~sigdig,
  "CHEMISTRY",    ".default", 3,
  "CHEMISTRY",    "ALBUMIN",  1,
  "CHEMISTRY",    "CALCIUM",   1,
  ".default",    ".default",  2
)

# Subset data for the example
data <- dplyr::filter(data_labs, group2 == "BASOPHILS", col1 %in% c("Placebo", "Xanomeline Low Dose"))
tfrmt_sigdig(sigdig_df = sig_input,
              group = vars(group1, group2),
              label = rowlbl,
              param_defaults = param_set("[{n}]" = NA)) %>%
tfrmt(column = vars(col1, col2),
       param = param,
       value = value,
       sorting_cols = vars(ord1, ord2, ord3),
       col_plan = col_plan(-starts_with("ord")))) %>%
print_to_gt(.data = data)
```

Description

Print to JSON

Usage

```
tfrmt_to_json(tfrmt, path = NULL)
```

Arguments

<code>tfrm</code>	tfrm to print
<code>path</code>	file path to save JSON to. If not provided the JSON will just print to the console

Value

JSON

Examples

```
tfrm(
  label = label,
  column = column,
  param = param,
  value=value) %>%
tfrm_to_json()
```

<code>update_group</code>	<i>Remap group values in a tfrm</i>
---------------------------	-------------------------------------

Description

Remap group values in a tfrm

Usage

```
update_group(tfrm, ...)
```

Arguments

<code>tfrm</code>	a tfrm
<code>...</code>	Use new_name = old_name to rename selected variables

Value

A tfrm with the group variables updated in all places
 tfrm object with updated groups#'

Examples

```
tfrm_spec <- tfrm(
  group = c(group1, group2),
  body_plan = body_plan(
    frmt_structure(
      group_val = list(group2 = "value"),
      label_val = ".default",
      frmt("XXX"))))
```

```
    ),
  frmt_structure(
    group_val = list(group1 = "value", group2 = "value"),
    label_val = ".default",
    frmt("XXX")
  )
))

tfrmt_spec %>%
  update_group(New_Group = group1)
```

Index

* **datasets**
 data_ae, 10
 data_demog, 11
 data_efficiency, 11
 data_labs, 12

apply_frmrmt, 2

big_n_structure, 4
big_n_structure(), 34

body_plan, 5
body_plan(), 20–22, 34

col_plan, 6
col_plan(), 34

col_style_plan, 8
col_style_plan(), 10, 34

col_style_structure, 9
col_style_structure(), 8

cols_hide, 6

data_ae, 10
data_demog, 11
data_efficiency, 11
data_labs, 12

display_row_frmrmts, 13
display_val_frmrmts, 14

dplyr::case_when(), 19, 20

element_block, 15
element_block(), 17, 31, 32

element_row_grp_loc, 16
element_row_grp_loc(), 16, 31

everything, 6

footnote_plan, 17
footnote_plan(), 34

footnote_structure, 18
footnote_structure(), 18

frmrt, 19

frmrt(), 4, 5, 21, 22

frmrt_combine (frmrt), 19
frmrt_combine(), 5, 21, 22

frmrt_structure, 21
frmrt_structure(), 5, 20

frmrt_when (frmrt), 19
frmrt_when(), 5, 21, 22

is_frmrt, 22

is_frmrt_combine (is_frmrt), 22

is_frmrt_structure (is_frmrt), 22

is_frmrt_when (is_frmrt), 22

is_row_grp_structure (is_frmrt), 22

json_to_tfrmrt, 23

layer_tfrmrt, 24

make_mock_data, 25

page_plan, 25
page_plan(), 34

page_structure, 26
page_structure(), 26

param_set, 27

print_mock_gt, 28

print_to_ggplot, 29

print_to_gt, 30

row_grp_plan, 31
row_grp_plan(), 16, 17, 32, 34

row_grp_structure, 32
row_grp_structure(), 16, 17, 31

span_structure (col_plan), 6

tfrmrt, 33
tfrmrt_n_pct, 37
tfrmrt_sigdig, 38
tfrmrt_to_json, 39

update_group, 40