

# Package ‘thorn’

October 14, 2022

**Type** Package

**Title** 'HTMLwidgets' Displaying Some 'WebGL' Shaders

**Version** 0.2.0

**Description** Creates some 'WebGL' shaders. They can be used as the background of a 'Shiny' app. They also can be visualized in the 'RStudio' viewer pane or included in 'Rmd' documents, but this is pretty useless, besides contemplating them.

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**Imports** htmlwidgets

**Suggests** shiny, htmltools

**URL** <https://github.com/stla/thorn>

**BugReports** <https://github.com/stla/thorn/issues>

**RoxygenNote** 7.1.1

**NeedsCompilation** no

**Author** Stéphane Laurent [aut, cre],  
Scott Boyle [ctb, cph] ('Hamster.js' library),  
Mathew Groves [ctb, cph] ('PixiJS' library),  
Chad Engler [ctb, cph] ('PixiJS' library)

**Maintainer** Stéphane Laurent <laurent\_step@outlook.fr>

**Repository** CRAN

**Date/Publication** 2020-11-12 19:30:02 UTC

## R topics documented:

thorn . . . . .	2
thorn-shiny . . . . .	3

<b>Index</b>	<b>6</b>
--------------	----------

---

thorn	<i>HTML widget displaying a shader</i>
-------	--

---

### Description

Creates a HTML widget displaying a shader.

### Usage

```
thorn(shader, width = NULL, height = NULL, elementId = NULL)
```

### Arguments

shader	the name of the shader, one of "thorn", "thorn-color", "ikeda", "sweet", "biomorph1", "biomorph2", "biomorph3", "apollony", "smoke", "plasma"
width, height	a valid CSS measurement (like "100%", "400px", "auto") or a number, which will be coerced to a string and have "px" appended
elementId	a HTML id for the widget

### Examples

```
library(thorn)
thorn("ikeda") # click on the shader to animate it
thorn("thorn") # you can also use the mouse wheel on this one

# four shaders ####
library(htmltools)

hw1 <- thorn("thorn-color", width = "50vw", height = "50vh")
hw2 <- thorn("ikeda", width = "50vw", height = "50vh")
hw3 <- thorn("sweet", width = "50vw", height = "50vh")
hw4 <- thorn("biomorph3", width = "50vw", height = "50vh")

if(interactive()){
  browsable(
    withTags(
      div(
        div(
          style = "position:absolute; top:0;",
          div(hw1, style="position:fixed; left:0;"),
          div(hw2, style="position:fixed; left:50vw;")
        ),
        div(
          style = "position:absolute; top:50vh;",
          div(hw3, style="position:fixed; left:0;"),
          div(hw4, style="position:fixed; left:50vw;")
        )
      )
    )
  )
}
```

```
  )
}
```

---

 thorn-shiny

*Shiny bindings for thorn*


---

## Description

Output and render functions for using `thorn` within Shiny applications and interactive Rmd documents.

## Usage

```
thornOutput(outputId, width = "100%", height = "100%")

renderThorn(expr, env = parent.frame(), quoted = FALSE)
```

## Arguments

<code>outputId</code>	output variable to read from
<code>width, height</code>	a valid CSS measurement (like <code>"100%"</code> , <code>"400px"</code> , <code>"auto"</code> ) or a number, which will be coerced to a string and have <code>"px"</code> appended
<code>expr</code>	an expression that generates a shader created with <code>thorn</code>
<code>env</code>	the environment in which to evaluate <code>expr</code>
<code>quoted</code>	logical, whether <code>expr</code> is a quoted expression

## Examples

```
# use a shader as the background of a Shiny app ####
library(thorn)
library(shiny)

ui <- fluidPage(
  thornOutput("thorn", width = "100%", height = "100%"),
  br(),
  sidebarLayout(
    sidebarPanel(
      sliderInput(
        "slider", "Slide me",
        value = 10, min = 0, max = 20
      ),
      selectInput(
        "select", "Select me", choices = c("Choice 1", "Choice 2")
      )
    ),
    mainPanel()
  )
)
```

```

server <- function(input, output){

  output[["thorn"]] <- renderThorn({
    thorn("biomorph2")
  })

}

if(interactive()){
  shinyApp(ui, server)
}

# all available shaders ####
library(thorn)
library(shiny)

ui <- fluidPage(
  br(),
  sidebarLayout(
    sidebarPanel(
      wellPanel(
        radioButtons(
          "shader", "Shader",
          choices = c(
            "thorn",
            "thorn-color",
            "ikedai",
            "biomorph1",
            "biomorph2",
            "biomorph3",
            "sweet",
            "apollony",
            "smoke"
          )
        )
      )
    ),
    mainPanel(
      thornOutput("shader", width = "calc(100% - 15px)", height = "400px")
    )
  )
)

server <- function(input, output){

  output[["shader"]] <- renderThorn({
    thorn(input[["shader"]])
  })

}

if(interactive()){

```

```
  shinyApp(ui, server)  
}
```

# Index

`renderThorn (thorn-shiny)`, 3

`thorn`, 2, 3

`thorn-shiny`, 3

`thornOutput (thorn-shiny)`, 3