

# Package ‘vvbitwarden’

April 9, 2025

**Title** Interacts with 'Bitwarden Secrets Manager'

**Version** 0.1.0

## Description

Provides functions to securely retrieve secrets from a 'Bitwarden Secrets Manager' vault using the 'Bitwarden CLI', enabling secret and configuration management within R packages and workflows.

For more information visit <<https://bitwarden.com/products/secrets-manager/>>.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**Suggests** knitr, rmarkdown, testthat (>= 3.0.0), withr

**Config/testthat.edition** 3

**Imports** jsonlite, processx

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Hajo Bons [aut, cre],  
Tomer Iwan [aut]

**Maintainer** Hajo Bons <h.b.bons@vu.nl>

**Repository** CRAN

**Date/Publication** 2025-04-09 08:10:02 UTC

## Contents

get_bws_access_token . . . . .	2
get_bws_secret . . . . .	2
get_bws_server_url . . . . .	3

## Index

4

`get_bws_access_token`    *Retrieve BWS Access Token from Environment*

### Description

Retrieves the BWS\_ACCESS\_TOKEN from environment variables. This token is used to authenticate with the Bitwarden Secrets Manager API.

### Usage

```
get_bws_access_token()
```

### Value

A character string containing the BWS access token.

`get_bws_secret`                *Get a secret from your Bitwarden Secrets Manager vault*

### Description

This function retrieves the value of a secret stored in your Bitwarden Secrets Manager vault using the specified key.

### Usage

```
get_bws_secret(
  key,
  bws_access_token = get_bws_access_token(),
  bws_server_url = get_bws_server_url()
)
```

### Arguments

`key`                A character string representing the key of the secret.

`bws_access_token`                Optional. A character string representing the Bitwarden access token. Defaults to the value of the "BITWARDEN\_ACCESS\_TOKEN" environment variable.

`bws_server_url`                Optional. A character string representing the Bitwarden server URL. Defaults to the value of the "BWS\_SERVER\_URL" environment variable. For example "https://vault.bitwarden.eu".

### Value

A character string containing the value of the secret.

## Examples

```
## Not run:  
# Set environment variables for testing (example values)  
Sys.setenv(BWS_ACCESS_TOKEN = "your_access_token_here")  
Sys.setenv(BWS_SERVER_URL = "https://vault.bitwarden.eu")  
  
# Retrieve a secret using a key (the key must exist in your vault)  
my_secret <- get_bws_secret("my-secret-key")  
print(my_secret)  
  
## End(Not run)
```

---

get\_bws\_server\_url      *Retrieve BWS Server URL from Environment*

---

## Description

Retrieves the BWS\_SERVER\_URL from environment variables. This URL is used to define the Bitwarden Secrets Manager server endpoint.

## Usage

```
get_bws_server_url()
```

## Value

A character string containing the BWS server URL.

# Index

[get\\_bws\\_access\\_token, 2](#)  
[get\\_bws\\_secret, 2](#)  
[get\\_bws\\_server\\_url, 3](#)