Package 'wav'

November 28, 2022

Title Read and Write WAV Files

Version 0.1.0

Description Efficiently read and write Waveform (WAV) audio files https://en.wikipedia.org/wiki/WAV>.

Support for unsigned 8 bit Pulse-code modulation (PCM), signed 12, 16, 24 and 32 bit PCM and other encodings.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.2.1

LinkingTo Rcpp

Imports Rcpp

Suggests covr, testthat (>= 3.0.0), patrick

Config/testthat/edition 3

SystemRequirements C++11

URL https://github.com/mlverse/wav, https://mlverse.github.io/wav/

BugReports https://github.com/mlverse/wav/issues

NeedsCompilation yes

Author Daniel Falbel [aut, cre, cph], Posit, PBC [cph], David Reid [cph] (For the vendored dr_wav.h code.)

Maintainer Daniel Falbel <daniel@rstudio.com>

Repository CRAN

Date/Publication 2022-11-28 09:40:02 UTC

R topics documented:

read_wav	• •	•	 •	•	 •	·	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	·	•	·	•	•	2

4

Index

read_wav

Description

Efficiently read and write WAV files.

Usage

read_wav(path)

```
write_wav(x, path, sample_rate = 44100, bit_depth = 32, ..., normalize = TRUE)
```

Arguments

path	Path to file that will be read or written to.
X	Numeric matrix with dimensions [n_channels, n_samples]. Values in the matrix should be <double> in the range [-1, 1] or integers in the range [Machine\$integer.max, .Ma ie. 32 bits signed integers like R integers containing the amplitudes. Depending on the value of normalize and the bit_depth you can use different ranges.</double>
sample_rate	Sample rate in Hz of the associated samples.
bit_depth	Bit depth of associated samples. This only affects the precision data is saved to the file.
	Currently unused.
normalize	Boolean idicating wheter integers should be normalized before writing. Only used when write_wav() is called with a integer matrix. For example when you write a sample with a amplitude value of 2147483647 and bit_depth = 8, you would need to normalize this integer so it actually refers to the maximum unsigned int available (i.e. 255). You can avoid normalizing when the amplitudes are already in the correct integer range for the bit_depth you are saving, in this case provide normalize = FALSE.

Value

- When reading: A numeric matrix with samples. It also contains the attributes sample_rate and bit_depth.
- When writing: A boolean which is TRUE if writing was sucessful and FALSE otherwise.

Functions

• write_wav(): Write a wav file.

read_wav

Examples

```
x <- matrix(sin(440 * seq(0, 2*pi, length = 44100)), nrow=1)
tmp <- tempfile(fileext = ".wav")
write_wav(x, tmp)
y <- read_wav(tmp)
all.equal(as.numeric(x), as.numeric(y), tolerance = 1e-7)</pre>
```

Index

read_wav,2

write_wav(read_wav), 2
write_wav(), 2